

SeaweedFS + WordPress

Local Setup Guide

Windows + XAMPP + Advanced Media Offloader Plugin

What We Built

Connected WordPress (XAMPP) → Advanced Media Offloader plugin → SeaweedFS so all WordPress media uploads go to SeaweedFS instead of wp-content/uploads.

Step 1 — Download SeaweedFS

- Go to: <https://github.com/seaweedfs/seaweedfs/releases>
- Download the latest windows_amd64.tar.gz file
- Extract it — you will get a single binary: weed.exe
- Place it at: D:\wampp\seaweedfs\weed.exe

Step 2 — Create the Data Folder

Open Command Prompt and run:

```
mkdir D:\wampp\seaweedfs\data
```

Step 3 — Start SeaweedFS

Run the following command in CMD:

```
D:\wampp\seaweedfs\weed.exe mini -dir=D:\wampp\seaweedfs\data -s3.port=8333
```

This single command starts all components:

- Master server → port 9333
- Volume server → port 8080
- Filer → port 8888
- S3 gateway → port 8333
- Admin UI → http://192.168.145.1:23646

Step 4 — Create S3 Credentials

In a second CMD window, run:

```
setx AWS_ACCESS_KEY_ID "weed-access-key"  
setx AWS_SECRET_ACCESS_KEY "weed-secret-key"
```

Then in Admin UI → Users → Create user weedadmin with auto-generated keys:

```
Access Key: 9K0B86F1MLIDQ4IASQLM  
Secret Key: EHqOyogxtVAw9uR1SqWjECDrCVt9LbcnF0J4S5kGZJ
```

Step 5 — Create Bucket

1. Open Admin UI at <http://192.168.145.1:23646>
2. Click Buckets in the left menu
3. Click Create New S3 Bucket
4. Enter bucket name: wordpress-media
5. Click + Create Bucket

Step 6 — Install WordPress Plugin

6. Go to WordPress Admin: <http://enayaprogramdev-local/wp-admin>
7. Click Plugins → Add New
8. Search for: Advanced Media Offloader
9. Click Install Now → then Activate

Step 7 — Configure Plugin Settings

Go to Settings → Advanced Media Offloader and fill in:

Field	Value
Cloud Provider	Any S3-Compatible Storage
Provider Name	SeaweedFS Local
Access Key ID	9K0B86F1MLIDQ4IASQLM
Secret Access Key	EHqOyogxtVAw9uR1SqWjECDrCVt9LbcnF0J4S5kGZJ
S3 Endpoint URL	http://localhost:8333
Region	us-east-1
Use Path-Style Endpoint	☒ Checked
Bucket Name	wordpress-media
Custom Domain	Leave empty

10. Click Save Credentials
11. Click Test Connection → should show Connected

Step 8 — Fix Public Access (Bucket Policy)

In Admin UI → Buckets → wordpress-media → add this bucket policy:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": "*",
      "Action": "s3:GetObject",
      "Resource": "arn:aws:s3:::wordpress-media/*"
    }
  ]
}
```

Step 9 — Test Upload

12. Go to WordPress Media → Add New
13. Upload any image from your PC
14. Check the file URL — it should now show:

Old URL (before):

`http://enayaprogramdev-local/wp-content/uploads/...`

New URL (after):

`http://localhost:8333/wordpress-media/2026/06/filename.jpg`

How It Works

WordPress upload → Plugin intercepts → Sends to SeaweedFS S3 gateway → Stored in wordpress-media bucket

Important Reminder — Every Restart

SeaweedFS does NOT start automatically. Every time you restart your PC, you must run:

```
D:\wampp\seaweedfs\weed.exe mini -dir=D:\wampp\seaweedfs\data -  
s3.port=8333
```

Keep the CMD window open while working — closing it stops SeaweedFS.