






https://www.kaggle.com/c/dogs-vs-cats/data

 Search  Competitions Datasets Kernels Discussion Learn ...  



Dogs vs. Cats

Create an algorithm to distinguish dogs from cats

215 teams · 5 years ago


[Overview](#) [Data](#) [Kernels](#) [Discussion](#) [Leaderboard](#) [Rules](#) [Team](#)


Data Description


The training archive contains 25,000 images of dogs and cats. Train your algorithm on these files and predict the labels for test1.zip (1 = dog, 0 = cat).


A note on hand labeling

Per the rules and spirit of this contest, please do not manually label your submissions. We work hard to fair and fun contests, and ask for the same respect in return.









```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```



```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```



```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```



```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```




```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```



```
validation_dataset = tf.keras.utils.image_dataset_from_directory(  
    validation_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```



```
AUTOTUNE = tf.data.AUTOTUNE

train_dataset_final =
train_dataset_scaled.cache().shuffle(1000).prefetch(buffer_size=AUTOTUNE)

validation_dataset_final =
validation_dataset_scaled.cache().prefetch(buffer_size=AUTOTUNE)
```

```
model = tf.keras.models.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.Rescaling(1./255),
    tf.keras.layers.Conv2D(16, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(32, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(512, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```



```
model = tf.keras.models.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.Rescaling(1./255),
    tf.keras.layers.Conv2D(16, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(32, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(512, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```



```
model = tf.keras.models.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.Rescaling(1./255),
    tf.keras.layers.Conv2D(16, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(32, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(512, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```

```
model = tf.keras.models.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.Rescaling(1./255),
    tf.keras.layers.Conv2D(16, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(32, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(512, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```

```
model = tf.keras.models.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.Rescaling(1./255),
    tf.keras.layers.Conv2D(16, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(32, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(512, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```



Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 148, 148, 16)	448
max_pooling2d (MaxPooling2D)	(None, 74, 74, 16)	0
conv2d_1 (Conv2D)	(None, 72, 72, 32)	4640
max_pooling2d_1 (MaxPooling2D)	(None, 36, 36, 32)	0
conv2d_2 (Conv2D)	(None, 34, 34, 64)	18496
max_pooling2d_2 (MaxPooling2D)	(None, 17, 17, 64)	0
flatten (Flatten)	(None, 18496)	0
dense (Dense)	(None, 512)	9470464
dense_1 (Dense)	(None, 1)	513

Total params: 9,494,561
 Trainable params: 9,494,561
 Non-trainable params: 0

```
model.compile(loss='binary_crossentropy',  
              optimizer=tf.keras.optimizers.RMSprop(learning_rate=0.001),  
              metrics=['accuracy'])
```

```
history = model.fit(  
    train_dataset_final,  
    epochs=15,  
    validation_data=validation_dataset_final,  
    verbose=2)
```