

```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```

```
SHUFFLE_BUFFER_SIZE = 1000  
PREFETCH_BUFFER_SIZE = tf.data.AUTOTUNE
```

```
train_dataset_final = (train_dataset  
    .cache()  
    .shuffle(SHUFFLE_BUFFER_SIZE)  
    .prefetch(buffer_size=AUTOTUNE))
```

```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```

```
SHUFFLE_BUFFER_SIZE = 1000  
PREFETCH_BUFFER_SIZE = tf.data.AUTOTUNE
```

```
train_dataset_final = (train_dataset  
    .cache()  
    .shuffle(SHUFFLE_BUFFER_SIZE)  
    .prefetch(buffer_size=AUTOTUNE))
```

```
train_dataset = tf.keras.utils.image_dataset_from_directory(  
    train_dir,  
    image_size=(150, 150),  
    batch_size=20,  
    label_mode='binary')
```

```
SHUFFLE_BUFFER_SIZE = 1000  
PREFETCH_BUFFER_SIZE = tf.data.AUTOTUNE
```

```
train_dataset_final = (train_dataset  
    .cache()  
    .shuffle(SHUFFLE_BUFFER_SIZE)  
    .prefetch(buffer_size=AUTOTUNE))
```




```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```





```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```




```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```



```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```







```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```



```
data_augmentation = tf.keras.Sequential([
    tf.keras.Input(shape=(150, 150, 3)),
    tf.keras.layers.RandomFlip('horizontal'),
    tf.keras.layers.RandomRotation(0.2, fill_mode='nearest'),
    tf.keras.layers.RandomTranslation(0.2, 0.2, fill_mode='nearest'),
    tf.keras.layers.RandomZoom(0.2, fill_mode='nearest')
])
```



```
model_without_aug = create_model()

model_with_aug = tf.keras.models.Sequential([
    data_augmentation,
    model_without_aug
])

model_with_aug.compile(
    loss='binary_crossentropy',
    optimizer=tf.keras.optimizers.RMSprop(learning_rate=1e-4),
    metrics=[ 'accuracy' ]
```



```
model_without_aug = create_model()

model_with_aug = tf.keras.models.Sequential([
    data_augmentation,
    model_without_aug
])

model_with_aug.compile(
    loss='binary_crossentropy',
    optimizer=tf.keras.optimizers.RMSprop(learning_rate=1e-4),
    metrics=[ 'accuracy' ]
```



```
model_without_aug = create_model()

model_with_aug = tf.keras.models.Sequential([
    data_augmentation,
    model_without_aug
])

model_with_aug.compile(
    loss='binary_crossentropy',
    optimizer=tf.keras.optimizers.RMSprop(learning_rate=1e-4),
    metrics=['accuracy']
```

