

CSEN 703 Analysis and Design of Algorithms, Winter Term 2022
Practice Assignment 6

Exercise 6-1

Give examples of problems and/or algorithms where the Divide and Conquer technique is more efficient than Dynamic Programming and state your reasons.

Solution:

Divide and Conquer is efficient for any problem where the sub-problems are independent and unique e.g. Sorting algorithms and Towers Of Hanoi. If we take merge sort as an example of a sorting algorithm and write it using the dynamic programming technique, the algorithm would start with n arrays of size 1. At every iteration the algorithm will merge two consecutive arrays into one and store the results which is a huge overhead in terms of space complexity. In divide and conquer, the algorithm will merge in a local array and copy the results back to the original one thus saving the space occupied by storing the results of sub-problems. If we consider the Towers of Hanoi, the fact that every disk move is unique makes it useless to store any partial results.

Exercise 6-2

Consider the factorial algorithm:

- i. Write a recurrence for the algorithm.

Solution:

$$T(n) = \begin{cases} T(n-1) + \Theta(1) & \text{if } n \geq 1; \\ \Theta(1) & \text{if } n = 0. \end{cases}$$

- ii. Using the dynamic programming paradigm, provide an algorithm based on the given recurrence. Make sure that you use an efficient data structure to store the partial results.

Solution:

```
1: function FACTORIAL(int n)
2:   fac ← (int)AllocateArray(n+1)
3:   fac[0] ← 1
4:   for i = 1 to n do
5:     fac[i] ← i*fac[i-1]
6:   end for
7:   return fac[n]
8: end function
```

Exercise 6-3

Consider the following recursive definition for the problem of calculating a given binomial coefficient $\binom{n}{k}$:

$$\binom{n}{k} = \begin{cases} \binom{n-1}{k-1} + \binom{n-1}{k} & \text{if } 0 < k < n; \\ 1 & \text{if } k = 0 \text{ or } k = n. \end{cases}$$

- i. Write a divide-and-conquer algorithm to compute the binomial coefficients.

Solution:

```

1: function BCREC(int n, int k)
2:   if k = 0 or k = n then
3:     return 1
4:   else
5:     return BCREC(n - 1, k) + BCREC(n - 1, k - 1)
6:   end if
7: end function

```

- ii. Provide the recurrence relation for your answer in part (i).

Solution:

$$T(n, k) = \begin{cases} T(n-1, k) + T(n-1, k-1) & \text{if } 0 < k < n; \\ \Theta(1) & \text{if } k = 0 \text{ or } k = n. \end{cases}$$

- iii. Write an iterative algorithm that employs the dynamic programming technique using the bottom-up approach.

Solution:

```

1: function BCDP(int n, int k)
2:   bCDPArray ← integerAllocateArray(n + 1, k + 1)
3:   for i ← 0 to n do
4:     for j ← 0 to min(i, k) do
5:       if j = 0 or j = i then
6:         bCDPArray[i][j] ← 1
7:       else
8:         bCDPArray[i][j] ← bCDPArray[i - 1][j] + bCDPArray[i - 1][j - 1]
9:       end if
10:    end for
11:  end for
12:  return bCDPArray[n][k]
13: end function

```

- iv. Write an algorithm for the same problem using the memoization technique.

Solution:

```

1: bCMemArray ← integerAllocateArray(n + 1, k + 1)
2:                                     ▷ bCMemArray is a global array initialized to -∞
3: function BCMEM(int n, int k)
4:   if k = 0 or k = n then
5:     bCMemArray[n][k] ← 1
6:   else if bCMemArray[n][k] = -∞ then
7:     bCMemArray[n][k] ← BCMEM(n - 1, k) + BCMEM(n - 1, k - 1)
8:   end if
9:   return bCMemArray[n][k]
10: end function

```

- v. Modify your answer in (iii) to use a single one-dimensional array indexed from 0 to *k*. What was your tradeoff?

Solution:

```

int[] B = new int[k+1];

for ( int i = 0; i <= k; i++ )

```

```

    B[i] = 1;

    for ( int i = 0; i < n; i++ ) {
        int j = min(i,k);

        while ( j > 0 ) {
            B[j] += B[j-1];
            j--;
        }
    }

```

Exercise 6-4

Suppose that you are given an $n \times n$ checkerboard and a checker. You must move the checker from the bottom edge of the board to the top edge of the board according to the following rule. At each step you may move the checker to one of three squares:

- the square immediately above,
- the square that is one up and one to the left (but only if the checker is not already in the leftmost column),
- the square that is one up and one to the right (but only if the checker is not already in the rightmost column).

Each time you move from square x to square y , you receive $p(x, y)$ dollars. You are given $p(x, y)$ for all pairs (x, y) for which a move from x to y is legal. Do not assume that $p(x, y)$ is positive. Give an algorithm that figures out the set of moves that will move the checker from somewhere along the bottom edge to somewhere along the top edge while gathering as many dollars as possible. Your algorithm is free to pick any square along the bottom edge as a starting point and any square along the top edge as a destination in order to maximize the number of dollars gathered along the way. What is the running time of your algorithm?

Solution:

The recursive definition for calculating the score is as follows:

$$\text{score}[i,j] = \begin{cases} 0 & \text{if } i = 1 \text{ and } 1 \leq j \leq n; \\ \max \begin{cases} \text{score}[i-1,j-1] + p((i-1,j-1),(i,j)) & \text{if } j > 1; \\ \text{score}[i-1,j] + p((i-1,j),(i,j)) & \forall j; \\ \text{score}[i-1,j+1] + p((i-1,j+1),(i,j)) & \text{if } j < n; \end{cases} & \text{and } 2 \leq i \leq n \end{cases}$$

function CHECKERBOARDSCORE(int size, matrix p)

 score \leftarrow (float)ALLOCATEARRAY(n,n)

for j \leftarrow 1 **to** n **do**

 score[1][j] \leftarrow 0

end for

for i \leftarrow 2 **to** n **do**

for j \leftarrow 1 **to** n **do**

 point x \leftarrow new point(i-1,j)

 point y \leftarrow new point(i,j)

 temp \leftarrow score[i-1][j] + p(x,y)

if j > 1 **then**

```

        x ← new point(i-1,j-1)

        if temp < (score[i-1][j-1] + p(x,y)) then
            temp ← (score[i-1][j-1] + p(x,y))
        end if
    end if
    if j < n then
        x ← new point(i-1,j+1)

        if temp < (score[i-1][j+1] + p(x,y)) then
            temp ← (score[i-1][j+1] + p(x,y))
        end if
    end if
    score[i][j] ← temp
end for
return score
end function

function CHECKERMOVES(matrix score)
    index max ← GETMAX(score[n][1..n])
    BACKTRACK(score,n,max)
end function

function GETMAX(array score)
    index max ← 1
    for i ← 2 to n do
        if score[i] > score[max] then
            max ← i
        end if
    end for
    return max
end function

function BACKTRACK(matrix score, index i, index j)
    if i > 1 then
        if score[i][j] = score[i-1][j] + p((i-1,j),(i,j)) then
            backtrack (score, i-1,j)
        else if (j>1) and (score[i][j] = score [i-1][j-1] + p((i-1,j-1),(i,j)) ) then
            backtrack (score,i-1,j-1)
        else
            backtrack(score,i-1,j+1)
        end if
        PRINT (i j)
    end if
end function

```