

Week-12-user defined functions

Question 1

Correct

Marked out of
1.00[Flag question](#)

A binary number is a combination of 1s and 0s. Its n^{th} least significant digit is the n^{th} digit starting from the right starting with 1. Given a decimal number, convert it to binary and determine the value of the 4^{th} least significant digit.

Example

number = 23

- Convert the decimal number 23 to binary number: $23^{10} = 2^4 + 2^2 + 2^1 + 2^0 = (10111)_2$.
- The value of the 4^{th} index from the right in the binary representation is 0.

Function Description

Complete the function fourthBit in the editor below.

fourthBit has the following parameter(s):

int number: a decimal integer

Returns:

int: an integer 0 or 1 matching the 4th least significant digit in the binary representation of number.

Source code

```
1  /*
2  * Complete the 'fourthBit' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER number as parameter.
6  */
7
8  int fourthBit(int number)
9  {
10     int binary[32];
11     int i=0;
12     while(number>0)
13     {
14         binary[i]=number%2;
15         number/=2;
16         i++;
17     }
18     if(i>=4)
19     {
20         return binary[3];
21     }
22     else
23     return 0;
24 }
25
```

Result

| | Test | Expected | Got | |
|---|-----------------------------|----------|-----|---|
| ✓ | printf("%d", fourthBit(32)) | 0 | 0 | ✓ |
| ✓ | printf("%d", fourthBit(77)) | 1 | 1 | ✓ |

Passed all tests! ✓

Question **2**

Correct

Marked out of
1.00

 Flag question

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Function Description

Complete the function `pthFactor` in the editor below.

`pthFactor` has the following parameter(s):

`int n`: the integer whose factors are to be found

`int p`: the index of the factor to be returned

[Source code](#)

```
1  /*
2   * Complete the 'pthFactor' function below.
3   *
4   * The function is expected to return a LONG_INTEGER.
5   * The function accepts following parameters:
6   * 1. LONG_INTEGER n
7   * 2. LONG_INTEGER p
8   */
9
10 long pthFactor(long n, long p)
11 {
12     int count=0;
13     for(long i=1;i<=n;++i)
14     {
15         if(n%i==0)
16         {
17             count++;
18             if(count == p)
19             {
20                 return i;
21             }
22         }
23     }
24     return 0;
25 }
26 }
```

Result

| | Test | Expected | Got | |
|---|---------------------------------|----------|-----|---|
| ✓ | printf("%ld", pthFactor(10, 3)) | 5 | 5 | ✓ |
| ✓ | printf("%ld", pthFactor(10, 5)) | 0 | 0 | ✓ |
| ✓ | printf("%ld", pthFactor(1, 1)) | 1 | 1 | ✓ |

Passed all tests! ✓

