

Ransomware Evolution: Emerging Cyber Threats and Defense Mechanisms in the Digital Age

Sarah Elshiaty
Dept. of Computer Science
Effat University
Jeddah, Saudi Arabia
skelshiaty@effat.edu.sa

Dr. Sohail Khan
Dept. of Computer Science
Effat University
Jeddah, Saudi Arabia
sohkhan@effatuniversity.edu.sa

Seifeldin Elshiaty
Dept. of Computer Science
Effat University
Jeddah, Saudi Arabia
skhelshiaty@effat.edu.sa

Abstract— Ransomware has emerged as one of the most formidable cyber threats in recent years. It continues to evolve from simple file-locking malware into complex ecosystems driven by Ransomware-as-a-Service (RaaS) and advanced encryption mechanisms. This paper examines the progression of ransomware, focusing on new tactics such as double extortion, AI-driven payloads, and delivery techniques including phishing and remote desktop protocol exploitation. We explore the human, economic, and technical impacts of ransomware, analyze common defense strategies such as endpoint detection, backups, user training, and Zero Trust models, and evaluate their effectiveness. Real-world case studies such as the WannaCry and Colonial Pipeline attacks are reviewed to demonstrate the scope and consequences of modern ransomware campaigns. The paper concludes with statistical trends from 2020 to 2024 and proposes research directions aimed at improving ransomware resilience.

Keywords—Ransomware, Cybersecurity, Double Extortion, Zero Trust, AI Malware, Phishing, Ransomware-as-a-Service, WannaCry, Colonial Pipeline.

I. INTRODUCTION

Ransomware is a form of malicious software that encrypts files or locks access to computer systems, demanding a ransom from victims to restore functionality. Initially, ransomware targeted individual users through opportunistic spam campaigns. Over time, the scope has expanded dramatically, with sophisticated variants targeting large enterprises, critical infrastructure, and even national governments.

The threat has been amplified by developments like Ransomware-as-a-Service (RaaS), in which professional criminal groups lease their ransomware platforms to affiliates for a share of the profits [1]. Notable attacks such as WannaCry in 2017 and Colonial Pipeline in 2021 demonstrate ransomware's capacity to disrupt global operations. In response, organizations have adopted layered defense mechanisms; however, challenges remain in detection, response, and policy regulation. This paper explores ransomware's evolution, classifications, delivery techniques, human and organizational impacts, and emerging defense mechanisms. It offers statistical insights and real-world case studies to assess whether current strategies can counter the growing threat.

II. LITERATURE REVIEW

A. Definitions and Classifications

Ransomware has evolved into a multifaceted threat, with distinct forms engineered to exploit varying technical and human vulnerabilities. It is commonly categorized based on its core functionality and method of coercion. Encryption ransomware is the most prevalent type, leveraging cryptographic algorithms to lock users out of their files. Victims must pay a ransom—often in cryptocurrency—to obtain the decryption key. Notable examples include LockBit and Ryuk, both of which have disrupted large organizations globally [2]. Locker ransomware, by contrast, obstructs access to entire systems without necessarily encrypting files. Variants such as Reveton display fake law enforcement notices or similar psychological triggers to extract payment [2]. Leakware, or doxware, raises the stakes by exfiltrating sensitive files before encryption. Victims are then threatened with public data leaks in addition to file loss. This dual-leverage strategy, used by groups like Maze and Conti, increases the likelihood of ransom compliance [3]. Meanwhile, mobile ransomware exploits the vulnerabilities of smartphones and tablets. Typically masquerading as legitimate apps or updates, these variants can lock devices or encrypt content—posing increasing risks as mobile device use grows [2]. Ransomware classifications have thus evolved in tandem with growing threat sophistication, reflecting a shift from straightforward technical attacks to multifaceted extortion schemes involving social and psychological pressure.

B. Emerging Techniques

To evade detection and maximize impact, ransomware actors now employ a range of advanced techniques. One of the most impactful innovations is double extortion. Introduced by the Maze group, this tactic involves not only encrypting files but also stealing them for additional leverage. Victims face both data loss and the reputational fallout of sensitive information being publicly released [3]. Another transformative development is Ransomware-as-a-Service (RaaS). In this model, experienced developers offer ready-to-use ransomware kits to affiliates, who in turn launch attacks for a share of the profit. RaaS has commodified ransomware, allowing threat actors with limited technical skills to conduct enterprise-grade campaigns [4]. Furthermore, some modern ransomware variants incorporate

AI and machine learning to increase stealth. These systems analyze and mimic user behavior to evade anomaly detection tools, delaying recognition and allowing greater damage [5]. Together, these techniques signal a fundamental shift in how ransomware is deployed—toward professionalized, persistent, and highly evasive campaigns.

C. Evolution Over the Years

Ransomware's evolution demonstrates a transformation from opportunistic attacks to highly organized, enterprise-grade cybercrime operations. Between 2010 and 2015, attacks were largely opportunistic and technically unsophisticated. Many early ransomware strains used weak or hardcoded encryption that researchers could reverse-engineer. These campaigns primarily targeted individual users via spam, with limited scalability. From 2016 to 2019, ransomware entered a new phase, enabled by nation-state-grade vulnerabilities. The 2017 WannaCry outbreak, for instance, utilized the EternalBlue exploit to propagate across global networks within hours. This marked the rise of worm-based ransomware capable of self-spreading, and it set a precedent for infrastructure-level targeting[6].

The period from 2020 to 2024 witnessed the industrialization of ransomware. RaaS operations proliferated, enabling cybercriminals to scale attacks across sectors with alarming speed. Variants like LockBit and BlackCat demonstrated modular payloads, extortion sites, and customer support portals—further blurring the line between criminal syndicates and professional software vendors [6]. These historical trends reveal how ransomware evolved from isolated code to a complex cybercrime ecosystem that thrives on automation, monetization, and psychological manipulation.

D. Common Tactics and Delivery Methods

The effectiveness of ransomware stems from its multifaceted delivery strategies and relentless adaptation.

1) Phishing emails remain the most common entry point. These socially engineered messages lure users into clicking malicious links or downloading infected attachments. The success of phishing highlights the human factor in cybersecurity vulnerabilities [7].

2) Exploitation of known software vulnerabilities is another central tactic. High-profile attacks like WannaCry capitalized on unpatched systems—specifically targeting Microsoft's SMBv1 protocol using the leaked EternalBlue exploit [6].

3) Remote Desktop Protocol (RDP) exploitation is also widespread. Attackers scan for exposed RDP ports and use brute-force techniques to gain access, especially on systems with weak or default credentials [8].

In addition, ransomware can spread via network shares, removable drives, and compromised update mechanisms, making lateral movement a serious concern in poorly segmented networks.

What unites these methods is their dual focus: technical vulnerability exploitation and human deception. This blend makes ransomware especially difficult to defend against using a single-layered security model.

E. Current Defense Approaches

In response to the ransomware crisis, organizations have adopted a spectrum of defense strategies. However, each solution presents its own limitations, especially against evolving threat models.

Endpoint Detection and Response (EDR) solutions provide real-time system monitoring and telemetry. While EDR is effective against known threats, its dependence on behavioral baselines makes it vulnerable to polymorphic ransomware, which mutates continuously to avoid detection. Thus, EDR must be integrated with AI-powered threat analysis to detect anomalies not covered by static rules [5].

Zero Trust Architecture (ZTA) has gained traction for its "never trust, always verify" approach. By eliminating implicit trust and enforcing strict access controls, ZTA minimizes lateral spread. Still, full implementation is often resource-heavy and may require organizational restructuring—barriers that delay widespread adoption [9]. User awareness training is vital for reducing phishing susceptibility. Many organizations run simulated phishing campaigns and instructional modules. Yet, attackers now employ increasingly convincing lures, including deepfake audio and video, which traditional training often fails to address [11].

Immutable backups offer a critical recovery option, especially when kept offline or air-gapped. Unfortunately, sophisticated ransomware variants now include scripts to locate and delete shadow copies or corrupt backup configurations. Ensuring resilient backups requires redundancy, encryption, and regular testing [10]. Despite their promise, these defenses are often siloed and reactive. They require seamless integration, policy support, and continuous adaptation to remain effective in dynamic threat landscapes.

F. Gaps in Research and Implementation

While defensive technologies have advanced, ransomware remains a dominant threat due to persistent gaps in both research and implementation. A key shortfall is the limited adoption of behavior-based detection mechanisms. Traditional antivirus and firewalls still dominate enterprise environments despite being inadequate against ransomware that uses novel evasion methods [4].

Training programs also struggle to keep pace. Most simulations focus on basic phishing detection but fail to address modern tactics like deepfake impersonation, which use synthetic voice or video to deceive even vigilant users [11].

From a regulatory standpoint, global inconsistencies in breach disclosure laws hinder cross-border cooperation. Without unified reporting frameworks, organizations lack incentives to share incident data—slowing collective learning and response [14].

Perhaps most critically, there is an insufficient focus on the psychological and human-centered impacts of ransomware. Sectors such as healthcare and education are especially vulnerable—not just because of outdated infrastructure, but

because of the emotional distress and workforce instability caused by prolonged system outages. Despite efforts to enhance technical defenses, limited focus is placed on the psychological burden ransomware imposes on staff, patients, and students [12].

Achieving meaningful ransomware resilience will require organizations to bridge the gap between technical security, human psychology, and coordinated policy enforcement—ensuring a proactive, rather than reactive, approach to evolving threats.

III. ANALYSIS & EVALUATION

Ransomware's impact extends far beyond immediate data loss. It inflicts layered consequences on individuals, organizations, and society at large—disrupting critical operations, damaging trust, and threatening national security. This section examines those tiers of impact and evaluates how current defenses fare against an increasingly sophisticated threat landscape.

A. Individual Impact

At the individual level, ransomware attacks can result in permanent loss of personal data, including medical records, photographs, and financial documents. Beyond material loss, victims often suffer psychological trauma stemming from the violation of privacy, uncertainty, and financial strain. Identity theft and social engineering often follow in the wake of ransomware, compounding the long-term impact on victims' security and well-being [12].

For example, mobile ransomware that targets individuals frequently employs deceptive notifications or fake antivirus pop-ups, creating anxiety and urgency to pay. These human responses are intentionally manipulated—an aspect of ransomware strategy that technical defenses rarely address.

B. Organizational Impact

Ransomware's consequences at the organizational level are extensive and multifaceted. Enterprises face significant financial losses not only from ransom payments but from downtime, incident response costs, legal penalties, and reputation damage. Studies show that the total cost of a ransomware breach often far exceeds the ransom itself—especially when operational disruption stretches into days or weeks [13].

Healthcare organizations, in particular, face acute risks. During the Ryuk ransomware campaign, hospitals in the United States were forced to cancel surgeries, divert ambulances, and delay patient care. These disruptions had both clinical and reputational repercussions, undermining public confidence in essential services [13]. Moreover, reputational harm can lead to customer attrition, investor skepticism, and long-term loss of brand trust—making ransomware recovery a protracted and costly affair.

C. Societal Impact

Ransomware's reach has grown to encompass societal and national infrastructure, raising alarms at the highest levels of government and industry. Attacks targeting energy grids, public health systems, and educational institutions affect not just operations, but the social fabric that relies on them.

The 2021 Colonial Pipeline incident is a notable example. The ransomware attack forced a shutdown of the largest fuel pipeline in the eastern United States, leading to fuel shortages, panic buying, and emergency declarations across multiple states [14]. While the pipeline resumed operations after a ransom was paid, the broader implications were clear.

Beyond direct operational disruption, ransomware attacks on critical infrastructure create widespread economic consequences and expose national security vulnerabilities. These sectors often lack comprehensive cybersecurity resources and are attractive targets for attackers aiming to maximize leverage with minimal effort.

The growing scale of ransomware attacks against critical infrastructure underscores the urgency for robust defenses. However, as ransomware operators refine their techniques, traditional cybersecurity measures face mounting challenges.

D. Evaluation of Current Defenses

While organizations deploy multiple security measures, ransomware's rapid evolution has exposed critical gaps, demanding a reassessment of defensive strategies. Attackers have adapted their tactics faster than most institutions can update their defenses—forcing a shift from reliance on static tools to dynamic, integrated resilience planning.

a) Endpoint Detection and Response (EDR) and Antivirus Solutions: These tools provide foundational protection by monitoring system behavior and flagging known malware signatures. However, polymorphic ransomware continuously mutates to evade signature-based detection. Without AI-driven analytics and anomaly detection, EDRs are often reactive rather than preventive [5].

b) Multi-Factor Authentication (MFA): MFA adds a critical layer of identity verification, reducing unauthorized access through stolen credentials. While highly effective when implemented, adoption remains inconsistent, particularly in small and mid-sized enterprises [10]. MFA's efficacy also depends on user behavior, making education and enforcement key.

c) Security Awareness Training: Continuous user education is essential to combat phishing and social engineering. Simulated attacks and scenario-based training can reduce susceptibility. However, many programs are outdated or sporadic. Moreover, they often fail to address newer techniques such as deepfake-based voice phishing, which exploit trust in familiar voices or visual cues [11].

d) Zero Trust Architecture (ZTA) and Microsegmentation: ZTA represents a robust defense philosophy, enforcing strict access controls and verifying each request before granting access. Microsegmentation isolates systems, minimizing lateral movement during

breaches. While conceptually strong, these strategies are resource-intensive, requiring high implementation costs, skilled personnel, and organizational alignment [15].

e) Backups and Disaster Recovery: Immutable and air-gapped backups remain a cornerstone of ransomware resilience. However, attackers now increasingly design payloads to seek out and destroy backup repositories, undermining this last line of defense. Regular backup testing and versioning are essential to ensure effective recovery. To counter modern ransomware, security strategies must shift from reactive containment to proactive, intelligence-driven adaptation—fusing technological defenses with human awareness and cross-sector collaboration. A truly resilient cybersecurity framework must integrate adaptive defenses, intelligence-sharing, and behavioral insight, ensuring that security strategies evolve faster than the ransomware threats they aim to counter.

IV. STAGES OF RANSOMWARE ATTACK

Ransomware attacks follow a structured lifecycle, beginning with infiltration and culminating in financial extortion, data exposure, or persistent network compromise. Understanding each phase of the attack is essential for developing timely and effective cybersecurity responses [16].

Identifying the stage at which an attack occurs enables defenders to implement precise countermeasures—interrupting the attack chain before it reaches critical damage thresholds. This section outlines the key stages commonly observed in modern ransomware campaigns [16].




Fig.1. Ransomware lifecycle stages, from infiltration to post-encryption persistence. Adapted from [16].

Stage	Description
1. Initial Access	Attackers gain a foothold in the system using phishing emails, malicious attachments, Remote Desktop Protocol (RDP) brute-force attacks, or unpatched software vulnerabilities.
2. Execution	The ransomware payload is deployed, often through PowerShell scripts, DLL injections, or macro-enabled Office files. It begins scanning the environment for files, shared drives, and connected backups.
3. Privilege Escalation	To maximize reach and control, attackers attempt to obtain administrative or domain-level privileges. This allows them to disable endpoint protections and expand access across networked systems.
4. Lateral Movement	Leveraging tools like Mimikatz, PSEXec, or RDP, attackers spread across the network, accessing additional systems to widen the impact and encrypt as many critical assets as possible.
5. Data Exfiltration (Optional)	In double or triple extortion scenarios, sensitive data is extracted and sent to attacker-controlled servers. This is used to amplify ransom pressure through blackmail or legal threats.
6. Encryption and Lockdown	Files are encrypted using algorithms like AES, ChaCha20, or RSA. Victims are presented with a ransom note, often accompanied by deleted backups and disabled system recovery options.
7. Persistence and Cleanup	Beyond encryption, attackers may use persistence mechanisms to maintain access—often leading to prolonged system breaches, secondary extortion attempts, or resale of compromised credentials on dark web marketplaces.

Fig.2. Key Stages in a Ransomware Lifecycle (Adapted from Djenna et al., 2024 [16])

While many view ransomware as a one-time attack culminating in a ransom demand, modern operations increasingly employ post-encryption tactics [16]. These include selling access to affected networks or launching follow-up attacks under new malware strains—often exploiting the same unpatched vulnerabilities.

As ransomware continues to evolve, lifecycle awareness must remain a cornerstone of cybersecurity strategies—ensuring defenders stay ahead of emerging threats through early detection, segmentation, and proactive threat hunting [16].

VI. CASE STUDY: WANNACRY RANSOMWARE ATTACK (2017)

A. Overview of the Attack

The WannaCry ransomware attack, which surfaced in May 2017, was one of the most disruptive global cyber incidents of the decade. It exploited a critical vulnerability in Microsoft's Server Message Block protocol (SMBv1), known as EternalBlue—a weaponized exploit originally developed by the U.S. National Security Agency (NSA) and later leaked by a hacker group called Shadow Brokers [1], [2]. What made WannaCry particularly dangerous was its ability to propagate autonomously, functioning as a network worm. Once inside a network, it scanned for other vulnerable systems and spread rapidly without requiring user interaction [3].

The attack impacted more than 230,000 systems across 150 countries within just a few days [4]. Major organizations including the United Kingdom's National Health Service (NHS), FedEx, Deutsche Bahn, and Telefónica were severely affected [5]. WannaCry's payload encrypted critical files and displayed a ransom demand—typically \$300–\$600 in Bitcoin—with threats of file deletion if payment wasn't received within 72 hours [6]. It exploited known but unpatched systems, most notably on outdated or unsupported operating systems such as Windows XP [1].

B. Impact

i Financial Loss

WannaCry caused widespread financial harm, not just through ransom payments, but also through business interruption, loss of productivity, emergency response costs, and long-term IT recovery. Estimates suggest global damages ranging from \$4 to \$8 billion USD [7]. Even organizations that did not pay the ransom incurred significant costs due to downtime and system rebuilding [8].

ii Reputational Damage

The attack attracted intense media scrutiny, especially in public sector organizations that failed to patch critical vulnerabilities. For instance, the UK's NHS was heavily criticized for continuing to use unsupported systems and for its delayed response to cybersecurity modernization efforts [5], [9]. This led to public trust erosion, legal reviews, and policy discussions in multiple countries about the accountability of digital infrastructure operators [10].

iii Operational Disruption

The operational impact of WannaCry was immediate and severe. In the healthcare sector, over 19,000 NHS appointments were canceled, affecting patient diagnostics, treatments, and emergency procedures [5]. Some hospitals were forced to

divert ambulances and revert to manual documentation. The attack disrupted not only IT services, but also life-critical operations, illustrating how ransomware can pose risks to human safety, not just data security [11].

C. Lessons Learned and Mitigation Measures

1. Patch Management as a Cybersecurity Priority

WannaCry's spread was made possible by the widespread failure to apply Microsoft's March 2017 security update (MS17-010), released well before the attack [12]. This underscored the importance of timely patch management, particularly for critical infrastructure and enterprise systems. Organizations were urged to implement automated patching frameworks, vulnerability scanning, and asset inventory tracking to reduce the attack surface [13].

2. Risks of Legacy Systems

The attack disproportionately affected systems running outdated or unsupported operating systems, such as Windows XP and Windows 7 [9]. Many of these environments lacked basic security configurations, making them vulnerable to lateral movement. WannaCry emphasized the necessity of phasing out legacy systems or, where decommissioning is not immediately possible, isolating them with strict network segmentation and limited permissions [14].

3. Global Cybersecurity Collaboration

WannaCry revealed substantial gaps in international cybersecurity collaboration. The speed and scale of the outbreak prompted organizations like Europol, INTERPOL, and national CERTs to coordinate incident response and information sharing [15]. The event catalyzed discussions on establishing cross-border cyber threat intelligence networks, shared early warning systems, and best practice dissemination for incident containment [16].

D. Summary

The WannaCry attack illustrated the dangers of unpatched vulnerabilities, the catastrophic impact ransomware can have on critical sectors, and the urgent need for coordinated global responses [1], [7]. It demonstrated how a single unmitigated exploit could be weaponized to shut down hospitals, disrupt logistics, and trigger economic loss on a global scale [4]. As ransomware continues to evolve, examining historical breaches like WannaCry offers invaluable insight into proactive defense, cyber hygiene enforcement, and policy design—all critical components of building a more resilient cybersecurity ecosystem [17].

Ransomware has undergone significant transformation in recent years, shifting from isolated attacks to a highly organized, multi-layered cyber threat. The following analysis highlights ransomware trends from 2020 to 2024, illustrating how these attacks have evolved in scope, complexity, and impact. Understanding these trends is critical for anticipating future risks and developing adaptive cybersecurity responses [1].

A. Yearly Ransomware Trends and Industry Impact

Year	Key Development	Description
2020	Remote Work Exploitation	COVID-19 exposed unpatched endpoints, phishing increased
2021	Rise of RaaS	Affiliate models enabled mass deployment of ransomware
2022	Law Enforcement Disruptions	Temporary decline after REvil and DarkSide dismantled
2023	Critical Infrastructure Targeting	Attacks on ICS, OT, and government escalated
2024	AI-Powered Multi-Stage Extortion (Projected)	Forecasted rise of persistent, AI-guided extortion strategies

Fig.3. Year-by-Year Ransomware Trends (2020–2024)

B. Notable Ransomware Variants and Methodologies

To understand how ransomware tactics have evolved, it is essential to examine major ransomware families and their attack techniques. Each variant highlights unique trends in propagation, encryption, and extortion strategy [1], [5].

Name	Year	Encryption Type	Delivery Method	Notable Impact
WannaCry	2017	AES (Wormable)	SMBv1 (EternalBlue)	Infected 230K+ systems, NHS crisis, global impact [8]
LockBit	2020	AES + RSA	RDP, phishing	Fast encryption, high-value targeting, public sector [9]
Ryuk	2018	AES-256	Emotet, TrickBot loaders	Healthcare shutdowns, hospital record encryption [10]
Conti	2020	AES	VPNs, RaaS, phishing	National emergency in Costa Rica, data leaks [11]
NotPetya	2016	Disk Wipe (MBR)	Supply chain compromise	Maersk, Merck outages, no recovery mechanism [12]

Fig.4. Comparison of Major Ransomware Variants

Section Summary

The escalation of ransomware tactics, particularly the adoption of AI-driven extortion methods, highlights the need for adaptive cybersecurity frameworks. Traditional endpoint protection and reactive incident response are no longer sufficient in the face of evolving multi-stage threats. The next section explores broader strategies to counter ransomware’s expanding threat, including proactive monitoring, Zero Trust policies, and collaborative intelligence sharing [7].

VII. CONCLUSION

Ransomware has evolved from a disruptive cyber nuisance into one of the most pressing global security threats, influencing geopolitical stability, public safety, and economic resilience [1], [2]. Its shift from isolated, financially

motivated attacks to sophisticated, multi-stage campaigns targeting critical infrastructure reflects a broader transformation in the cyber threat landscape [3]. While current defenses offer a baseline level of protection, they must evolve in parallel with emerging threats. Strengthening architectures such as Zero Trust and deploying AI-enhanced detection systems [4], [5] must be complemented by deeper research into the psychological manipulation tactics used by threat actors [6], as well as the financial infrastructures—including cryptocurrencies and affiliate networks—that sustain ransomware ecosystems [7], [8].

A multidisciplinary, proactive defense strategy is no longer optional—it is critical for outpacing ransomware’s rapid evolution and mitigating its growing global threat [9].

VIII. REFERENCES

- [1] S. Hoang, K. N. Hoang, S. N. D. Hoang, and V. T. Le, “Analyzing the ransomware kill chain,” *SN Comput. Sci.*, vol. 6, 2025. [Online]. Available: <https://link.springer.com/article/10.1007/s42979-025-03858-w>
- [2] S. Ali, A. Ali, M. Uzair, H. Amir, and R. Z. A. Bari, “Empowering cybersecurity: CyberShield AI integration of machine learning and deep learning for ransomware detection,” in *Proc. Int. Conf. Deep Learn. Appl.*, Springer, 2024. [Online]. Available: https://link.springer.com/chapter/10.1007/978-3-031-66705-3_7
- [3] M. Sharma, “Double extortion ransomware,” *Comput. Secur.*, vol. 131, 2023. [Online]. Available: <https://doi.org/10.1016/j.cose.2023.102874>
- [4] D. Sathish, R. Singh, and K. S. Subramanian, “Malware detection using federated learning,” *IEEE Syst. J.*, 2024. [Online]. Available: <https://doi.org/10.1109/JSYST.2024.10859994>
- [5] Y. Himeur, A. Alsulaiman, A. S. Al-Nuaimi, and F. Bensaali, “AI-based cyber threat modeling: A review,” *Artif. Intell. Rev.*, vol. 56, pp. 1081–1124, 2023. [Online]. Available: <https://doi.org/10.1007/s10462-022-10315-w>
- [6] IBM X-Force, “Threat Intelligence Index 2023,” IBM Corp., 2023. [Online]. Available: <https://www.ibm.com/reports/threat-intelligence>
- [7] Verizon, “2023 Data Breach Investigations Report,” Verizon Enterprise, 2023. [Online]. Available: <https://www.verizon.com/business/resources/reports/dbir/>
- [8] Symantec, “WannaCry ransomware: Technical analysis report,” Symantec, 2017. [Online]. Available: <https://symantec-enterprise-blogs.security.com/blogs/threat-intelligence/wannacry-ransomware-attack>
- [9] Kaspersky, “How LockBit ransomware exploits RDP,” SecureList, 2023. [Online]. Available: <https://securelist.com/lockbit-ransomware-analysis/108465/>
- [10] M. Rouse, “What is zero trust? Explained,” TechTarget, 2024. [Online]. Available: <https://www.techtarget.com/searchsecurity/definition/zero-trust-security>
- [11] ISACA, “The human side of ransomware: Social engineering & psychological pressure,” ISACA, 2022. [Online]. Available: <https://www.isaca.org/resources/news-and-trends/newsletters/atisaca/2022/volume-5/the-human-side-of-ransomware>
- [12] S. Kirubavathi and R. Anitha, “Ransomware threats in healthcare: An overview,” in *Cybersecurity and Resilience in the Digital Age*, Springer, 2024, pp. 201–219. [Online]. Available: https://link.springer.com/chapter/10.1007/978-3-031-38212-3_12
- [13] SonicWall, “2024 Cyber Threat Report,” SonicWall Inc., 2024. [Online]. Available: <https://www.sonicwall.com/resources/white-papers/cyber-threat-report/>
- [14] Europol, “Ransomware attacks targeting critical infrastructure: The Colonial Pipeline case,” Europol, 2022. [Online]. Available: <https://www.europol.europa.eu/media-press/newsroom/news/ransomware-attacks-targeting-critical-infrastructure>
- [15] CISA, “Stop ransomware guide: Updated version,” U.S. Cybersecurity and Infrastructure Security Agency, 2023. [Online]. Available: <https://www.cisa.gov/resources-tools/resources/stopransomware-guide>
- [16] A. Djenna, H. A. Nacer, and M. Abid, “Modeling the ransomware lifecycle and mitigation strategies,” in *Advances in Cybersecurity*, Springer, 2024, pp. 145–162. [Online]. Available: https://doi.org/10.1007/978-3-031-60391-4_6
- [17] Microsoft, “Lessons learned from the WannaCry ransomware attack,” Microsoft Security Blog, 2018. [Online]. Available: <https://www.microsoft.com/en-us/security/blog/2018/05/14/wannacry-ransomware-one-year-later/>
- [18] SonicWall, “2024 Cyber Threat Report: Global ransomware trends,” SonicWall Inc., 2024. [Online]. Available: <https://www.sonicwall.com/resources/white-papers/2024-cyber-threat-report/>