

1. K-Nearest Neighbors[1] (KNN) Review

- Pick k -nearest neighbors.
- Easy, intuitive, and effective.
- Not suitable for random data.
- Assumptions:
 - There is a pattern to discern.
 - Computationally, the algorithm calculates distance, sorts, and selects k nearest neighbors.
 - Data structures to facilitate this process include k-d trees and ball trees.
 - Example: Is the star a cat or a dog?
- k is a hyperparameter:
 - A hyperparameter is not learned or trained by the model.
 - You select the “best” k by tuning and training models on various different values of k .
 - Examples:
 - * Cross-validation
 - * Grid search

Cross-Validation[2]

- What determines the split? The amount of data you have.
- Most common splits are 80/20 or 70/30.
- The more training data you have, the better the model performance.




Figure 1: Model Training Process

Model Evaluation

How do we know whether a model is good? For classification models, we use the following metrics:

	+	-	
+	TP	FN	RP
-	FP	TN	RN
	PT	PN	GT

Figure 2: Confusion Matrix

- **Accuracy:** The proportion of correct predictions. $\frac{TP+TN}{TP+FP+TN+FN}$
- **Error Rate:** $1 - \text{Accuracy} = \frac{FP+FN}{GT}$
- **Precision:** Measures how well the model classifies positives. $\frac{TP}{TP+FP}$
- **Recall (Sensitivity):** Measures how many positive instances were correctly predicted. $\frac{TP}{TP+FN}$
- **Specificity:** Measures the proportion of true negatives correctly identified. $\frac{TN}{FP+TN}$
- **F-Score:** The harmonic mean of precision and recall. Best when $B = 1$.

2. Perceptron Algorithm

- First machine learning/AI algorithm, introduced by Frank Rosenblatt in 1957[3].
- The goal is to find a decision boundary or hyperplane to separate the data. There can be multiple decision boundaries.
- For non-linear decision boundaries, techniques like the kernel trick can be used to create a hyperplane.
- **Kernel Trick:** The kernel trick enables the perceptron to operate in higher-dimensional spaces by replacing the standard dot product with a kernel function. This kernel function effectively computes the dot product in a transformed, higher-dimensional space without explicitly performing the transformation. It acts as a similarity measure between points, corresponding to a dot product in that space. The trick works because the perceptron decision function is based solely on dots between data points. By substituting a kernel function, the perceptron can classify data in a higher-dimensional space, where it might become linearly separable, without the computational expense of transforming the points directly.
- Assumptions:
 - The data is linearly separable.
- Definition: Hyperplane
 - $\{(\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)\}$ where y are labels.
 - $\mathcal{H} = \{x_i \mid w^T x + b = 0\}$ where w is the vector of weights and b is the bias and $b \in \mathbb{R}$.
 - Goal is to find w and b .
- Code example of perceptron:

```

def perceptron(D, max_epochs=100):
    """
    Perceptron algorithm for binary classification.

    Input:
    - D: Training dataset, a list of tuples (x_i, y_i), where x_i is the feature vector
        and y_i is the label (-1 or 1).
    - max_epochs: Maximum number of iterations over the dataset.

    Output:
    - w: Learned weight vector (including bias term).
    """

    # Step 1: Initialize weight vector and bias to zero
    n_features = len(D[0][0]) # Number of features in x_i
    w = [0.0] * n_features # Weight vector
    b = 0.0 # Bias term

    # Step 2: Initialize misclassification counter
    m = 1 # Assume at least one misclassification

    # Step 3: Iterate until no misclassifications or max_epochs reached
    epoch = 0
    while m > 0 and epoch < max_epochs:
        m = 0 # Reset misclassification counter

        # Step 5: Iterate over all training examples
        for x_i, y_i in D:
            # Step 6: Check if the example is misclassified
            # Compute the dot product w · x_i, add bias, and check if y_i * (w · x_i + b) <= 0
            if y_i * (sum(w[j] * x_i[j] for j in range(n_features)) + b) <= 0:
                # Step 7: Update weight vector and bias
                for j in range(n_features):
                    w[j] += y_i * x_i[j]
                b += y_i
            m += 1 # Increment misclassification counter

        epoch += 1

    # Bundle weights and bias into a single vector
    w.append(b) # Append bias as the last element of w
    return w

```

- First machine learning/AI algorithm, introduced by Frank Rosenblatt in 1957.
- The goal is to find a decision boundary or hyperplane to separate the data. There can be multiple decision boundaries.
- For non-linear decision boundaries, techniques like the kernel trick can be used to create a hyperplane.

- Assumptions:
 - The data is linearly separable.
- Definition: Hyperplane
 - $\{(\vec{x}_1, y_1), (\vec{x}_2, y_2), \dots, (\vec{x}_n, y_n)\}$ where y are labels.
 - $\mathcal{H} = \{x_i \mid w^T x + b = 0\}$ where w is the vector of weights and b is the bias and $b \in \mathbb{R}$.
 - Goal is to find w and b .

1 Exploration (XPL) Problems

1. Is it possible to have 100% Sensitivity?
2. For multiple values of β , determine β 's effect on the F_β score.

References

- [1] Gongde Guo, Hui Wang, David Bell, Yaxin Bi, and Kieran Greer. Knn model-based approach in classification. In *On The Move to Meaningful Internet Systems 2003: CoopIS, DOA, and ODBASE: OTM Confederated International Conferences, CoopIS, DOA, and ODBASE 2003, Catania, Sicily, Italy, November 3-7, 2003. Proceedings*, pages 986–996. Springer, 2003.
- [2] Ron Kohavi. A study of cross-validation and bootstrap for accuracy estimation and model selection. In *International Joint Conference on Artificial Intelligence*, 1995.
- [3] Frank Rosenblatt. The perceptron: A probabilistic model for information storage and organization in the brain. Technical report, Cornell Aeronautical Laboratory, 1958.