Acme Test API Reference

Fictional REST API specification for retrieval and cross-document question answering | Version 1.0

1. Base URL and authentication

Base URL: **https://api.acme.test/v1**. All endpoints require a bearer token in the Authorization header: **Authorization: Bearer YOUR_TOKEN**. Tokens expire after 60 minutes. This is a fictional training API; the .test domain is not a live service.

2. GET /users/{user_id}

Returns one user. Example response fields: id (integer), name (string), email (string), active (boolean). A successful request returns HTTP 200. If the user does not exist, the API returns HTTP 404 with error code USER_NOT_FOUND.

3. GET /users

Returns a paginated list of users. Optional query parameters: page (default 1) and limit (default 20, maximum 100). Response includes data, page, limit and total. Invalid limit values return HTTP 400.

4. POST /users

Creates a user. Required JSON fields are name and email. The email must be unique. A successful creation returns HTTP 201 and the created user object. Missing required fields return HTTP 400; duplicate email returns HTTP 409.

5. PATCH /users/{user_id}

Updates one or more user fields. At least one supported field must be supplied. A successful update returns HTTP 200. Unknown users return HTTP 404.

6. Common status codes

• 200 OK: request succeeded.

• 201 Created: resource created successfully.

• 400 Bad Request: request validation failed.

• 401 Unauthorized: token is missing, invalid or expired.

• 404 Not Found: requested resource does not exist.

• 409 Conflict: resource conflicts with existing data.

• 500 Internal Server Error: unexpected server-side failure.

7. Rate limits

The API permits 100 requests per minute per token. When the limit is exceeded, the API returns HTTP 429 and a Retry-After header indicating the number of seconds to wait.

8. Pagination example

To request the third page with 25 users, call **GET /users?page=3&limit=25**. The maximum permitted limit remains 100.