



IPSEC TECHNICAL AUDIT & CONTROL-PLANE DISSECTION

IPsec VPN Technical Dissection & Stream Telemetry

Deterministic protocol evaluation, IKE negotiation transforms, ESP telemetry, and gateway configuration patches

Section 1: Capture & Interface Metadata

Capture source (live tap br-ipsec or uploaded PCAP), interface stats, total packet counts, and flow volume

CAPTURE SOURCE / INGESTION INTERFACE

Live Software Tap: br-ipsec (Overlay Interface)

ANALYSIS TIMEFRAME WINDOW

Live Telemetry (FULL): +0.0s - +15.0s (15.0s)

AGGREGATION GATEWAY

Enterprise Datacenter Core

OS: Ubuntu Linux 24.04 LTS
Interface: br-ipsec / eth0
Private IP: 172.28.0.2
VPN Daemon: StrongSwan v5.9.8
Multi-Peer

IPsec ESP

Aggregated IPsec ESP Mesh · 3 Active Peer Tunnels

Enc: AES-256-GCM · ICV: 128-bit
Tunnel Encapsulation: RFC 3948
Payload: Strictly Monotonic

EDGE PEER NODES

Distributed Tactical Nodes (3 Tunnels)

OS: Linux Tactical Endpoints
Interface: esp0 / eth1
Private IP: 172.28.0.x Subnet
VPN Daemon: StrongSwan Gateway

TOTAL PACKETS

2,793

Frames Ingested

FLOW VOLUME

1.66 MB

Encrypted Payload

AVG RATE

186 pkt/s

Throughput Velocity

PEAK RATE

209 pkt/s

Observed Burst

INTERFACE MTU

1500
bytes

UP / ACTIVE

DROPS / ERRORS

0 (0.00%)

Monotonic Verified



CONTROL-PLANE CRYPTOGRAPHIC NEGOTIATION

Deterministic Control-Plane Dissection

Deterministic state machine tracing, cryptographic proposal evaluation, and live Security Association parameters

Section 2: Deterministic Control-Plane Dissection

Exact IKEv1/IKEv2 exchange breakdown, SA proposals, negotiated encryption/PRF transforms, and active SPI pairs

IKE PROTOCOL EXCHANGES & HANDSHAKE SEQUENCE

RFC 7296 STATE MACHINE

IKE_SA_INIT (Exchange 34) [COMPLETED / SUCCESS] Initiator/Responder DH public keys and nonces exchanged. Enforced ECP-256 (Group 19).

IKE_AUTH (Exchange 35) [COMPLETED / SUCCESS] Mutual authentication executed via Pre-Shared Key. Initial Child SA established with AES-256-GCM.

CREATE_CHILD_SA (Exchange 36) [MONITORED] Child SA rekeying evaluated. No ephemeral DH transform negotiated (PFS not enforced).

ACTIVE SECURITY ASSOCIATION (SPI) PAIRS

KERNEL XFRM STATE

INITIATOR SPI
0x8b14e9f28a1c9034

RESPONDER SPI
0x4a7c10b83f09de21

INBOUND ESP SPI
0xc0a80102

OUTBOUND ESP SPI
0xc0a80103

NEGOTIATED TRANSFORMS & SECURITY ASSOCIATION PROPOSALS

COMPLIANCE VERIFIED

TRANSFORM TYPE	IKE SA NEGOTIATED	CHILD SA NEGOTIATED	COMPLIANCE	BENCHMARK STANDARD
Encryption Algorithm	AES-256-GCM	AES-256-GCM	APPROVED	RFC 8221 / CNSA 2.0
Key Exchange (Diffie-Hellman)	ECP-256 (Group 19)	None (PFS Disabled)	NON-COMPLIANT	NIST SP 800-77 §4.2
Pseudo-Random Function (PRF)	HMAC-SHA2-256	N/A (AEAD Suite)	APPROVED	RFC 7296
Integrity / Authentication	Built-in (128-bit ICV)	Built-in (128-bit ICV)	APPROVED	NIST SP 800-77 Rev 1
Extended Sequence Numbers (ESN)	N/A	64-bit ESN Active	APPROVED	RFC 4303 §2.2.1



DATA-PLANE STREAM TELEMETRY & SEQUENCE INTEGRITY

Data-Plane Stream Dynamics & Telemetry


High-frequency packet arrival profiling, inter-arrival time (IAT) distribution, sequence monotonicity, and burst cadence

Section 3: Data-Plane (ESP) Stream Telemetry

Packet size histograms, Inter-Arrival Time (IAT) statistics, and sequence counter progression

PACKET SIZE DISTRIBUTION HISTOGRAM

BINNED MTU



INTER-ARRIVAL TIME & SEQUENCE INTEGRITY

RFC 4303

MEAN IAT
2.36 ms

MEDIAN IAT
1.82 ms

JITTER (σ)
0.48 ms

MIN / MAX
0.12 ms / 18.40 ms

Sequence Monotonicity: 100.0% Strict Monotonic | Out of Order: 0 packets (0.00%)
Rollover Protection: SAFE (64-bit Extended Sequence Numbers active)
Anti-Replay Verification: RFC 4303 64-packet bitmap verified; 0 duplicate packets accepted

THROUGHPUT TIMELINE & BURST RATE DYNAMICS

● Observed Rate (pkt/s) ● Identified Burst Window



Traffic Spike (00:15 – 00:18)

Burst of high-throughput encrypted packet activity.

Large Transfer (00:27 – 00:30)

Elevated data payload transmission cluster.

Throughput Dip (00:41 – 00:43)

Activity briefly stabilized to baseline keepalive rate.

Session Steady (00:49 – 00:56)

Continuous isochronous frame cadence observed.




AI/ML PAYLOAD INFERENCE & REMEDIATION PATCHES

Inference Classification & Hardening Patches

Autonomous payload categorization, covert timing analysis, and production-ready gateway configuration directives

Section 4: AI/ML Inference Analysis

Operating mode determination (Tunnel vs. Transport) and inner encrypted traffic classification with model confidence intervals



Section 5: Implementation Remediation Patches

Actionable gateway configuration blocks ready to apply on target gateways (e.g., swanctl.conf, Cisco CLI)



VALIDATION COMMANDS:

```
$ swanctl --load-all && swanctl --initiate --child apex-child

$ swanctl --list-sas | grep -E 'AES_GCM|ECP_256'    $ ip xfrm state | grep -E 'proto esp|replay-window|sel'

$ tcpdump -ni any esp -vv -c 5
```



FORENSIC PACKET TRACE & PLATFORM ATTESTATION

Session Packet Trace & Audit Verdict

Complete deterministic packet ledger, raw telemetry export, and official cryptographic verification verdict

Section 6: Raw Session Trace Index

Appendix listing individual packet indices, exchange types, and flow JSON dumps

FORENSIC PACKET TRACE INDEX

DETERMINISTIC PACKET DISSECTION

PKT #	OFFSET	LAYER / PROTO	TYPE / EXCHANGE	SPI IDENTIFIER	LENGTH	DISSECTION SUMMARY
#1	+0.000s	UDP 500	IKE_SA_INIT (Req)	Initiator=0x8b14e9f2...	384 B	DH Group 19 proposal exchange
#2	+0.014s	UDP 500	IKE_SA_INIT (Resp)	Responder=0x4a7c10b8...	384 B	DH public key confirmation
#3	+0.028s	UDP 4500	IKE_AUTH (Req)	Initiator=0x8b14e9f2...	448 B	PSK mutual identity authentication
#4	+0.042s	UDP 4500	IKE_AUTH (Resp)	Responder=0x4a7c10b8...	448 B	Child SA creation and Traffic Selectors
#5	+0.056s	ESP (50)	ESP Stream Data	Inbound=0xc0a80102	1420 B	Seq #1 Monotonic AES-256-GCM payload
#6	+15.00s	ESP (50)	ESP Stream Data	Inbound=0xc0a80102	1420 B	Seq #2,793 Monotonic verified

RAW FLOW TELEMETRY JSON DUMP

RFC 8221 & SDX COMPATIBLE

```
{
  "session_id": "AV-20260916-TECH-7046",
  "protocol": "IPsec ESP / IKEv2",
  "endpoints": {
    "initiator": "172.28.0.2",
    "responder": "172.28.0.x Subnet"
  },
  "ike_transforms": {
    "encryption": "AES-256-GCM",
    "dh_group": "ECP-256 (Group 19)",
    "prf": "HMAC-SHA2-256"
  },
  "esp_transforms": {
    "encryption": "AES-256-GCM",
    "pfs": "None (PFS Disabled)",
    "esn": "active"
  },
  "stream_telemetry": {
    "total_packets": 2793,
    "volume_mb": 1.66,
    "avg_pps": 186,
    "peak_pps": 209
  },
  "side_channel": {
    "entropy": 7.98,
    "packet_size_clustering": 0.84,
    "traffic_profile": "Mixed Tactical & Voice Traffic"
  }
}
```

OVERALL TECHNICAL VERDICT

The analyzed IPsec session demonstrates hardened packet transport with AES-256-GCM encryption and strictly monotonic sequence progression. Implementing the provided swanctl / Cisco PFS remediation configuration will upgrade forward secrecy to meet NSA CNSA 2.0 and NIST SP 800-77 requirements.