

Aegis-24 Setup Guide

Environment Configuration

1. Environment Variables

Copy the example environment file:

```
cp harness/.env.example .env
```

Edit `.env` with your configuration:

```
# LLM Configuration
OPENAI_API_KEY=sk-your-api-key-here

# Guardrails Configuration
GUARDRAILS_CONFIG=config/guardrails_policy.json

# Observability (Optional)
PHOENIX_ENDPOINT=http://localhost:6000
LANGSMITH_API_KEY=lsv2_your-api-key-here
LANGSMITH_PROJECT=aegis-24

# E2B Sandbox (Optional)
E2B_API_KEY=e2b_your-api-key-here

# Database (Optional)
DATABASE_URL=postgresql://user:pass@localhost:5432/aegis24

# Redis (Optional, for deduplication)
REDIS_URL=redis://localhost:6379

# Slack Webhook (Optional, for alerts)
SLACK_WEBHOOK_URL=https://hooks.slack.com/services/YOUR/WEBHOOK/URL
```

2. Guardrails Policy

The guardrails policy is configured in `config/guardrails_policy.json` :

```

{
  "policy_version": "1.0.0"
  "guardrails":
    "input_guardrail":
      "enabled": true
      "block_prompt_injection": true
    }
    "output_guardrail":
      "enabled": true
      "redact_pii": true
      "enforce_financial_disclaimers": true
  }
  "escalation":
    "confidence_threshold": 0.5
  }
}

```

3. Agent Configuration

Configure agents in `config/agents.yaml` :

```

agents:
  ingestion_agent:
    max_throughput: 1000
    timeout_seconds: 360
  }
  research_agent:
    max_iterations: 10
    score_threshold: 0.8
  }
  security_agent:
    confidence_threshold: 0.8
  }
}

```

4. MCP Servers

Configure external data sources in `config/mcp_servers.json` :

```
{
  "mcp_servers": [
    {
      "sec_edgar": {
        "uri": "https://www.sec.gov/cgi-bin/browse-edgar",
        "rate_limit": 10
      },
      "github_api": {
        "uri": "https://api.github.com",
        "auth_type": "bearer token"
      }
    }
  ]
}
```

Arize Phoenix Setup

Local Phoenix Server

```
pip install arize-phoenix
python phoenix_server.py
```

Configure in `.env` :

```
PHOENIX_ENDPOINT=http://localhost:6006
```

LangSmith Setup

1. Create account at <https://smith.langchain.com>
2. Generate API key
3. Configure in `.env` :

```
LANGSMITH_API_KEY=lsv2_your-key
```

```
LANGSMITH_PROJECT=aegis-24
```

Docker Deployment (Optional)

```
docker-compose up -d
```

This starts:

- PostgreSQL database
- Redis cache
- Aegis-24 application

Verification

Run verification script:

```
python scripts/setup_phoenix.py
```

Expected output:

```
Phoenix endpoint configured: http://localhost:6000
```

```
Tracing enabled: True
```

Next Steps

1. Run tests: `pytest tests/ -v`
2. Run red team: `make run-redteam`
3. Generate audit report: `make generate-audit`