

Machine Learning: Collaborative Filtering



Recommender System

- **Goal:** To identify items that we like
- It **predicts user preference** for a set of items based on **users' past behaviour and feedback**.
- This system is personalizing user's web experience.
 - E.g. telling what to buy (Amazon), which movies to watch (Netflix, TikTok), whom to be friends with (Facebook), which songs to listen (Spotify) etc.

Everyday Examples of Collaborative Filtering

amazon Deliver to TING Skudai 81300 All machine learning

Today's Deals Customer Service Buy Again TING's Amazon.com Browsing History Gift Cards Sell Registry

Books Advanced Search New Releases Best Sellers & More Children's Books Textbooks Textbook Rentals Magazines Best Books of the Month

Books > Computers & Technology > Computer Science

You last purchased this item on October 8, 2018.
[View this order](#)

Deep Learning (Adaptive Computation and Machine Learning series) Illustrated Edition
by Ian Goodfellow (Author), Yoshua Bengio (Author), Aaron Courville (Author)
★★★★☆ 1,385 ratings

Kindle \$50.99 **Hardcover** \$17.73 **Other Sellers** See all 4 versions

Rent
Due Date: Aug 10, 2021 Rental Details
• FREE return shipping at the end of the semester.
• Access codes and supplements are not guaranteed with rentals.
In Stock. Rented from Amazon Warehouse, Fulfilled by Amazon

FREE Shipping \$17.73
List Price: \$80.00
Save: \$62.27 (78%)

This item cannot be shipped to your selected delivery location. Please choose a different delivery location.

Deliver to TING - Skudai 81300
[Add to Cart](#)

Customers who viewed this item also viewed

Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow
Aurélien Géron
★★★★☆ 1,944
Paperback
#1 Best Seller in Data Processing
\$31.99

Deep Learning with Python
François Chollet
★★★★☆ 899
Paperback
#1 Best Seller in Speech & Audio Processing
\$27.48

Mathematics for Machine Learning
Marc Peter Deisenroth
★★★★☆ 257
Paperback
\$46.99

Pattern Recognition and Machine Learning (Information Science and Statistics)
Christopher M. Bishop
★★★★☆ 448
Hardcover
\$24.96

The Elements of Statistical Learning: Data Mining, Inference, and Prediction, Second...
Trevor Hastie
★★★★☆ 715
Hardcover
\$46.50


Deep Learning (MIT Press Essential Knowledge series)
John D. Kelleher
★★★★☆ 187
Paperback
40 offers from \$7.95

Reinforcement Learning, second edition: An Introduction (Adaptive Computation and...
Richard S. Sutton
★★★★☆ 281
Hardcover
\$30.98

Page 1 of 8

User feedback


- **Explicit feedback:** Direct preferences given by the user to the item (e.g., user rating) ★★★★★
- **Implicit feedback :** Indirect feedback, gathered from user behaviour (e.g. number of views, clicks, shares likes, visited/brought objects etc.).




Recommender System

- Two common approaches:
 - Content based
 - **Collaborative Filtering**

Collaborative filtering is a method of making **automatic predictions (filtering)** about the interests of a user **by collecting preferences from many users (collaborating)**




Content based Filtering



- ❑ **Main Idea:** Recommend items similar to the items previously liked by the user
- ❑ Example:
 - **Movie recommendations:** Recommend movies with the same actor(s), director, and genre.
 - **Websites, blogs, news:** Recommend other sites with “similar” content
- ❑ It requires a sufficient amount of information about the content of the items


Collaborative Filtering (CF)



- ❑ **Main Idea:** Use input/behavior of all previous users to make future recommendation
- ❑ Recommend items to a user based on the items liked by **another set of users whose rating pattern (like & dislike) are similar to the user**
- ❑ Example:
 - **Movie recommendations:** Recommend movies watched by similar user
- ❑ It's domain-free - It does not look at the details of content, only looks at who is rating the content & what is the rating
- ❑ Make use of **similarity between users** past feedback/preferences (**user-based CF**)

Collaborative Filtering

- **Collaborative filtering** is a method to predict a user's rating on particular item by comparing one user to all other users.
- *For example:*
To predict *PersonA* rating on a particular item,
 - Compute the similarity between *PersonA* with all users.
 - Find the top users who are most similar to the *PersonA*
 - Predict ratings of *PersonA* on the item based on the rating of similar users.



Why Collaborative Filtering?

- It benefits from large user bases.
- It's flexible across different domains.
- It produces the level of recommendations required.
- It can capture more nuance around items.

Collaborative Filtering Process


Data Collection -> Data Processing -> Calculate Referrals -> Derive Results

- **Data collection:** Collecting user behaviour and associated data items
- **Data processing:** Processing the collected data
- **Recommendation Calculation:** The recommended calculation method used to calculate referrals
- **Derive the result:** Extract the similarity, sort it, and extract the top N to complete

Memory-based Collaborative Filtering

Memory-based (neighborhood approach) CF recommends items by finding similarities between users or items

- **User-based CF:** To recommend items to a user based on another set of users with a similar rating pattern to the user
- **Item-based CF:** To recommend items with the most similarity with the user's other favourite items.




Collaborative Filtering – User based

It calculates the **similarity between users** to make implicit recommendation.

Steps:

1. Calculate the similarity between *PersonA* and all other users.
2. Predict the ratings of items for *PersonA* based on similar users.
3. Select top-N rated items for *PersonA*.




Collaborative Filtering – Item based

It calculates the **similarity between items** to make implicit recommendation

Steps:

1. Calculate the similarity between any two items to get item-item similarity matrix.
2. Predict the ratings of items for *PersonA* based on similar items.
3. Select top-N rated items for *PersonA*.



User-Based Vs Item-Based CF



The procedure of memory-based collaborative filtering RS

User-based CF

	Item					
	p1	p2	p3	p4	p5	p6
a	5	4	4	?	?	2
b	4	?	?	2	4	3
c	2	2	3	?	5	?
d	3	5	?	3	4	?
e	1	?	2	5	?	3

Active user: a

Calculate similarity of neighbors

Item-based CF

	Item					
	p1	p2	p3	p4	p5	p6
a	5	4	4	?	?	2
b	4	?	?	2	4	3
c	2	2	3	?	5	?
d	3	5	?	3	4	?
e	1	?	2	1	?	3

Active item: p4

Calculate similarity of neighbor items

User-Item matrix

For both user-based or item-based CF, the **computation of similarity is based on the preference for the item.**

The features used to calculate similarity can be user's purchase frequency, user's preference rating, number of product clicks, or a combination of all of these.

How to get similarity?

❑ Cosine similarity:


- Measures the **cosine of the vector angle between ratings of two users**
- If cosine value is 1, two users are completely similar in their preference,
- if cosine value is -1, they are completely dissimilar
- Similar to Pearson correlation, which measures correlation between two users

❑ Euclidean distance:

- Measures distance in rating/preference between two users
- If the distance is small, two users have a similar preference (i.e., the similarity is high).

$$\text{sim}(u, u') = \cos(\theta) = \frac{\mathbf{r}_u \cdot \mathbf{r}_{u'}}{\|\mathbf{r}_u\| \|\mathbf{r}_{u'}\|}$$

$\|\cdot\|$ = Norm (magnitude) of vector



Collaboration Filtering (User-based): Walkthrough Example

User-Item matrix

Name	Star Trek	Star wars	Superman	Batman	Hulk
Harry	4	2	?	5	4
John	5	3	4	?	3
Rob	3	?	4	4	3


Aim: Recommend top-2 movies
to Harry

Collaborative Filtering – User based(same as slide 17)

It calculates the **similarity between users** to make implicit recommendation.

Steps:

1. Calculate the similarity between *PersonA* and all other users.
2. Predict the ratings of items for *PersonA* based on similar users.
3. Select top-N rated items for *PersonA*.



Collaboration Filtering: Walkthrough Example (user-based)

Step 1: Calculate the similarity between Harry and all other users

Name	Star Trek	Star wars	Superman	Batman	Hulk
Harry	4	2	?	5	4
John	5	3	4	?	3
Rob	3	?	4	4	3

Cosine similarity

$$\text{sim}(u, u') = \cos(\theta) = \frac{\mathbf{r}_u \cdot \mathbf{r}_{u'}}{\|\mathbf{r}_u\| \|\mathbf{r}_{u'}\|} = \sum_i \frac{r_{ui} r_{u'i}}{\sqrt{\sum_i r_{ui}^2} \sqrt{\sum_i r_{u'i}^2}}$$

r_{ui} - value of ratings user u gives to item i

Collaboration Filtering: Walkthrough Example (user-based)

Step 1: Calculate the similarity between Harry and all other users

Name	Star Trek	Star wars	Superman	Batman	Hulk
Harry	4	2	?	5	4
John	5	3	4	?	3
Rob	3	?	4	4	3

$$\text{sim}(u, u') = \sum_i \frac{r_{ui}r_{u'i}}{\sqrt{\sum_i r_{ui}^2} \sqrt{\sum_i r_{u'i}^2}}$$

r_{ui} - value of ratings user u gives to item i

Cosine similarity

$$\begin{aligned}\text{Sim}(\text{Harry}, \text{John}) &= \frac{(4*5)+(2*3)+(4*3)}{\text{sqrt}(4^2+2^2+4^2)*\text{sqrt}(5^2+3^2+3^2)} \\ &= 0.97\end{aligned}$$

$$\begin{aligned}\text{Sim}(\text{Harry}, \text{Rob}) &= \frac{(4*3)+(5*4)+(4*3)}{\text{sqrt}(4^2+5^2+4^2)*\text{sqrt}(3^2+4^2+3^2)} \\ &= 1.00\end{aligned}$$

$$r_{\text{Harry}} = \begin{bmatrix} 4 \\ 2 \\ 4 \end{bmatrix} \quad r_{\text{John}} = \begin{bmatrix} 5 \\ 3 \\ 3 \end{bmatrix}$$

$$r_{\text{Harry}} = \begin{bmatrix} 4 \\ 5 \\ 4 \end{bmatrix} \quad r_{\text{Rob}} = \begin{bmatrix} 3 \\ 4 \\ 3 \end{bmatrix}$$

Collaboration Filtering: Walkthrough Example (user-based)

Step 2: Predict the ratings of movies for Harry

Name	Star Trek	Star wars	Superman	Batman	Hulk
Harry	4	2	?	5	4
John	5	3	4	?	3
Rob	3	?	4	4	3

Predicted rating is calculated based on aggregation of some similar users' rating of the item

$$r_{u,i} = k \sum_{u' \in U} \text{simil}(u, u') r_{u',i}$$

U – set of similar users {John, Rob}

with normalising factor

$$k = 1 / \sum_{u' \in U} |\text{simil}(u, u')|,$$

Calculate k as a normalising factor $k = \frac{1}{(0.97+1)} = 0.51$

$$\begin{aligned} R(\text{Harry}, \text{Superman}) &= k * ((\text{sim}(\text{Harry}, \text{John}) * R(\text{John}, \text{Superman})) + (\text{sim}(\text{Harry}, \text{Rob}) * R(\text{Rob}, \text{Superman}))) \\ &= 0.51((0.97 * 4) + (1 * 4)) = 4.02 \end{aligned}$$

Collaboration Filtering: Walkthrough Example (user-based)

Step 3: Select top-2 rated movies for Harry

Name	Star Trek	Star wars	Superman	Batman	Hulk
Harry	4	2	4.02	5	4
John	5	3	4	?	3
Rob	3	?	4	4	3

$Top-2(Harry, movies) = \text{Batman, Superman}$

Model-based Collaborative Filtering

- ❑ Latent factor model-based CF learns the (latent) user and item profiles through **matrix factorisation**
- ❑ **Matrix factorisation:** Factor a large matrix into some smaller representation of the original matrix through **alternating least squares**. The product of lower dimensional matrices equals the original one
- ❑ Example: Factor the rating matrix **R** into user matrix **U** and item matrix **V**

User-Item matrix

	item 1	item 2	item 3	...	item n
user 1					
user 2					
user 3					
user 4					
user 5					
user 6					
user 7					
user 8					
...					
user n					

R

$N \times M$

Latent features (or factors)

	feature 1	feature 2
user 1		
user 2		
user 3		
user 4		
user 5		
user 6		
user 7		
user 8		
...		
user n		

U

$N \times r$

	item 1	item 2	item 3	...	item n
feature 1					
feature 2					

V

$r \times M$

r = number of latent features (rank)


Alternating least squares

- ALS method aims to estimate the user and item factor matrices (**U** & **V**) such that their product will approximate the original rating matrix **R**.
- This is achieved by minimizing **root mean square error (RMSE)** between the original ratings **R** and the predicted values $\hat{\mathbf{R}}$

ALS Procedure:

Optimizing alternately to find **U**, **V**

- Randomly initialize **U** and **V**
- Iterating the following steps:
 - Fixing **U** → Optimizing **V**
 - Fixing **V** → Optimizing **U**
- Each iteration will minimize the square errors



Collaborative filtering in Spark

- `spark.ml` currently supports **model-based collaborative filtering**, in which users and products are described by **a small set of latent factors** that can be used to predict missing entries.
- `spark.ml` uses the Alternating Least Squares (ALS) algorithm to learn these latent factors.

Challenges of Collaborative Filtering

- Cold Start Problem
- Data sparsity can affect the quality of user-based recommenders
- Scaling can be challenging for growing datasets as the complexity can become too large. Item-based recommenders are faster than user-based when the dataset is large.
- You might observe that the recommendations tend to be already popular, and the items from the long tail section might get ignored.