





SWIGGY ANALYSIS



Presented by Saransh Garg

INTRODUCTION



Swiggy is India's go-to food delivery app, making it easy to satisfy cravings with just a few taps. It's known for its fast deliveries, a wide range of restaurant options, and frequent discounts. Whether you're in the mood for local street food or a fancy dinner, Swiggy's got you covered. Plus, with features like Swiggy Genie, you can get almost anything delivered—not just food. It's all about convenience and variety, right at your doorstep!

-
- **Display all customers who live in 'Delhi'.**

```
SELECT  
  *  
FROM  
  customers  
WHERE  
  city = "Delhi";
```

-
- Find the average rating of all restaurants in 'Mumbai'.

```
SELECT  
city, AVG(rating)  
FROM  
restaurants  
WHERE  
city = "Mumbai"  
GROUP BY city;
```

-
- List all customers who have placed at least one order.

```
SELECT DISTINCT  
  customers.name  
FROM  
  customers  
JOIN  
orders ON customers.customer_id = orders.customer_id;
```

-
- Display the total number of orders placed by each customer.

```
SELECT
customers.name, COUNT(orders.order_id) AS total_orders
FROM
customers
LEFT JOIN
orders ON customers.customer_id = orders.customer_id
GROUP BY customers.name;
```

-
- Find the total revenue generated by each restaurant.

```
SELECT
restaurants.name, COALESCE(SUM(orders.total_amount), 0)
FROM
restaurants
LEFT JOIN
orders ON orders.restaurant_id = restaurants.restaurant_id
GROUP BY restaurants.name;
```

-
- Find the top 5 restaurants with the highest average rating.

```
SELECT  
name, rating  
FROM  
restaurants  
ORDER BY rating DESC  
LIMIT 5;
```


-
- Display all customers who have never placed an order.

```
SELECT DISTINCT
  customers.name
FROM
  customers
LEFT JOIN
orders ON customers.customer_id = orders.customer_id
WHERE
  orders.order_id IS NULL;
```

-
- Find the number of orders placed by each customer in 'Mumbai'.

```
SELECT
customers.name, COUNT(orders.order_id)
FROM
customers
LEFT JOIN
orders ON customers.customer_id = orders.customer_id
WHERE
customers.city = "Mumbai"
GROUP BY customers.name;
```

-
- Display all orders placed in the last 30 days.

```
SELECT  
  *  
FROM  
  orders  
WHERE  
order_date >= DATE_SUB(CURDATE(), INTERVAL 30 DAY);
```

-
- List all delivery partners who have completed more than 1 delivery

```
SELECT
deliverypartners.name, COUNT(orderdelivery.order_id)
FROM
deliverypartners
JOIN
orderdelivery ON deliverypartners.partner_id =
orderdelivery.partner_id
JOIN
deliveryupdates ON deliveryupdates.order_id = orderdelivery.order_id
WHERE
deliveryupdates.status <> "Failed"
GROUP BY deliverypartners.name
HAVING COUNT(orderdelivery.order_id) > 1;
```

-
- Find the customers who have placed orders on exactly three different days.

```
SELECT
customers.name
FROM
customers
JOIN
orders ON customers.customer_id = orders.customer_id
GROUP BY customers.name
HAVING COUNT(DISTINCT orders.order_date) = 3;
```

-
- Find the delivery partner who has worked with the most different customers.

```
SELECT
    deliverypartners.partner_id,
    deliverypartners.name,
    COUNT(DISTINCT orders.customer_id) AS diff_customers
FROM
    deliverypartners
JOIN
    orderdelivery ON deliverypartners.partner_id =
        orderdelivery.partner_id
JOIN
    orders ON orderdelivery.order_id = orders.order_id
GROUP BY deliverypartners.partner_id, deliverypartners.name
ORDER BY diff_customers DESC
LIMIT 1;
```

-
- Identify customers who have the same city and have placed orders at the same restaurants, but on different dates.

```
SELECT DISTINCT
  c1.name AS customer1,
  c2.name AS customer2,
  c1.city,
  r.name AS restaurant,
  o1.order_date AS order_date1,
  o2.order_date AS order_date2
FROM
  Customers c1
  JOIN
    Orders o1 ON c1.customer_id = o1.customer_id
  JOIN
    Orders o2 ON o1.restaurant_id = o2.restaurant_id
  JOIN
    Customers c2 ON c1.city = c2.city
  AND c1.customer_id <> c2.customer_id
  AND o2.customer_id = c2.customer_id
  JOIN
    Restaurants r ON o1.restaurant_id = r.restaurant_id
WHERE
  o1.order_date <> o2.order_date
ORDER BY c1.city , r.name , o1.order_date;
```

THANK YOU

for your time and attention

*Please Like, Share & Do
Comment*
