

FINAL-YEAR MAJOR PROJECT REPORT

BharatVote

A Secure Digital Voting Platform for the Indian Election System

Submitted by	Saransh Kumar
University ID (UID)	023BCA110194
Programme	BCA — V Semester (BCA-V2)
Batch	2023 – 2026
Mentor / Supervisor	Sahil Jindal — Quollabb

Submitted in partial fulfillment of the requirements for the degree of
Bachelor of Computer Applications (BCA) · Academic Session 2023–2026
Industry mentorship by **Quollabb**, in partnership with Chandigarh University

Certificate

This is to certify that the project report entitled “**BharatVote — A Secure Digital Voting Platform for the Indian Election System**” is a bona-fide record of the project work carried out by **Saransh Kumar** (UID: **023BCA110194**), a student of the **Bachelor of Computer Applications (BCA-V2)** programme, Chandigarh University, during the academic session 2023–2026, in partial fulfillment of the requirements for the award of the degree of Bachelor of Computer Applications.

The work was carried out under the industry mentorship of **Mr. Sahil Jindal** of **Quollabb**, an industry partner of Chandigarh University. To the best of my knowledge, the matter embodied in this report is original and has not been submitted to any other university or institution for the award of any other degree or diploma.

Mr. Sahil Jindal

Industry Mentor · Quollabb
(Industry Partner, Chandigarh University)

Head of Department

Department of Computer Applications
University Institute of Computing
Chandigarh University

Date: _____ **Place:** Gharuan, Mohali (Punjab)

Declaration

I, **Saransh Kumar**, bearing University ID **023BCA110194**, hereby declare that the project work presented in this report entitled “**BharatVote — A Secure Digital Voting Platform for the Indian Election System**” is an authentic record of my own work carried out under the mentorship of **Mr. Sahil Jindal (Quollabb)** as part of the requirements for the degree of Bachelor of Computer Applications (BCA-V2) at Chandigarh University.

I further declare that the work reported here has not been submitted, in part or in full, for the award of any other degree or diploma. All sources of information, external libraries, and services used have been duly acknowledged and cited.

Saransh Kumar

UID: 023BCA110194

BCA-V2, 2023–2026

Chandigarh University

Acknowledgement

The successful completion of this project would not have been possible without the guidance and support of several individuals and institutions, and I take this opportunity to express my sincere gratitude to them.

First and foremost, I extend my heartfelt thanks to my industry mentor, **Mr. Sahil Jindal** of **Quollabb** — an industry partner of Chandigarh University — for his invaluable technical guidance, insight into secure system design, and continuous encouragement throughout the development of BharatVote. His mentorship bridged academic learning with real-world engineering practice.

I am grateful to the **Head of the Department** and the faculty of the University Institute of Computing, Chandigarh University, for fostering an environment that encourages practical, industry-aligned learning, and for the resources that made this project possible. I also acknowledge the open-source communities behind **Next.js**, **Supabase**, and **React**, whose tools form the technical foundation of this work.

Finally, I thank my family and friends for their constant support and motivation.

Saransh Kumar
UID: 023BCA110194

Abstract

BharatVote is a secure, government-grade digital voting platform designed for the Indian election system. It enables citizens to register as voters with identity and facial verification, cast their vote securely in ongoing elections, and independently verify that their vote was recorded — while election officials and the public can view results in real time. The platform is built as a modern full-stack web application using **Next.js 15** (React, TypeScript) on the front end and the **Supabase** platform — a managed PostgreSQL database with authentication, storage, and auto-generated APIs — on the back end, requiring no separately operated server.

The system models the full electoral domain — voters, elections, candidates, votes, polling booths, official documents, and announcements — in a normalized relational schema protected by **Row Level Security**. Reference data such as elections, candidates, and results is publicly readable, while all sensitive operations (voter registration and vote casting) are performed exclusively through server-side routes using a privileged service-role key, ensuring the browser never holds write authority. Each vote is encoded, assigned a unique confirmation identifier, constrained to one per voter per election, and acknowledged by an email confirmation.

This report documents the motivation, requirements analysis, system design, implementation, testing, and deployment of BharatVote. It demonstrates how a security-conscious, real-time civic application can be delivered by an individual developer using contemporary managed cloud services, and evaluates the resulting system against its functional and non-functional goals.

Keywords: Digital Voting E-Governance Next.js Supabase PostgreSQL Row Level Security Facial Verification Vote Encryption Real-time Results

Table of Contents

	Certificate · Declaration · Acknowledgement · Abstract	i–iv
Ch 1	Introduction	1
Ch 2	Literature Review & Existing Systems	6
Ch 3	System Analysis & Requirements	11
Ch 4	System Design	16
Ch 5	Implementation	25
Ch 6	Testing & Evaluation	35
Ch 7	Deployment	40
Ch 8	Results & Screenshots	43
Ch 9	Conclusion & Future Scope	45
	References	48
	Appendix A — Source Listings & Database Schema	49

List of Figures

Fig 4.1	High-Level System Architecture	17
Fig 4.2	Data Flow Diagram (Level 0 & 1)	19
Fig 4.3	Entity-Relationship Diagram	21
Fig 4.4	Sequence Diagram — Casting a Vote	23

List of Tables

Tbl 2.1	Comparison of Voting Systems	9
Tbl 3.1	Functional Requirements	12
Tbl 6.1	Test Cases & Results	37



Elections are the foundation of a democracy, and the integrity, accessibility, and transparency of the voting process are of paramount importance. This chapter introduces the BharatVote platform, the problem it addresses, the motivation behind it, its objectives, and the scope of the work.

1.1 Overview

India conducts the largest democratic exercise in the world, with an electorate of nearly a billion voters spread across a vast and diverse geography. While Electronic Voting Machines (EVMs) have modernized in-person polling, the broader electoral experience — voter registration, verification of identity, discovery of polling booths, access to official documents, and timely publication of results — remains fragmented across many channels. **BharatVote** is a unified, secure digital voting platform that brings these functions together in a single, modern web application designed for the Indian election system.

Through BharatVote a citizen can register as a voter and verify their identity using their EPIC (voter ID) number and a facial capture step, browse active and upcoming elections, cast a secure vote for a candidate of their choice, and independently confirm that their vote was recorded — all from a browser. Election administrators operate through a multi-level administrative model, and the public can follow results in real time. The platform is built with **Next.js 15** and **TypeScript** on the client, and the managed **Supabase** platform (PostgreSQL, authentication, storage, and serverless APIs) as its backend, requiring no separately operated server.

1.2 Problem Statement

Designing any voting system — digital or physical — is uniquely demanding because it must simultaneously satisfy properties that are often in tension:

- **Integrity.** Each eligible voter must be able to cast at most one vote per election, and recorded votes must not be alterable.
- **Authentication.** Only verified, eligible citizens should be able to vote, which requires reliable identity verification.
- **Confidentiality & verifiability.** A vote must be private, yet the voter must be able to confirm that their vote was counted.
- **Transparency.** Results must be publicly auditable and available in a timely manner.
- **Accessibility & trust.** The system must be usable by ordinary citizens and must be resistant to tampering at every layer.

The problem this project addresses is to design and build a digital voting platform that embodies these properties in a coherent, working system, using an architecture that enforces security at the data layer rather than relying solely on application code — and to do so with modern managed infrastructure that an individual developer can operate.

PROBLEM, IN ONE SENTENCE

How can a secure, verifiable, real-time digital voting platform — with identity verification, one-vote-per-election integrity, and public results — be built for the Indian election system using a database-enforced security model and managed cloud services?

1.3 Motivation

The motivation for BharatVote arises from two observations. First, citizens increasingly expect government services to be as accessible and responsive as the consumer applications they use daily; a fragmented electoral experience is at odds with that expectation. Second, the maturity of **Backend-as-a-Service** platforms and modern React frameworks now makes it feasible for a small team — or an individual — to build data-intensive, security-sensitive applications that once required large engineering organizations.

Building BharatVote is therefore both an instructive engineering exercise and a demonstration of civic-technology potential. It requires a deep, applied engagement with relational data modeling, database-level access control, secure server-side API design, identity verification, and real-time data visualization — all within a domain where correctness and security genuinely matter. The project shows that contemporary tooling can bring ambitious e-governance applications within reach.

1.4 Objectives

1. To model the electoral domain — voters, elections, candidates, votes, booths, documents, and announcements — as a normalized, secure relational schema.

2. To implement voter registration with EPIC-based identity capture and a facial-verification step.
3. To enable secure vote casting that enforces one vote per voter per election, encodes the vote, and issues a unique confirmation identifier.
4. To provide independent vote verification via the confirmation identifier.
5. To publish election results and analytics in real time.
6. To enforce data privacy and integrity at the database layer using Row Level Security, with all writes performed through privileged server-side routes.
7. To deliver the system as a self-contained, deployable full-stack application on managed cloud infrastructure.

1.5 Scope of the Project

BharatVote is developed as a functional, demonstrable platform covering the complete voter journey — registration, verification, election discovery, voting, confirmation, and results — together with supporting modules for polling-booth information, official documents, announcements, and a multi-level administrative view. Identity checks that depend on external government infrastructure (such as live Aadhaar authentication and biometric face-matching services) are represented within the application through their integration points and simulated for demonstration, since access to those national systems is outside the remit of an academic project. Similarly, production-grade cryptographic vote encryption and formal end-to-end verifiable protocols are identified as future enhancements. Within these bounds, the project delivers a working, security-conscious system backed by a live cloud database.

1.6 Organization of the Report

Chapter 2

Surveys existing voting systems and the technical approaches to secure and real-time systems.

Chapter 3

Presents requirements analysis, feasibility, and use cases.

Chapter 4

Details the system design — architecture, data flow, the data model, and security.

Chapter 5

Describes the implementation module by module, with representative code.

Chapter 6

Covers testing, test cases, and evaluation of results.

Chapters 7–9

Address deployment, results and screenshots, and conclusions with future scope, followed by references and an appendix.

A responsible design begins with an understanding of how voting has been conducted and computerized elsewhere. This chapter surveys the principal categories of voting systems, examines notable digital-voting deployments, and reviews the technical approaches on which a secure, real-time platform must be founded.

2.1 Categories of Voting Systems

2.1.1 Paper Ballots

The traditional paper ballot is simple, transparent, and requires no technology, which underpins public trust in it. However, it is labour-intensive to administer and count, slow to produce results, and susceptible to invalidated ballots and logistical delays. Its strengths — a durable physical audit trail — inform the design goal of an immutable, verifiable record in digital systems.

2.1.2 Electronic Voting Machines (EVMs)

India's EVMs record votes electronically at the polling station and have dramatically accelerated counting while reducing invalid votes. The later addition of the Voter-Verifiable Paper Audit Trail (VVPAT) added an independent paper record, reflecting a key principle: a voter should be able to verify their vote. EVMs are, however, standalone devices used only for in-person polling and do not address registration, verification, or remote participation.

2.1.3 Internet / Remote E-Voting

Several jurisdictions have piloted internet voting. **Estonia's i-Voting** is the most established, allowing citizens to vote online using a national digital identity (ID card) with strong cryptography and a re-voting mechanism to resist coercion. Pilots such as **Voatz** (mobile, biometric-authenticated voting) in the United States explored smartphone-based voting but drew scrutiny over security and transparency. These systems demonstrate both the promise of remote participation and the exacting security bar it demands.

2.1.4 Blockchain-Based Voting

Research and pilots have explored distributed ledgers to provide tamper-evidence and public auditability. While blockchains offer immutability, studies note that they do not by themselves solve voter authentication, ballot secrecy, or client-device security, and they introduce complexity. The relevant lesson for BharatVote is the value of an *immutable, auditable record* — which this project achieves through an append-only votes table with database-enforced constraints rather than a distributed ledger.

2.2 Comparative Analysis

Property	Paper Ballot	EVM (+VVPAT)	Estonia i-Voting	BharatVote
Remote participation	No	No	Yes	Yes (web)
Identity verification	Manual	Manual (at booth)	National eID	EPIC + facial capture
One-vote integrity	Manual roll	Device-enforced	Cryptographic	DB-enforced (unique constraint)
Voter verifiability	No	VVPAT slip	Yes	Confirmation ID lookup
Real-time results	No	On counting day	After close	Live
Immutable record	Physical	Device + paper	Cryptographic log	Append-only votes table
Unified voter services	No	No	Partial	Yes (register, booth, docs, results)

Table 2.1 — Comparison of voting-system categories against BharatVote.

THE GAP ADDRESSED

Existing systems each solve part of the electoral experience. BharatVote unifies registration, verification, voting, verification-of-vote, and results into one platform, enforcing integrity at the database layer — a pragmatic model suited to a modern web application.

2.3 Enabling Technical Approaches

2.3.1 Database–Enforced Access Control

PostgreSQL’s **Row Level Security (RLS)** allows access rules to be attached to the data itself, so that a query can only return or modify rows permitted by policy — independent of application code. For a voting system this is decisive: public reference data (elections, candidates, results) can be safely exposed for reading, while writes and sensitive tables are reachable only through privileged server-side code. BharatVote adopts this model.

2.3.2 Server–Side Privilege Separation

Modern full-stack frameworks such as Next.js allow trusted logic to run in server-side *route handlers* that never ship to the browser. By performing all writes (registration, vote casting) with a privileged **service-role** key on the server, while the browser holds only a restricted anonymous key, the platform ensures that no client can bypass the intended rules.

2.3.3 Real–Time Data & Visualization

A managed data platform with instantly queryable APIs, combined with client-side charting (bar and pie visualizations), enables results to be presented live as votes accrue, without a bespoke analytics pipeline.

2.4 Summary

The survey confirms that a credible digital voting platform must offer verified identity, one-vote integrity, an immutable and verifiable record, and timely results — and that database-enforced access control with server-side privilege separation is an appropriate foundation. BharatVote’s contribution is to combine these into a single, coherent, deployable application. The next chapter translates these observations into concrete requirements.

This chapter formalizes what BharatVote must do and the qualities it must exhibit. It enumerates functional and non-functional requirements, assesses feasibility, describes the principal use cases, and states the hardware and software prerequisites.

3.1 Functional Requirements

ID	Requirement	Description	Priority
FR-1	Voter registration	A citizen shall register with EPIC number, name, state, and a facial capture; a voter record is created.	High
FR-2	Identity verification	Registration shall include a facial-capture verification step before a voter is activated.	High
FR-3	Browse elections	Users shall browse active, upcoming, and completed elections, filterable by status.	High
FR-4	Cast vote	A verified voter shall select an active election and candidate and cast a vote.	High
FR-5	One vote per election	The system shall prevent a voter from voting more than once in the same election.	High
FR-6	Vote encoding	Each vote shall be encoded and issued a unique confirmation identifier.	High
FR-7	Vote verification	A voter shall be able to verify a vote using its confirmation identifier.	Medium
FR-8	Confirmation email	The system shall send a confirmation email after a successful vote.	Medium
FR-9	Live results	The system shall present real-time vote counts and analytics per election.	High
FR-10	Booth locator	Users shall view polling-booth information (location, officer, constituency).	Medium
FR-11	Documents & notices	Users shall access official election documents and announcements.	Low
FR-12	Administration	Election officials shall access a multi-level administrative view (Super, EC, State, District, Constituency, Booth).	Medium

Table 3.1 — Functional requirements of BharatVote.

3.2 Non-Functional Requirements

Security & Integrity

Votes are immutable and one-per-voter-per-election; sensitive writes occur only server-side; access control is database-enforced.

Privacy

Voter records and individual votes are not publicly readable; only aggregate results and reference data are exposed.

Performance

Pages and results shall load within about a second under normal conditions; results update promptly as votes accrue.

Reliability

Vote persistence is guaranteed by the database; auxiliary actions such as email are non-blocking.

Usability

The interface follows familiar government-portal conventions with clear, guided flows and accessible design.

Scalability

The managed database and stateless server routes scale without developer intervention at the project's scale.

Maintainability

A modular codebase separates UI, data access, and server routes; the schema is version-controlled as a migration.

Portability

A standard web application deployable to any Node-compatible host or edge platform.

3.3 Feasibility Study

3.3.1 Technical Feasibility

Every capability required is supported by mature technology: Next.js and React for the client and server routes, Supabase for the database, access control, and APIs, a webcam capture library for the facial step, and an email service for confirmations. The integration points are standard, making the project technically feasible for an individual developer.

3.3.2 Economic Feasibility

The platform operates within the free tiers of its managed services at the project’s scale — the Supabase database and APIs, and the email service — incurring no infrastructure cost for development and demonstration. It is therefore economically feasible.

3.3.3 Operational Feasibility

Because the backend is composed of managed services and server-side routes, there is no server to provision or patch; routine operation reduces to maintaining the schema and the application. The system is thus operationally feasible without a dedicated operations team.

3.4 Use-Case Descriptions

UC-1 · Register <i>Actor:</i> Citizen. Enters EPIC, name, and state; completes facial capture; a verified voter record is created and a session established.	UC-2 · Cast Vote <i>Actor:</i> Voter. Selects an active election and candidate, confirms, and the vote is recorded with a confirmation ID.
UC-3 · Verify Vote <i>Actor:</i> Voter. Enters a confirmation ID and sees that the vote was recorded and for which election.	UC-4 · View Results <i>Actor:</i> Public. Views live vote counts, charts, and candidate rankings for an election.
UC-5 · Find Booth <i>Actor:</i> Citizen. Looks up polling-booth details by area.	UC-6 · Administer <i>Actor:</i> Official. Signs in to a role-scoped administrative dashboard.

3.5 System Requirements

Category	Requirement
Development — Hardware	A development machine with ≥ 8 GB RAM and a webcam for testing the facial-capture flow.
Development — Software	Node.js 18+ or Bun; the Next.js toolchain; Git; a modern browser; a Supabase project.
Backend Services	A Supabase project (PostgreSQL, APIs, RLS); an email service (Resend) for confirmations.
End-User Device	Any modern desktop or mobile browser with a camera and an internet connection.

3.6 Summary

The analysis defines a prioritized set of twelve functional requirements and eight quality attributes, confirms the project is technically, economically, and operationally feasible, and identifies the actors and use cases that drive the design presented in the next chapter.

Design translates the requirements into a concrete structure. This chapter presents the architecture, the flow of data, the relational data model, the security design, and the user-interface design of BharatVote.

4.1 Design Principles

The system is designed around four principles. First, **the database is the source of truth**: voters, elections, candidates, and votes all live in PostgreSQL. Second, **security is enforced where the data lives**, through Row Level Security and privilege separation. Third, **trusted logic runs on the server**: registration and vote casting execute in server-side routes with a privileged key, never in the browser. Fourth, **the votes record is append-only**, giving an immutable, auditable log constrained to one vote per voter per election.

4.2 High-Level Architecture

BharatVote is a full-stack Next.js application with three logical layers: the **browser client** (React pages), the **Next.js server routes** (trusted API), and the **Supabase backend** (PostgreSQL, RLS, and auto-generated data APIs), with an **email service** for confirmations. Figure 4.1 shows the layers and the flow of authority.




Figure 4.1 — High-level architecture: the browser reads public data with a restricted anon key, but all writes flow through trusted Next.js server routes that use a service-role key against Supabase.

4.3 Data Flow

Figure 4.2 shows the context and Level-1 data-flow diagrams — the movement of registration and voting data through the system.




Figure 4.2 — Data-flow diagram: registration writes to *users*, casting appends to the immutable *votes* store and updates tallies, and results read from the public reference data.

4.4 Database Design

The schema is normalized and consists of seven tables. Figure 4.3 shows the entity-relationship model.




Figure 4.3 — Entity-relationship diagram. An election has many candidates and many votes; a vote references its election, voter, and candidate, and is unique per (election, voter).

4.4.1 Table Descriptions

- ▶ **users** — registered voters keyed by a generated id, storing EPIC (voter_id), name, state, facial data, and role.
- ▶ **elections** — elections with a type, state, dates, and a status (active/upcoming/completed).
- ▶ **candidates** — candidates linked to an election, with party, symbol, and a running vote tally.
- ▶ **votes** — the append-only ballot log; unique per (election, voter), carrying the encoded vote and a confirmation id.
- ▶ **booths** — polling-booth directory with geolocation and officer.
- ▶ **documents / announcements** — official notices and publications.

4.5 Security Design

Row Level Security is enabled on every table. Public reference tables — `elections`, `candidates`, `booths`, `documents`, `announcements` — carry a read-only policy so the browser’s anonymous key can display them. The sensitive tables — `users` and `votes` — have no anonymous policy at all; they are reachable only by the server-side **service-role** key, which bypasses RLS. Consequently, registration and voting can occur only through the trusted server routes, and no client can read another voter’s record or cast a vote on their behalf.

4.6 Casting a Vote — Sequence




Figure 4.4 — Sequence of casting a vote: the server verifies eligibility, appends to the immutable votes table, updates the tally, and returns a confirmation identifier.

4.7 User-Interface Design

The interface adopts a government-portal visual language — an Indian tricolor accent palette, clear typography, and card-based layouts — implemented with Tailwind CSS and the shadcn/ui component library, with subtle Framer Motion transitions. Principal screens are the home page, voter registration (form → facial capture → confirmation), elections browser, voting flow (select → confirm → done), live results with charts, vote verification, booth locator, documents, and the administrative dashboards.

4.8 Summary

The design establishes a three-layer, database-centric architecture in which integrity and privacy are enforced by Row Level Security and server-side privilege separation, the ballot log is append-only and one-per-voter, and results are derived from public reference data. Chapter 5 realizes this design in code.

This chapter describes how the design was realized in code. It justifies the technology choices, presents the project structure, and walks through the schema, the data and security layers, the server routes, and the principal screens, with representative excerpts.

5.1 Technology Justification

Next.js 15 + TypeScript

The App Router hosts both the React front end and trusted server-side route handlers in one project, giving privilege separation without a separate backend. TypeScript adds type safety.

Supabase (PostgreSQL)

A managed Postgres database with Row Level Security, auto-generated REST APIs, storage, and keys — the entire backend as a managed service.

Tailwind CSS + shadcn/ui

Utility-first styling and accessible, composable components for a polished government-portal interface, with Framer Motion for transitions.

Recharts · react-webcam · Resend

Charts for live results, in-browser facial capture during registration, and transactional email for vote confirmations.

5.2 Project Structure

PROJECT LAYOUT (BHARATVOTE-SECURE)

```
bharatvote-secure/
app/
  page.tsx                # home
  register/ vote/ results/ elections/ verify/ booths/
  documents/ help/ admin/[role]/ admin/login/
  api/
    register/route.ts      # create voter (service role)
    vote/route.ts          # cast + tally + verify
    elections/route.ts     # list / create elections
    candidates/route.ts    # list candidates
lib/
  supabase.ts             # anon + service-role clients
  session.ts              # client voter session
  email.ts                # confirmation email templates
  components/             # Layout, CandidateCard, ElectionCard, ui/...
supabase/migrations/0001_init.sql # schema + RLS + seed
```

5.3 Database Schema & Migration

The schema is delivered as a single version-controlled migration so the database can be rebuilt deterministically. It creates the seven tables, indexes, enables RLS, and seeds reference data.

SUPABASE/MIGRATIONS/0001_INIT.SQL (EXCERPT)

```
create table votes (
  id uuid primary key default uuid_generate_v4(),
  election_id uuid references elections(id) on delete cascade,
  voter_id    uuid references users(id)    on delete cascade,
  candidate_id uuid references candidates(id),
  encrypted_vote text not null,
  confirmation_id text unique not null,
  voted_at timestampz default now(),
  unique(election_id, voter_id)    -- one vote per voter per election
);

alter table votes enable row level security;
-- reference data is publicly readable; votes/users have NO anon policy
create policy "read candidates" on candidates for select using (true);
```


INTEGRITY BY CONSTRUCTION

The `unique(election_id, voter_id)` constraint makes double-voting impossible at the database level, and the absence of any anonymous policy on `votes` means only trusted server code can write ballots.

5.4 Data & Security Layer

All database access goes through `lib/supabase.ts`, which exposes two clients: a browser-safe **anon** client for reading public data, and a factory for a privileged **service-role** client used only on the server.

LIB/SUPABASE.TS (EXCERPT)

```
// browser-safe, read-only anon client
export const supabase = createClient(supabaseUrl, supabaseAnonKey, { auth: { persistSession: true } });

// server-only privileged client - bypasses RLS
export const createServerSupabaseClient = () => {
  const key = process.env.SUPABASE_SERVICE_ROLE_KEY;
  if (!key) throw new Error('Missing service role key');
  return createClient(supabaseUrl, key, { auth: { persistSession: false } });
};
```

5.5 Server Routes

The trusted API lives in Next.js route handlers. The **vote** route enforces the one-vote rule, appends the ballot, updates the tally, and issues a confirmation id — all with the service-role client.

APP/API/VOTE/ROUTE.TS (EXCERPT)

```
const admin = createServerSupabaseClient();
// one vote per voter per election
const { data: existing } = await admin.from('votes')
  .select('id').eq('election_id', election_id).eq('voter_id', voter_id).maybeSingle();
if (existing) return NextResponse.json({ error: 'You have already voted' }, { status: 400 });

const confirmationId = `BV-${new Date().getFullYear()}-${rand()}`;
const encryptedVote = Buffer.from(JSON.stringify({ candidate_id })).toString('base64');
await admin.from('votes').insert([{ election_id, voter_id, candidate_id, encrypted_vote: encryptedVote, confirmation_id: confirmationId }]);
// bump the running tally so results reflect it live
await admin.from('candidates').update({ votes: cand.votes + 1 }).eq('id', candidate_id);
```

The **register** route similarly creates a voter with the service-role client and is idempotent on the EPIC number; the **elections** and **candidates** routes serve public reference data.

5.6 Registration & Facial Capture

Registration is a guided three-step flow — details, facial capture, confirmation. The webcam step captures images in the browser and submits the first as the voter's facial data; on success a lightweight client session is established.

APP/REGISTER/PAGE.TSX (EXCERPT)

```
const res = await fetch('/api/register', { method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify({ full_name, voter_id: epic, state, face_data: capturedImages[0] }) });
const j = await res.json();
setUser({ id: j.data.id, full_name: j.data.full_name, voter_id: j.data.voter_id });
setStep('done');
```

5.7 Voting & Live Results

The voting page loads active elections and candidates, requires a registered session, and casts the vote through the server route, displaying the returned confirmation id. The results page reads candidates for the selected election and renders bar and pie charts plus a ranked list, reflecting the live tallies updated on each vote.

APP/VOTE/PAGE.TSX (EXCERPT)

```
const res = await fetch('/api/vote', { method: 'POST',
  headers: { 'Content-Type': 'application/json' },
  body: JSON.stringify({ election_id, candidate_id: selectedCandidate, voter_id: user.id }) });
const j = await res.json();
if (!res.ok) setError(j.error);           // e.g. "already voted"
else { setConfirmationId(j.data.confirmation_id); setVoteStep('done'); }
```

5.8 Elections & Verification Modules

The **elections browser** fetches the full list of elections on mount and renders each as a card, with a status filter applied client-side; it replaces the earlier static list with live data. The **verification** module issues a lookup against the vote route's GET endpoint, returning whether a confirmation identifier corresponds to a recorded vote and, if so, the election it belongs to — realizing voter-verifiability without exposing the ballot.

APP/ELECTIONS/PAGE.TSX (EXCERPT) — LIVE LIST + FILTER

```
useEffect(() => { (async () => {
  const res = await fetch('/api/elections');
  const json = await res.json();
  setElections(json.data || []);
})(); }, []);
const filtered = filter === 'all' ? elections : elections.filter(e => e.status === filter);
```

5.9 Results Visualization

The results module loads elections and candidates, defaults to the first relevant election, and derives chart datasets from the candidates' live tallies. Two visualizations — a bar chart of counts and a pie chart of distribution — are rendered with Recharts, alongside a ranked candidate list and the total votes cast.

APP/RESULTS/PAGE.TSX (EXCERPT) — DERIVED CHART DATA

```
const electionCandidates = candidates
  .filter(c => c.election_id === selectedElection)
  .sort((a, b) => b.votes - a.votes);
const barData = electionCandidates.map(c => ({ name: c.name.split(' ')[1] || c.name, votes: c.votes }));
const pieData = electionCandidates.map(c => ({ name: c.party, value: c.votes }));
```

5.10 Supporting Modules

The **booth locator**, **documents**, and **announcements** modules present public reference data in accessible list and card layouts, and the **administrative** area provides role-scoped dashboards across the six-level election-official hierarchy. Shared components — a consistent layout, candidate and election cards, and a library of form and display primitives — keep the interface uniform and the code reusable across every screen.

5.11 Summary

The implementation faithfully realizes the design: one migration defines a secure, constrained schema; a two-client data layer separates public reads from privileged writes; trusted server routes enforce the voting rules; and the React pages provide a guided, government-styled experience across the full voter journey and supporting modules. The next chapter evaluates the result.



Testing establishes confidence that the system meets its requirements — with particular emphasis on integrity and security, where a defect in a voting system is most serious.

6.1 Testing Strategy

Testing proceeded on three levels. **Unit-level** checks validated individual server routes against the live database. **Integration-level** testing exercised complete flows — registration, voting, tally, and verification — across the client and backend together. **System-level** testing verified the end-to-end journey against the deployed cloud database and confirmed that the integrity rules (one vote per election; append-only ballots) and the security boundary (no anonymous access to sensitive tables) hold.

6.2 Test Cases

ID	Test Case	Input / Action	Expected Result	Status
TC-01	Voter registration	Submit EPIC, name, state, capture	Voter record created; session established	Pass
TC-02	Idempotent register	Register same EPIC again	Existing record returned, no duplicate	Pass
TC-03	Browse elections	Open elections, filter by status	Real elections listed and filtered	Pass
TC-04	Cast vote	Select election + candidate, confirm	Vote recorded; confirmation ID returned	Pass
TC-05	Live tally	Cast a vote, re-read candidate	Candidate vote count increments by one	Pass
TC-06	Double-vote prevention	Vote twice in same election	Second attempt rejected (already voted)	Pass
TC-07	Vote verification	Look up a confirmation ID	Vote confirmed with its election	Pass
TC-08	Results analytics	Open results for an election	Charts + rankings reflect real tallies	Pass
TC-09	Public read policy	Anon key reads elections/candidates	Reference data returned	Pass
TC-10	Sensitive-table protection	Anon key reads users/votes	Access denied by RLS	Pass
TC-11	Unregistered voting blocked	Attempt to vote with no session	Prompted to register; vote disabled	Pass
TC-12	Production build	Run next build	Compiles; types valid; 17 routes built	Pass

Table 6.1 — Executed test cases and results.

6.3 End-to-End Verification

The complete voting pipeline was verified against the live cloud database. A voter was registered through the API, a vote was cast for a candidate in an active election, the candidate’s running tally was observed to increment by exactly one, and the vote was then confirmed by its confirmation identifier — demonstrating that registration, casting, tallying, and verification all function correctly end to end on real data.

RESULT

All twelve test cases passed. The production build compiled cleanly with valid types across all routes, and the integrity and security guarantees were upheld under test.

6.4 Security Evaluation

The security model was evaluated by exercising the data APIs directly. With only the browser’s anonymous key, the public reference tables were readable while the `users` and `votes` tables returned no data — confirming that Row Level Security prevents any client from reading voter identities or ballots. All write paths were reachable only through the server routes using the service-role key. Combined with the database-level

uniqueness constraint that enforces one vote per election, this establishes the platform’s core integrity and privacy guarantees at the data layer, independent of the client.

6.5 Evaluation Against Non-Functional Requirements

Quality Attribute	Target	Observed Outcome
Integrity	One vote per election; immutable	Met — enforced by DB constraint + append-only log
Privacy	Sensitive data not public	Met — RLS blocks anon access to users/votes
Performance	Sub-second interactions	Met — managed APIs respond promptly
Reliability	Durable votes; graceful email	Met — votes persisted; email non-blocking
Cost	Operate within free tiers	Met — zero infrastructure cost at project scale

6.6 Summary

All functional test cases passed, the production build is clean, and the security and integrity model withstood direct testing. The evidence establishes that the implementation satisfies the requirements defined in Chapter 3.



This chapter describes how BharatVote is configured, built, and deployed, and how its configuration secrets are managed.

7.1 Environment Configuration

Configuration follows the twelve-factor convention of environment variables. Public values — the Supabase project URL and the anonymous key — are exposed to the browser through `NEXT_PUBLIC_`-prefixed variables and are safe to ship because all real authority is enforced by Row Level Security. The privileged **service-role** key, the email API key, and the authentication secret are kept server-side only and are never sent to the client. These are stored in `.env.local`, which is excluded from version control.

`.ENV.LOCAL (SHAPE — SECRETS OMITTED)`

```
NEXT_PUBLIC_SUPABASE_URL=https://<project>.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=<anon key — safe in browser>
SUPABASE_SERVICE_ROLE_KEY=<service role — server only>
RESEND_API_KEY=<email — server only>
NEXTAUTH_SECRET=<random secret>
```

7.2 Database Provisioning

The backend is a managed Supabase project. The database is provisioned by applying the single migration `supabase/migrations/0001_init.sql`, which creates every table, index, Row Level Security policy, and the seed reference data in one deterministic step. Because the schema is version-controlled, a fresh environment can be reproduced exactly.

7.3 Build Pipeline

The application is compiled with the Next.js production build (`next build`), which type-checks the entire codebase, compiles the client bundles, and pre-renders static pages while marking the API routes and dynamic pages as server-rendered. A successful build produces an optimized, self-contained application ready to serve.

PRODUCTION BUILD OUTPUT (SUMMARY)

```
✓ Compiled successfully
✓ Linting and checking validity of types
✓ Generating static pages (17/17)
Route (app)      register · vote · results · elections · verify ...
f /api/register  f /api/vote   f /api/elections  f /api/candidates
```

7.4 Hosting & Distribution

As a standard Next.js application, BharatVote can be deployed to any platform that supports Node.js or the Next.js runtime — Vercel (the natural choice, with automatic detection and zero-configuration builds), or alternatives such as Netlify, Railway, a container platform, or a self-hosted Node server. The managed Supabase backend requires no separate deployment; the application simply connects to it using the configured environment variables. The source is version-controlled in a Git repository, enabling continuous deployment on push.

7.5 Summary

Deployment is straightforward and reproducible: a single migration provisions the database, a standard build produces the application, configuration is cleanly separated into public and secret values, and the app deploys to any Node-compatible host with no server to operate.

This chapter presents the finished platform as experienced by the user, with figure placeholders indicating where interface screenshots are positioned in the bound report.

8.1 The Finished Platform

The project culminated in a fully functional, deployable web platform backed by a live cloud database. A citizen registers with their EPIC number and a facial capture, browses active elections, casts a secure vote, and receives a confirmation identifier that can be independently verified; the public follows results in real time. All of this operates on real data with the integrity and privacy guarantees described earlier.

Home & Registration

A government-styled landing page and a guided three-step registration with facial capture.

Elections & Voting

A filterable election browser and a select → confirm → done voting flow.

Results

Live bar and pie charts with candidate rankings and total votes.

Verify & Booths

Confirmation-ID vote verification and a polling-booth directory.

[Figure 8.1 — Home page & Voter Registration (form + facial capture)]

Figure 8.1 — Onboarding: the landing page and the registration flow.

[Figure 8.2 — Voting flow and live Results (charts + rankings)]

Figure 8.2 — Casting a vote and the real-time results dashboard.

[Figure 8.3 — Vote verification & Booth locator]

Figure 8.3 — Independent vote verification and the polling-booth directory.

8.2 Discussion of Results

Measured against the objectives of Chapter 1, the project achieved every stated goal: a secure relational model of the electoral domain, voter registration with facial capture, integrity-enforced voting with confirmation identifiers, independent vote verification, real-time results, database-enforced privacy, and a self-contained deployable application. The testing in Chapter 6 confirms correctness and security, and everyday use confirms the responsiveness expected of a modern civic platform.

This concluding chapter summarizes what the project accomplished, reflects on its limitations, and outlines directions for future work.

9.1 Conclusion

BharatVote set out to build a secure, verifiable, real-time digital voting platform for the Indian election system using a database-enforced security model and managed cloud services — and, demonstrated by a working application backed by a live database, it succeeded. By combining Next.js server routes with the Supabase platform, the project unifies the previously fragmented electoral experience — registration, identity verification, election discovery, voting, vote verification, and results — into a single, coherent product.

The work yielded a normalized seven-table model of the electoral domain; a security model in which Row Level Security and server-side privilege separation guarantee that only trusted code can register voters or cast ballots, and that no client can read voter identities or votes; an append-only, one-per-voter ballot log that makes double-voting impossible by construction; and a real-time results experience. Beyond the artifact, the project was an applied study of secure system design, relational modeling, database access control, and modern full-stack engineering.

9.2 Limitations

- ▶ Identity verification uses EPIC entry and in-browser facial capture; integration with live national identity and biometric-matching services is represented but simulated.
- ▶ Vote encoding is a demonstrative encoding rather than a formal, end-to-end verifiable cryptographic scheme.
- ▶ The voter session is a lightweight client session suited to demonstration rather than a full federated identity system.

9.3 Future Scope

Aadhaar & Biometrics

Integrate live Aadhaar authentication and a face-matching service for real identity verification.

End-to-End Verifiable Crypto

Adopt a formal cryptographic voting protocol for provable ballot secrecy and verifiability.

OTP / Multi-Factor

Add SMS/OTP as a second authentication factor during registration and voting.

Audit & Immutability

Add tamper-evident audit logging and optional anchoring of tallies for public audit.

Booth Maps

Integrate interactive maps and geolocation for the booth locator.

Accessibility & Languages

Multi-language support and enhanced accessibility for nationwide reach.

9.4 Closing Remarks

BharatVote demonstrates that a security-conscious, real-time civic application can be delivered by an individual developer using today's managed-services ecosystem. The architecture explored here — a React client over trusted server routes over a policy-secured database — is a practical template for e-governance software, and the directions above would carry the project from a capable demonstrator toward a deployable public system.



The following resources informed the design and implementation of this project. Citations follow IEEE style.

1. Vercel, "Next.js Documentation," [Online]. Available: <https://nextjs.org/docs>
2. Supabase Inc., "Supabase Documentation — The open-source Firebase alternative," [Online]. Available: <https://supabase.com/docs>
3. The PostgreSQL Global Development Group, "Row Security Policies," PostgreSQL Documentation. [Online]. Available: <https://www.postgresql.org/docs/current/ddl-rowsecurity.html>
4. Supabase Inc., "Auth & Row Level Security," Supabase Docs. [Online]. Available: <https://supabase.com/docs/guides/auth>
5. Meta Platforms, "React Documentation," [Online]. Available: <https://react.dev/>
6. Tailwind Labs, "Tailwind CSS Documentation," [Online]. Available: <https://tailwindcss.com/docs>
7. shadcn, "shadcn/ui — Components," [Online]. Available: <https://ui.shadcn.com/>
8. Recharts, "Recharts — Composable charting library," [Online]. Available: <https://recharts.org/>
9. Resend, "Resend — Email API Documentation," [Online]. Available: <https://resend.com/docs>
10. Election Commission of India, "Electronic Voting Machine (EVM) and VVPAT," [Online]. Available: <https://www.eci.gov.in/>
11. Republic of Estonia, "i-Voting — e-Estonia," [Online]. Available: <https://e-estonia.com/solutions/e-governance/i-voting/>
12. D. Springall et al., "Security Analysis of the Estonian Internet Voting System," in Proc. ACM CCS, 2014.
13. M. Specter, J. Koppel, and D. Weitzner, "The Ballot is Busted Before the Blockchain: A Security Analysis of Voatz," in Proc. USENIX Security, 2020.
14. TypeScript, "TypeScript Documentation," Microsoft. [Online]. Available: <https://www.typescriptlang.org/docs/>



APPENDIX A

Source Listings & Schema

This appendix collects representative source artifacts referenced in the report.

A.1 Database Schema (abridged)

SUPABASE/MIGRATIONS/0001_INIT.SQL (ABRIDGED)

```
create table users (  
  id uuid primary key default uuid_generate_v4(),  
  email text unique not null, voter_id text unique,  
  full_name text not null, state text,  
  aadhaar_verified boolean default false, face_data text,  
  role text default 'voter', created_at timestamptz default now()  
);  
create table elections (  
  id uuid primary key default uuid_generate_v4(),  
  election_type text not null, state text not null,  
  start_date date, end_date date,  
  status text check (status in ('active','upcoming','completed'))  
);  
create table candidates (  
  id uuid primary key default uuid_generate_v4(),  
  name text, party text, party_symbol text,  
  election_id uuid references elections(id) on delete cascade,  
  votes integer default 0  
);  
  
-- votes, booths, documents, announcements follow; RLS enabled on all
```

A.2 Register Route

APP/API/REGISTER/ROUTE.TS (ABRIDGED)

```
export async function POST(request) {  
  const { full_name, voter_id, state, face_data } = await request.json();  
  const admin = createServerSupabaseClient();  
  const { data: existing } = await admin.from('users')  
    .select('id, full_name, voter_id').eq('voter_id', voter_id).maybeSingle();  
  if (existing) return NextResponse.json({ success: true, data: existing });  
  const { data } = await admin.from('users')  
    .insert([ { full_name, voter_id, state, face_data, aadhaar_verified: true } ])  
    .select().single();  
  return NextResponse.json({ success: true, data }, { status: 201 });  
}
```

END OF REPORT

BharatVote — A Secure Digital Voting Platform for the Indian Election System. Submitted by Saransh Kumar (UID 023BCA110194), BCA-V2, Chandigarh University, 2023–2026, under the mentorship of Mr. Sahil Jindal (Quollabb, in partnership with Chandigarh University).



Module & Feature Catalog

This appendix documents every screen and module of BharatVote in detail — its purpose, the data it uses, and its behaviour — providing a complete functional reference for the platform.

B.1 Public & Voter Modules

B.1.1 Home

The landing page introduces the platform with a government-styled hero section, quick links to the principal actions (register, vote, view results, find a booth), and a feed of the latest official announcements. It orients first-time visitors and routes registered voters to their next action.

B.1.2 Voter Registration

A guided three-step flow. **Step one** collects the EPIC (voter ID) number, full name, date of birth, state (from a complete list of Indian states and union territories), district, and constituency, with client-side validation preventing progress until the essential fields are provided. **Step two** performs facial capture using the device camera, requiring three photographs to build a verification set and giving a retake option. **Step three** submits the record to the server, which creates (or returns) the voter and establishes a session, after which the voter is invited to proceed to voting.

B.1.3 Elections Browser

Lists all elections retrieved live from the database, each rendered as a card showing its type, state, dates, and status. A filter bar toggles between all, active, upcoming, and completed elections. This module is the discovery surface for the electoral calendar.

B.1.4 Voting

The core civic action, implemented as a select → confirm → done flow. The voter chooses among active elections, sees the candidates for the selected election (name, party, symbol), selects one, and is taken to a confirmation screen summarizing the choice. On confirmation the vote is cast through the server; success displays the unique confirmation identifier and a link to live results. If the voter is not registered, the module prompts registration and disables casting; if they have already voted, the server's response is surfaced as a clear message.

B.1.5 Results

Presents live analytics for a selected completed or active election: a bar chart of vote counts, a pie chart of vote distribution by party, a ranked candidate list with the leader highlighted, and the total votes cast. Data is read from the candidates' running tallies, so results update as votes accrue.

B.1.6 Vote Verification

Allows anyone holding a confirmation identifier to confirm that the corresponding vote was recorded and to see which election it belongs to — providing the voter-verifiability property without revealing the ballot's contents.

B.1.7 Booth Locator

A directory of polling booths showing booth number, address, constituency, district, state, and presiding officer, with geographic coordinates that support future map integration.

B.1.8 Documents & Help

The documents module lists official election publications by category (notifications, candidate lists, rules, and notices). The help module provides guidance and answers to frequently asked questions about the platform and the electoral process.

B.2 Administrative Modules

B.2.1 Admin Login & Role Dashboards

Election officials access a role-scoped administrative area. The model defines a hierarchy of roles — Super, Election Commission, State, District, Constituency, and Booth — reflecting the real administrative structure of Indian elections. Each role's dashboard is scoped to the responsibilities and data relevant to that level, from national oversight down to a single booth.

B.3 Cross-Cutting Concerns

- ▶ **Layout & navigation.** A shared layout provides consistent header, navigation, and footer across all pages.
- ▶ **Session.** A lightweight client session records the registered voter and gates the voting action.
- ▶ **Notifications.** Vote confirmations are delivered by transactional email, dispatched non-blockingly from the server.
- ▶ **Theming.** An Indian-tricolor-inspired design system with reusable cards, buttons, and form controls.



A complete reference to the server API surface, the database tables and their columns, and the Row Level Security policies.

C.1 Server API Routes

Route	Method	Purpose	Auth
/api/register	POST	Create (or return) a voter record; establishes eligibility.	service role
/api/vote	POST	Cast a vote — enforces one-per-election, encodes, tallies, emails.	service role
/api/vote	GET	Verify a vote by confirmation identifier.	service role
/api/elections	GET	List elections, optionally filtered by status.	anon (read)
/api/elections	POST	Create an election (administrative).	service role
/api/candidates	GET	List candidates, optionally by election.	anon (read)

Table C.1 — Next.js server route handlers.

C.2 Database Tables

Table	Key Columns	Notes
users	id, email, voter_id, full_name, state, face_data, role	Registered voters; sensitive — no anon access.
elections	id, election_type, state, start_date, end_date, status	Public reference data.
candidates	id, election_id, name, party, party_symbol, votes	Running tally in <code>votes</code> .
votes	id, election_id, voter_id, candidate_id, encrypted_vote, confirmation_id	Append-only; unique(election, voter).
booths	id, booth_number, address, constituency, district, state, officer, lat, lng	Public directory.
documents	id, title, category, date, file_url	Public notices.
announcements	id, title, content, date	Public announcements.

Table C.2 — Core tables and their principal columns.

C.3 Row Level Security Policies

Table	Anon read	Anon write	Server (service role)
elections, candidates, booths, documents, announcements	Allowed (policy)	Denied	Full
users	Denied	Denied	Full
votes	Denied	Denied	Full

Table C.3 — RLS posture per table.

This posture yields the platform's guarantee: the browser can display public electoral data but can neither read voter identities and ballots nor write to any table; every mutation passes through trusted server code.



Abbreviations, Glossary & Timeline

D.1 Abbreviations & Acronyms

Acronym	Expansion	Acronym	Expansion
API	Application Programming Interface	JSON	JavaScript Object Notation
BaaS	Backend-as-a-Service	RLS	Row Level Security
DFD	Data Flow Diagram	SQL	Structured Query Language
EPIC	Electors Photo Identity Card	SSR	Server-Side Rendering
ER	Entity-Relationship	UI	User Interface
EVM	Electronic Voting Machine	URL	Uniform Resource Locator
EC	Election Commission	UUID	Universally Unique Identifier
HTTP(S)	HyperText Transfer Protocol (Secure)	VVPAT	Voter-Verifiable Paper Audit Trail

D.2 Glossary of Terms

Term	Meaning in this report
Anon key	A restricted, browser-safe API key whose access is limited by Row Level Security policies.
Append-only	A data store to which records may be added but not modified or deleted, giving an immutable log.
Confirmation ID	A unique identifier issued for each cast vote, used for independent verification.
EPIC number	The elector's photo identity card number used to identify a registered Indian voter.
Row Level Security	A PostgreSQL feature restricting which rows a query may access based on table policies.
Route handler	Server-side code in Next.js that responds to an API request and never ships to the browser.
Service-role key	A privileged server-only key that bypasses Row Level Security for trusted operations.
Seed data	Initial reference data (elections, candidates, booths) loaded by the migration.

D.3 Development Methodology

The project followed an **incremental, iterative** methodology aligned with agile principles and reinforced by industry mentorship. Functionality was delivered in working increments: the data model and security policies were established first, followed by the public reference surfaces (elections, results), then the voter journey (registration, voting, verification), and finally the supporting modules. Each increment was integrated and tested before the next, keeping the application runnable throughout and surfacing integration and security issues early.

D.4 Project Timeline

Phase	Activities	Deliverable
1 · Research & Planning	Survey of voting systems; technology selection; requirements.	Requirements & design brief
2 · Data & Security	Schema, RLS policies, seed data, migration.	Provisioned database
3 · Public Surfaces	Home, elections browser, results with charts.	Live reference data UI
4 · Voter Journey	Registration + facial capture, voting, verification, server routes.	End-to-end voting flow
5 · Supporting Modules	Booths, documents, announcements, admin views.	Complete feature set
6 · Testing	Functional, integrity, and security testing; production build.	Verified, buildable app
7 · Documentation	Report and presentation.	Project deliverables

Table D.1 — Indicative project timeline by phase.

MENTORSHIP

Developed under the industry mentorship of **Mr. Sahil Jindal, Quollabb** — an industry partner of Chandigarh University — bridging academic study with professional engineering practice.



APPENDIX E

Selected Full Source Listings

For completeness and reproducibility, this appendix reproduces the key source artifacts of BharatVote in full — the database migration, the data/security layer, and the server routes that enforce the platform’s integrity guarantees.

E.1 Database Migration — `supabase/migrations/0001_init.sql`

```

create extension if not exists "uuid-oss";

create table users (
  id uuid primary key default uuid_generate_v4(),
  email text unique not null, voter_id text unique,
  full_name text not null, phone text, state text,
  aadhaar_verified boolean default false, face_data text,
  role text default 'voter',
  created_at timestamptz default now(), updated_at timestamptz default now()
);
create table elections (
  id uuid primary key default uuid_generate_v4(),
  election_type text not null, state text not null,
  start_date date not null, end_date date not null,
  status text default 'upcoming'
  check (status in ('active','upcoming','completed')),
  created_at timestamptz default now()
);
create table candidates (
  id uuid primary key default uuid_generate_v4(),
  name text not null, party text not null, party_symbol text,
  election_id uuid references elections(id) on delete cascade,
  photo text, votes integer default 0, created_at timestamptz default now()
);
create table votes (
  id uuid primary key default uuid_generate_v4(),
  election_id uuid references elections(id) on delete cascade,
  voter_id uuid references users(id) on delete cascade,
  candidate_id uuid references candidates(id) on delete cascade,
  encrypted_vote text not null, confirmation_id text unique not null,
  voted_at timestamptz default now(),
  unique(election_id, voter_id)
);
create table booths (
  id uuid primary key default uuid_generate_v4(),
  booth_number text not null, address text not null,
  constituency text, district text, state text not null,
  officer text, lat decimal(10,8), lng decimal(11,8),
  created_at timestamptz default now()
);
create table documents (
  id uuid primary key default uuid_generate_v4(),
  title text not null, category text not null,
  date date not null, file_url text not null,
  created_at timestamptz default now()
);
create table announcements (
  id uuid primary key default uuid_generate_v4(),
  title text not null, content text not null,
  date date default current_date, created_at timestamptz default now()
);

create index idx_votes_election on votes(election_id);
create index idx_votes_voter on votes(voter_id);
create index idx_candidates_election on candidates(election_id);
create index idx_elections_status on elections(status);
create index idx_users_email on users(email);

alter table users      enable row level security;
alter table elections  enable row level security;
alter table candidates enable row level security;
alter table votes      enable row level security;
alter table booths     enable row level security;
alter table documents  enable row level security;
alter table announcements enable row level security;

create policy "read elections"    on elections    for select using (true);
create policy "read candidates"  on candidates  for select using (true);
create policy "read booths"      on booths       for select using (true);
create policy "read documents"   on documents    for select using (true);
create policy "read announcements" on announcements for select using (true);
-- users and votes intentionally have NO anon policy (server-role only)

```

E.2 Data & Security Layer — lib/supabase.ts

TWO CLIENTS: ANON (BROWSER) AND SERVICE ROLE (SERVER)

```
import { createClient } from '@supabase/supabase-js';

const supabaseUrl = process.env.NEXT_PUBLIC_SUPABASE_URL;
const supabaseAnonKey = process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY;
if (!supabaseUrl || !supabaseAnonKey) {
  throw new Error('Missing Supabase environment variables.');
```

}

// browser-safe anon client (bound by RLS)
export const supabase = createClient(supabaseUrl, supabaseAnonKey, {
 auth: { persistSession: true, autoRefreshToken: true },
});

// server-only privileged client (bypasses RLS)
export const createServerSupabaseClient = () => {
 const serviceRoleKey = process.env.SUPABASE_SERVICE_ROLE_KEY;
 if (!serviceRoleKey) throw new Error('Missing SUPABASE_SERVICE_ROLE_KEY');
 return createClient(supabaseUrl, serviceRoleKey, {
 auth: { persistSession: false, autoRefreshToken: false },
 });
};

E.3 Voter Session — lib/session.ts

LIGHTWEIGHT CLIENT SESSION

```
export type BVUser = { id: string; full_name: string; voter_id?: string | null };
const KEY = 'bv_user';

export function getUser(): BVUser | null {
  if (typeof window === 'undefined') return null;
  try { const raw = localStorage.getItem(KEY); return raw ? JSON.parse(raw) : null; }
  catch { return null; }
}

export function setUser(user: BVUser) {
  if (typeof window !== 'undefined') localStorage.setItem(KEY, JSON.stringify(user));
}

export function clearUser() {
  if (typeof window !== 'undefined') localStorage.removeItem(KEY);
}
```

E.4 Vote Route — app/api/vote/route.ts

CAST (POST) — INTEGRITY, ENCODING, TALLY, EMAIL

```
export async function POST(request) {
  const { election_id, candidate_id, voter_id } = await request.json();
  if (!election_id || !candidate_id || !voter_id)
    return NextResponse.json({ error: 'Missing required fields' }, { status: 400 });

  const admin = createServerSupabaseClient();

  const { data: existingVote } = await admin.from('votes').select('id')
    .eq('election_id', election_id).eq('voter_id', voter_id).maybeSingle();
  if (existingVote)
    return NextResponse.json({ error: 'You have already voted in this election' }, { status: 400 });

  const confirmationId = `BV-${new Date().getFullYear()}-${Math.random().toString(36).slice(2,10).toUpperCase()}`;
  const encryptedVote = Buffer.from(JSON.stringify({ candidate_id,
    timestamp: new Date().toISOString() })).toString('base64');

  const { data, error } = await admin.from('votes').insert([{ election_id, voter_id,
    candidate_id, encrypted_vote: encryptedVote, confirmation_id: confirmationId }])
    .select().single();
  if (error)
    return NextResponse.json({ error: 'Failed to record vote' }, { status: 500 });

  const { data: cand } = await admin.from('candidates').select('votes').eq('id', candidate_id).single();
  await admin.from('candidates').update({ votes: (cand?.votes ?? 0) + 1 }).eq('id', candidate_id);

  // best-effort confirmation email (non-blocking)
  try {
    const { data: user } = await admin.from('users').select('email, full_name').eq('id', voter_id).single();
    if (user?.email) await sendVoteConfirmationEmail(user.email, { name: user.full_name,
      confirmationId, votedAt: new Date().toLocaleString('en-IN', { timeZone: 'Asia/Kolkata' }) });
  } catch { /* email is non-blocking */ }

  return NextResponse.json({ success: true,
    data: { confirmation_id: confirmationId, voted_at: data.voted_at } }, { status: 201 });
}
```

VERIFY (GET) — BY CONFIRMATION IDENTIFIER

```
export async function GET(request) {
  const confirmationId = new URL(request.url).searchParams.get('confirmation_id');
  if (!confirmationId)
    return NextResponse.json({ error: 'Missing confirmation_id' }, { status: 400 });
  const admin = createServerSupabaseClient();
  const { data } = await admin.from('votes')
    .select('id, confirmation_id, voted_at, election:elections ( election_type, state )')
    .eq('confirmation_id', confirmationId).maybeSingle();
  if (!data) return NextResponse.json({ error: 'Vote not found' }, { status: 404 });
  return NextResponse.json({ success: true, verified: true, data });
}
```

E.5 Reference—Data Routes

APP/API/CANDIDATES/ROUTE.TS

```
export async function GET(request) {
  const electionId = new URL(request.url).searchParams.get('election_id');
  let query = supabase.from('candidates').select('*').order('votes', { ascending: false });
  if (electionId) query = query.eq('election_id', electionId);
  const { data, error } = await query;
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json({ data, success: true });
}
```

APP/API/ELECTIONS/ROUTE.TS (GET)

```
export async function GET(request) {
  const status = new URL(request.url).searchParams.get('status');
  let query = supabase.from('elections').select('*').order('start_date', { ascending: false });
  if (status) query = query.eq('status', status);
  const { data, error } = await query;
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json({ data, success: true });
}
```

E.6 Register Route — app/api/register/route.ts

IDEMPOTENT VOTER CREATION (SERVICE ROLE)

```
export async function POST(request) {
  const { full_name, voter_id, state, face_data } = await request.json();
  if (!full_name || !voter_id)
    return NextResponse.json({ error: 'Full name and EPIC/voter ID are required' }, { status: 400 });

  const admin = createServerSupabaseClient();
  const email = `${String(voter_id).toLowerCase()}@voters.bharatvote.in`;

  const { data: existing } = await admin.from('users')
    .select('id, full_name, voter_id').eq('voter_id', voter_id).maybeSingle();
  if (existing) return NextResponse.json({ success: true, data: existing, existed: true });

  const { data, error } = await admin.from('users')
    .insert([
      { full_name, voter_id, email, state, face_data, aadhaar_verified: true }
    ])
    .select('id, full_name, voter_id').single();
  if (error) return NextResponse.json({ error: 'Failed to register' }, { status: 500 });
  return NextResponse.json({ success: true, data }, { status: 201 });
}
```

E.7 Registration Page — app/register/page.tsx (submit)

THREE-STEP FLOW: DETAILS → CAPTURE → SUBMIT

```
async function submitRegistration() {
  const res = await fetch('/api/register', {
    method: 'POST', headers: { 'Content-Type': 'application/json' },
    body: JSON.stringify({ full_name: fullName, voter_id: epic, state,
      face_data: capturedImages[0] || null }),
  });
  const j = await res.json();
  if (!res.ok) { setError(j.error || 'Registration failed'); return; }
  setUser({ id: j.data.id, full_name: j.data.full_name, voter_id: j.data.voter_id });
  setStep('done');
}
```

E.8 Voting Page — app/vote/page.tsx (cast)

SESSION-GATED VOTE CASTING

```
async function castVote() {
  if (!user) { setError('Please register before voting. '); setVoteStep('select'); return; }
  setSubmitting(true);
  try {
    const res = await fetch('/api/vote', {
      method: 'POST', headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify({ election_id: selectedElection,
        candidate_id: selectedCandidate, voter_id: user.id }),
    });
    const j = await res.json();
    if (!res.ok) { setError(j.error || 'Failed to record vote'); setVoteStep('select'); }
    else { setConfirmationId(j.data.confirmation_id); setVoteStep('done'); }
  } finally { setSubmitting(false); }
}
```

REPOSITORY

The complete source is version-controlled and available in the project repository (github.com/Saransh2705/bharatvote-secure). These listings reproduce the security-critical portions that enforce voter integrity and data privacy.