TIMBER & TERRA ARCHITECTURAL SPECIFIER 2025

Pacific Northwest Luxury Outdoor Living & Engineering Standards

DOCUMENT REF: TT-SPEC-2025-V4 | DIVISION 06 15 00 WOOD DECKING

---

1. GEOTECHNICAL SUBSTRUCTURE & FOUNDATION PROTOCOL

- Level to Moderate Slopes (0 deg - 20 deg): Continuous spread footings to frost depth (min. 36 in).
- Severe Escarpments & Bluffs (21 deg - 45 deg+): Galvanized helical steel piles torqued to bedrock refusal.
- Hardware Standard: ASTM A153 hot-dipped galvanized & AISI Type 316 marine stainless fasteners.

2. TIMBER & POLYMER SUBSTRATE MATRIX

- FSC Brazilian Ipe: Janka hardness 3,680 lbf, Class A flame spread, 50-75+ year service lifespan.
- Genuine Cumaru Hardwood: Janka hardness 3,340 lbf, natural golden-brown tone, subterranean rot immunity.
- TimberTech AZEK Vintage: Capped cellular PVC core, zero annual oiling, stay-cool heat reflection.
- Thermally Modified Ash: Steam-stabilized domestic hardwood, 25-year structural exterior rating.

3. ARCHITECTURAL INTEGRATION SPECIFICATIONS

- Balustrades: Frameless 1/2 in monolithic tempered laminated structural glass with shoe base channel.
- Bioclimatic Pavilions: Motorized dual-wall extruded aluminum louvers with wind-sensor auto closure.
- Integrated Culinary: Natural gas line sleeve, 304 stainless chassis, reinforced cantilever joist bays.

4. WARRANTY & ESTIMATING DESK

- 25-Year Master Craftsmanship Warranty on all structural timber and framing joints.
- Fixed-Sum Binding Protocol: Subterranean anomalies absorbed upon completed geotechnical core drilling.

Direct Estimating Desk: (555) 846-2377 | Inquiries: estimating@timberterra.com | Seattle, WA