

**RAJALAKSHMI ENGINEERING
COLLEGE RAJALAKSHMI NAGAR, THANDALAM – 602**

105



**RAJALAKSHMI
ENGINEERING COLLEGE**
An AUTONOMOUS Institution
Affiliated to ANNA UNIVERSITY, Chennai

**CS23332 DATABASE MANAGEMENT
SYSTEMS LAB**

Laboratory Record Note Book

Name SARANYA . M

Year / Branch / Section : II/ CSE / A

University Register No. : 2116230701510

College Roll No. : 230701510

Semester : III SEM

Academic Year : 2024 - 2025

CS23332 DATABASE MANAGEMENT SYSTEMS

NAME	SARANYA .M
ROLL NO	230701510
DEPT	COMPUTER SCIENCE AND ENGINEERING
SEC	A

INDEX

S.NO	DATE	TITLE	SIGN
1	2-8-2024	Creation of base table and DLM operations	
2	5-8-2024	Data manipulation	
3	7-8-2024	Writing basic SQL select statement	
4	9-8-2024	Working with constraints	
5	21-8-2024	Creating views	
6	28-8-2024	Restricting and storing data.	
7	31-08-2024	Using Set Operators	
8	06-09-2024	Working with Multiple Tables	
9	07-09-2024	Subqueries	
10	21-09-2024	Aggregating Data Using Group Functions	
11	27-09-2024	Working with Joins	
12	04-10-2024	Creating and Managing Indexes	
13	05-10-2024	PL/SQL Programming with Control Structures	
14	18-10-2024	Procedures and Functions	

SQL Statements

1. Data Retrieval(DR)
2. Data Manipulation Language(DML)
3. Data Definition Language(DDL)
4. Data Control Language(DCL)
5. Transaction Control Language(TCL)

TYPE	STATEMENT	DESCRIPTION
DR	SELECT	Retrieves the data from the database
DML	1.INSERT 2.UPDATE 3.DELETE 4.MERGE	Enter new rows, changes existing rows, removes unwanted rows from tables in the database respectively.
DDL	1.CREATE 2.ALTER 3.DROP 4.RENAME 5.TRUNCATE	Sets up, changes and removes data structures from tables.
TCL	1.COMMIT 2.ROLLBACK 3.SAVEPOINT	Manages the changes made by DML statements. Changes to the data can be grouped together into logical transactions.
DCL	1.GRANT 2.REVOKE	Gives or removes access rights to both the oracle database and the structures within it.

DATA TYPES

1. Character Data types:

- Char – fixed length character string that can varies between 1-2000 bytes
- Varchar / Varchar2 – variable length character string, size ranges from 1-4000 bytes.it saves the disk space(only length of the entered value will be assigned as the size of column)
- Long - variable length character string, maximum size is 2 GB

2. Number Data types : Can store +ve, -ve, zero, fixed point, floating point with 38

precision.

- Number – {p=38,s=0}
- Number(p) - fixed point
- Number(p,s) –floating point (p=1 to 38,s= -84 to 127)

3. Date Time Data type: used to store date and time in the table.

- DB uses its own format of storing in fixed length of 7 bytes for century, date, month, year, hour, minutes, and seconds.
- Default data type is —dd-mon-yy||
- New Date time data types have been introduced. They are
TIMESTAMP-Date with fractional seconds
INTERVAL YEAR TO MONTH-stored as an interval of years and months

INTERVAL DAY TO SECOND-stored as o interval of days to hour's minutes and seconds

4. Raw Data type: used to store byte oriented data like binary data and byte string.

5. Other :

- CLOB – stores character object with single byte character.
- BLOB – stores large binary objects such as graphics, video, sounds.
- BFILE – stores file pointers to the LOB's.

Creating and Managing Tables

OBJECTIVE

After the completion of this exercise, students should be able to do the following:

- ☐ Create tables
- ☐ Describing the data types that can be used when specifying column definition
- ☐ Alter table definitions
- ☐ Drop, rename, and truncate tables

NAMING RULES

Table names and column names:

- Must begin with a letter
- Must be 1-30 characters long
- Must contain only A-Z, a-z, 0-9, _, \$, and #
- Must not duplicate the name of another object owned by the same user
- Must not be an oracle server reserve words
- 2 different tables should not have same name.
- Should specify a unique column name.
- Should specify proper data type along with width

- Can include —not null condition when needed. By default it is _null‘.

OBJECTIVE

After, the completion of this exercise the students will be able to do the following

- Describe each DML statement
- Insert rows into tables
- Update rows into table
- Delete rows from table
- Control Transactions

A DML statement is executed when you:

- Add new rows to a table
- Modify existing rows
- Removing existing rows

A transaction consists of a collection of DML statements that form a logical unit of

work. **The ALTER TABLE Statement**

The ALTER statement is used to

- Add a new column
- Modify an existing column
- Define a default value to the new column
- Drop a column
- To include or drop integrity constraint.

DROPPING A TABLE

- All data and structure in the table is deleted.
- Any pending transactions are committed.
- All indexes are dropped.
- Cannot roll back the drop table statement

To Add a New Row

INSERT Statement

Syntax

INSERT INTO table_name VALUES (column1 values, column2 values, ..., columnn values);

Example:

INSERT INTO department (70, _Public relations‘, 100,1700);

Inserting rows with null values

Implicit Method: (Omit the column)

INSERT INTO department VALUES (30,'purchasing');
Explicit Method: (Specify NULL keyword)

INSERT INTO department VALUES (100,'finance', NULL, NULL);

Inserting Special Values

Example:

Using SYSDATE

INSERT INTO employees VALUES (113,'louis', _popp', _lpopp', '5151244567',SYSDATE, _ac_account', 6900, NULL, 205, 100);

Inserting Specific Date Values

Example:

INSERT INTO employees VALUES (114,'den', _raphealy', _drapheal', _5151274561', TO_DATE('feb 3,1999','mon, dd ,yyyy'), _ac_account', 11000,100,30);

To Insert Multiple Rows

& is the placeholder for the variable value

Example:

INSERT INTO department VALUES (&dept_id, &dept_name, &location);

Copying Rows from another table

☐ Using Subquery

Example:

INSERT INTO sales_reps(id, name, salary, commission_pct)
SELECT employee_id, Last_name, salary, commission_pct
FROM employees
WHERE job_id LIKE '%REP');

CHANGING DATA IN A TABLE

UPDATE Statement

Syntax1: (to update specific rows)

UPDATE table_name SET column=value WHERE condition;

Syntax 2: (To update all rows)

UPDATE table_name SET column=value;

Updating columns with a subquery

```
UPDATE employees
SET job_id= (SELECT job_id
FROM employees
WHERE employee_id=205)
WHERE employee_id=114;
```

REMOVING A ROW FROM A TABLE

DELETE STATEMENT

Syntax

DELETE FROM table_name WHERE conditions;

Example:

DELETE FROM department WHERE dept_name='finance';

Ex.No.: 1		CREATION OF BASE TABLE AND DML OPERATIONS
Date:	2-8-2024	

AIM:

ALGORITHM:

STEP-1: Start.

STEP-2: Create a base Table

Syntax:

CREATE TABLE <table name> (column1 type, column2 type, ...);

STEP-3: Describe the Table structure

Syntax:

DESC <table name>

STEP-4: Add a new row to a Table using INSERT statement.

Syntax:

- INSERT INTO <table name> VALUES (value1, value2..);
- INSERT INTO <table name> (column1, column2..) VALUES (value1, value2..);
- INSERT INTO <table name>VALUES (&column1,‘&column‘);

STEP-5: Modify the existing rows in the base Table with UPDATE statement.

Syntax:

UPDATE <table name> SET column1=value, column2 = ‘value‘
WHERE (condition);

STEP-6: Remove the existing rows from the Table using DELETE statement. Syntax:

DELETE FROM <table name> WHERE <condition>;

STEP-7: Perform a Query using SELECT statement.

Syntax:

SELECT [DISTINCT] {*,<column1,,...>} FROM <table name>
WHERE <condition>;

STEP-8: The truncate command deletes all rows from the table. Only the structure of the table remains.

Syntax:

```
TRUNCATE TABLE <table name>;
```

STEP-9: Alter the existing table using ALTER statement.

Syntax:

Add Column:

```
ALTER TABLE <table name> ADD (column data type  
[DEFAULTexpr][,column data type]);
```

Modify Column:

```
ALTER TABLE <table name> MODIFY (column data type  
[DEFAULT expr], [,column data type]);
```

Drop Column:

```
ALTER TABLE <table name> DROP COLUMN <column name>;
```

STEP-10: To drop the entire table using DROP statement.

Syntax:

```
DROP TABLE <table name>;
```

STEP-11: Exit.

1. Create MY EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

```
CREATE TABLE MY_EMPLOYEE (  
  ID NUMBER(4) NOT NULL,  
  LAST_NAME VARCHAR2(25),  
  FIRST_NAME VARCHAR2(25),
```

```

USERID VARCHAR2(25),
SALARY NUMBER(9,2)
);

```

2. Add the first and second rows data to MY_EMPLOYEE table from the following sample data.

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbiri	1100
4	Newman	Chad	Cnewman	750
5	Ropebur	Audrey	aropebur	1550

```

INSERT INTO MY_EMPLOYEE (ID, LAST_NAME, FIRST_NAME, USERID, SALARY)
VALUES (1, 'Patel', 'Ralph', 'rpatel', 895),
      (2, 'Dancs', 'Betty', 'bdancs', 860);

```

3. Display the table with values.

```

SELECT * FROM MY_EMPLOYEE;

```

4. Populate the next two rows of data from the sample data. Concatenate the first letter of the first_name with the first seven characters of the last_name to produce Userid.

```

INSERT INTO MY_EMPLOYEE (ID, LAST_NAME, FIRST_NAME, USERID, SALARY)
VALUES (3, 'Biri', 'Ben', 'Bbiri', 1100), (4, 'Newman', 'Chad', 'Cnewman', 750);

```

5. Delete Betty dancs from MY_EMPLOYEE table

```
DELETE FROM MY_EMPLOYEE WHERE FIRST_NAME = 'Betty' AND LAST_NAME = 'Dancs';
```

6. Empty the fourth row of the emp table.

```
UPDATE MY_EMPLOYEE  
SET LAST_NAME = NULL,  
    FIRST_NAME = NULL,  
    USERID = NULL,  
    SALARY = NULL  
WHERE ID = 4;
```

8. Change the last name of employee 3 to Drexler

```
UPDATE MY_EMPLOYEE  
SET LAST_NAME = 'Drexler'  
WHERE ID = 3;
```

9. Change the salary to 1000 for all the employees with a salary less than 900.

```
UPDATE MY_EMPLOYEE  
SET SALARY = 1000  
WHERE SALARY < 900;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 2		DATA MANIPULATIONS
Date:	5-8-2-24	

Create the following tables with the given structure.

EMPLOYEES TABLE

NAME	NULL?	TYPE
Employee_id	Not null	Number(6)
First_Name		Varchar(20)
Last_Name	Not null	Varchar(25)
Email	Not null	Varchar(25)
Phone_Number		Varchar(20)
Hire_date	Not null	Date
Job_id	Not null	Varchar(10)
Salary		Number(8,2)
Commission_pct		Number(2,2)
Manager_id		Number(6)
Department_id		Number(4)

```
CREATE TABLE EMPLOYEES (
  EMPLOYEE_ID NUMBER(6) NOT NULL,
  FIRST_NAME VARCHAR2(20),
  LAST_NAME VARCHAR2(25) NOT NULL,
  EMAIL VARCHAR2(25) NOT NULL,
  PHONE_NUMBER VARCHAR2(20),
  HIRE_DATE DATE NOT NULL,
  JOB_ID VARCHAR2(10) NOT NULL,
  SALARY NUMBER(8,2),
  COMMISSION_PCT NUMBER(2,2),
  MANAGER_ID NUMBER(6),
  DEPARTMENT_ID NUMBER(4)
```

);

(a) Find out the employee id, names, salaries of all the employees

```
SELECT EMPLOYEE_ID, FIRST_NAME || ' ' || LAST_NAME AS FULL_NAME, SALARY  
FROM EMPLOYEES;
```

(b) List out the employees who works under manager 100

```
SELECT EMPLOYEE_ID, FIRST_NAME || ' ' || LAST_NAME AS FULL_NAME  
FROM EMPLOYEES  
WHERE MANAGER_ID = 100;
```

(c) Find the names of the employees who have a salary greater than or equal to 4800

```
SELECT FIRST_NAME || ' ' || LAST_NAME AS FULL_NAME  
FROM EMPLOYEES WHERE SALARY >= 4800;
```

(d) List out the employees whose last name is 'AUSTIN'

```
SELECT *  
FROM EMPLOYEES  
WHERE LAST_NAME = 'AUSTIN';
```

(e) Find the names of the employees who works in departments 60,70 and 80

```
SELECT FIRST_NAME || ' ' || LAST_NAME AS FULL_NAME  
FROM EMPLOYEES WHERE DEPARTMENT_ID IN (60, 70, 80);
```

(f) Display the unique Manager_Id.

```
SELECT DISTINCT MANAGER_ID  
FROM EMPLOYEES;
```

Create an Emp table with the following fields: (EmpNo, EmpName, Job,Basic, DA, HRA,PF, GrossPay, NetPay) (Calculate DA as 30% of Basic and HRA as 40% of Basic)

(a) Insert Five Records and calculate GrossPay and NetPay.

```
CREATE TABLE Emp (EmpNo NUMBER(6),EmpName VARCHAR2(20),Job  
VARCHAR2(20),Basic NUMBER(8,2),DA NUMBER(8,2),HRA NUMBER(8,2), PF  
NUMBER(8,2),GrossPay NUMBER(8,2),NetPay NUMBER(8,2));
```

```
INSERT INTO Emp (EmpNo, EmpName, Job, Basic)VALUES (1, 'Alice', 'Manager', 20000),(2,  
'Bob', 'Developer', 15000), (3, 'Charlie', 'Tester', 12000),(4, 'David', 'Analyst', 18000),(5, 'Eve',
```

'Designer', 16000);UPDATE EmpSET DA = 0.3 * Basic,HRA = 0.4 * Basic,
PF = 0.12 * Basic,GrossPay = Basic + DA + HRA,NetPay = GrossPay - PF;

(b) Display the employees whose Basic is lowest in each department.
SELECT *FROM EmpWHERE (Basic, Department_ID) IN (SELECT MIN(Basic),
Department_IDFROM EmpGROUP BY Department_ID);

(c) If Net Pay is less than
SELECT *FROM Emp WHERE NetPay < 10000; -- Replace 10000 with your desired threshold

DEPARTMENT TABLE

NAME	NULL?	TYPE
Dept_id	Not null	Number(6)
Dept_name	Not null	Varchar(20)
Manager_id		Number(6)
Location_id		Number(4)

JOB GRADE TABLE

NAME	NULL?	TYPE
Grade_level		Varchar(2)

Lowest_sal		Number
Highest_sal		Number

LOCATION TABLE

NAME	NULL?	TYPE
Location_id	Not null	Number(4)
St_addr		Varchar(40)
Postal_code		Varchar(12)
City	Not null	Varchar(30)
State_province		Varchar(25)
Country_id		Char(2)

1. Create the DEPT table based on the DEPARTMENT following the table instance chart below. Confirm that the table is created.

```
CREATE TABLE DEPT (
  ID NUMBER(7) PRIMARY KEY,
  NAME VARCHAR2(25)
);
```

-- To confirm the table creation, you can use:
DESCRIBE DEPT;

Column name	ID	NAME
Key Type		
Nulls/Unique		
FK table		
FK column		
Data Type	Number	Varchar2

Length	7	25
---------------	---	----

2. Create the EMP table based on the following instance chart. Confirm that the table is created.

```
CREATE TABLE EMP (
  ID NUMBER(7) PRIMARY KEY,
  LAST_NAME VARCHAR2(25),
  FIRST_NAME VARCHAR2(25),
  DEPT_ID NUMBER(7),
  FOREIGN KEY (DEPT_ID) REFERENCES DEPT(ID)
);
```

-- To confirm the table creation, you can use:
DESCRIBE EMP;

Column name	ID	LAST_NAME	FIRST_NAME	DEPT_ID
Key Type				
Nulls/Unique				
FK table				
FK column				
Data Type	Number	Varchar2	Varchar2	Number
Length	7	25	25	7

- 3 Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

```
ALTER TABLE EMP MODIFY LAST_NAME VARCHAR2(50);
DESCRIBE EMP;
```

- 4 Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee_id, First_name, Last_name, Salary and Dept_id coloumns. Name the columns Id, First_name, Last_name, salary and Dept_id respectively.

```
CREATE TABLE EMPLOYEES2 ( ID NUMBER(6),FIRST_NAME  
VARCHAR2(20),LAST_NAME VARCHAR2(25),SALARY NUMBER(8,2),DEPT_ID  
NUMBER(4);
```

5 Drop the EMP table.
DROP TABLE EMP;

6 Rename the EMPLOYEES2 table as EMP.
RENAME EMPLOYEES2 TO EMP;

7 Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

```
COMMENT ON TABLE DEPT IS 'Department Information';  
COMMENT ON TABLE EMP IS 'Employee Information';
```

```
DESCRIBE DEPT;  
DESCRIBE EMP;
```

8 Drop the First_name column from the EMP table and confirm it.
ALTER TABLE EMP DROP COLUMN FIRST_NAME;
DESCRIBE EMP;

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 3		WRITING BASIC SQL SELECT STATEMENTS
Date:	7-8-2024	

OBJECTIVES

After the completion of this exercise, the students will be able to do the following:

- List the capabilities of SQL SELECT Statement
- Execute a basic SELECT statement

Capabilities of SQL SELECT statement

A SELECT statement retrieves information from the database. Using a select statement, we can perform

- ✓ Projection: To choose the columns in a table
- ✓ Selection: To choose the rows in a table
- ✓ Joining: To bring together the data that is stored in different tables

Basic SELECT Statement

Syntax

```
SELECT *|DISTINCT Column_ name| alias
` FROM table_name;
```

NOTE:

DISTINCT—Suppress the duplicates.

Alias—gives selected columns different headings.

Example: 1

```
SELECT * FROM departments;
```

Example: 2

```
SELECT location_id, department_id FROM departments;
```

Writing SQL Statements

- SQL statements are not case sensitive
- SQL statements can be on one or more lines.
- Keywords cannot be abbreviated or split across lines

- Clauses are usually placed on separate lines
- Indents are used to enhance readability

Using Arithmetic Expressions

Basic Arithmetic operators like *, /, +, - can be used

Example:1

```
SELECT last_name, salary, salary+300 FROM employees;
```

Example:2

```
SELECT last_name, salary, 12*salary+100 FROM employees;
```

The statement is not same as

```
SELECT last_name, salary, 12*(salary+100) FROM employees;
```

Example:3

```
SELECT last_name, job_id, salary, commission_pct FROM employees;
```

Example:4

```
SELECT last_name, job_id, salary, 12*salary*commission_pct FROM  
employees; Using Column Alias
```

- To rename a column heading with or without AS keyword.

Example:1

```
SELECT last_name AS Name  
FROM employees;
```

Example: 2

```
SELECT last_name —Name|| salary*12 —Annual Salary —  
FROM employees;
```

Concatenation Operator

- Concatenates columns or character strings to other columns •
- Represented by two vertical bars (||)
- Creates a resultant column that is a character expression

Example:

```
SELECT last_name||job_id AS —EMPLOYEES JOB|| FROM employees;
```

Using Literal Character String

- A literal is a character, a number, or a date included in the SELECT list.
- Date and character literal values must be enclosed within single quotation marks.

Example:

```
SELECT last_name||'is a'||job_id AS —EMPLOYEES JOB|| FROM
```

employees; **Eliminating Duplicate Rows**

- Using DISTINCT keyword.

Example:

```
SELECT DISTINCT department_id FROM employees;
```

Displaying Table Structure

- Using DESC keyword.

Syntax

```
DESC table_name;
```

Example:

```
DESC employees;
```

Find the Solution for the following:

True OR False

1. The following statement executes successfully.

Identify the Errors

```
SELECT employee_id, last_name  
sal*12 ANNUAL SALARY  
FROM employees;
```

ans:

```
SELECT employee_id, last_name, salary * 12 AS ANNUAL_SALARY  
FROM employees;
```

Queries

2. Show the structure of departments the table. Select all the data from it.

```
DESCRIBE departments;  
SELECT * FROM departments;
```

3. Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first.

```
SELECT employee_id, last_name, job_id, hire_date  
FROM employees;
```

4. Provide an alias STARTDATE for the hire date.

```
SELECT employee_id, last_name, job_id, hire_date AS STARTDATE  
FROM employees;
```

5. Create a query to display unique job codes from the employee table.

```
SELECT DISTINCT job_id FROM employees;
```

6. Display the last name concatenated with the job ID , separated by a comma and space, and name the column EMPLOYEE and TITLE.

```
SELECT last_name || ', ' || job_id AS EMPLOYEE_AND_TITLE
```

FROM employees;

7. Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE_OUTPUT.

```
SELECT employee_id || ',' || last_name || ',' || job_id || ',' || hire_date || ',' || salary || ',' ||  
commission_pct || ',' || manager_id || ',' || department_id AS THE_OUTPUT  
FROM employees;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 4		WORKING WITH CONSTRAINTS
Date:	9-8-2024	

OBJECTIVE

After the completion of this exercise the students should be able to do the following

- Describe the constraints
- Create and maintain the constraints

What are Integrity constraints?

- Constraints enforce rules at the table level.
- Constraints prevent the deletion of a table if there are dependencies **The**

following types of integrity constraints are valid

a) Domain Integrity

- ✓ NOT NULL
- ✓ CHECK

b) Entity Integrity

- ✓ UNIQUE
- ✓ PRIMARY KEY

c) Referential Integrity

- ✓ FOREIGN KEY

Constraints can be created in either of two ways

1. At the same time as the table is created
2. After the table has been created.

Defining Constraints

Create table tablename (column_name1 data_type constraints, column_name2 data_type constraints ...);

Example:

Create table employees (employee_id number(6), first_name varchar2(20), ..job_id varchar2(10), CONSTRAINT emp_emp_id_pk PRIMARY KEY (employee_id));

Domain Integrity

This constraint sets a range and any violations that takes place will prevent the user from performing the manipulation that caused the breach. It includes:

NOT NULL Constraint

While creating tables, by default the rows can have null value. the enforcement of not null constraint in a table ensure that the table contains values.

Principle of null values:

- Setting null value is appropriate when the actual value is unknown, or when a value would not be meaningful.
- A null value is not equivalent to a value of zero.
- A null value will always evaluate to null in any expression.
- When a column name is defined as not null, that column becomes a mandatory i.e., the user has to enter data into it.
- Not null Integrity constraint cannot be defined using the alter table command when the table contain rows.

Example

```
CREATE TABLE employees (employee_id number (6), last_name varchar2(25) NOT NULL, salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL'....);
```

CHECK

Check constraint can be defined to allow only a particular range of values. when the manipulation violates this constraint, the record will be rejected. Check condition cannot contain sub queries.

```
CREATE TABLE employees (employee_id number (6), last_name varchar2 (25) NOT NULL, salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL'...,CONSTRAINT emp_salary_mi CHECK(salary > 0));
```

Entity Integrity

Maintains uniqueness in a record. An entity represents a table and each row of a table represents an instance of that entity. To identify each row in a table uniquely we need to use this constraint. There are 2 entity constraints:

a) Unique key constraint

It is used to ensure that information in the column for each record is unique, as with telephone or driver's license numbers. It prevents the duplication of value with rows of a specified column in a set of column. A column defined with the constraint can allow null value.

If unique key constraint is defined in more than one column i.e., combination of column cannot be specified. Maximum combination of columns that a composite unique key can contain is 16.

Example:

```
CREATE TABLE employees (employee_id number(6), last_name varchar2(25) NOT NULL, email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL, CONSTRAINT emp_email_uk UNIQUE(email));
```

PRIMARY KEY CONSTRAINT

A primary key avoids duplication of rows and does not allow null values. Can be defined on one or more columns in a table and is used to uniquely identify each row in a table. These values should never be changed and should never be null.

A table should have only one primary key. If a primary key constraint is assigned to more than one column or combination of column is said to be composite primary key, which can contain 16 columns.

Example:

```
CREATE TABLE employees (employee_id number(6) , last_name varchar2(25) NOT NULL, email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date constraint emp_hire_date_nn NOT NULL, Constraint emp_id pk PRIMARY KEY (employee_id), CONSTRAINT emp_email_uk UNIQUE(email));
```

c) Referential Integrity

It enforces relationship between tables. To establish parent-child relationship between 2 tables having a common column definition, we make use of this constraint. To implement this, we should define the column in the parent table as primary key and same column in the child table as foreign key referring to the corresponding parent entry.

Foreign key

A column or combination of column included in the definition of referential integrity, which would refer to a referenced key.

Referenced key

It is a unique or primary key upon which is defined on a column belonging to the parent table. Keywords:

FOREIGN KEY: Defines the column in the child table at the table level constraint.

REFERENCES: Identifies the table and column in the parent table.

ON DELETE CASCADE: Deletes the dependent rows in the child table when a row in the parent table is deleted.

ON DELETE SET NULL: converts dependent foreign key values to null when the parent value is removed.

```
CREATE TABLE employees (employee_id number(6), last_name varchar2(25) NOT
NULL,email varchar2(25), salary number(8,2), commission_pct number(2,2), hire_date date
constraint emp_hire_date_nn NOT NULL, Constraint emp_id pk PRIMARY KEY
(employee_id), CONSTRAINT emp_email_uk UNIQUE(email), CONSTRAINT emp_dept_fk
FOREIGN KEY (department_id) references departments(dept_id));
```

ADDING A CONSTRAINT

Use the ALTER to

- Add or Drop a constraint, but not modify the structure
- Enable or Disable the constraints
- Add a not null constraint by using the Modify clause

Syntax

```
ALTER TABLE table name ADD CONSTRAINT Cons_name type(column name);
```

Example:

```
ALTER TABLE employees ADD CONSTRAINT emp_manager_fk FOREIGN KEY
(manager_id) REFERENCES employees (employee_id);
```

DROPPING A CONSTRAINT

Example:

```
ALTER TABLE employees DROP CONSTRAINT emp_manager_fk;
```

CASCADE IN DROP

- The CASCADE option of the DROP clause causes any dependent constraints also to be dropped.

Syntax

```
ALTER TABLE departments DROP PRIMARY KEY|UNIQUE (column)| CONSTRAINT
constraint_name CASCADE;
```

DISABLING CONSTRAINTS

- Execute the DISABLE clause of the ALTER TABLE statement to deactivate an integrity constraint
- Apply the CASCADE option to disable dependent integrity constraints.

Example

ALTER TABLE employees DISABLE CONSTRAINT emp_emp_id_pk CASCADE;

ENABLING CONSTRAINTS

- Activate an integrity constraint currently disabled in the table definition by using the ENABLE clause.

Example

ALTER TABLE employees ENABLE CONSTRAINT emp_emp_id_pk CASCADE;

CASCADING CONSTRAINTS

The CASCADE CONSTRAINTS clause is used along with the DROP column clause. It drops all referential integrity constraints that refer to the primary and unique keys defined on the dropped Columns.

This clause also drops all multicolumn constraints defined on the dropped column.

Example:

Assume table TEST1 with the following structure

CREATE TABLE test1 (pk number PRIMARY KEY, fk number, col1 number,col2 number, CONSTRAINT fk_constraint FOREIGN KEY(fk) references test1, CONSTRAINT ck1 CHECK (pk>0 and col1>0), CONSTRAINT ck2 CHECK (col2>0));

An error is returned for the following statements

ALTER TABLE test1 DROP (pk);

ALTER TABLE test1 DROP (col1);

The above statement can be written with CASCADE CONSTRAINT

ALTER TABLE test 1 DROP(pk) CASCADE CONSTRAINTS;

(OR)

```
ALTER TABLE test 1 DROP(pk, fk, col1) CASCADE CONSTRAINTS;
```

VIEWING CONSTRAINTS

Query the USER_CONSTRAINTS table to view all the constraints definition and

names. **Example:**

```
SELECT constraint_name, constraint_type, search_condition FROM  
user_constraints WHERE table_name='employees';
```

Viewing the columns associated with constraints

```
SELECT constraint_name, constraint_type, FROM user_cons_columns  
WHERE table_name='employees';
```

Find the Solution for the following:

1. Add a table-level PRIMARY KEY constraint to the EMP table on the ID column. The constraint should be named at creation. Name the constraint my_emp_id_pk.

```
ALTER TABLE EMP
```

```
ADD CONSTRAINT my_emp_id_pk PRIMARY KEY (ID);
```

2. Create a PRIMAY KEY constraint to the DEPT table using the ID colum. The constraint should be named at creation. Name the constraint my_dept_id_pk.

```
ALTER TABLE DEPT
```

ADD CONSTRAINT my_dept_id_pk PRIMARY KEY (ID);

3. Add a column DEPT_ID to the EMP table. Add a foreign key reference on the EMP table that ensures that the employee is not assigned to nonexistent department. Name the constraint my_emp_dept_id_fk.

ALTER TABLE EMP

ADD DEPT_ID NUMBER(7);ALTER TABLE EMP

ADD CONSTRAINT my_emp_dept_id_fk FOREIGN KEY (DEPT_ID) REFERENCES DEPT(ID);

4. Modify the EMP table. Add a COMMISSION column of NUMBER data type, precision 2, scale 2. Add a constraint to the commission column that ensures that a commission value is greater than zero.

ALTER TABLE EMP

ADD COMMISSION NUMBER(2,2) CHECK (COMMISSION > 0);

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 5		CREATING VIEWS
Date:	21-8-2024	

After the completion of this exercise, students will be able to do the following: • Describe a view

- Create, alter the definition of, and drop a view
- Retrieve data through a view
- Insert, update, and delete data through a view
- Create and use an inline view

View

A view is a logical table based on a table or another view. A view contains no data but is like a window through which data from tables can be viewed or changed. The tables on which a view is based are called base tables.

Advantages of Views

- To restrict data access
- To make complex queries easy
- To provide data independence
- To present different views of the same data

Classification of views

1. Simple view
2. Complex view

Feature	Simple	Complex
No. of tables	One	One or more
Contains functions	No	Yes
Contains groups of data	No	Yes
DML operations thr' view	Yes	Not always

Creating a view

Syntax

CREATE OR REPLACE FORCE/NOFORCE VIEW view_name AS Subquery WITH CHECK OPTION CONSTRAINT constraint WITH READ ONLY CONSTRAINT constraint;

FORCE - Creates the view regardless of whether or not the base tables exist.

NOFORCE - Creates the view only if the base table exist.

WITH CHECK OPTION CONSTRAINT-specifies that only rows accessible to the view can be inserted or updated.

WITH READ ONLY CONSTRAINT-ensures that no DML operations can be performed on the view.

Example: 1 (Without using Column aliases)

Create a view EMPVU80 that contains details of employees in

department80. **Example 2:**

```
CREATE VIEW empvu80 AS SELECT employee_id, last_name, salary FROM employees
WHERE department_id=80;
```

Example:1 (Using column aliases)

```
CREATE VIEW salvu50
AS SELECT employee_id,id_number, last_name NAME, salary *12 ANN_SALARY
FROM employees
WHERE department_id=50;
```

Retrieving data from a view

Example:

```
SELECT * from salvu50;
```

Modifying a view

A view can be altered without dropping, re-creating.

Example: (Simple view)

Modify the EMPVU80 view by using CREATE OR REPLACE.

```
CREATE OR REPLACE VIEW empvu80 (id_number, name, sal, department_id)
AS SELECT employee_id,first_name, last_name, salary, department_id FROM
employees
WHERE department_id=80;
```

Example: (complex view)

```
CREATE VIEW dept_sum_vu (name, minsal, maxsal,avgsal)
```

```
AS SELECT d.department_name, MIN(e.salary), MAX(e.salary), AVG(e.salary)
FROM employees e, department d
WHERE e.department_id=d.department_id
GROUP BY d.department_name;
```

Rules for performing DML operations on view

- Can perform operations on simple views
- Cannot remove a row if the view contains the following:
 - Group functions
 - Group By clause
 - Distinct keyword
- Cannot modify data in a view if it contains
 - Group functions
 - Group By clause
 - Distinct keyword
 - Columns contain by expressions
- Cannot add data through a view if it contains
 - Group functions
 - Group By clause
 - Distinct keyword
 - Columns contain by expressions
 - NOT NULL columns in the base table that are not selected by the view

Example: (Using the WITH CHECK OPTION clause)

```
CREATE OR REPLACE VIEW empvu20
AS SELECT *
FROM employees
WHERE department_id=20
WITH CHECK OPTION CONSTRAINT empvu20_ck;
```

Note: Any attempt to change the department number for any row in the view fails because it violates the WITH CHECK OPTION constraint.

Example – (Execute this and note the error)

```
UPDATE empvu20 SET department_id=10 WHERE employee_id=201;
```

Denying DML operations

Use of WITH READ ONLY option.

Any attempt to perform a DML on any row in the view results in an oracle server

error. **Try this code:**

```
CREATE OR REPLACE VIEW empvu10(employee_number, employee_name, job_title)
AS SELECT employee_id, last_name, job_id
FROM employees
WHERE department_id=10
WITH READ ONLY;
```

Find the Solution for the following:

1. Create a view called EMPLOYEE_VU based on the employee numbers, employee names and department numbers from the EMPLOYEES table. Change the heading for the employee name to EMPLOYEE.

```
CREATE VIEW EMPLOYEE_VU AS

SELECT EMPLOYEE_ID, LAST_NAME || ', ' || FIRST_NAME AS EMPLOYEE,
DEPARTMENT_ID

FROM EMPLOYEES;
```

2. Display the contents of the EMPLOYEES_VU view.
SELECT * FROM EMPLOYEE_VU;

3. Select the view name and text from the USER_VIEWS data dictionary views.
SELECT VIEW_NAME, TEXT FROM USER_VIEWS;

4. Using your EMPLOYEES_VU view, enter a query to display all employees names and department.

```
SELECT EMPLOYEE, DEPARTMENT_ID FROM EMPLOYEE_VU;
```

5. Create a view named DEPT50 that contains the employee number, employee last names and department numbers for all employees in department 50. Label the view columns EMPNO, EMPLOYEE and DEPTNO. Do not allow an employee to be reassigned to another department through the view.

```
CREATE VIEW DEPT50 (EMPNO, EMPLOYEE, DEPTNO) AS  
SELECT EMPLOYEE_ID, LAST_NAME, DEPARTMENT_ID  
FROM EMPLOYEES  
WHERE DEPARTMENT_ID = 50  
WITH CHECK OPTION;
```

6. Display the structure and contents of the DEPT50 view.

```
DESCRIBE DEPT50;  
SELECT * FROM DEPT50;
```

7. Attempt to reassign Matos to department 80.

```
UPDATE DEPT50  
SET DEPTNO = 80  
WHERE LAST_NAME = 'Matos';
```

8. Create a view called SALARY_VU based on the employee last names, department names, salaries, and salary grades for all employees. Use the Employees, DEPARTMENTS and JOB_GRADE tables. Label the column Employee, Department, salary, and Grade respectively.

```
CREATE VIEW SALARY_VU (Employee, Department, Salary, Grade)AS
SELECT E.LAST_NAME, D.DEPARTMENT_NAME, E.SALARY, J.GRADE
FROM EMPLOYEES E
JOIN DEPARTMENTS D ON E.DEPARTMENT_ID = D.DEPARTMENT_ID
JOIN JOB_GRADES J ON E.JOB_ID = J.JOB_ID;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 6		RESTRICTING AND SORTING DATA
Date:	28-8-2024	

After the completion of this exercise, the students will be able to do the following:

- Limit the rows retrieved by the queries
- Sort the rows retrieved by the queries
-

Limiting the Rows selected

- Using WHERE clause
- Alias cannot be used in WHERE clause

Syntax

SELECT-----
FROM-----
WHERE condition;

Example:

```
SELECT employee_id,last_name, job_id, department_id FROM employees WHERE
department_id=90;
```

Character strings and Dates

Character strings and date values are enclosed in single quotation marks. Character values are case sensitive and date values are format sensitive.

Example:

```
SELECT employee_id,last_name, job_id, department_id FROM
employees WHERE last_name='WHALEN';
```

Comparison Conditions

All relational operators can be used. (=, >, >=, <, <=, <>, !=)

Example:

```
SELECT last_name, salary
FROM employees
```

WHERE salary<=3000;

Other comparison conditions

Operator	Meaning
BETWEEN ...AND...	Between two values
IN	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null values

Example:1

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500;
```

Example:2

```
SELECT employee_id, last_name, salary , manager_id
FROM employees
WHERE manager_id IN (101, 100,201);
```

Example:3

- Use the LIKE condition to perform wildcard searches of valid string values. •
- Two symbols can be used to construct the search string
- % denotes zero or more characters
- _ denotes one character

```
SELECT first_name, salary
FROM employees
WHERE first_name LIKE _%s';
```

Example:4

```
SELECT last_name, salary
FROM employees
WHERE last_name LIKE __o%';
```

Example:5

ESCAPE option-To have an exact match for the actual % and _ characters
To search for the string that contain _SA_ ‘

```
SELECT employee_id, first_name, salary, job_id
FROM employees
WHERE job_id LIKE _%sa\__%‘ESCAPE‘\‘;
```

Test for NULL

- Using IS NULL operator

Example:

```
SELECT employee_id, last_name, salary , manager_id
FROM employees
WHERE manager_id IS NULL;
```

Logical Conditions

All logical operators can be used.(AND,OR,NOT)

Example:1

```
SELECT employee_id, last_name, salary , job_id
FROM employees
WHERE salary >= 10000
AND job_id LIKE _%MAN%‘;
```

Example:2

```
SELECT employee_id, last_name, salary , job_id
FROM employees
WHERE salary >= 10000
OR job_id LIKE _%MAN%‘;
```

Example:3

```
SELECT employee_id, last_name, salary , job_id
FROM employees
WHERE job_id NOT IN (_it_prog‘, st_clerk‘, sa_rep‘);
```

Rules of Precedence

Order Evaluated	Operator
1	Arithmetic

2	Concatenation
3	Comparison
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	Logical NOT
7	Logical AND
8	Logical OR

Example:1

```
SELECT employee_id, last_name, salary ,
job_id FROM employees
WHERE job_id ='sa_rep'
OR job_id='ad_pres'
AND salary>15000;
```

Example:2

```
SELECT employee_id, last_name, salary ,
job_id FROM employees
WHERE (job_id ='sa_rep'
OR job_id='ad_pres')
AND salary>15000;
```

Sorting the rows

Using ORDER BY Clause

ASC-Ascending Order,Default

DESC-Descending order

Example:1

```
SELECT last_name, salary , job_id,department_id,hire_date
FROM employees
ORDER BY hire_date;
```

Example:2

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY hire_date DESC;
```

Example:3**Sorting by column alias**

```
SELECT last_name, salary*12 annsal , job_id,department_id,hire_date  
FROM employees  
ORDER BY annsal;
```

Example:4**Sorting by Multiple columns**

```
SELECT last_name, salary , job_id,department_id,hire_date  
FROM employees  
ORDER BY department_id, salary DESC;
```

Find the Solution for the following:

1. Create a query to display the last name and salary of employees earning more than 12000.

```
SELECT LAST_NAME, SALARY
```

```
FROM EMPLOYEES
```

```
WHERE SALARY > 12000;
```

2. Create a query to display the employee last name and department number for employee

number 176.

```
SELECT LAST_NAME, DEPARTMENT_ID
FROM EMPLOYEES
WHERE EMPLOYEE_ID = 176;
```

3. Create a query to display the last name and salary of employees whose salary is not in the range of 5000 and 12000. (hints: not between)

```
SELECT LAST_NAME, SALARY
FROM EMPLOYEES
WHERE SALARY NOT BETWEEN 5000 AND 12000;
```

4. Display the employee last name, job ID, and start date of employees hired between February 20,1998 and May 1,1998.order the query in ascending order by start date.(hints: between)

```
SELECT LAST_NAME, JOB_ID, HIRE_DATE AS START_DATE FROM
EMPLOYEES WHERE HIRE_DATE BETWEEN TO_DATE('20-FEB-1998',
'DD-MON-YYYY') AND TO_DATE('01-MAY-1998', 'DD-MON-YYYY') ORDER BY
```

HIRE_DATE ASC;

5. Display the last name and department number of all employees in departments 20 and 50 in alphabetical order by name.(hints: in, orderby)

```
SELECT LAST_NAME, DEPARTMENT_ID
FROM EMPLOYEES
WHERE DEPARTMENT_ID IN (20, 50)
ORDER BY LAST_NAME ASC;
```

6. Display the last name and salary of all employees who earn between 5000 and 12000 and are in departments 20 and 50 in alphabetical order by name. Label the columns EMPLOYEE, MONTHLY SALARY respectively.(hints: between, in)

```
SELECT LAST_NAME AS EMPLOYEE, SALARY AS MONTHLY_SALARY
FROM EMPLOYEES WHERE SALARY BETWEEN 5000 AND 12000 AND DEPARTMENT_ID
IN (20, 50) ORDER BY LAST_NAME ASC;
```

7. Display the last name and hire date of every employee who was hired in 1994.(hints: like)

```
SELECT LAST_NAME, HIRE_DATE
FROM EMPLOYEES WHERE HIRE_DATE LIKE '%1994%';
```

8. Display the last name and job title of all employees who do not have a manager.(hints: is null)
SELECT LAST_NAME, JOB_ID FROM EMPLOYEES WHERE MANAGER_ID IS NULL;

9. Display the last name, salary, and commission for all employees who earn commissions. Sort data in descending order of salary and commissions.(hints: is not nul,orderby)

```
SELECT LAST_NAME, SALARY, COMMISSION_PCT
FROM EMPLOYEES
WHERE COMMISSION_PCT IS NOT NULL
ORDER BY SALARY DESC, COMMISSION_PCT DESC;
```

10. Display the last name of all employees where the third letter of the name is *a*.(hints:like)

```
SELECT LAST_NAME FROM EMPLOYEES WHERE LAST_NAME LIKE '__A%';
```

11. Display the last name of all employees who have an *a* and an *e* in their last name.(hints: like)

```
SELECT LAST_NAME
FROM EMPLOYEES
WHERE LAST_NAME LIKE '%A%'
AND LAST_NAME LIKE '%E%';
```

12. Display the last name and job and salary for all employees whose job is sales representative or stock clerk and whose salary is not equal to 2500 ,3500 or 7000.(hints:in,not in)

```
SELECT LAST_NAME, JOB_ID, SALARY
FROM EMPLOYEES
WHERE JOB_ID IN ('SA_REP', 'ST_CLERK')
AND SALARY NOT IN (2500, 3500, 7000);
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 7		USING SET OPERATORS
Date:		

Objectives

After the completion this exercise, the students should be able to do the following:

- Describe set operators
- Use a set operator to combine multiple queries into a single query
- Control the order of rows returned

The set operators combine the results of two or more component queries into one result. Queries containing set operators are called *compound queries*.

Operator	Returns
UNION	All distinct rows selected by either query
UNION ALL	All rows selected by either query, including all duplicates
INTERSECT	All distinct rows selected by both queries
MINUS	All distinct rows that are selected by the first SELECT statement and not selected in the second SELECT statement

The tables used in this lesson are:

- EMPLOYEES: Provides details regarding all current employees
- JOB_HISTORY: Records the details of the start date and end date of the former job, and the job identification number and department when an employee switches jobs

UNION Operator

Guidelines

- The number of columns and the data types of the columns being selected must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- UNION operates over all of the columns being selected.
- NULL values are not ignored during duplicate checking.
- The IN operator has a higher precedence than the UNION operator.

- By default, the output is sorted in ascending order of the first column of the SELECT clause. **Example:**

Display the current and previous job details of all employees. Display each employee only once.

```
SELECT employee_id, job_id FROM employees UNION SELECT employee_id,  
job_id FROM job_history;
```

Example:

```
SELECT employee_id, job_id, department_id  
FROM employees  
UNION  
SELECT employee_id, job_id, department_id  
FROM job_history;
```

UNION ALL Operator

Guidelines

The guidelines for UNION and UNION ALL are the same, with the following two exceptions that pertain to UNION ALL:

- Unlike UNION, duplicate rows are not eliminated and the output is not sorted by default.
- The DISTINCT keyword cannot be used.

Example:

Display the current and previous departments of all employees.

```
SELECT employee_id, job_id, department_id  
FROM employees  
UNION ALL  
SELECT employee_id, job_id, department_id  
FROM job_history  
ORDER BY employee_id;
```

INTERSECT Operator

Guidelines

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- Reversing the order of the intersected tables does not alter the result.
- INTERSECT does not ignore NULL values.

Example:

Display the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired (that is, they changed jobs but have now gone back to doing their original job).

```
SELECT employee_id, job_id FROM employees
INTERSECT
SELECT employee_id, job_id
FROM job_history;
```

Example

```
SELECT employee_id, job_id, department_id
FROM employees
INTERSECT
SELECT employee_id, job_id, department_id
FROM job_history;
```

MINUS Operator

Guidelines

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- All of the columns in the WHERE clause must be in the SELECT clause for the MINUS operator to work.

Example:

Display the employee IDs of those employees who have not changed their jobs even once.

```
SELECT employee_id, job_id
FROM employees
MINUS
SELECT employee_id, job_id
FROM job_history;
```

Find the Solution for the following:

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST_CLERK. Use set operators to create this report.

```
SELECT department_id
FROM departments
MINUS
SELECT department_id
FROM employees
WHERE job_id = 'ST_CLERK';
```

2. The HR department needs a list of countries that have no departments located in them. Display the country ID and the name of the countries. Use set operators to create this report.

```
SELECT country_id, country_name
FROM countries
MINUS
SELECT country_id, country_name
FROM departments
JOIN locations USING (location_id);
```

3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and department ID using set operators

```
SELECT job_id, department_id
FROM employees
WHERE department_id IN (10)
UNION ALL
SELECT job_id, department_id
FROM employees
WHERE department_id IN (50)
UNION ALL
SELECT job_id, department_id
```

```
FROM employees
WHERE department_id IN (20);
```

4. Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

```
SELECT employee_id, job_id
FROM job_history
WHERE (employee_id, job_id) IN (
SELECT employee_id, job_id
FROM employees
);
```

5. The HR department needs a report with the following specifications:

- Last name and department ID of all the employees from the EMPLOYEES table, regardless of whether or not they belong to a department.
- Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

```
SELECT last_name, department_id
FROM employees

UNION

SELECT department_name, department_id
FROM departments;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 8	WORKING WITH MULTIPLE TABLES
Date:	

Objective

After the completion of this exercise, the students will be able to do the following: • Write SELECT statements to access data from more than one table using equality and nonequality joins

- View data that generally does not meet a join condition by using outer joins
- Join a table to itself by using a self join

Sometimes you need to use data from more than one table.

Cartesian Products

- A Cartesian product is formed when:
 - A join condition is omitted
 - A join condition is invalid
 - All rows in the first table are joined to all rows in the second table
- To avoid a Cartesian product, always include a valid join condition in a WHERE clause. A Cartesian product tends to generate a large number of rows, and the result is rarely useful. You should always include a valid join condition in a WHERE clause, unless you have a specific need to combine all rows from all tables.

Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

Example:

To displays employee last name and department name from the EMPLOYEES and DEPARTMENTS tables.

```
SELECT last_name, department_name dept_name  
FROM employees, departments;
```

Types of Joins

- Equijoin
- Non-equijoin
- Outer join
- Self join
- Cross joins
- Natural joins
- Using clause
- Full or two sided outer joins
- Arbitrary join conditions for outer joins

Joining Tables Using Oracle Syntax

```
SELECT table1.column, table2.column  
FROM table1, table2  
WHERE table1.column1 = table2.column2;
```

Write the join condition in the WHERE clause.

- Prefix the column name with the table name when the same column name appears in more than one table.

Guidelines

- When writing a SELECT statement that joins tables, precede the column name with the table name for clarity and to enhance database access.
- If the same column name appears in more than one table, the column name must be prefixed with the table name.
- To join n tables together, you need a minimum of n-1 join conditions. For example, to join four tables, a minimum of three joins is required. This rule may not apply if your table has a concatenated primary key, in which case more than one column is required to uniquely identify each row

What is an Equijoin?

To determine an employee's department name, you compare the value in the DEPARTMENT_ID column in the EMPLOYEES table with the DEPARTMENT_ID values in the DEPARTMENTS table.

The relationship between the EMPLOYEES and DEPARTMENTS tables is an equijoin—that is, values

in the DEPARTMENT_ID column on both tables must be equal. Frequently, this type of join involves

primary and foreign key complements.

Note: Equijoins are also called simple joins or inner joins

```
SELECT employees.employee_id, employees.last_name, employees.department_id,  
departments.department_id, departments.location_id  
FROM employees, departments  
WHERE employees.department_id = departments.department_id;
```

Additional Search Conditions

Using the AND Operator

Example:

To display employee Matos' department number and department name, you need an additional condition in the WHERE clause.

```
SELECT last_name, employees.department_id,  
department_name  
FROM employees, departments  
WHERE employees.department_id = departments.department_id AND last_name = 'Matos';
```

Qualifying Ambiguous

Column Names

- Use table prefixes to qualify column names that are in multiple tables.
- Improve performance by using table prefixes.
- Distinguish columns that have identical names but reside in different tables by using column aliases.

Using Table Aliases

- Simplify queries by using table aliases.
- Improve performance by using table prefixes

Example:

```
SELECT e.employee_id, e.last_name, e.department_id,  
d.department_id, d.location_id  
FROM employees e, departments d  
WHERE e.department_id = d.department_id;
```

Joining More than Two Tables

To join n tables together, you need a minimum of n-1 join conditions. For example, to join three tables, a minimum of two joins is required.

Example:

To display the last name, the department name, and the city for each employee, you have to join the EMPLOYEES, DEPARTMENTS, and LOCATIONS tables.

```
SELECT e.last_name, d.department_name, l.city  
FROM employees e, departments d, locations l  
WHERE e.department_id = d.department_id
```

AND d.location_id = l.location_id;

Non-Equi Joins

A non-equijoin is a join condition containing something other than an equality operator. The relationship between the EMPLOYEES table and the JOB_GRADES table has an example of a non-equijoin. A relationship between the two tables is that the SALARY column in the EMPLOYEES table must be between the values in the LOWEST_SALARY and HIGHEST_SALARY columns of the JOB_GRADES table. The relationship is obtained using an operator other than equals (=).

Example:

```
SELECT e.last_name, e.salary, j.grade_level
FROM employees e, job_grades j
WHERE e.salary
BETWEEN j.lowest_sal AND j.highest_sal;
```

Outer Joins

Syntax

- You use an outer join to also see rows that do not meet the join condition.
- The Outer join operator is the plus sign (+).

```
SELECT table1.column, table2.column
FROM table1, table2
WHERE table1.column(+) = table2.column;
SELECT table1.column, table2.column
FROM table1, table2
WHERE table1.column = table2.column(+);
```

The missing rows can be returned if an outer join operator is used in the join condition. The operator is a plus sign enclosed in parentheses (+), and it is placed on the —side of the join that is deficient in information. This operator has the effect of creating one or more null rows, to which one or more rows from the nondeficient table can be joined.

Example:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e, departments d
WHERE e.department_id(+) = d.department_id ;
```

Outer Join Restrictions

- The outer join operator can appear on only one side of the expression—the side that has information missing. It returns those rows from one table that have no direct match in the other

table.

- A condition involving an outer join cannot use the IN operator or be linked to another condition by the OR operator

Self Join

Sometimes you need to join a table to itself.

Example:

To find the name of each employee's manager, you need to join the EMPLOYEES table to itself, or perform a self join.

```
SELECT worker.last_name || ' works for '
|| manager.last_name
FROM employees worker, employees manager
WHERE worker.manager_id = manager.employee_id ;
```

Use a join to query data from more than one table.

```
SELECT table1.column, table2.column
FROM table1
[CROSS JOIN table2] |
[NATURAL JOIN table2] |
[JOIN table2 USING (column_name)] |
[JOIN table2
ON(table1.column_name = table2.column_name)] |
[LEFT|RIGHT|FULL OUTER JOIN table2
ON (table1.column_name = table2.column_name)];
```

In the syntax:

table1.column Denotes the table and column from which data is retrieved

CROSS JOIN Returns a Cartesian product from the two tables

NATURAL JOIN Joins two tables based on the same column name

JOIN table USING column_name Performs an equijoin based on the column name JOIN table

ON table1.column_name Performs an equijoin based on the condition in the ON clause

= table2.column_name

LEFT/RIGHT/FULL OUTER

Creating Cross Joins

- The CROSS JOIN clause produces the crossproduct of two tables.
- This is the same as a Cartesian product between the two tables.

Example:

```
SELECT last_name, department_name
FROM employees
```



```
CROSS JOIN departments ;
SELECT last_name, department_name
FROM employees, departments;
```

Creating Natural Joins

- The NATURAL JOIN clause is based on all columns in the two tables that have the same name.
- It selects rows from the two tables that have equal values in all matched columns. • If the columns having the same names have different data types, an error is returned.

Example:

```
SELECT department_id, department_name,
location_id, city
FROM departments
NATURAL JOIN locations ;
```

LOCATIONS table is joined to the DEPARTMENT table by the LOCATION_ID column, which is the only column of the same name in both tables. If other common columns were present, the join would have used them all.

Example:

```
SELECT department_id, department_name,
location_id, city
FROM departments
NATURAL JOIN locations
WHERE department_id IN (20, 50);
```

Creating Joins with the USING Clause

- If several columns have the same names but the data types do not match, the NATURAL JOIN clause can be modified with the USING clause to specify the columns that should be used for an equijoin.
- Use the USING clause to match only one column when more than one column matches. • Do not use a table name or alias in the referenced columns.
- The NATURAL JOIN and USING clauses are mutually exclusive.

Example:

```
SELECT l.city, d.department_name
FROM locations l JOIN departments d USING (location_id)
WHERE location_id = 1400;
EXAMPLE:
```

```
SELECT e.employee_id, e.last_name, d.location_id
FROM employees e JOIN departments d
USING (department_id) ;
```

Creating Joins with the ON Clause

- The join condition for the natural join is basically an equijoin of all columns with the same name.
- To specify arbitrary conditions or specify columns to join, the ON clause is used.
- The join condition is separated from other searchconditions.
- The ON clause makes code easy to understand.

Example:

```
SELECT e.employee_id, e.last_name, e.department_id,
d.department_id, d.location_id
FROM employees e JOIN departments d
ON (e.department_id = d.department_id);
EXAMPLE:
```

```
SELECT e.last_name emp, m.last_name mgr
FROM employees e JOIN employees m
ON (e.manager_id = m.employee_id);
INNER Versus OUTER Joins
```

- A join between two tables that returns the results of the inner join as well as unmatched rows left (or right) tables is a left (or right) outer join.
- A join between two tables that returns the results of an inner join as well as the results of a left and right join is a full outer join.

LEFT OUTER JOIN

Example:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
LEFT OUTER JOIN departments d
ON (e.department_id = d.department_id) ;
```

Example of LEFT OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, which is the left table even if there is no match in the DEPARTMENTS table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e, departments d
WHERE d.department_id (+) = e.department_id;
```

RIGHT OUTER JOIN

Example:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
RIGHT OUTER JOIN departments d
ON (e.department_id = d.department_id) ;
```

This query retrieves all rows in the DEPARTMENTS table, which is the right table even if there is no

match in the EMPLOYEES table.

This query was completed in earlier releases as follows:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e, departments d
WHERE d.department_id = e.department_id (+);
```

FULL OUTER JOIN

Example:

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
FULL OUTER JOIN departments d
ON (e.department_id = d.department_id) ;
```

This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

Find the Solution for the following:

1. Write a query to display the last name, department number, and department name for all employees.

```
SELECT e.last_name, e.department_id, d.department_name
FROM employees e
JOIN departments d ON e.department_id = d.department_id
```

2. Create a unique listing of all jobs that are in department 80. Include the location of the department in the output.

```

SELECT DISTINCT e.job_id, d.location_id
FROM employees e
JOIN departments d ON e.department_id = d.department_id
WHERE e.department_id = 80;

```

3. Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

```

SELECT e.last_name, d.department_name, d.location_id, l.city
FROM employees e
JOIN departments d ON e.department_id = d.department_id
JOIN locations l ON d.location_id = l.location_id
WHERE e.commission_pct IS NOT NULL;

```

5. Write a query to display the last name, job, department number, and department name for all employees who work in Toronto.

```

SELECT e.last_name, e.job_id, e.department_id, d.department_name
FROM employees e
JOIN departments d ON e.department_id = d.department_id
JOIN locations l ON d.location_id = l.location_id
WHERE l.city = 'Toronto';

```

6. Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

```

SELECT e.last_name AS Employee, e.employee_id AS Emp#, m.last_name AS Manager,
m.employee_id AS Mgr#
FROM employees
LEFT JOIN employees m ON e.manager_id = m.employee_id

```

7. Modify lab4_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

```

wSELECT e.last_name AS Employee, e.employee_id AS Emp#, m.last_name AS Manager,
m.employee_id AS Mgr#
FROM employees e
LEFT JOIN employees m ON e.manager_id = m.employee_id
ORDER BY e.employee_id;

```

8. Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

```
SELECT e1.last_name AS Employee, e1.department_id AS Dept#, e2.last_name AS Colleague
FROM employees e
JOIN employees e2 ON e1.department_id = e2.department_id
WHERE e1.employee_id <> e2.employee_id;
```

9. Show the structure of the JOB_GRADES table. Create a query that displays the name, job, department name, salary, and grade for all employees

```
DESCRIBE job_grades
SELECT e.last_name, e.job_id, d.department_name, e.salary, j.grade_level
FROM employees e
JOIN departments d ON e.department_id = d.department_id
JOIN job_grades j ON e.salary BETWEEN j.lowest_sal AND j.highest_sal;
```

10. Create a query to display the name and hire date of any employee hired after employee Davies.

```
SELECT e.last_name, e.hire_date
FROM employees e
WHERE e.hire_date > (SELECT hire_date FROM employees WHERE last_name = 'Davies')
```

11. Display the names and hire dates for all employees who were hired before their managers, along with their manager's names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

```
SELECT e.last_name AS Employee, e.hire_date AS "Emp Hired", m.last_name AS Manager,
m.hire_date AS "Mgr Hired"
FROM employees e
JOIN employees m ON e.manager_id = m.employee_id
WHERE e.hire_date < m.hire_date;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	

Total (15)	
Faculty Signature	

Ex.No.: 9	SUB QUERIES	
Date:		

Objectives

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

Using a Subquery to Solve a Problem

Who has a salary greater than Abel's?

Main query:

Which employees have salaries greater than Abel's salary?

Subquery:

What is Abel's salary?

Subquery Syntax

SELECT *select_list* FROM *table* WHERE *expr operator* (SELECT *select_list* FROM

table); • The subquery (inner query) executes once before the main query (outer query). •

The result of the subquery is used by the main query.

A subquery is a SELECT statement that is embedded in a clause of another SELECT statement. You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself.

You can place the subquery in a number of SQL clauses, including the following:

- WHERE clause

- HAVING clause
- FROM clause

In the syntax:

operator includes a comparison condition such as >, =, or IN

Note: Comparison conditions fall into two classes: single-row operators (>, =, >=, <, <>, <=) and multiple-row operators (IN, ANY, ALL). statement. The subquery generally executes first, and its output is used to complete the query condition for the main (or outer) query

Using a Subquery

```
SELECT last_name FROM employees WHERE salary > (SELECT salary FROM
employees WHERE last_name = 'Abel');
```

The inner query determines the salary of employee Abel. The outer query takes the result of the inner query and uses this result to display all the employees who earn more than this amount.

Guidelines for Using Subqueries

- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition.
- The ORDER BY clause in the subquery is not needed unless you are performing Top-N analysis.
- Use single-row operators with single-row

subqueries, and use multiple-row operators with multiple-row

subqueries. **Types of Subqueries**

- Single-row subqueries: Queries that return only one row from the inner SELECT statement.
- Multiple-row subqueries: Queries that return more than one row from the inner SELECT statement.

Single-Row Subqueries

- Return only one row
- Use single-row comparison operators

Example

Display the employees whose job ID is the same as that of employee 141:

```
SELECT last_name, job_id FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141);
```

Displays employees whose job ID is the same as that of employee 141 and whose salary is greater than that of employee 143.

```
SELECT last_name, job_id, salary FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141) AND salary > (SELECT salary FROM employees WHERE employee_id = 143);
```

Using Group Functions in a Subquery

Displays the employee last name, job ID, and salary of all employees whose salary is equal to the minimum salary. The MIN group function returns a single value (2500) to the outer query.

```
SELECT last_name, job_id, salary FROM employees WHERE salary = (SELECT MIN(salary) FROM employees);
```

The HAVING Clause with Subqueries

- The Oracle server executes subqueries first.
- The Oracle server returns results into the HAVING clause of the main query. Displays all the departments that have a minimum salary greater than that of department 50.

```
SELECT department_id, MIN(salary) FROM employees GROUP BY department_id HAVING MIN(salary) > (SELECT MIN(salary) FROM employees WHERE department_id = 50);
```

Example

Find the job with the lowest average salary.

```
SELECT job_id, AVG(salary)
```



```
FROM employees
GROUP BY job_id
HAVING AVG(salary) = (SELECT MIN(AVG(salary))
FROM employees
GROUP BY job_id);
```

What Is Wrong in this Statements?

```
SELECT employee_id, last_name
FROM employees
WHERE salary =(SELECT MIN(salary) FROM employees GROUP BY
department_id); Will This Statement Return Rows?
SELECT last_name, job_id
FROM employees
WHERE job_id =(SELECT job_id FROM employees WHERE last_name =
```

'Haas'); **Multiple-Row Subqueries**

- Return more than one row
- Use multiple-row comparison operators

Example

Find the employees who earn the same salary as the minimum salary for each department.

```
SELECT last_name, salary, department_id FROM employees WHERE salary IN (SELECT
MIN(salary)
FROM employees GROUP BY department_id);
```

Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary FROM employees WHERE salary < ANY
(SELECT salary FROM employees WHERE job_id = 'IT_PROG') AND job_id <>
'IT_PROG';
```

Displays employees who are not IT programmers and whose salary is less than that of any IT programmer. The maximum salary that a programmer earns is \$9,000.

< ANY means less than the maximum. >ANY means more than the minimum. =ANY is equivalent to IN.

Using the ALL Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM employees
```

WHERE salary < ALL (SELECT salary FROM employees WHERE job_id = 'IT_PROG') AND job_id <> 'IT_PROG';

Displays employees whose salary is less than the salary of all employees with a job ID of IT_PROG and whose job is not IT_PROG.

- ALL means more than the maximum, and <ALL means less than the minimum.

The NOT operator can be used with IN, ANY, and ALL operators.

Null Values in a Subquery

```
SELECT emp.last_name FROM employees emp
WHERE emp.employee_id NOT IN (SELECT mgr.manager_id FROM employees mgr);
```

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

```
SELECT emp.last_name
FROM employees emp
WHERE emp.employee_id IN (SELECT mgr.manager_id FROM employees mgr);
```

Display all employees who do not have any subordinates:

```
SELECT last_name FROM employees
WHERE employee_id NOT IN (SELECT manager_id FROM employees WHERE manager_id
IS NOT NULL);
```

Find the Solution for the following:

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

```
SELECT last_name, hire_date
```

```
FROM employees
```

```
WHERE department_id = (
```

```
    SELECT department_id
```

FROM employees

WHERE last_name = :last_name -- The user input

AND ROWNUM = 1 -- Ensure that we are getting a single result

)

AND last_name != :last_name; -- Exclude the employee whose last name is entered

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

SELECT employee_id, last_name, salary

FROM employees

WHERE salary > (SELECT AVG(salary) FROM employees)

ORDER BY salary ASC;

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a *u*.

ANS

```
SELECT e1.employee_id, e1.last_name
FROM employees e1
JOIN employees e2 ON e1.department_id = e2.department_id
WHERE e2.last_name LIKE '%u%';
```

4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

ANS

```
SELECT e.last_name, e.department_id, e.job_id
FROM employees e
JOIN departments d ON e.department_id = d.department_id
WHERE d.location_id = 1700;
```

5. Create a report for HR that displays the last name and salary of every employee who reports to King.

```
SELECT last_name, salary
```

```
FROM employees
```

```
WHERE manager_id = (SELECT employee_id FROM employees WHERE last_name =  
'King');
```

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

```
SELECT e.department_id, e.last_name, e.job_id
```

```
FROM employees e
```

```
JOIN departments d ON e.department_id = d.department_id
```

```
WHERE d.department_name = 'Executive';
```

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a *u*.

```
SELECT e1.employee_id, e1.last_name, e1.salary
```

```
FROM employees e1
```

```
JOIN employees e2 ON e1.department_id = e2.department_id
```

```
WHERE e2.last_name LIKE '%u%'
```

AND e1.salary > (SELECT AVG(salary) FROM employees)

ORDER BY e1.salary ASC;

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 10

AGGREGATING DATA USING GROUP FUNCTIONS

Date:		
--------------	--	--

Objectives

After the completion of this exercise, the students be will be able to do the following:

- Identify the available group functions
- Describe the use of group functions
- Group data by using the GROUP BY clause
- Include or exclude grouped rows by using the HAVING clause

What Are Group Functions?

Group functions operate on sets of rows to give one result per group

Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE

Each of the functions accepts an argument. The following table identifies the options that you can use in the syntax:

Function	Description
AVG ([DISTINCT <u>ALL</u>] <i>n</i>)	Average value of <i>n</i> , ignoring null values
COUNT ({ * [DISTINCT <u>ALL</u>] <i>expr</i> })	Number of rows, where <i>expr</i> evaluates to something other than null (count all selected rows using *, including duplicates and rows with nulls)
MAX ([DISTINCT <u>ALL</u>] <i>expr</i>)	Maximum value of <i>expr</i> , ignoring null values
MIN ([DISTINCT <u>ALL</u>] <i>expr</i>)	Minimum value of <i>expr</i> , ignoring null values
STDDEV ([DISTINCT <u>ALL</u>] <i>x</i>)	Standard deviation of <i>n</i> , ignoring null values
SUM ([DISTINCT <u>ALL</u>] <i>n</i>)	Sum values of <i>n</i> , ignoring null values
VARIANCE ([DISTINCT <u>ALL</u>] <i>x</i>)	Variance of <i>n</i> , ignoring null values

Group Functions: Syntax

```
SELECT [column,] group_function(column), ...
FROM table
[WHERE condition]
[GROUP BY column]
[ORDER BY column];
```

Guidelines for Using Group Functions

- DISTINCT makes the function consider only nonduplicate values; ALL makes it consider every value, including duplicates. The default is ALL and therefore does not need to be specified.
- The data types for the functions with an expr argument may be CHAR, VARCHAR2, NUMBER, or DATE.
- All group functions ignore null values.

Using the AVG and SUM Functions

You can use AVG and SUM for numeric data.

```
SELECT AVG(salary), MAX(salary),
MIN(salary), SUM(salary)
FROM employees
WHERE job_id LIKE '%REP%';
```

Using the MIN and MAX Functions

You can use MIN and MAX for numeric, character, and date data types.

```
SELECT MIN(hire_date), MAX(hire_date)
FROM employees;
```

You can use the MAX and MIN functions for numeric, character, and date data types. example displays the most junior and most senior employees.

The following example displays the employee last name that is first and the employee last name that is last in an alphabetized list of all employees:

```
SELECT MIN(last_name), MAX(last_name)
FROM employees;
```

Note: The AVG, SUM, VARIANCE, and STDDEV functions can be used only with numeric data types. MAX and MIN cannot be used with LOB or LONG data types.

Using the COUNT Function

COUNT(*) returns the number of rows in a table:

```
SELECT COUNT(*)
FROM employees
WHERE department_id = 50;
```

COUNT(expr) returns the number of rows with nonnull values for the *expr*:

```
SELECT COUNT(commission_pct)
FROM employees
WHERE department_id = 80;
```

Using the DISTINCT Keyword

- COUNT(DISTINCT expr) returns the number of distinct non-null values of the *expr*.
- To display the number of distinct department values in the EMPLOYEES table:

```
SELECT COUNT(DISTINCT department_id) FROM employees;
```

Use the DISTINCT keyword to suppress the counting of any duplicate values in a column. **Group Functions and Null Values**

Group functions ignore null values in the column:

```
SELECT AVG(commission_pct)
FROM employees;
```

The NVL function forces group functions to include null values:

```
SELECT AVG(NVL(commission_pct, 0))
FROM employees;
```

Creating Groups of Data

To divide the table of information into smaller groups. This can be done by using the GROUP BY clause.

GROUP BY Clause Syntax

```
SELECT column, group_function(column)
FROM table
[WHERE condition]
[GROUP BY group_by_expression]
[ORDER BY column];
```

In the syntax:

group_by_expression specifies columns whose values determine the basis for grouping rows

Guidelines

- If you include a group function in a SELECT clause, you cannot select individual

results as well, *unless* the individual column appears in the GROUP BY clause. You receive an error message if you fail to include the column list in the GROUP BY clause.

- Using a WHERE clause, you can exclude rows before dividing them into groups.
- You must include the *columns* in the GROUP BY clause.
- You cannot use a column alias in the GROUP BY clause.

Using the GROUP BY Clause

All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id ;
```

The GROUP BY column does not have to be in the SELECT list.

```
SELECT AVG(salary) FROM employees GROUP BY department_id ;
```

You can use the group function in the ORDER BY clause:

```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id ORDER
BY AVG(salary);
```

Grouping by More Than One Column

```
SELECT department_id dept_id, job_id, SUM(salary) FROM employees
GROUP BY department_id, job_id ;
```

Illegal Queries Using Group Functions

Any column or expression in the SELECT list that is not an aggregate function must be in the GROUP

BY clause:

```
SELECT department_id, COUNT(last_name) FROM employees;
```

You can correct the error by adding the GROUP BY clause:

```
SELECT department_id, count(last_name) FROM employees GROUP BY
```

department_id; You cannot use the WHERE clause to restrict groups.

- You use the HAVING clause to restrict groups.
- You cannot use group functions in the WHERE clause.

```
SELECT department_id, AVG(salary) FROM employees WHERE AVG(salary) > 8000  
GROUP BY department_id;
```

You can correct the error in the example by using the HAVING clause to restrict groups:

```
SELECT department_id, AVG(salary) FROM employees  
HAVING AVG(salary) > 8000 GROUP BY department_id;
```

Restricting Group Results

With the HAVING Clause .When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are displayed.

Using the HAVING Clause

```
SELECT department_id, MAX(salary) FROM employees  
GROUP BY department_id HAVING MAX(salary) > 10000 ;
```

The following example displays the department numbers and average salaries for those departments with a maximum salary that is greater than \$10,000:

```
SELECT department_id, AVG(salary) FROM employees GROUP BY department_id  
HAVING max(salary) > 10000;
```

Example displays the job ID and total monthly salary for each job that has a total payroll exceeding \$13,000. The example excludes sales representatives and sorts the list by the total monthly salary.

```
SELECT job_id, SUM(salary) PAYROLL FROM employees WHERE job_id NOT LIKE  
'%REP%'  
GROUP BY job_id HAVING SUM(salary) > 13000 ORDER BY SUM(salary);
```

Nesting Group Functions

Display the maximum average salary:

Group functions can be nested to a depth of two. The slide example displays the maximum average salary.

```
SELECT MAX(AVG(salary)) FROM employees GROUP BY department_id;
```

Summary

In this exercise, students should have learned how to:

- Use the group functions COUNT, MAX, MIN, and AVG
- Write queries that use the GROUP BY clause
- Write queries that use the HAVING clause

```
SELECT column, group_function
FROM table
[WHERE condition]
[GROUP BY group_by_expression]
[HAVING group_condition]
[ORDER BY column];
```

Find the Solution for the following:

Determine the validity of the following three statements. Circle either True or False.

1. Group functions work across many rows to produce one result per group. True/False
2. Group functions include nulls in calculations.
True/False
3. The WHERE clause restricts rows prior to inclusion in a group calculation. True/False

The HR department needs the following reports:

4. Find the highest, lowest, sum, and average salary of all employees. Label the columns Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number

```
SELECT

    ROUND(MAX(salary)) AS Maximum,

    ROUND(MIN(salary)) AS Minimum,

    ROUND(SUM(salary)) AS Sum,

    ROUND(AVG(salary)) AS Average

FROM employees;
```

5. Modify the above query to display the minimum, maximum, sum, and average salary for each job type.

6. Write a query to display the number of people with the same job. Generalize the query so that the user in the HR department is prompted for a job title.

```
SELECT
    job_title,
    COUNT(*) AS Number_of_Employees
FROM employees
WHERE job_title = :job_title -- Assuming you're using a parameterized query
GROUP BY job_title;
```

7. Determine the number of managers without listing them. Label the column Number of Managers. *Hint: Use the MANAGER_ID column to determine the number of managers.* *SELECT e.last_name AS Employee, e.employee_id AS Emp#, m.last_name AS Manager, m.employee_id AS Mgr#*

FROM employees e

LEFT JOIN employees m ON e.manager_id = m.employee_id

ORDER BY e.employee_id;

8. Find the difference between the highest and lowest salaries. Label the column DIFFERENCE. SELECT e1.last_name AS Employee, e1.department_id AS Dept#, e2.last_name AS Colleague

FROM employees e1


```
JOIN employees e2 ON e1.department_id = e2.department_id
```

```
WHERE e1.employee_id <> e2.employee_id;
```

9. Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is \$6,000 or less. Sort the output in descending order of salary.

```
SELECT
```

```
manager_id,
```

```
MIN(salary) AS Lowest_Salary
```

```
FROM employees
```

WHERE manager_id IS NOT NULL

GROUP BY manager_id

HAVING MIN(salary) > 6000

ORDER BY Lowest_Salary DESC;

10. Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings.

```
SELECT
```

```
    COUNT(*) AS Total_Employees,
```

```
    SUM(CASE WHEN hire_date BETWEEN '01-01-1995' AND '12-31-1995' THEN 1 ELSE  
0 END) AS Hired_1995,
```

```
SUM(CASE WHEN hire_date BETWEEN '01-01-1996' AND '12-31-1996' THEN 1 ELSE  
0 END) AS Hired_1996,
```

```
SUM(CASE WHEN hire_date BETWEEN '01-01-1997' AND '12-31-1997' THEN 1 ELSE  
0 END) AS Hired_1997,
```

```
SUM(CASE WHEN hire_date BETWEEN '01-01-1998' AND '12-31-1998' THEN 1 ELSE  
0 END) AS Hired_1998
```

```
FROM employees;
```

11. Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading.
SELECT

```
job_title AS Job,  
department_id AS Department,  
ROUND(AVG(salary)) AS Average_Salary,  
SUM(salary) AS Total_Salary  
FROM employees  
WHERE department_id IN (20, 50, 80, 90)  
GROUP BY job_title, department_id;
```

12. Write a query to display each department's name, location, number of employees, and the average salary for all the employees in that department. Label the column name-Location, Number of people, and salary respectively. Round the average salary to two decimal places.

```
SELECT
```

```
d.department_name AS Name,
```

```
d.location_id AS Location,
```

COUNT(e.employee_id) AS Number_of_People,

ROUND(AVG(e.salary), 2) AS Salary

FROM departments d

LEFT JOIN employees e ON d.department_id = e.department_id

GROUP BY d.department_name, d.location_id;

Evaluation Procedure	Marks awarded
----------------------	---------------

Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

Ex.No.: 11	PL SQL PROGRAMS	
Date:		

PROGRAMS

TO DISPLAY HELLO MESSAGE

```
SQL> set serveroutput on;
SQL> declare
2 a varchar2(20);
3 begin
4 a:='Hello';
5 dbms_output.put_line(a);
6 end;
7 /
Hello
```

PL/SQL procedure successfully completed.

TO INPUT A VALUE FROM THE USER AND DISPLAY IT

```
SQL> set serveroutput on;
SQL> declare
2 a varchar2(20);
3 begin
4 a:=&a;
5 dbms_output.put_line(a);
6 end;
7 /
Enter value for a: 5
old 4: a:=&a;
```



```
new 4: a:=5;  
5
```

PL/SQL procedure successfully completed.

GREATEST OF TWO NUMBERS

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 a number(7);  
3 b number(7);  
4 begin  
5 a:=&a;  
6 b:=&b;  
7 if(a>b) then  
8 dbms_output.put_line (' The grerater of the two is' || a);  
9 else  
10 dbms_output.put_line (' The grerater of the two is' || b);  
11 end if;  
12 end;  
13 /
```

Enter value for a: 5

old 5: a:=&a;

new 5: a:=5;

Enter value for b: 9

old 6: b:=&b;

new 6: b:=9;

The grerater of the two is9

PL/SQL procedure successfully completed.

GREATEST OF THREE NUMBERS

```
SQL> set serveroutput on;
```

```
SQL> declare  
2 a number(7);  
3 b number(7);  
4 c number(7);  
5 begin  
6 a:=&a;  
7 b:=&b;  
8 c:=&c;  
9 if(a>b and a>c) then  
10 dbms_output.put_line (' The greatest of the three is ' || a);
```

```

11 else if (b>c) then
12 dbms_output.put_line (' The greatest of the three is ' || b);
13 else
14 dbms_output.put_line (' The greatest of the three is ' || c);
15 end if;
16 end if;
17 end;
18 /
Enter value for a: 5
old 6: a:=&a;
new 6: a:=5;
Enter value for b: 7
old 7: b:=&b;
new 7: b:=7;
Enter value for c: 1
old 8: c:=&c;
new 8: c:=1;
The greatest of the three is 7

```

PL/SQL procedure successfully completed.

PRINT NUMBERS FROM 1 TO 5 USING SIMPLE

LOOP SQL> set serveroutput on;

```

SQL> declare
2 a number:=1;
3 begin
4 loop
5 dbms_output.put_line (a);
6 a:=a+1;
7 exit when a>5;
8 end loop;
9 end;
10 /
1
2
3
4
5

```

PL/SQL procedure successfully completed.

PRINT NUMBERS FROM 1 TO 4 USING WHILE LOOP

SQL> set serveroutput on;

```
SQL> declare
2 a number:=1;
3 begin
4 while(a<5)
5 loop
6 dbms_output.put_line (a);
7 a:=a+1;
8 end loop;
9 end;
10 /
1
2
3
4
```

PL/SQL procedure successfully completed.

PRINT NUMBERS FROM 1 TO 5 USING FOR LOOP

SQL> set serveroutput on;

```
SQL> declare
2 a number:=1;
3 begin
4 for a in 1..5
5 loop
6 dbms_output.put_line (a);
7 end loop;
8 end;
9 /
1
2
3
4
5
```

PL/SQL procedure successfully completed.

PRINT NUMBERS FROM 1 TO 5 IN REVERSE ORDER USING FOR LOOP

SQL> set serveroutput on;

```
SQL> declare
2 a number:=1;
3 begin
4 for a in reverse 1..5
5 loop
```

```

6 dbms_output.put_line (a);
7 end loop;
8 end;
9 /
5
4
3
2
1

```

PL/SQL procedure successfully completed.

TO CALCULATE AREA OF CIRCLE

```

SQL> set serveroutput on;
SQL> declare
2 pi constant number(4,2):=3.14;
3 a number(20);
4 r number(20);
5 begin
6 r:=&r;
7 a:= pi* power(r,2);
8 dbms_output.put_line (' The area of circle is ' || a);
9 end;
10 /

```

Enter value for r: 2

old 6: r:=&r;

new 6: r:=2;

The area of circle is 13

PL/SQL procedure successfully completed.

TO CREATE SACCOUNT TABLE

```

SQL> create table saccount ( accno number(5), name varchar2(20), bal number(10));
Table created.

```

```

SQL> insert into saccount values ( 1,'mala',20000);
1 row created.

```

```

SQL> insert into saccount values (2,'kala',30000);
1 row created.

```

```

SQL> select * from saccount;

```

ACCNO NAME BAL

1 mala 20000

2 kala 30000

```

SQL> set serveroutput on;

```

```

SQL> declare
2 a_bal number(7);
3 a_no varchar2(20);
4 debit number(7):=2000;
5 minamt number(7):=500;

```

```

6 begin
7 a_no:=&a_no;
8 select bal into a_bal from saccount where accno= a_no;
9 a_bal:= a_bal-debit;
10 if (a_bal > minamt) then
11 update saccount set bal=bal-debit where accno=a_no;
12 end if;
13 end;
14
15 /

```

Enter value for a_no: 1

old 7: a_no:=&a_no;

new 7: a_no:=1;

PL/SQL procedure successfully completed.

SQL> select * from saccount;

ACCNO NAME BAL

1 mala 18000

2 kala 30000

TO CREATE TABLE SROUTES

SQL> create table sroutes (rno number(5), origin varchar2(20), destination varchar2(20), fare

numbe

r(10), distance number(10));

Table created.

SQL> insert into sroutes values (2, 'chennai', 'dindugal', 400,230);

1 row created.

SQL> insert into sroutes values (3, 'chennai', 'madurai', 250,300);

1 row created.

SQL> insert into sroutes values (6, 'thanjavur', 'palani', 350,370);

1 row created.

SQL> select * from sroutes;

RNO ORIGIN DESTINATION FARE DISTANCE -----

2 chennai dindugal 400 230

3 chennai madurai 250 300

6 thanjavur palani 350 370

SQL> set serveroutput on;

SQL> declare

2 route sroutes.rno % type;

3 fares sroutes.fare % type;

4 dist sroutes.distance % type;

5 begin

6 route:=&route;

```

7 select fare, distance into fares , dist from sroutes where rno=route;
8 if (dist < 250) then
9 update sroutes set fare=300 where rno=route;
10 else if dist between 250 and 370 then
11 update sroutes set fare=400 where rno=route;
12 else if (dist > 400) then
13 dbms_output.put_line('Sorry');
14 end if;
15 end if;
16 end if;
17 end;
18 /

```

Enter value for route: 3

old 6: route:=&route;

new 6: route:=3;

PL/SQL procedure successfully completed.

SQL> select * from sroutes;

```

RNO ORIGIN DESTINATION FARE DISTANCE -----
-----
2 chennai dindugal 400 230
3 chennai madurai 400 300
6 thanjavur palani 350 370

```

TO CREATE SCALCULATE TABLE

SQL> create table scalculate (radius number(3), area
number(5,2)); Table created.

SQL> desc scalculate;

```

Name Null? Type
-----
----- RADIUS NUMBER(3)
AREA NUMBER(5,2)

```

SQL> set serveroutput on;

SQL> declare

2 pi constant number(4,2):=3.14;

3 area number(5,2);

4 radius number(3);

5 begin

6 radius:=3;

```

7 while (radius <=7)
8 loop
9 area:= pi* power(radius,2);
10 insert into scalculate values (radius,area);
11 radius:=radius+1;
12 end loop;
13 end;
14 /

```

PL/SQL procedure successfully completed.

```

SQL> select * from scalculate;
RADIUS AREA

```

```

3 28.26
4 50.24
5 78.5
6 113.04
7 153.86

```

TO CALCULATE FACTORIAL OF A GIVEN NUMBER

```

SQL> set serveroutput on;
SQL> declare
2 f number(4):=1;
3 i number(4);
4 begin
5 i:=&i;
6 while(i>=1)
7 loop
8 f:=f*i;
9 i:=i-1;
10 end loop;
11 dbms_output.put_line('The value is ' || f);
12 end;
13 /

```

Enter value for i: 5

old 5: i:=&i;

new 5: i:=5;

The value is 120

PL/SQL procedure successfully completed.

PROGRAM 1

Write a PL/SQL block to calculate the incentive of an employee whose ID is 110.

DECLARE

```

v_salary      employees.salary%TYPE;
v_incentive_pct employees.incentive_percentage%TYPE;
v_incentive    NUMBER;
BEGIN
    -- Retrieve the salary and incentive percentage for employee 110
    SELECT salary, incentive_percentage
    INTO v_salary, v_incentive_pct
    FROM employees
    WHERE employee_id = 110;

    -- Calculate the incentive
    v_incentive := v_salary * (v_incentive_pct / 100);

    -- Output the incentive (could be stored, logged, or used further)
    DBMS_OUTPUT.PUT_LINE('Employee ID 110: Salary = ' || v_salary || ', Incentive = ' ||
v_incentive);

    -- Optionally, update the incentive value in the employees table (if needed)
    UPDATE employees
    SET incentive = v_incentive
    WHERE employee_id = 110;

    COMMIT; -- Commit the transaction if an update was performed

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        DBMS_OUTPUT.PUT_LINE('Employee ID 110 not found.');
```


WHEN OTHERS THEN

DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);

END;

/

PROGRAM 2

Write a PL/SQL block to show an invalid case-insensitive reference to a quoted and without quoted user-defined identifier.

ANS

DECLARE

v_salary employees.salary%TYPE;

v_incentive_pct employees.incentive_percentage%TYPE;

v_incentive NUMBER;

BEGIN

-- Retrieve the salary and incentive percentage for employee 110

SELECT salary, incentive_percentage

INTO v_salary, v_incentive_pct

FROM employees

WHERE employee_id = 110;

-- Calculate the incentive

v_incentive := v_salary * (v_incentive_pct / 100);

-- Output the incentive (could be stored, logged, or used further)

DBMS_OUTPUT.PUT_LINE('Employee ID 110: Salary = ' || v_salary || ', Incentive = ' || v_incentive);

-- Optionally, update the incentive value in the employees table (if needed)

UPDATE employees

```

SET incentive = v_incentive
WHERE employee_id = 110;

COMMIT; -- Commit the transaction if an update was performed

EXCEPTION

WHEN NO_DATA_FOUND THEN

    DBMS_OUTPUT.PUT_LINE('Employee ID 110 not found.');
```

WHEN OTHERS THEN

```

    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;

/
```

PROGRAM 3

Write a PL/SQL block to adjust the salary of the employee whose ID 122. Sample table: employees

```
DECLARE
```

```

    v_current_salary employees.salary%TYPE; -- Variable to store the
current salary of the employee
```

```

    v_new_salary      employees.salary%TYPE; -- Variable to store the
new adjusted salary
```

```

    v_adjustment_pct  NUMBER := 10;          -- Percentage increase
(e.g., 10% increase)
```

```
BEGIN
```

```

    -- Retrieve the current salary of employee ID 122
```

```

    SELECT salary
```

```

INTO v_current_salary

FROM employees

WHERE employee_id = 122;

-- Calculate the new salary with the percentage adjustment

v_new_salary := v_current_salary * (1 + v_adjustment_pct / 100);

-- Output the current and new salary for verification

DBMS_OUTPUT.PUT_LINE('Employee ID 122: Current Salary = ' ||
v_current_salary || ', New Salary = ' || v_new_salary);

-- Update the employee's salary with the new adjusted value

UPDATE employees

SET salary = v_new_salary

WHERE employee_id = 122;

-- Commit the changes to make them permanent

COMMIT;

DBMS_OUTPUT.PUT_LINE('Salary updated successfully for
Employee ID 122.');
```

```

EXCEPTION

WHEN NO_DATA_FOUND THEN

    DBMS_OUTPUT.PUT_LINE('Employee ID 122 not found.');
```

```
WHEN OTHERS THEN

    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);

END;

/
```

PROGRAM 4

Write a PL/SQL block to create a procedure using the "IS [NOT] NULL Operator" and show AND operator returns TRUE if and only if both operands are TRUE.

ANS

```
CREATE OR REPLACE PROCEDURE check_null_and_operator (

    param1 IN VARCHAR2,

    param2 IN VARCHAR2
```

```

) IS
    v_result BOOLEAN;
BEGIN
    -- Check if both parameters are not NULL using the AND operator
    IF (param1 IS NOT NULL AND param2 IS NOT NULL) THEN
        v_result := TRUE;
        DBMS_OUTPUT.PUT_LINE('Both parameters are NOT NULL. AND operator returns TRUE.');
```

```

    ELSE
        v_result := FALSE;
        DBMS_OUTPUT.PUT_LINE('At least one parameter is NULL. AND operator returns FALSE.');
```

```

    END IF;

    -- Output the result of the AND condition
    DBMS_OUTPUT.PUT_LINE('Result: ' || CASE WHEN v_result THEN 'TRUE' ELSE 'FALSE' END);

EXCEPTION
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
/

```

PROGRAM 5

Write a PL/SQL block to describe the usage of LIKE operator including wildcard characters and escape character.

ANS

DECLARE

v_name employees.first_name%TYPE;

CURSOR employee_cursor IS

SELECT first_name

FROM employees

WHERE first_name LIKE 'J%' -- Names starting with 'J'

OR first_name LIKE '_a%' -- Names where the second character is 'a'

OR first_name LIKE 'A_%' ESCAPE '\' -- Names that start with 'A_' (escape the underscore)

OR first_name LIKE '%\%%%' ESCAPE '\' -- Names that contain '%' symbol

;

BEGIN

-- Open the cursor and fetch each employee name that matches the patterns

OPEN employee_cursor;

LOOP

FETCH employee_cursor INTO v_name;

EXIT WHEN employee_cursor%NOTFOUND;

-- Display the name that matches the pattern

DBMS_OUTPUT.PUT_LINE('Matching Name: ' || v_name);

END LOOP;

CLOSE employee_cursor;

EXCEPTION

WHEN OTHERS THEN

```
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;

/
```

PROGRAM 6

Write a PL/SQL program to arrange the number of two variable in such a way that the small number will store in num_small variable and large number will store in num_large variable.

ANS

```
DECLARE
    num1    NUMBER := 20;    -- First input number
    num2    NUMBER := 10;    -- Second input number
    num_small NUMBER;        -- Variable to store the smaller number
    num_large NUMBER;        -- Variable to store the larger number
BEGIN
    -- Compare the two numbers and assign to num_small and num_large
    IF num1 < num2 THEN
        num_small := num1;
        num_large := num2;
    ELSE
        num_small := num2;
        num_large := num1;
    END IF;
END;
```

```

END IF;

-- Output the results using DBMS_OUTPUT
DBMS_OUTPUT.PUT_LINE('Smaller number: ' || num_small);
DBMS_OUTPUT.PUT_LINE('Larger number: ' || num_large);

EXCEPTION
  WHEN OTHERS THEN
    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
/

```

PROGRAM 7

Write a PL/SQL procedure to calculate the incentive on a target achieved and display the message either the record updated or not.

ANS

```

CREATE OR REPLACE PROCEDURE calculate_incentive (
  p_employee_id IN NUMBER,    -- Employee ID
  p_target_achieved IN NUMBER, -- Target achieved percentage (e.g., 100%)
  p_incentive_pct IN NUMBER    -- Incentive percentage (e.g., 10%)
) IS
  v_salary      employees.salary%TYPE; -- Employee's current salary
  v_incentive    NUMBER;                -- Calculated incentive
  v_target_threshold NUMBER := 100;     -- Target threshold to qualify for incentive
BEGIN
  -- Retrieve the employee's salary
  SELECT salary
  INTO v_salary
  FROM employees
  WHERE employee_id = p_employee_id;

  -- Check if the target achieved meets or exceeds the threshold
  IF p_target_achieved >= v_target_threshold THEN
    -- Calculate the incentive as a percentage of the salary
    v_incentive := v_salary * (p_incentive_pct / 100);

    -- Update the employee's incentive
    UPDATE employees
    SET incentive = v_incentive
    WHERE employee_id = p_employee_id;

    -- Check if the update was successful
    IF SQL%ROWCOUNT > 0 THEN
      DBMS_OUTPUT.PUT_LINE('Record updated. Incentive for Employee ' ||
        p_employee_id || ' is ' || v_incentive);
    END IF;
  END IF;
END;

```



```

ELSE
    DBMS_OUTPUT.PUT_LINE('No record found for Employee ' ||
p_employee_id);
END IF;

```

PROGRAM 8

Write a PL/SQL procedure to calculate incentive achieved according to the specific sale limit.

ANS

```

CREATE OR REPLACE PROCEDURE calculate_incentive_based_on_sales (
    p_employee_id IN NUMBER,    -- Employee ID
    p_sales_achieved IN NUMBER  -- Total sales achieved by the employee
) IS
    v_sales_limit    NUMBER := 10000; -- Predefined sales target (limit)
    v_incentive_pct  NUMBER;          -- Incentive percentage based on sales achieved
    v_incentive      NUMBER;          -- Calculated incentive
    v_sales          NUMBER;          -- Employee's sales from the table
BEGIN
    -- Retrieve the sales from the employees table for the given employee ID
    SELECT sales
    INTO v_sales
    FROM employees
    WHERE employee_id = p_employee_id;

    -- Check if the sales achieved is less than the sales limit
    IF p_sales_achieved < v_sales_limit THEN
        -- If sales are below the limit, no incentive

```

```

    v_incentive := 0;
    DBMS_OUTPUT.PUT_LINE('Sales target not achieved for Employee ' || p_employee_id || '.
No incentive calculated. ');
ELSE
    -- Calculate incentive based on sales achieved
    IF p_sales_achieved < v_sales_limit * 1.2 THEN
        -- If sales are within 20% more than the target, give 5% incentive
        v_incentive_pct := 5;
    ELSE
        -- If sales exceed the target by 20% or more, give 10% incentive
        v_incentive_pct := 10;
    END IF;

    -- Calculate the incentive based on the sales achieved and percentage
    v_incentive := p_sales_achieved * (v_incentive_pct / 100);

    UPDATE employees
    SET incentive = v_incentive
    WHERE employee_id = p_employee_id;

    IF SQL%ROWCOUNT > 0 THEN
        DBMS_OUTPUT.PUT_LINE('Record updated for Employee ' || p_employee_id || '.
Incentive calculated: ' || v_incentive);
    ELSE
        DBMS_OUTPUT.PUT_LINE('Employee with ID ' || p_employee_id || ' not found. ');
    END IF;
END IF;

COMMIT;

EXCEPTION
    WHEN NO_DATA_FOUND THEN
        DBMS_OUTPUT.PUT_LINE('Employee with ID ' || p_employee_id || ' not found. ');
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
/

```