

# CS5560 Knowledge Discovery and Management

## Problem Set 7 & 8

Submission Deadline: July 28, 2017

<https://goo.gl/forms/aTXnl4oRHMdS8j1L2>

Name: Mudunuri Sri Sai Sarat Chandra Varma

Class ID: 14

### References

#### I. Logical knowledge representation

First Order Logic Reference: <http://pages.cs.wisc.edu/~dyer/cs540/notes/fopc.html>

1) Let us define the statements as follows:

- $G(x)$ : “x is a giraffe”
- $F(x)$ : “x is 15 feet or higher,”
- $Z(x)$ : “x is animal in this zoo”
- $M(x)$ : “x belongs to me”

Express each of the following statements in First-Order Logic using  $G(x)$ ,  $F(x)$ ,  $Z(x)$ , and  $M(x)$ .

- a) Nothing, except giraffes, can be 15 feet or higher;
- b) There is no animal in this zoo that does not belong to me;
- c) I have no animals less than 15 feet high.
- d) All animals in this zoo are giraffes.

#### Answer:

Possible answers are:

$$\begin{aligned} & \forall x(\neg G(x) \rightarrow \neg F(x)) \text{ OR } \forall x(F(x) \rightarrow G(x)) \\ & \neg \exists x(Z(x) \wedge \neg M(x)) \text{ OR } \forall x(Z(x) \rightarrow M(x)) \\ & \forall x(M(x) \rightarrow F(x)) \\ & \forall x(Z(x) \rightarrow G(x)) \end{aligned}$$

2) Which of the following are semantically and syntactically correct translations of “No dog bites a child of its owner”? Justify your answer

- a)  $\forall x \text{ Dog}(x) \Rightarrow \neg \text{Bites}(x, \text{Child}(\text{Owner}(x)))$
- b)  $\neg \exists x, y \text{ Dog}(x) \wedge \text{Child}(y, \text{Owner}(x)) \wedge \text{Bites}(x, y)$
- c)  $\forall x \text{ Dog}(x) \Rightarrow (\forall y \text{ Child}(y, \text{Owner}(x)) \Rightarrow \neg \text{Bites}(x, y))$
- d)  $\neg \exists x \text{ Dog}(x) \Rightarrow (\exists y \text{ Child}(y, \text{Owner}(x)) \wedge \text{Bites}(x, y))$

**Answers:**

- b)  $\neg \exists x, y \text{ Dog}(x) \wedge \text{Child}(y, \text{Owner}(x)) \wedge \text{Bites}(x, y)$
- c)  $\forall x \text{ Dog}(x) \Rightarrow (\forall y \text{ Child}(y, \text{Owner}(x)) \Rightarrow \neg \text{Bites}(x, y))$

3) For each of the following queries, describe each using Description Logic  
Reference: <http://www.inf.ed.ac.uk/teaching/courses/kmm/PDF/L3-L4-DL.pdf>

- a) Define a person is Vegan

**Answer:**

Value restrictions are often combined with appropriate classes using intersection:

Vegan  $\equiv$  Person  $\sqcap \forall \text{eats.Plant}$

Vegan  $\equiv$  Person  $\sqcap \forall \text{eats.Plant} \sqcap \exists \text{eats.Plant}$

- b) Define a person is Vegetarian

**Answer:**

Vegetarian  $\equiv$  Person  $\sqcap \forall \text{eats.}(\text{Plant} \sqcup \text{Dairy})$

Vegetarian  $\equiv$  Person  $\sqcap \forall \text{eats.Plant} \sqcap \exists \text{eats.Plant} \sqcap \exists \text{eats.Diary}$

- c) Define a person is Omnivore

**Answer:**

Omnivore  $\equiv$  Person  $\sqcap \exists \text{eats.Animal} \sqcap \exists \text{eats.}(\text{Plant} \sqcup \text{Dairy})$

Omnivore  $\equiv$  Person  $\sqcap \forall \text{eats.Plant} \sqcap \exists \text{eats.Plant} \sqcap \exists \text{eats.Diary} \sqcap \exists \text{eats.Animal}$

## II. SPARQL

Reference: <https://www.w3.org/2009/Talks/0615-qbe/>

Design a SPARQL query for following queries and show an expected output.

Query #1: Multiple triple patterns: property retrieval

*Find me all the people in Tim Berners-Lee's FOAF file that have names and email addresses. Return each person's URI, name, and email address.*

**Answer:**

**Query:**

```
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
SELECT *
WHERE {
    ?person foaf:name ?name .
    ?person foaf:mbox ?email .
}
```

**Output:**

<http://www.w3.org/People/karl/karl-foaf.xrdf#me>	"Karl Dubost"	<mailto:karl@w3.org>
<http://www.w3.org/People/Berners-Lee/card#amy>	"Amy van der Hiel"	<mailto:amy@w3.org>
<http://www.w3.org/People/Berners-Lee/card#edd>	"Edd Dumbill"	<mailto:edd@xmlhack.com>
<http://www.w3.org/People/Berners-Lee/card#dj>	"Dean Jackson"	<mailto:dean@w3.org>

Query #2: Multiple triple patterns: traversing a graph

*Find me the homepage of anyone known by Tim Berners-Lee.*

**Answer:**

**Query:**

```
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
PREFIX card: <http://www.w3.org/People/Berners-Lee/card#>
SELECT ?homepage
```

```

FROM <http://www.w3.org/People/Berners-Lee/card>
WHERE {
    card:i foaf:knows ?known .
    ?known foaf:homepage ?homepage .
}

```

**Output:**

http://www.w3.org/1999/02/22-rdf-syntax-ns#Property
http://xmlns.com/foaf/0.1/Person
http://dbpedia.org/class/yago/Landmark108624891
http://dbpedia.org/class/Book
http://www.w3.org/2004/02/skos/core#Concept
http://dbpedia.org/class/yago/CoastalCities
http://dbpedia.org/class/yago/AmericanAbolitionists

Query #3: Basic SPARQL filters

*Find me all landlocked countries with a population greater than 15 million.*

**Answer:**

**Query:**

```

PREFIX rdfs: <http://www.w3.org/2000/01/rdf-schema#>
PREFIX type: <http://dbpedia.org/class/yago/>
PREFIX prop: <http://dbpedia.org/property/>
SELECT ?country_name ?population
WHERE {
    ?country a type:LandlockedCountries ;
        rdfs:label ?country_name ;
        prop:populationEstimate ?population .
    FILTER (?population > 15000000) .
}

```

**Output:**

country_name	population
Afghanistan	31889923
Afganistán	31889923
Afghanistan	31889923
Afganistan	31889923
Afghanistan	31889923

Afghanistan	31889923
-------------	----------

Query #4: Finding artists' info

*Find all Jamendo artists along with their image, home page, and the location they're near, if any.*

**Answer:**

**Query:**

```
PREFIX mo: <http://purl.org/ontology/mo/>
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
SELECT ?name ?img ?hp ?loc
WHERE {
    ?a a mo:MusicArtist ;
        foaf:name ?name .
    OPTIONAL { ?a foaf:img ?img }
    OPTIONAL { ?a foaf:homepage ?hp }
    OPTIONAL { ?a foaf:based_near ?loc }
}
```

**Output:**

```
"Cicada"^^xsd:string http://img.jamendo.com/artists/hattrickman.jpg http://www.cicada.fr/st http://sws.geonames.org/3031359/
```

```
"Hace Soul"^^xsd:string http://img.jamendo.com/artists/h/hace.soul.jpg http://www.hacesoul.com http://sws.geonames.org/2510769/
```

```
"vincentj"^^xsd:string http://img.jamendo.com/artists/v/vincentj.jpg http://v.joudrier.free.fr/SiteV http://sws.geonames.org/3020781/
```

Query #5. Design your own query

**Answer:**

**Query:**

```
SELECT DISTINCT ?person
WHERE {
    ?person foaf:name ?name .
```

```

GRAPH ?g1 { ?person a foaf:Person }
GRAPH ?g2 { ?person a foaf:Person }
GRAPH ?g3 { ?person a foaf:Person }
FILTER(?g1 != ?g2 && ?g1 != ?g3 && ?g2 != ?g3) .
}

```

**Output:**

<http://data.semanticweb.org/person/riichiro-mizoguchi>

<http://data.semanticweb.org/person/philippe-cudre-mauroux>

<http://data.semanticweb.org/person/lyndon-j-b-nixon>

<http://data.semanticweb.org/person/nigel-shadbolt>

<http://data.semanticweb.org/person/eero-hyvoenen>

### III. SWRL

References:

<https://www.w3.org/Submission/SWRL/>

<https://dior.ics.muni.cz/~makub/owl/>

Design SWRL rules for the following cases

Rule #1: design hasUncle property using hasParent and hasBrother properties

**Answer:**

A simple use of these rules would be to assert that the combination of the hasParent and hasBrother properties implies the hasUncle property. Informally, this rule could be written as:

$$\text{hasParent}(\text{?x1}, \text{?x2}) \wedge \text{hasBrother}(\text{?x2}, \text{?x3}) \Rightarrow \text{hasUncle}(\text{?x1}, \text{?x3})$$

Rule #2: an individual X from the Person class, which has parents Y and Z such that Y has spouse Z, belongs to a new class ChildOfMarriedParents.

**Answer:**

We can add a SWRL rule saying that an individual X from the Person class, which has parents Y and Z such that Y has spouse Z, belongs to a new class *ChildOfMarriedParents*. Such rule is best described in the Protege syntax:

```
Person(?x), hasParent(?x, ?y), hasParent(?x, ?z), hasSpouse(?y, ?z) ->
ChildOfMarriedParents(?x)
```

Rule #3: persons who have age higher than 18 are adults.

**Answer:**

The following rules from the listing use the core built-ins, they would be most correctly written as:

```
Person(?p), hasAge(?p, ?age), swrlb:greaterThan(?age, 18) -> Adult(?p)
```

Rule #4: Compute the person's born in year

**Answer:**

```
Person(?p), bornOnDate(?p, ?date), xsd:date(?date), swrlb:date(?date, ?year,
?month, ?day, ?timezone) -> bornInYear(?p, ?year)
```

Rule #5: Compute the person's age in years

**Answer:**

```
Person(?p), bornInYear(?p, ?year), my:thisYear(?nowyear),
swrlb:subtract(?age, ?nowyear, ?year) -> hasAge(?p, ?age)
```

Rule #6: Design your own rule

**Answer:**

```
Person(?x), hasChild min 1 Person(?x) -> Parent(?x)
```