

Rotation distance in trees

Sarath Krishna.S

December 30,2025

1 Literature Review

1.1 Paper 1: Rotation Distance, Triangulations, and Associahedra

Authors: William P. Thurston, Daniel D. Sleator, and Robert E. Tarjan

1.1.1 Motivation

Binary trees are fundamental data structures in computer science, and tree rotations are widely used to maintain balance in structures such as AVL and Red–Black trees. While rotations are local operations, transforming one binary tree into another may require many such operations.

The motivation of this paper is to understand the worst-case number of rotations required to transform one binary tree into another with the same number of internal nodes. Prior to this work, no tight global bounds were known for this problem. The authors aim to establish a clear theoretical upper bound on rotation distance and to place the problem within a geometric and combinatorial framework that allows rigorous analysis.

1.1.2 Methodology

The paper aims to establish an upper bound on the maximum rotation distance required to transform one binary tree into another binary tree with the same number of internal nodes. To analyze rotation distance more effectively, the paper introduces a one-to-one correspondence between binary trees with n internal nodes and triangulations of a convex $(n + 2)$ -gon.

Under this correspondence:

- Each internal edge of a binary tree maps to a diagonal in the polygon triangulation.
- A single tree rotation corresponds exactly to a **flip** of a diagonal in the polygon.

This geometric interpretation allows the authors to reason about rotations using combinatorial properties of polygon triangulations. To derive global bounds, the paper extends the triangulation model to three-dimensional structures, specifically the triangulation of a sphere and a 3-dimensional ball, using topological arguments to bound the number of required rotations.

1.1.3 Results

By relating binary tree rotations to polygon triangulations, the paper derives a linear upper bound on the rotation distance between any two binary trees with n internal nodes. The analysis shows that the maximum number of rotations required grows linearly with the size of the tree, with an explicit bound:

$$d(n) \leq 2n - 6$$

for sufficiently large n . This result establishes that transforming one binary tree into another is computationally efficient in terms of asymptotic complexity.

1.2 Paper 2: On the Rotation Distance between Binary Trees

Authors: Patrick Dehornoy

1.2.1 Motivation

While classical results establish linear upper bounds, understanding tight lower bounds remains a challenge. Previous constructions showed that certain pairs of trees require at least $\frac{3}{2}n$ rotations, but a significant gap remained between these lower bounds and the known upper bound of $2n - O(1)$. This paper develops a combinatorial and geometric framework to close that gap.

1.2.2 Methodology

The core methodology is based on introducing **covering** and **co-covering** relations between leaf labels in a binary tree. These relations encode geometric information about relative subtree positions.

A major technical tool introduced is the **collapsing operation**, which reduces trees by identifying intervals of leaves while preserving essential covering information. This allows the analysis to focus on critical subsets of labels. By applying the collapsing technique hierarchically, the paper ensures that most labels are forced to participate in multiple rotations.

1.2.3 Results

Using this framework, the paper establishes strong lower bounds on rotation distance. The main result proves that for infinitely many values of n , the rotation distance satisfies:

$$\text{dist}(T, T') \geq 2n - O(\sqrt{n})$$

This shows that the maximum rotation distance grows almost exactly as $2n$, differing from the best known upper bound only by a sublinear error term.

1.3 Comparison of Key Results in Literature

Table 1 summarizes the main theoretical contributions of the key papers reviewed.

Table 1: Comparison of Key Results on Rotation Distance Between the Two Papers

Aspect	Sleator, Tarjan, Thurston (1988)	Dehornoy (2010)
Primary Objective	Establish a global upper bound on rotation distance	Obtain near-tight lower bounds on rotation distance
Main Technique	Geometric correspondence between binary trees and polygon triangulations; associahedra	Combinatorial covering and co-covering relations; collapsing arguments
Geometric Interpretation	Diagonal flips in convex polygon triangulations	Relative positions of subtrees encoded by covering relations
Upper Bound Result	$2n - 6$	$2n - O(1)$
Lower Bound Result	$\frac{3}{2}n - O(1)$	$2n - O(\sqrt{n})$
Significance	Shows rotation distance grows linearly with tree size	Shows the linear upper bound is essentially tight

2 Execution Time Benchmarking and Memory Usage Profiling

2.1 Performance Benchmarking

As the number of internal nodes n increases, the number of binary trees grows according to the Catalan number $C_n = \frac{1}{n+1} \binom{2n}{n}$.

2.1.1 Runtime Execution Profiling

Table 2 details the time taken for various computational stages. We observe that the computation of the distance matrix (via Breadth-First Search) scales exponentially.

Table 2: Runtime Execution Benchmarking (seconds)

n	Trees (#)	Generation Time	Graph Const.	Dist. Matrix
3	5	3.68×10^{-5}	0.0005	0.0001
4	14	7.52×10^{-5}	0.0004	0.0011
5	42	0.00018	0.0012	0.0469
6	132	0.00034	0.0036	2.0628
7	429	0.00105	0.0238	86.6847

2.1.2 Memory Usage Profiling

Table 3 shows the memory required to store tree objects, the rotation graph, and the distance matrix.

Table 3: Memory Usage Profiling (KB)

n	Trees (#)	Memory (Trees)	Memory (Graph)	Memory (Matrix)
3	5	0.70	3.30	0.87
4	14	0.66	7.50	2.09
5	42	0.84	20.24	14.23
6	132	1.48	81.81	136.47
7	429	102.22	552.85	1438.08

The benchmarking data confirms that computing exact rotation distances is computationally expensive. For $n > 7$, the size of the graph and the $O(V^2)$ complexity of distance calculations makes full matrix computation impractical without specialized hardware.

3 Evaluation Metrics

The diameter of the rotation graph is defined as the maximum shortest-path distance between any pair of binary trees of size n .

Table 4: Computed Rotation Graph Diameters Compared with Theoretical Bounds

Nodes (n)	Computed Diameter	Lower Bound ($\frac{3}{2}n - O(1)$)	Upper Bound ($2n - 6$)
3	2	≥ 1	0
4	3	≥ 2	2
5	4	≥ 3	4
6	5	≥ 4	6
7	6	≥ 5	8

The experimentally computed diameters increase linearly with n . For all tested values, the observed diameters lie within the theoretical bounds. While the upper bound $2n - 6$ is asymptotic, the experimental values exhibit linear growth, supporting the result that rotation distance scales as $\Theta(n)$.