

Calling Functions

```
// C-style function call  
showMessage(123);
```

Calling Functions

```
// C-style function call  
showMessage(123);
```

```
// Swift style function call  
showMessage(number: 123)  
           |  
    argument label
```

Calling Functions

```
// C-style function call  
showMessage(123);
```

```
// Swift style function call  
showMessage(number: 123)  
           |  
    argument label
```

```
// Swift style function call with three arguments  
showMessage(number: 123, name: "Grace", largeFont: true)
```

Calling Functions: Example

```
// C-style function call  
stride(0, 256, 16)
```

Calling Functions: Example

```
// C-style function call  
stride(0, 256, 16)
```

```
// Swift style function call  
stride(from: 0, through: 256, by: 16)
```

Function parameters are
constants, and immutable
by default.

Functions Without Return Values

```
func simpleFunction(number: Int) {  
  
    // code  
    // ...  
  
}
```

Functions Without Return Values

```
func simpleFunction(number: Int) {
```

```
    // code
```

```
    // ...
```

```
}
```


Functions Without Return Values

```
func simpleFunction(number: Int) {
```

```
    // code
```

```
    // ...
```

```
}
```

Functions Without Return Values

```
func simpleFunction(number: Int) -> Void {  
  
    // code  
    // ...  
  
}
```

Functions Without Return Values

```
func simpleFunction(number: Int) -> Void {  
    // code  
    // ...  
}
```

no return value



```
// example functions
playMP3(filename: String) -> Bool {
    ...
}

playOGG(oggFile: String) -> Bool {
    ...
}

showImage(at url: String) -> Bool {
    ...
}

loadVector(_ url: String) -> Bool {
    ...
}
```

Swift Function Type

`() ->`

Swift Function Type

(parameter_type) -> return_type

Swift Function Type

```
// example functions  
playMP3(filename: String) -> Bool { ... }  
  
playOGG(oggFile: String) -> Bool { ... }  
  
showImage(at url: String) -> Bool { ... }  
  
loadVector(_ url: String) -> Bool { ... }
```

Swift Function Type

`(String) -> Bool`

`// example functions`

`playMP3(filename: String) -> Bool { ... }`

`playOGG(oggFile: String) -> Bool { ... }`

`showImage(at url: String) -> Bool { ... }`

`loadVector(_ url: String) -> Bool { ... }`

Swift Function Type

(parameter_type) -> return_type

(String) -> Bool

// example functions

`playMP3(filename: String) -> Bool { ... }`

`playOGG(oggFile: String) -> Bool { ... }`

`showImage(at url: String) -> Bool { ... }`

`loadVector(_ url: String) -> Bool { ... }`

Swift Function Type

(parameter_type) -> return_type

(String) -> Bool

Swift Function Type

(parameter_type) -> return_type

(String) -> Bool

**"a function that takes a String
and returns a Bool"**

(Int) -> String

**"a function that takes an Int
and returns a String"**

(Double, Double) -> [String]

**"a function that takes two Doubles and
returns an Array of Strings"**

Functions Without Return Values

```
func simpleFunction(number: Int) {  
    // code goes here  
    // ...  
}
```

no return arrow



Has the Function Type:

(Int) -> Void

**"a function that takes an Int
and returns nothing"**

Functions Without Return Values

```
func verySimpleFunction() {  
    // code goes here  
    // ...  
}
```

Has the Function Type:


() -> Void

**"a function that takes no parameters
and returns nothing"**

Defining and Calling Functions


```
func showMessage(number: Int, name: String) {  
    ...  
}
```

parameter name

Two curved arrows originate from the handwritten label 'parameter name' on the right. One arrow points to the word 'number' in the function signature, and the other points to the word 'name'.

```
// later..  
showMessage(number: 123, name: "Grace")
```

argument label

Two curved arrows originate from the handwritten label 'argument label' on the right. One arrow points to the word 'number' in the function call, and the other points to the word 'name'.

Defining and Calling Functions

```
func showMessage(number: Int, name: String) {  
    ...  
}
```

parameter name

argument label

```
// later..  
showMessage(number: 123, nickname: "Grace")
```

Functions With Multiple Parameters

```
// define the function
```

```
func purchase(_ item: Int, account: String, isDigital: Bool) {  
    ...  
}
```

```
// call the function
```

```
purchase(23728, account: "ADF543", isDigital: false)
```


Functions With Multiple Parameters

```
// define the function
```

```
func purchase(_ item: Int, _ account: String, _ isDigital: Bool) {  
    ...  
}
```

```
// call the function
```

```
purchase(23728, "ADF543", false)
```

Calling Functions: Example

```
// C-style  
process("A674", 4, false, true, 8.2)
```

Calling Functions: Example

```
// C-style
```

```
process("A674", 4, false, true, 8.2)
```

```
// Swift style
```

```
process(itemID: "A674", quantity: 4, expedite: false,  
        freeShipping: true, tax: 8.2)
```

Argument Labels

```
func showMessage(message textToShow: String) {  
    ...  
}
```

argument label
(used outside the function)

parameter name
(used inside the function)

Naming Functions

```
// in JavaScript  
typeof someVariable
```

```
// in C#  
typeof(someVariable)
```

```
// in Swift  
type(of: someVariable)
```

Naming Functions

```
// could be written as a choice of  
strideThrough(0,256,16)  
// or  
strideTo(0,256,16)
```

Naming Functions

```
// could be written as a choice of  
strideThrough(0, 256, 16)  
// or  
strideTo(0, 256, 16)
```

```
// in Swift  
stride(from: 0, through: 256, by: 16)  
// or  
stride(from: 0, to: 256, by: 16)
```