

Max Consecutive Ones

Give DSA notes for this problem::Given a binary array `nums`, return the maximum number of consecutive 1's in the array.

Here are concise notes for solving the problem "**Maximum Number of Consecutive 1's in a Binary Array**":

Problem Statement

Given a binary array `nums` (containing only `0`s and `1`s), return the maximum number of consecutive `1`s in the array.

Approach

1. Iterative Traversal with a Counter

- Traverse the array and keep a count of consecutive `1`s.
- Reset the counter when encountering a `0`.
- Track the maximum count of consecutive `1`s encountered during the traversal.

2. Algorithm

- Initialize two variables:
 - `currentCount` → Tracks the current streak of consecutive `1`s.
 - `maxCount` → Stores the maximum streak encountered so far.
- Iterate through the array:
 - If the current element is `1`, increment `currentCount`.
 - If the current element is `0`, reset `currentCount` to `0`.
 - Update `maxCount` to be the maximum of itself and `currentCount`.
- Return `maxCount`.

3. Edge Cases

- An empty array (`nums = []`) → Return `0`.
 - No `1` s in the array (`nums = [0, 0, 0]`) → Return `0`.
 - Only `1` s in the array (`nums = [1, 1, 1]`) → Return the size of the array.
-

Code Template

java

```
public int findMaxConsecutiveOnes(int[] nums) {  
    int maxCount = 0; // Maximum number of consecutive 1s  
    int currentCount = 0; // Current streak of 1s  
  
    for (int num : nums) {  
        if (num == 1) {  
            currentCount++;  
            maxCount = Math.max(maxCount, currentCount);  
        } else {  
            currentCount = 0;  
        }  
    }  
  
    return maxCount;  
}
```

Complexity Analysis

1. Time Complexity:

- $O(n)$: The array is traversed once.

2. Space Complexity:

- $O(1)$: Only a fixed amount of extra space is used (`maxCount` and `currentCount`).
-

Example Walkthrough

Example 1:

Input: `nums = [1, 1, 0, 1, 1, 1]`

Process:

- `1` → `currentCount = 1, maxCount = 1`
- `1` → `currentCount = 2, maxCount = 2`
- `0` → `currentCount = 0, maxCount = 2`
- `1` → `currentCount = 1, maxCount = 2`
- `1` → `currentCount = 2, maxCount = 2`
- `1` → `currentCount = 3, maxCount = 3`

Output: `3`

Example 2:

Input: `nums = [0, 0, 0]`

Output: `0`

Example 3:

Input: `nums = [1, 1, 1, 1]`

Output: `4`

Let me know if you'd like to dive deeper into variations or related problems!