MAIN
PERFORM $LB-9000-$INIT-UP-THRU $LB-1000-$EXIT
PERFORM $LB-1000-$START-UP
IF W-NOT-FIRST-CALL
GO TO $LB-1000-$EXIT
SET W-NOT-FIRST-CALL TO TRUE
MOVE FUNCTION WHEN-COMPILED TO W-COMPILED-DATE
DISPLAY 'PASCOMP compiled on ' W-COMPILED-DATE-YYYY '/' W-COMPILED-DATE-MM '/' W-COMPILED-DATE-DD ' at ' W-COMPILED-TIME-HH ':' W-COMPILED-TIME-MM
WHEN W-COMPILED-DATE-YYYY NOT NUMERIC
EVALUATE TRUE
WHEN W-COMPILED-DATE-YYYY < W-CURRENT-DATE-YYYY
MOVE 'PASCOMP' TO W-COMPILED-PROGRAM-ID
MOVE 'Y' TO W-COMPILED-OBSOLETE
WHEN W-COMPILED-DATE-YYYY = W-CURRENT-DATE-YYYY AND W-COMPILED-DATE-MM < W-CURRENT-DATE-MM
MOVE 'PASCOMP' TO W-COMPILED-PROGRAM-ID
MOVE 'Y' TO W-COMPILED-OBSOLETE
WHEN OTHER
MOVE 'PASCOMP' TO W-COMPILED-PROGRAM-ID
MOVE 'N' TO W-COMPILED-OBSOLETE
END-EVALUATE
IF W-COMPILED-OBSOLETE = 'Y'
DISPLAY '*** PASCOMP IS OBSOLETE - RECOMPILE ***'
END-IF
SET W-PERSON-LAST-NAME TO W-PARM-PARAMETER TO TRUE
CALL W-PARM-FMT USING W-PARM-PARAMETER
MOVE 'LAST-NAME' TO W-TABLE-1
ADD 1 TO PARM-INFO-CNT IN L-PARAMETER
SET PARM-INFO-CNT IN L-PARAMETER TO TRUE
PERFORM $LB-9200-$LAST-NAME THRU $LB-9200-$EXIT
STRING 'Unknown PASCOMP literal: "' DELIMITED SIZE INTO PARM-RESPONSE-MSG IN L-PARAMETER
GO TO $LB-9000-$EXIT
$LB-9200-$LAST-NAME.
WHEN 'CN'
WHEN 'CN'
MOVE 'SPACES' TO W-TABLE-1
SET PARM-UNKNOWN-P-ORDAT IN L-PARAMETER TO TRUE
$LB-9000-$EXIT
PERFORM $LB-9000-$XMODE-FIND-P-ORDAT THRU $LB-9000-$EXIT
EVALUATE W-P-ORDAT-ENTRY
WHEN 'CN'
MOVE 'SPACES' TO W-TABLE-1
SET PARM-UNKNOWN-P-ORDAT IN L-PARAMETER TO TRUE
$LB-9000-$XMODE-FIND-P-ORDAT
STRING 'Unknown PARCOMP literal: "' DELIMITED SIZE INTO PARM-RESPONSE-MSG IN L-PARAMETER
IF NOT PARM-RESPONSE-GOOD IN L-PARAMETER
PERFORM $LB-9000-$XMODE-FIND-P-ORDAT THRU $LB-9000-$EXIT
$LB-9000-$EXIT
EXIT
MOVE W-$LB-1 SAVE TO W-$LB-1
MOVE W-BIT-CLSED-P-ORDAT (W-$LB-1) TO W-BIT-CLSED-P-ORDAT
IF W-P-ORDAT-ENTRY-IS-P-ORDAT
MOVE W-BIT-CLSED-P-ORDAT (W-$LB-1) TO W-BIT-CLSED-P-ORDAT (W-$LB-1 SAVE)
STRING W-PARM-P-ORDAT DELIMITED
UNSTRING W-BIT-CLSED-P-ORDAT INTO W-P-ORDAT-ENTRY
MOVE W-BIT-CLSED-P-ORDAT (W-$LB-1) TO W-BIT-CLSED-P-ORDAT (W-$LB-1 SAVE)
MOVE W-PARM-P-ORDAT DELIMITED
UNSTRING W-BIT-CLSED-P-ORDAT INTO W-P-ORDAT-ENTRY POINTER W-$LB-1 SAVE
GO TO $LB-2110-EXIT
END-IF
IF NOT PARM-RESPONSE-GOOD IN L-PARAMETER
END-IF
$LB-2110-EXIT
EXIT
PERFORM $LB-2110-BIT-CLSED-P-ORDATS THRU $LB-2110-EXIT UNTIL W-$LB-1 > LENGTH OF W-BIT-CLSED-P-ORDAT OR NOT PARM-RESPONSE-GOOD IN L-PARAMETER
MOVE 1 TO W-$LB-1
MOVE W-PARM-P-ORDAT TO W-BIT-CLSED-P-ORDAT
MOVE W-BIT-CLSED-P-ORDAT (W-$LB-1) TO W-P-ORDAT-ENTRY
IF W-BIT-CLSED-P-ORDAT (W-$LB-1) NOT = W-P-ORDAT-START
END-IF
ADD 1 TO W-$LB-1
GO TO $LB-2110-EXIT
END-IF
MOVE W-$LB-1 TO W-$LB-1-SAVE
ADD 1 TO W-$LB-1
GO TO $LB-2110-EXIT
END-IF
$LB-2110-BIT-CLSED-P-ORDATS
IF NOT PARM-RESPONSE-GOOD IN L-PARAMETER
END-IF
GO TO $LB-2100-EXIT
STRING W-PARM-P-ORDAT DELIMITED
UNSTRING W-BIT-CLSED-P-ORDAT INTO W-P-ORDAT-ENTRY POINTER W-$LB-1
MOVE W-BIT-CLSED-P-ORDAT (W-$LB-1) TO W-BIT-CLSED-P-ORDAT
MOVE W-P-ORDAT-ENTRY TO W-PARM-P-ORDAT
IF W-P-ORDAT-ENTRY-IS-P-ORDAT
END-IF
$LB-2100-EXIT
EXIT
MOVE W-$LB-1 SAVE TO W-$LB-1
PERFORM $LB-9000-FIND-P-ORDAT THRU $LB-9000-EXIT
$LB-9000-EXIT
EXIT
PERFORM $LB-9000-$XMODE-CONDENT THRU $LB-9000-EXIT
MOVE W-$AUDIT-2 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
MOVE W-$AUDIT-1 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
SET P-UC1 TO PARM-INFO-CNT IN L-PARAMETER
ADD 1 TO PARM-INFO-CNT IN L-PARAMETER
$LB-9800-EXIT
SET W-$AUDIT-1 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
SET W-$AUDIT-2 TO PARM-$AUDIT IN L-PARAMETER (P-UC2)
MOVE W-$AUDIT-NO TO W-$AUDIT-NO
MOVE W-$AUDIT-NO TO PARM-$AUDIT IN L-PARAMETER (P-UC2)
MOVE W-$AUDIT-NO TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
$LB-9800-FIND-$AUDIT-CONDENT
PERFORM $LB-9800-FIND-$AUDIT-CONDENT THRU $LB-9800-EXIT
EXIT
END-EVALUATE
EVALUATE TRUE
WHEN W-$AUDIT-1 = 'FIRST-NAME' OR 'LAST-NAME'
MOVE W-$AUDIT-1 (1 : 1) = 'FORMATS:'
WHEN OTHER
END-EVALUATE
IF W-$AUDIT-1 (1 : 1) = 'FORMATS:'
MOVE W-$AUDIT-1 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
SET P-UC1 TO PARM-INFO-CNT IN L-PARAMETER
ADD 1 TO PARM-INFO-CNT IN L-PARAMETER
MOVE W-$AUDIT-2 TO PARM-$AUDIT IN L-PARAMETER (P-UC2)
SET P-UC2 TO PARM-INFO-CNT IN L-PARAMETER
ADD 1 TO PARM-INFO-CNT IN L-PARAMETER
END-IF
PERFORM $LB-9100-FIND-$AUDIT-CONDENT THRU $LB-9100-EXIT
EXIT
$LB-9100-EXIT.
MOVE W-$AUDIT-1 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
MOVE W-$AUDIT-2 TO PARM-$AUDIT IN L-PARAMETER (P-UC2)
MOVE W-$AUDIT-NO TO PARM-$AUDIT IN L-PARAMETER (P-UC3)
$LB-9100-FIND-$AUDIT-CONDENT
PERFORM $LB-9100-$XMODE-FIND-$AUDIT-CONDENT THRU $LB-9100-EXIT
EXIT
$LB-9100-EXIT.
MOVE W-$AUDIT-1 TO PARM-$AUDIT IN L-PARAMETER (P-UC1)
MOVE W-$AUDIT-2 TO PARM-$AUDIT IN L-PARAMETER (P-UC2)
MOVE W-$AUDIT-NO TO PARM-$AUDIT IN L-PARAMETER (P-UC3)
$LB-9100-$XMODE