


## BEFORE | AFTER INSERT

## **BEFORE INSERT**

Jadvalga biror yangi qator qo'shilishidan oldin BEFORE INSERT triggeri ishga tushadi.



Qolip: DELIMITER \$\$ CREATE TRIGGER trigger\_name BEFORE INSERT ON table\_name FOR EACH ROW BEGIN -- statements END\$\$ DELIMITER;

BEFORE INSERT triggerida, NEW qiymatlardan foydalanish va ularni o'zgartirish mumkin. Ammo OLD qiymatlarga bunday huquq yo'q, chunki OLD qiymatlar mavjud emas.

Misolda ko'ramiz: Products jadvalida har bir produktdan nechtadan skladda borligi ko'rsatilgan. Agar mijoz qaysidir produktdan sotib olsa, skladda ham shuncha kamayishi kerak. Endi alohida jadval hosil qilamiz va shunga yozib boramiz.

CREATE TABLE ostatka ( id INT AUTO\_INCREMENT PRIMARY KEY, product Number VARCHAR(11) NOT NULL, soni INT NOT NULL ); DROP TRIGGER IF EXISTS ostatka\_produkt\_trigger; DELIMITER \$\$ CREATE TRIGGER ostat ka\_produkt\_trigger BEFORE INSERT ON orderdetails FOR EACH ROW BEG IN DECLARE rowcount INT; DECLARE jami INT DEFAULT 0; SELECT COUNT (\*) INTO rowcount FROM ostatka where productNumber = new.productC ode; SELECT quantityInStock into jami from products where product Code = new.productCode; IF rowcount > 0 THEN UPDATE ostatka SET s oni = soni - new.quantityOrdered; ELSE INSERT INTO ostatka (productNumber, soni) VALUES (new.productCode, jami-new.quantityOrdered); END IF; END \$\$ DELIMITER;

Endi "orderdetails" jadvaliga yangi ma'lumot tushadigan bo'lsa ushbu trigger ishga tushadi.

Heading 3

## **AFTER INSERT**

CREATE TABLE members ( id INT AUTO\_INCREMENT, name VARCHAR(100) N OT NULL, email VARCHAR(255), birthDate DATE, PRIMARY KEY (id) ); // reminders jadvali CREATE TABLE reminders ( id INT AUTO\_INCREME NT, memberId INT, message VARCHAR(255) NOT NULL, PRIMARY KEY (id, memberId) ); // AFTER INSERT trigger hosil qilamiz DELIMITER \$\$ CREATE TRIGGER after\_members\_insert AFTER INSERT ON members FOR E ACH ROW BEGIN IF NEW.birthDate IS NULL THEN INSERT INTO reminders (memberId, message) VALUES(new.id,CONCAT('Hi', NEW.name, ', plea se update your date of birth.')); END IF; END\$\$ DELIMITER; // me mbers jadvaliga ma'lumot qo'shamiz INSERT INTO members(name, emai l, birthDate) VALUES ('John Doe', 'john.doe@example.com', NULL), ('Jane Doe', 'jane.doe@example.com','2000-01-01');