

Guided Tour of Machine Learning in Finance

The No Free Lunch Theorem

Igor Halperin

NYU Tandon School of Engineering, 2017

The Bias-Variance Tradeoff

$$\mathbb{E}\left[\left(y - \hat{f}(x)\right)^2\right] = (\text{bias})^2 + \text{variance} + \text{noise}$$

- **Bias-variance tradeoff:**

- Complex models (more features) tend to have low bias and high variance
- Simple models (less features) tend to have high bias and low variance
- Important to control **model complexity** to have an optimal tradeoff!

The No Free Lunch Theorem


- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.

The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.


The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.
- **Example:** Hot stock or not hot stock?




The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.
- **Example:** Hot stock or not hot stock?




The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.
- **Example:** Hot stock or not hot stock?



The No Free Lunch Theorem


- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.
- **Example:**



The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.

- **Example:**



The No Free Lunch Theorem

- The **No Free Lunch Theorem** (Wolpert, 1996): all classifiers have the **same error rate** when averaged over **all** possible data-generating distributions.
- Meaning: no single ML classification algorithm can be universally better than any other one on all domains.
- **A practical remedies:**
 - ♦ Look for ML algorithms that perform best on certain classes of domains (characterized by a data-generating distribution p_{data}).