EXP NO:14

EXPERIMENT TO UNDERSTAND FEATURE SCALING

AIM:

Understand the importance of feature scaling.

PROGRAM:

```
import numpy as np
import pandas as pd
df=pd.read_csv("/content/pre_process_datasample.csv")
df
df.head()
df.Country.fillna(df.Country.mode()[0],inplace=True)
features=df.iloc[:,:-1].values
label=df.iloc[:,-1].values

from sklearn.impute import SimpleImputer
age=SimpleImputer(strategy="mean",missing_values=np.nan)
Salary=SimpleImputer(strategy="mean",missing_values=np.nan)
age.fit(features[:,[1]])
Salary.fit(features[:,[2]])
SimpleImputer()
features[:,[1]]=age.transform(features[:,[1]])
features[:,[2]]=Salary.transform(features[:,[2]])
Features

from sklearn.preprocessing import OneHotEncoder
oh = OneHotEncoder(sparse_output=False)
Country=oh.fit_transform(features[:,[0]])
Country
final_set=np.concatenate((Country,features[:,[1,2]]),axis=1)
final_set
from sklearn.preprocessing import StandardScaler
sc=StandardScaler()
sc.fit(final_set)
feat_standard_scaler=sc.transform(final_set)
```

```
feat_standard_scaler
from sklearn.preprocessing import MinMaxScaler
mms=MinMaxScaler(feature_range=(0,1))
mms.fit(final_set)
feat_minmax_scaler=mms.transform(final_set)
feat_minmax_scaler
```

OUTPUT:


	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	Germany	50.0	83000.0	No
9	France	37.0	67000.0	Yes


	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes


```
/tmp/ipykernel_1980/3424832005.py:1: FutureWarning: A value is trying to
be set on a copy of a DataFrame or Series through chained assignment using
an inplace method.
The behavior will change in pandas 3.0. This inplace method will never
work because the intermediate object on which we are setting values always
behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using
'df.method({col: value}, inplace=True)' or df[col] = df[col].method(value)
instead, to perform the operation inplace on the original object.
```

```
  df.Country.fillna(df.Country.mode()[0],inplace=True)
```








```
array([['France', 44.0, 72000.0],
       ['Spain', 27.0, 48000.0],
       ['Germany', 30.0, 54000.0],
       ['Spain', 38.0, 61000.0],
       ['Germany', 40.0, 63777.77777777778],
       ['France', 35.0, 58000.0],
       ['Spain', 38.77777777777778, 52000.0],
       ['France', 48.0, 79000.0],
       ['Germany', 50.0, 83000.0],
       ['France', 37.0, 67000.0]], dtype=object)
```

```
array([[1., 0., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [1., 0., 0.],
       [0., 0., 1.],
```

```
       [1., 0., 0.],
       [0., 1., 0.],
       [1., 0., 0.]])

array([[1.0, 0.0, 0.0, 44.0, 72000.0],
       [0.0, 0.0, 1.0, 27.0, 48000.0],
       [0.0, 1.0, 0.0, 30.0, 54000.0],
       [0.0, 0.0, 1.0, 38.0, 61000.0],
       [0.0, 1.0, 0.0, 40.0, 63777.77777777778],
       [1.0, 0.0, 0.0, 35.0, 58000.0],
       [0.0, 0.0, 1.0, 38.77777777777778, 52000.0],
       [1.0, 0.0, 0.0, 48.0, 79000.0],
       [0.0, 1.0, 0.0, 50.0, 83000.0],
       [1.0, 0.0, 0.0, 37.0, 67000.0]], dtype=object)

array([[ 1.22474487e+00, -6.54653671e-01, -6.54653671e-01,
         7.58874362e-01,  7.49473254e-01],
       [-8.16496581e-01, -6.54653671e-01,  1.52752523e+00,
        -1.71150388e+00, -1.43817841e+00],
       [-8.16496581e-01,  1.52752523e+00, -6.54653671e-01,
        -1.27555478e+00, -8.91265492e-01],
       [-8.16496581e-01, -6.54653671e-01,  1.52752523e+00,
        -1.13023841e-01, -2.53200424e-01],
       [-8.16496581e-01,  1.52752523e+00, -6.54653671e-01,
         1.77608893e-01,  6.63219199e-16],
       [ 1.22474487e+00, -6.54653671e-01, -6.54653671e-01,
        -5.48972942e-01, -5.26656882e-01],
       [-8.16496581e-01, -6.54653671e-01,  1.52752523e+00,
         0.00000000e+00, -1.07356980e+00],
       [ 1.22474487e+00, -6.54653671e-01, -6.54653671e-01,
         1.34013983e+00,  1.38753832e+00],
       [-8.16496581e-01,  1.52752523e+00, -6.54653671e-01,
         1.63077256e+00,  1.75214693e+00],
       [ 1.22474487e+00, -6.54653671e-01, -6.54653671e-01,
        -2.58340208e-01,  2.93712492e-01]])
array([[1.        , 0.        , 0.        , 0.73913043, 0.68571429],
       [0.        , 0.        , 1.        , 0.        , 0.        ],
       [0.        , 1.        , 0.        , 0.13043478, 0.17142857],
       [0.        , 0.        , 1.        , 0.47826087, 0.37142857],
       [0.        , 1.        , 0.        , 0.56521739, 0.45079365],
       [1.        , 0.        , 0.        , 0.34782609, 0.28571429],
       [0.        , 0.        , 1.        , 0.51207729, 0.11428571],
       [1.        , 0.        , 0.        , 0.91304348, 0.88571429],
       [0.        , 1.        , 0.        , 1.        , 1.        ],
       [1.        , 0.        , 0.        , 0.43478261, 0.54285714]])
```

RESULT:

The experiment has been carried out successfully