

Use Case Descriptions GUI

Use case: Previous Page

Iteration: 1

Primary Actor: Player

Goal in Context: The player wants to navigate to the previous page in the application.

Preconditions:

1. The player must be logged into the system or interacting with the application.
2. The system must have a history of navigated pages.

Trigger: The player clicks on the "**Previous Page**" button.

Scenario:

1. The player initiates the action by selecting the "Previous Page" option.
2. The system verifies if there is a previously visited page.
3. If a previous page exists, the system loads it.
4. The player is redirected to the previous page with the same state as when they left.

Postconditions:

1. The player is successfully redirected to the previous page.
2. Any unsaved data from the current page may be lost unless saved before navigation.

Exceptions:

1. If there is no previous page to navigate to, the system may display an error or disable the option.
2. If the previous page requires authentication and the session has expired, the system prompts the player to log in again.
3. If the previous page is no longer available (due to logout or session timeout), the system redirects the player to a default page (the home page).

Priority: Medium

When Available: This feature is available anytime a user has navigated away from an initial page.

Frequency of Use: Frequently used, as players often navigate between pages.

Channel to Actor: GUI, typically via a button or browser back function.

Use case: Login

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Sign Up

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Forgot Password

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Manage Profile

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Home Page

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Logout

Iteration: 1

Primary Actor: Player

Goal in context: The player intends to terminate their session in the game system while ensuring that their personal data is preserved and protected.

Preconditions:

1. The player is logged into the game system.
2. The game system is operational.

Trigger: The player selects the log out option from the game menu or settings

Scenario:

1. The player navigates to the game platforms menu and selects the logout option.
2. The system asks the player to confirm that they wish to logout and the player confirms.
3. The system terminates the session, and the player is directed to the homepage.

Post conditions:

1. The session is terminated.
2. Temporary Data is cleared.

Exceptions:

1. Network Failure: player isn't able to properly logout if a network error occurs, process is stalled until issue is resolved.

Priority: High

When available: Available while player is logged in.

Frequency of use: High usage, mainly at the end of gaming sessions.

Channel to actor: The games GUI

Use case: Add Friend

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Search Friend

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Play Games

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

11. Use Case: Select Tic-Tac-Toe

Iteration: 1

Primary Actor: Player

Goal in Context: To initiate a match, the player selects Tic-Tac-Toe from the available games on the “**Play Games**” menu.

Preconditions:

1. The player is logged into the system.
2. The player has navigated to the “Play Games” section.
3. The system is online and operational.

Trigger:

The player interacts with the game selection menu and chooses Tic-Tac-Toe.

Scenario:

1. The player logs into the system and reaches the home page.
2. The player navigates to the “Play Games” section.
3. The system displays available game options (Tic-Tac-Toe, Checkers, Connect 4).
4. The player selects Tic-Tac-Toe.
5. The system includes the “Choose Opponent” use case.
6. The player selects an opponent (either a friend or a random player).
7. The system loads the Tic-Tac-Toe game interface.
8. The player now has access to in-game options, such as game chat, top players, game history, or quitting.

Postconditions:

1. The Tic-Tac-Toe game screen is displayed.
2. The player is matched with an opponent or waiting for one.
3. The game is ready to begin.

Exceptions:

- 1. Server Downtime:** If the game server is down, an error message is displayed.
- 2. Opponent Not Found:** If no opponent is available, the system prompts the player to wait or try again later.
- 3. Network Issues:** If the player loses connection, the system provides a reconnect option.

Priority: High

When Available: Initial game launch

Frequency of Use: Frequently, whenever a player wants to play Tic-Tac-Toe

Channel to Actor: Graphical User Interface (GUI)

Use case: Select Connect 4

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Select Checkers

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Choose Opponent

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Friend (Opponent Selection)

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: In-Game Options

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Game Chat

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Top Players

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Game History

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

- 1.

Exceptions:

- 1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Quit

Iteration: 1

Primary Actor: Player

Goal in context: The goal of this use case is to allow the player to safely exit the online multiplayer board game platform at any point during their session.

Preconditions:

1. The player must be logged into the system.

Trigger: The player selects the "Quit" option from the main.

Scenario:

1. The player selects the "Quit" option.
2. The system prompts the player to confirm their intention to quit.
3. Upon confirmation, the system performs any necessary cleanup tasks, like saving game progress and logging out the user.
4. The system closes the application window or returns the player to the initial login screen.
5. The system logs the action of quitting for session analysis.

Post conditions:

1. The player's current session is safely terminated without loss of data.
2. The player is logged out of the system.

Exceptions:

1. If the player cancels the quit operation, they are returned to their last active screen within the system.

Priority: High

When available: Available throughout the player's session, accessible from any point within the platform's user interface.

Frequency of use: Multiple times per session.

Channel to actor: The games GUI

Use case: Reset Password

Iteration:

Primary Actor:

Goal in context:

Preconditions:

- 1.

Trigger:

Scenario:

- 1.

Post conditions:

- 1.

Exceptions:

- 1.

Priority:

When available:

Frequency of use:

Channel to actor:

Use case: Delete Profile

Iteration: 1

Primary Actor: Player

Goal in context: The user wants to permanently delete their profile from the system, including all associated data.

Preconditions:

1. The user must be logged into their account.

Trigger: The player initiates the profile deletion process.

Scenario:

1. The player navigates to the delete account option.
2. The player selects the “Delete Profile” option.
3. The system prompts the player to confirm the deletion.
4. The player provides confirmation.
5. The system validates the request and deletes the player’s profile and data.
6. The system validates the request and deletes the player’s profile and data.
7. The player is logged out, and their account is no longer accessible.

Post conditions:

1. The player’s profile and all associated data are permanently removed from the system.
2. The user is logged out and cannot log in again.

Exceptions:

1. If a system failure occurs, the deletion request is logged, and the player is asked to try again later.

Priority: High

When available: Always available from “Manage Profile”.

Frequency of use: Rare

Channel to actor: The games GUI

Use case: Edit Profile

Iteration: 1

Primary Actor: Player

Goal in context: The player wants to update their profile information.

Preconditions:

1. The player must be logged into their account.

Trigger: The player selects the “Edit Profile” option from the “Manage Profile” page.

Scenario:

1. The player navigates to the “Manage Profile” page.
2. The player selects the “Edit Profile” option.
3. The system displays the editable profile fields.
4. The player updates the desired information.
5. The player submits the changes by clicking the “Save” button.
6. The system validates the input data.
7. If the data is valid, the system updates the profile and confirms the changes.
8. The updated information is reflected in the player’s profile.

Post conditions:

1. The player’s profile information is successfully updated in the system.
2. The player sees the updated information on their profile page.

Exceptions:

1. If the user enters invalid data, the system prompts an error message.

Priority: Medium

When available: Always available fr

Frequency of use:

Channel to actor:

Use case: Random (Opponent Selection)

Iteration:

Primary Actor:

Goal in context:

Preconditions:

1.

Trigger:

Scenario:

1.

Post conditions:

1.

Exceptions:

1.

Priority:

When available:

Frequency of use:

Channel to actor: