Summary in Graph

Exam Summary (GO Classes GATE CS/DA | DBMS | Functional Dependency | Weekly Quiz 2)

Qs. Attempted:	0 (0 + 0)	Correct Marks:	0 (0 + 0)
Correct Attempts:	0 (0 + 0)	Penalty Marks:	0 (0 + 0)
Incorrect Attempts:	0 (0 + 0)	Resultant Marks:	0 (0 + 0)

Total Questions:	10 (5 + 5)
Total Marks:	15 (5 + 10)
Exam Duration:	30 Minutes
Time Taken:	0 Minutes

Individual Question Statistics

Select Metric: Marks Obtained

Q1 Q2 Q3 Q4 Q5 Q6 Q7 Q8 Q9 Q10

* Average Stats based on first-attempt stats of Top 10% (88) out of 876 users

EXAM RESPONSE EXAM STATS FEEDBACK

Technical

Q #1 Multiple Choice Type Award: 1 Penalty: 0.33 Databases

Let x, y, z, a, b, c be the attributes of an entity set E. If $\{x\}, \{x, y\}, \{a, b\}, \{a, b, c\}, \{x, y, z\}$ are superkeys then which of the following are the candidate keys?

A. $\{x, y\}$ and $\{a, b\}$
B. $\{x\}$ and $\{a, b\}$
C. $\{x, y, z\}$ and $\{a, b, c\}$
D. $\{z\}$ and $\{c\}$

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #2 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

Armstrong's inference rule doesnot determine

A. Reflexivity

B. Augmentation

C. Transitivity

D. Mutual dependency

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #3 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

In functional dependency Armstrong inference rules refers to

A. Reflexive, Augmentation and Decomposition

B. Transitive, Augmentation and Reflexive

C. Augmentation, Transitive, Reflexive and Decomposition

D. Reflexive, Transitive and Decomposition

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #4 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

Considering the following table in a relational database :

Last Name	Rank	Room	shift
Smith	Manager	234	Morning
Jones	Custodian	33	Afternoon
Smith	Custodian	33	Evening
Doe	Clerical	222	Morning

According to the data shown in the table, which of the following could be a candidate key of the table?

A .$\{\text{Last Name}\}$

B. $\{\{\text{Room}\}\}$

C. $\{\{\text{Shift}\}\}$

D. $\{\{\text{Room, Shift}\}\}$

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #5 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

Purpose of 'Foreign Key' in a table is to ensure

A. Null Integrity

B. Referential Integrity

C .Domain Integrity

D. Null and Domain Integrity

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 01sec | Discuss

Q #6 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

If $\mathrm{D}_1, \mathrm{D}_2, \ldots \mathrm{D}_n$ are domains in a relational model, then the relation is a table, which is a subset of

A. $\mathrm{D}_1 \oplus \mathrm{D}_2 \oplus \cdots \oplus \mathrm{D}_n$

B. $\mathrm{D}_1 \times \mathrm{D}_2 \times \cdots \times \mathrm{D}_n$

C. $\mathrm{D}_1 \cup \mathrm{D}_2 \cup \cdots \cup \mathrm{D}_n$

D. $\mathrm{D}_1 \cap \mathrm{D}_2 \cap \cdots \cap \mathrm{D}_n$

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #7 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

Given the relational schema $R = (U, V, W, X, Y, Z)$ and the set of functional dependencies:

$$\{U \rightarrow V, U \rightarrow W, WX \rightarrow Y, WX \rightarrow Z, V \rightarrow X\}$$

Which of the following functional dependencies can be derived from the above set?

A. $VW \rightarrow YZ$

B. $WX \rightarrow YZ$

C. $VW \rightarrow U$

D. $VW \rightarrow Y$

Your Answer: | Correct Answer: A;B;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #8 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A functional dependency $F : X \rightarrow Y$ is termed as a useful functional dependency if and only if it satisfies all the following three conditions:

X is not the empty set.

Y is not the empty set.

Intersection of X and Y is the empty set.

For a relation R with 4 attributes, the total number of possible useful functional dependencies is ------.

Your Answer: | Correct Answer: 50 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #9 Multiple Select Type | Award: 2 | Penalty: 0 | Databases

The symbol $\rightarrow$ indicates functional dependency in the context of a relational database. Which of the following options is/are TRUE?

A. $(X, Y) \rightarrow (Z, W)$ implies $X \rightarrow (Z, W)$

B. $(X, Y) \rightarrow (Z, W)$ implies $(X, Y) \rightarrow Z$

C. $((X, Y) \rightarrow Z$ and $W \rightarrow Y)$ implies $(X, W) \rightarrow Z$

D. $(X \rightarrow Y$ and $Y \rightarrow Z)$ implies $X \rightarrow Z$

Your Answer: | Correct Answer: B;C;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #10 Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Relation R has eight attributes $\mathrm{ABCDEFGH}$. Fields of R contain only atomic values. $F=$ $\{\mathrm{CH}\rightarrow\mathrm{G}, \mathrm{A}\rightarrow\mathrm{BC}, \mathrm{B}\rightarrow\mathrm{CFH}, \mathrm{E}\rightarrow\mathrm{A}, \mathrm{F}\rightarrow\mathrm{EG}\}$ is a set of functional dependencies (FDs) so that F^+ is exactly the set of FDs that hold for R.

How many candidate keys does the relation R have?

A. 3

B. 4

C. 5

D. 6

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Copyright & Stuff