Summary in Graph

Exam Summary (GO Classes GATE CS/DA | DBMS | SQL | Weekly Quiz 7)

Qs. Attempted:	0 (0 + 0)	Correct Marks:	0 (0 + 0)
Correct Attempts:	0 (0 + 0)	Penalty Marks:	0 (0 + 0)
Incorrect Attempts:	0 (0 + 0)	Resultant Marks:	0 (0 + 0)

Total Questions:	10 (5 + 5)
Total Marks:	15 (5 + 10)
Exam Duration:	30 Minutes
Time Taken:	0 Minutes

Individual Question Statistics

Select Metric: Marks Obtained

Q1 Q2 Q3 Q4 Q5 Q6 Q7 Q8 Q9 Q10

* Average Stats based on first-attempt stats of Top 10% (50) out of 502 users

EXAM RESPONSE EXAM STATS FEEDBACK

Technical

Q #1 Multiple Choice Type Award: 1 Penalty: 0.33 Databases

A relational database contains two tables student and department in which student table has columns roll_no, name and dept_id and department table has columns dept_id and dept_name. The following insert statements were executed successfully to populate the empty tables:

```
    Insert into department values (1, 'Mathematics')
    Insert into department values (2, 'Physics')
    Insert into student values (1, 'Navin', 1)
    Insert into student values (2, 'Mukesh', 2)
5.  Insert into student values (3, 'Gita', 1)
```

How many rows and columns will be retrieved by the following SQL statement?

```
    Select * from student, department
```

A. 0 row and 4 columns
B. 3 rows and 4 columns
C. 3 rows and 5 columns
D. 6 rows and 5 columns

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #2 Numerical Type | Award: 1 | Penalty: 0 | Databases

Consider the following relation:

Student

Roll_No	Student_Name
1	Raj
2	Rohit
3	Raj

Performance

Roll_No	Course	Marks
1	Math	80
1	English	70
2	Math	75
3	English	80
2	Physics	65
3	Math	80

Consider the following SQL query.

```
    SELECT S.Student_Name, Sum(P. Marks)
    FROM Student S, Performance P
    WHERE S.Roll_No= P.Roll_No
    GROUP BY S.STUDENT_Name
```

The numbers of rows that will be returned by the SQL query is_____.

Your Answer: | Correct Answer: 2 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #3 Numerical Type | Award: 1 | Penalty: 0 | Databases

A relational database contains two tables Student and Performance as shown below:

Table: student

Roll_no	Student_name
1	Amit
2	Priya
3	Vinit
4	Rohan
5	Smita

Table: Performance

Roll_no	Subject_code	Marks
1	A	86
1	B	95
1	C	90
2	A	89
2	C	92
3	C	80

The primary key of the Student table is Roll_no. For the performance table, the columns Roll_no. and Subject_code together form the primary key. Consider the SQL query given below:

```
SELECT S.Student_name, sum(P.Marks)
FROM Student S, Performance P
WHERE P.Marks >84
GROUP BY S.Student_name;
```

The number of rows returned by the above SQL query is _____

Your Answer: | Correct Answer: 5 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #4 Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

A relational schema for a train reservation database is given below.

- **passenger(pid, pname, age)**
- **reservation(pid, class, tid)**

Passenger

pid	pname	Age
0	Sachine	65
1	Rahul	66
2	Sourav	67
3	Anil	69

Reservation

pid	class	tid
0	AC	8200
1	AC	8201
2	SC	8201
5	AC	8203
1	SC	8204
3	AC	8202

What **pids** are returned by the following SQL query for the above instance of the tables?

```
SELECT pid
FROM Reservation
WHERE class='AC' AND
    EXISTS (SELECT *
            FROM Passenger
            WHERE age>65 AND
            Passenger.pid=Reservation.pid)
```

A. $1, 0$
B. $1, 2$
C. $1, 3$
D. $1, 5$

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 02sec | Discuss

Q #5 Multiple Choice Type | Award: 1 | Penalty: 0.33 | Databases

Suppose we have a relation $R(A, B)$ with one tuple, both of whose components are NULL:

A	B
NULL	NULL

The result of:

```
SELECT A, COUNT(B)
FROM R
GROUP BY A;
```

A. (NULL,NULL)
B. (NULL,0)
C. (NULL, 1)
D. Empty Table

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #6 | Numerical Type | Award: 2 | Penalty: 0 | Databases

Consider the following table named Student in a relational database. The primary key of this table is rollNum.

Student

rollNum	name	gender	marks
1	Naman	M	62
2	Aliya	F	70
3	Aliya	F	80
4	James	M	82
5	Swati	F	65

The SQL query below is executed on this database.

```
SELECT *
FROM Student
WHERE gender = 'F' AND
    marks  > 65;
```

The number of rows returned by the query is _____.

Your Answer: | Correct Answer: 2 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #7 | Numerical Type | Award: 2 | Penalty: 0 | Databases

Consider the following two tables named Raider and Team in a relational database maintained by a Kabaddi league. The attribute ID in table Team references the primary key of the Raider table, ID.

Raider

ID	Name	Raids	RaidPoints
1	Arjun	200	250
2	Ankush	190	219
3	Sunil	150	200
4	Reza	150	190
5	Pratham	175	220
6	Gopal	193	215

Team

City	ID	BidPoints
Jaipur	2	200
Patna	3	195
Hyderabad	5	175
Jaipur	1	250
Patna	4	200
Jaipur	6	200

The SQL query described below is executed on this database:

```
SELECT *
FROM Raider, Team
WHERE Raider.ID=Team.ID AND City="Jaipur" AND
RaidPoints > 200;
```

The number of rows returned by this query is _____.

Your Answer: | Correct Answer: 3 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #8 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

In SQL, relations can contain null values, and comparisons with null values are treated as unknown. Suppose all comparisons with a null value are treated as false. Which of the following pairs is/are not equivalent?

A. $x = 5 \quad not(not(x = 5))$
B. $x = 5 \quad x > 4$ and $x < 6$, where x is an integer
C. $x \neq 5 \quad not(x = 5)$
D. none of the above

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #9 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

The employee information in a company is stored in the relation

- Employee (name, sex, salary, deptName)

Consider the following SQL query

```
Select deptName
    From Employee
    Where sex = 'M'
    Group by deptName
    Having avg(salary) >
        (select avg (salary) from Employee)
```

It returns the names of the department in which

A. the average salary is more than the average salary in the company

B. the average salary of male employees is more than the average salary of all male employees in the company

C. the average salary of male employees is more than the average salary of employees in same the department

D. the average salary of male employees is more than the average salary in the company

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #10 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider the following relational schema:

Suppliers(sid:integer, sname:string, city:string, street:string)

Parts(pid:integer, pname:string, color:string)

Catalog(sid:integer, pid:integer, cost:real)

Consider the following relational query on the above database:

```
SELECT  S.sname
FROM    Suppliers S
WHERE S.sid NOT IN (SELECT C.sid
                    FROM Catalog C
                    WHERE C.pid NOT IN (SELECT P.pid
                                        FROM Parts P
                                        WHERE P.color<>'blue'))
```

Assume that relations corresponding to the above schema are not empty. Which one of the following is the correct interpretation of the above query?

A. Find the names of all suppliers who have supplied a non-blue part.

B. Find the names of all suppliers who have not supplied a non-blue part.

C. Find the names of all suppliers who have supplied only non-blue part.

D. Find the names of all suppliers who have not supplied only blue parts.

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Copyright & Stuff