Sales Quote

Soil Machine Dynamics Ltd
Turbinia Works
Davy Bank
Wallsend
Newcastle upon Tyne
NE28 6UZ
+44 191 2342222
Evan Robinson <evan.robinson@smd.co.uk>

Lewis Rundle

Quotation Number: 65932
Customer Reference: SMD Request for Order Quotation 68171
Payment Terms: 30 days net
Quote Valid: 30 days
Quote Date: 6 Jul 2026

Dear Evan,

Following your recent enquiry, we are very pleased to provide the following quotation for your consideration.

We trust that we have fully understood your requirements and preferences and that our offer is presented with enough detail for you to make your considered decision.

Should you require any further information, or wish to arrange a product demonstration please do not hesitate to contact us.

Please note that this quote is offered under our standard Terms and Conditions, a copy of which can be found on our website www.quantum-controls.co.uk or a hard copy is available, if required.

Kind Regards,

L Rundle

Lewis Rundle

After Sales Support Details

Technical Support 24/7	techsupport@quantum-controls.co.uk	0330 9000 247
Sales Support	sales@quantum-controls.co.uk	01661 835 566
Service Coordinators	servicecoordinators@quantum-controls.co.uk	01661 835 566

Quotation Number 65932

Quotation Date 6 Jul 2026

Quote Summary

Please also refer to further product notes in the Item Details section below

Line	Product	Description	Current Delivery	Quantity	Net Price	Subtotal
OFFERED						
10	WEG_MOTOR	WEG MOTOR 1596166399	Approx 14 weeks at time of order	1 Each	£ 321.86	321.86
20	1543749471	30kW 200L B35R(E) IE3	Approx 14 weeks at time of order	1 Each	£ 2038.06	2,038.06
30	CARRIAGE	Carriage		1 Each	£ 0.00	.00
				Offered Sub Total		**2,359.92**

Quotation Number 65932

Quotation Date 6 Jul 2026

Item Details

Line	Product	Description
10	WEG_MOTOR	WEG MOTOR 1596166399

****
Please see attached data sheets and drawings.

****
Phases Three-Phase
Altitude 1000 m.a.s.l.
Design N
Insulation Class F (DT=80K)
Service Factor 1.00
Frequency 50 Hz
Degree of Protection IP56 ●
Enclosure Material Cast Iron
Starting Method Direct On Line (D.O.L)
Standard IEC
Cooling TEFC - Totally Enclosed Fan Cooled - IC411
Duty Cycle S1 - Continuous
Rotation Direction Both
Maximum Ambient Temperature 50°C ●
Minimum Ambient Temperature-20°C
Coupling Direct
Bearing L10h Life 25.000 hours
Hazardous Area
Hazardous Area Marking
SAP Configuration Number 41242598 - 0001
W22 Line Efficiency Level IE3
Painting plan 212P (C5 and CX according to ISO 12944) ●
Finish Color: RAL 5009
Internal Tropicalized Painting ●
Thermistor 155ºC - Shutdown - Winding ●
Space Heater: 110-127/200-240 V ●
Additional Terminal Box: With Thread 1xM20x1,5
With Terminal Block - 6 Pins
W22 Main Terminal Box + Accessory Terminal Box ●
Sealing: Lip Seal Ring
Certification CSA Safe/UL Safe/CE/EAC/UKCA
Balancing: Without Balancing
Stainless steel screws AISI 316 ●
Material Plate: Stainless Steel 316 ●
Single grounding
Flange FF (IEC) or D (NEMA) - Standard Size
Marine Application: Non-Essential Service ★
● Optional Feature
★ Special Feature

Line	Product	Description
20	1543749471	30kW 200L B35R(E) IE3

****
Please see attached data sheets and drawings.

****
Type: Three Phase Induction Motor - Squirrel Cage
Product Code: 1543749471
Power: 30 Kw
Speed: 1480

Quotation Number 65932

Quotation Date 6 Jul 2026

Frame:200L
Mounting: B35R(E)
IE3
Phases Three-Phase
Altitude 1000 m.a.s.l.
Design N
Insulation Class F (DT=80K)
Service Factor 1.00
Frequency 50 Hz
Degree of Protection IP56 ●
Enclosure Material Cast Iron
Starting Method Direct On Line (D.O.L)
Standard IEC
Cooling TEFC - Totally Enclosed Fan Cooled - IC411
Duty Cycle S1 - Continuous
Rotation Direction Both
Maximum Ambient Temperature 50°C ●
Minimum Ambient Temperature-20°C
Coupling Direct
Bearing L10h Life 25.000 hours
Hazardous Area
Hazardous Area Marking
SAP Configuration Number 39770493 - 0006
W22 Line Efficiency Level IE3
Painting Plan 203A (C3 according to ISO 12944)
Finish Color: RAL 5009
Grease: Polyrex EM (-30ºC up to 165ºC) ●
PT-100 with 3 Cables - Alarm - 1 per Phase - Winding ●
Thermistor 155ºC - Shutdown - Winding
Space Heater: 110-127/200-240 V ●
Additional Terminal Box: With Thread 1xM20x1,5
With Terminal Block - 6 Pins
Load: Variable Torque ★
W22 Main Terminal Box + Accessory Terminal Box ●
Sealing: Lip Seal Ring
Certification CSA Safe/UL Safe/CE/EAC/UKCA ●
Balancing: Normal with 1/2 Key
Single grounding
Flange FF (IEC) or D (NEMA) - Standard Size
● Optional Feature
★ Special Feature

Line	Product	Description
30	CARRIAGE	Carriage

Carriage paid to NE28 6UZ only