

```

library(readxl)
library(afex)

## Loading required package: lme4

## Loading required package: Matrix

## *****
## Welcome to afex. For support visit: http://afex.singmann.science/

## - Functions for ANOVAs: aov_car(), aov_ez(), and aov_4()
## - Methods for calculating p-values with mixed(): 'S', 'KR', 'LRT', and 'PB'
## - 'afex_aov' and 'mixed' objects can be passed to emmeans() for follow-up tests
## - NEWS: emmeans() for ANOVA models now uses model = 'multivariate' as default.
## - Get and set global package options with: afex_options()
## - Set orthogonal sum-to-zero contrasts globally: set_sum_contrasts()
## - For example analyses see: browseVignettes("afex")
## *****

##
## Attaching package: 'afex'

## The following object is masked from 'package:lme4':
##
##      lmer

data <- read_excel("../Data/PredictingOutcomes_ParticipantPredictions.xlsx", sheet = "Study 2B")

# divide the data based on the generator
data1 <- data[data$generator == "analyst",]
data2 <- data[data$generator == "bingo",]
data3 <- data[data$generator == "stock",]

give count of entries in all three data

nrow(data1)

## [1] 1746

nrow(data2)

## [1] 1818

nrow(data3)

## [1] 1854

calculate the proportion of participants who predicted the prediction_recode=1 for each terminal_streak_length from 1 to 7

```

```
prop1 <- aggregate(data1$prediction_recode, by = list(data1$terminal_streak_length), FUN = mean)
prop2 <- aggregate(data2$prediction_recode, by = list(data2$terminal_streak_length), FUN = mean)
prop3 <- aggregate(data3$prediction_recode, by = list(data3$terminal_streak_length), FUN = mean)
```

```
prop1
```

```
##   Group.1      x
## 1      1 0.4054983
## 2      2 0.2268041
## 3      3 0.2577320
## 4      4 0.3402062
## 5      5 0.5154639
## 6      6 0.4948454
## 7      7 0.5154639
```

```
prop2
```


```
##   Group.1      x
## 1      1 0.4422442
## 2      2 0.3069307
## 3      3 0.1980198
## 4      4 0.2079208
## 5      5 0.2475248
## 6      6 0.2673267
## 7      7 0.3168317
```

```
prop3
```

```
##   Group.1      x
## 1      1 0.4207120
## 2      2 0.2621359
## 3      3 0.2718447
## 4      4 0.4077670
## 5      5 0.4660194
## 6      6 0.5339806
## 7      7 0.5339806
```

```
plot(prop1$Group.1,prop1$x, type = "l",ylim=c(0.0,0.9), xlab = "Terminal Streak", ylab = "Proportion of
lines(prop2$Group.1,prop2$x, col = "red")
lines(prop3$Group.1,prop3$x, col = "blue")
abline(h = 0.5, col = "green")
legend("topright", legend = c("Analyst", "Bingo", "Stock"), col = c("black", "red", "blue"), lty = 1:3)
```

Proportion of Prediction Recode=1 for each Terminal Streak



calculate the effect of condition on participant prediction

```
model11 <- lmer(prediction_recode ~ generator + (1|participant_id), data = data)
summary(model11)
```

```
## Linear mixed model fit by REML. t-tests use Satterthwaite's method [
## lmerModLmerTest]
## Formula: prediction_recode ~ generator + (1 | participant_id)
## Data: data
##
## REML criterion at convergence: 7625.4
##
## Scaled residuals:
## Min      1Q  Median      3Q      Max
## -1.1610 -0.8025 -0.6954  1.1671  1.4900
##
## Random effects:
## Groups      Name                Variance Std.Dev.
## participant_id (Intercept) 0.007499 0.08659
## Residual              0.232460 0.48214
## Number of obs: 5418, groups: participant_id, 301
##
## Fixed effects:
##              Estimate Std. Error    df t value Pr(>|t|)
## (Intercept)    0.40092    0.01451 298.00004  27.637 <2e-16 ***
## generatorbingo -0.02028    0.02031 298.00004  -0.998  0.319
```

```
## generatorstock 0.01710 0.02021 298.00004 0.846 0.398
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
## (Intr) gnrtrb
## generatrbnb -0.714
## genertrstck -0.718 0.513
```

```
anova(model1)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
## Sum Sq Mean Sq NumDF DenDF F value Pr(>F)
## generator 0.81278 0.40639 2 298 1.7482 0.1759
```

```
aov1<-aov_ez('participant_id','prediction_recode',data, between=c('generator'),within=c('terminal_streak_length'))
```

```
## Converting to factor: generator
```

```
## Warning: More than one observation per design cell, aggregating data using 'fun_aggregate = mean'.
## To turn off this warning, pass 'fun_aggregate = mean' explicitly.
```

```
## Contrasts set to contr.sum for the following variables: generator
```

```
aov1
```

```
## Anova Table (Type 3 tests)
##
## Response: prediction_recode
##          Effect          df MSE          F ges p.value
## 1          generator          2, 298 0.52    6.68 ** .017    .001
## 2 terminal_streak_length 5.17, 1541.14 0.16 16.90 *** .033    <.001
## 3 generator:terminal_streak_length 10.34, 1541.14 0.16 4.40 *** .018    <.001
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '+' 0.1 ' ' 1
##
## Sphericity correction method: GG
```

```
pairwise.t.test(data$prediction_recode, data$generator, p.adjust.method = "bonferroni")
```

```
##
## Pairwise comparisons using t tests with pooled SD
##
## data: data$prediction_recode and data$generator
##
## analyst bingo
## bingo 0.650 -
## stock 0.886 0.062
##
## P value adjustment method: bonferroni
```

```


id <- unique(data1$participant_id)

slope <- c()

for (i in id){
  x <- as.character(i)
  datax <- data1[data1$participant_id == x,]
  model <- glm(prediction_recode ~ terminal_streak_length, data = datax)
  slope <- c(slope, coef(model)[2])
}
slope <- slope*500

hist(slope,breaks=30,xlim=c(-200,200),prob=TRUE,main="AnalystUnknown")
curve(dnorm(x, mean = mean(slope), sd = sd(slope)), add = TRUE, col = "black")

```



```

id <- unique(data2$participant_id)


slope <- c()

for (i in id){
  x <- as.character(i)
  datax <- data2[data2$participant_id == x,]
  model <- glm(prediction_recode ~ terminal_streak_length, data = datax)
  slope <- c(slope, coef(model)[2])
}

```

```
slope <- slope*500
```

```
hist(slope,breaks=30,xlim=c(-200,200),prob=TRUE,main="BingoUnknown")
curve(dnorm(x, mean = mean(slope), sd = sd(slope)), add = TRUE, col = "black")
```



```
id <- unique(data3$participant_id)
```

```
slope <- c()
```

```
for (i in id){
  x <- as.character(i)
  datax <- data3[data3$participant_id == x,]
  model <- glm(prediction_recode ~ terminal_streak_length, data = datax)
  slope <- c(slope, coef(model)[2])
}
slope <- slope*500
```

```
hist(slope,breaks=30,xlim=c(-200,200),prob=TRUE,main="StockUnknown")
curve(dnorm(x, mean = mean(slope), sd = sd(slope)), add = TRUE, col = "black")
```

