

SQL CHEAT SHEET

Data Manipulation Language DML Commands

Command	Description	Syntax	Example
SELECT	The SELECT command retrieves data from a database.	SELECT column1, column2 FROM table_name;	SELECT first_name, last_name FROM customers;
INSERT	The INSERT command adds new records to a table.	INSERT INTO table_name (column1, column2) VALUES (value1, value2);	INSERT INTO customers (first_name, last_name) VALUES ('Mary', 'Doe');
UPDATE	The UPDATE command is used to modify existing records in a table.	UPDATE table_name SET column1 = value1, column2 = value2 WHERE condition;	UPDATE employees SET employee_name = 'John Doe', department = 'Marketing';
DELETE	The DELETE command removes records from a table.	DELETE FROM table_name WHERE condition;	DELETE FROM employees WHERE employee_name = 'John Doe';

Data Definition Language DDL Commands

Command	Description	Syntax	Example
CREATE	The CREATE command creates a new database and objects, such as a table, index, view, or stored procedure.	CREATE TABLE table_name (column1 datatype1, column2 datatype2,);	CREATE TABLE employees (employee_id INT PRIMARY KEY, first_name VARCHAR(50), last_name VARCHAR(50), age INT);
ALTER	The ALTER command adds, deletes, or modifies columns in an existing table.	ALTER TABLE table_name ADD column_name datatype;	ALTER TABLE customers ADD email VARCHAR(100);
DROP	The DROP command is used to drop an existing table in a database.	DROP TABLE table_name;	DROP TABLE customers;
TRUNCATE	The TRUNCATE command is used to delete the data inside a table, but not the table itself.	TRUNCATE TABLE table_name;	TRUNCATE TABLE customers;

Data Control Language DCL Commands

Command	Description	Syntax	Example
GRANT	The GRANT command is used to give specific privileges to users or roles.	GRANT SELECT, INSERT ON table_name TO user_name;	GRANT SELECT, INSERT ON employees TO 'John Doe';
REVOKE	The REVOKE command is used to take away privileges previously granted to users or roles.	REVOKE SELECT, INSERT ON table_name FROM user_name;	REVOKE SELECT, INSERT ON employees FROM 'John Doe';

Querying Data Commands

Command	Description	Syntax	Example
SELECT Statement	The SELECT statement is the primary command used to retrieve data from a database	SELECT column1, column2 FROM table_name;	SELECT first_name, last_name FROM customers;
WHERE Clause	The WHERE clause is used to filter rows based on a specified condition.	SELECT * FROM table_name WHERE condition;	SELECT * FROM customers WHERE age > 30;
ORDER BY Clause	The ORDER BY clause is used to sort the result set in ascending or descending order based on a specified column.	SELECT * FROM table_name ORDER BY column_name ASC DESC;	SELECT * FROM products ORDER BY price DESC;
GROUP BY Clause	The GROUP BY clause groups rows based on the values in a specified column. It is often used with aggregate functions like COUNT, SUM, AVG, etc.	SELECT column_name, COUNT(*) FROM table_name GROUP BY column_name;	SELECT category, COUNT(*) FROM products GROUP BY category;
HAVING Clause	The HAVING clause filters grouped results based on a specified condition.	SELECT column_name, COUNT(*) FROM table_name GROUP BY column_name HAVING condition;	SELECT category, COUNT(*) FROM products GROUP BY category HAVING COUNT(*) >5;

Joining Commands

Command	Description	Syntax	Example
INNER JOIN	The INNER JOIN command returns rows with matching values in both tables.	SELECT * FROM table1 INNER JOIN table2 ON table1.column = table2.column;	SELECT * FROM employees INNER JOIN departments ON employees.department_id = departments.id;
LEFT JOIN/LEFT OUTER JOIN	The LEFT JOIN command returns all rows from the left table (first table) and the matching rows from the right table (second table).	SELECT * FROM table1 LEFT JOIN table2 ON table1.column = table2.column;	SELECT * FROM employees LEFT JOIN departments ON employees.department_id = departments.id;
RIGHT JOIN/RIGHT OUTER JOIN	The RIGHT JOIN command returns all rows from the right table (second table) and the matching rows from the left table (first table).	SELECT * FROM table1 RIGHT JOIN table2 ON table1.column = table2.column;	SELECT * FROM employees RIGHT JOIN departments ON employees.department_id = departments.department_id;
FULL JOIN/FULL OUTER JOIN	The FULL JOIN command returns all rows when there is a match in either the left table or the right table.	SELECT * FROM table1 FULL JOIN table2 ON table1.column = table2.column;	SELECT * FROM employees LEFT JOIN departments ON employees.employee_id = departments.employee_id UNION SELECT * FROM employees RIGHT JOIN departments ON employees.employee_id = departments.employee_id;
CROSS JOIN	The CROSS JOIN command combines every row from the first table with every row from the second table, creating a Cartesian product.	SELECT * FROM table1 CROSS JOIN table2;	SELECT * FROM employees CROSS JOIN departments;
SELF JOIN	The SELF JOIN command joins a table with itself.	SELECT * FROM table1 t1, table1 t2 WHERE t1.column = t2.column;	SELECT * FROM employees t1, employees t2 WHERE t1.employee_id = t2.employee_id;
NATURAL JOIN	The NATURAL JOIN command matches columns with the same name in both tables.	SELECT * FROM table1 NATURAL JOIN table2;	SELECT * FROM employees NATURAL JOIN departments;

Subqueries in SQL

Command	Description	Syntax	Example
IN	The IN command is used to determine whether a value matches any value in a subquery result. It is often used in the WHERE clause.	SELECT column(s) FROM table WHERE value IN (subquery);	SELECT * FROM customers WHERE city IN (SELECT city FROM suppliers);
ANY	The ANY command is used to compare a value to any value returned by a subquery. It can be used with comparison operators like =, >, <, etc.	SELECT column(s) FROM table WHERE value < ANY (subquery);	SELECT * FROM products WHERE price < ANY (SELECT unit_price FROM supplier_products);
ALL	The ALL command is used to compare a value to all values returned by a subquery. It can be used with comparison operators like =, >, <, etc.	SELECT column(s) FROM table WHERE value > ALL (subquery);	SELECT * FROM orders WHERE order_amount > ALL (SELECT total_amount FROM previous_orders);

Aggregate Functions Commands

Command	Description	Syntax	Example
COUNT()	The COUNT command counts the number of rows or non-null values in a specified column.	SELECT COUNT(column_name) FROM table_name;	SELECT COUNT(age) FROM employees;
SUM()	The SUM command is used to calculate the sum of all values in a specified column.	SELECT SUM(column_name) FROM table_name;	SELECT SUM(revenue) FROM sales;
AVG()	The AVG command is used to calculate the average (mean) of all values in a specified column.	SELECT AVG(column_name) FROM table_name;	SELECT AVG(price) FROM products;
MIN()	The MIN command returns the minimum (lowest) value in a specified column.	SELECT MIN(column_name) FROM table_name;	SELECT MIN(price) FROM products;
MAX()	The MAX command returns the maximum (highest) value in a specified column.	SELECT MAX(column_name) FROM table_name;	SELECT MAX(price) FROM products;

String Functions in SQL

Command	Description	Syntax	Example
CONCAT()	The CONCAT command concatenates two or more strings into a single string.	SELECT CONCAT(string1, string2,) AS concatenated_string FROM table_name;	SELECT CONCAT(first_name, ' ', last_name) AS full_name FROM employees;
SUBSTRING()/SUBSTR()	The SUBSTRING command extracts a substring from a string.	SELECT SUBSTRING(string FROM start_position [FOR length]) AS substring FROM table_name;	SELECT SUBSTRING(product_name FROM 1 FOR 5) AS substring FROM products;
CHAR_LENGTH()/LENGTH()	The LENGTH command returns the length (number of characters) of a string.	SELECT CHAR_LENGTH(string) AS length FROM table_name;	SELECT CHAR_LENGTH(product_name) AS length FROM products;
UPPER()	The UPPER command converts all characters in a string to uppercase.	SELECT UPPER(string) AS uppercase_string FROM table_name;	SELECT UPPER(first_name) AS uppercase_first_name FROM employees;
LOWER()	The LOWER command converts all characters in a string to lowercase.	SELECT LOWER(string) AS lowercase_string FROM table_name;	SELECT LOWER(last_name) AS lowercase_last_name FROM employees;
TRIM()	The TRIM command removes specified prefixes or suffixes (or whitespace by default) from a string.	SELECT TRIM([LEADING TRAILING BOTH] characters FROM string) AS trimmed_string FROM table_name;	SELECT TRIM(TRAILING ' ' FROM full_name) AS trimmed_full_name FROM customers;
LEFT()	The LEFT command returns a specified number of characters from the left of a string.	SELECT LEFT(string, num_characters) AS left_string FROM table_name;	SELECT LEFT(product_name, 5) AS left_product_name FROM products;
RIGHT()	The RIGHT command returns a specified number of characters from the right of a string.	SELECT RIGHT(string, num_characters) AS right_string FROM table_name;	SELECT RIGHT(order_number, 4) AS right_order_number FROM orders;
REPLACE()	The REPLACE command replaces occurrences of a substring within a string.	SELECT REPLACE(string, old_substring, new_substring) AS replaced_string FROM table_name;	SELECT REPLACE(description, 'old_string', 'new_string') AS replaced_description FROM product_descriptions;

Date and Time SQL Commands

Command	Description	Syntax	Example
CURRENT_DATE()	The CURRENT_DATE command returns the current date.	SELECT CURRENT_DATE() AS current_date;	
CURRENT_TIME()	The CURRENT_TIME command returns the current time.	SELECT CURRENT_TIME() AS current_time;	
CURRENT_TIMESTAMP()	The CURRENT_TIMESTAMP command returns the current date and time.	SELECT CURRENT_TIMESTAMP() AS current_timestamp;	
DATE_PART()	The DATE_PART command extracts a specific part (e.g., year, month, day) from a date or time.	SELECT DATE_PART('part', date_expression) AS extracted_part;	SELECT DATE_PART('year', '2024-04-11') AS extracted_part;
DATE_ADD()/DATE_SUB()	The DATE_ADD command adds or subtracts a specified number of days, months, or years to/from a date.	SELECT DATE_ADD(date_expression, INTERVAL value unit) AS new_date;	<p>DATE_ADD Example</p> <p>SELECT DATE_ADD('2024-04-11', INTERVAL 1 DAY) AS new_date;</p> <p>DATE_SUB Example</p> <p>SELECT DATE_SUB('2024-04-11', INTERVAL 1 DAY) AS new_date;</p>
EXTRACT()	The EXTRACT command extracts a specific part (e.g., year, month, day) from a date or time.	SELECT EXTRACT(part FROM date_expression) AS extracted_part;	SELECT EXTRACT(YEAR FROM '2024-04-11') AS extracted_part;
TO_CHAR()	The TO_CHAR command converts a date or time to a specified format.	SELECT TO_CHAR(date_expression, 'format') AS formatted_date;	SELECT TO_CHAR('2024-04-11', 'YYYY-MM-DD') AS formatted_date;
TIMESTAMPDIFF()	The TIMESTAMPDIFF command calculates the difference between two timestamps in a specified unit (e.g., days, hours, minutes).	SELECT TIMESTAMPDIFF(unit, timestamp1, timestamp2) AS difference;	SELECT TIMESTAMPDIFF(DAY, '2024-04-10', '2024-04-11') AS difference;
DATEDIFF()	The DATEDIFF command calculates the difference in days between two dates.	SELECT DATEDIFF(date1, date2) AS difference_in_days;	SELECT DATEDIFF('2024-04-11', '2024-04-10') AS difference_in_days;

Conditional Expressions

Command	Description	Syntax	Example
CASE Statement	The CASE statement allows you to perform conditional logic within a query.	<pre>SELECT column1, column2, CASE WHEN condition1 THEN result1 WHEN condition2 THEN result2 ELSE default_result END AS alias FROM table_name;</pre>	<pre>SELECT order_id, total_amount, CASE WHEN total_amount > 1000 THEN 'High Value Order' WHEN total_amount > 500 THEN 'Medium Value Order' Order' ELSE 'Low Value END AS order_status FROM orders;</pre>
IF() Function	The IF function evaluates a condition and returns a value based on the evaluation.	<pre>SELECT IF(condition, true_value, false_value) AS alias FROM table_name;</pre>	<pre>SELECT name, age, IF(age > 50, 'Senior', 'Junior') AS employee_category FROM employees;</pre>
COALESCE() Function	The COALESCE function returns the first non-null value from a list of values.	<pre>SELECT COALESCE(value1, value2,) AS alias FROM table_name;</pre>	<pre>SELECT COALESCE(first_name, middle_name) AS preferred_name FROM employees;</pre>
NULLIF() Function	The NULLIF function returns null if two specified expressions are equal.	<pre>SELECT NULLIF(expression1, expression2) AS alias FROM table_name;</pre>	<pre>SELECT NULLIF(total_amount, discounted_amount) AS diff_amount FROM orders;</pre>

Set Operations

Command	Description	Syntax	Example
UNION	The UNION operator combines the result sets of two or more SELECT statements into a single result set.	<pre>SELECT column1, column2 FROM table1 UNION SELECT column1, column2 FROM table2;</pre>	<pre>SELECT first_name, last_name FROM customers UNION SELECT first_name, last_name FROM employees;</pre>
INTERSECT	The INTERSECT operator returns the common rows that appear in both result sets.	<pre>SELECT column1, column2 FROM table1 INTERSECT SELECT column1, column2 FROM table2;</pre>	<pre>SELECT first_name, last_name FROM customers INTERSECT SELECT first_name, last_name FROM employees;</pre>
EXCEPT	The EXCEPT operator returns the distinct rows from the left result set that are not present in the right result set.	<pre>SELECT column1, column2 FROM table1 EXCEPT SELECT column1, column2 FROM table2;</pre>	<pre>SELECT first_name, last_name FROM customers EXCEPT SELECT first_name, last_name FROM employees;</pre>

Transaction Control Commands

Command	Description	Syntax	Example
COMMIT	The COMMIT command is used to save all the changes made during the current transaction and make them permanent.	COMMIT;	<pre>BEGIN TRANSACTION; SQL statements and changes within the transaction INSERT INTO employees (name, age) VALUES ('Alice', 30); UPDATE products SET price = 25.00 WHERE category = 'Electronics'; COMMIT;</pre>
ROLLBACK	The ROLLBACK command is used to undo all the changes made during the current transaction and discard them.	ROLLBACK;	<pre>BEGIN TRANSACTION; SQL statements and changes within the transaction INSERT INTO employees (name, age) VALUES ('Bob', 35); UPDATE products SET price = 30.00 WHERE category = 'Electronics'; ROLLBACK;</pre>

SAVEPOINT	The SAVEPOINT command is used to set a point within a transaction to which you can later roll back.	SAVEPOINT savepoint_name;	BEGIN TRANSACTION; INSERT INTO employees (name, age) VALUES ('Carol', 28); SAVEPOINT before_update; UPDATE products SET price = 40.00 WHERE category = 'Electronics'; SAVEPOINT after_update; DELETE FROM customers WHERE age > 60; ROLLBACK TO before_update; At this point, the DELETE is rolled back, but the UPDATE remains. COMMIT;
ROLLBACK TO SAVEPOINT	The ROLLBACK TO SAVEPOINT command is used to roll back to a specific savepoint within a transaction.	ROLLBACK TO SAVEPOINT savepoint_name;	BEGIN TRANSACTION; INSERT INTO employees (name, age) VALUES ('David', 42); SAVEPOINT before_update; UPDATE products SET price = 50.00 WHERE category = 'Electronics'; SAVEPOINT after_update; DELETE FROM customers WHERE age > 60; Rollback to the savepoint before the update ROLLBACK TO SAVEPOINT before_update; At this point, the UPDATE is rolled back, but the INSERT remains. COMMIT;
SET TRANSACTION	The SET TRANSACTION command is used to configure properties for the current transaction, such as isolation level and transaction mode.	SET TRANSACTION [ISOLATION LEVEL { READ COMMITTED SERIALIZABLE}]	BEGIN TRANSACTION; Set the isolation level to READ COMMITTED SET TRANSACTION ISOLATION LEVEL READ COMMITTED; SQL statements and changes within the transaction INSERT INTO employees (name, age) VALUES ('Emily', 35); UPDATE products SET price = 60.00 WHERE category = 'Electronics'; COMMIT;