


Chapter 6: Process Synchronization





Chapter 6: Process Synchronization

- Background
- The Critical-Section Problem
- Peterson's Solution
- Synchronization Hardware
- Mutex Locks
- Semaphores
- Classic Problems of Synchronization
- Monitors
- Synchronization Examples
- Alternative Approaches





Objectives

- To present the concept of process synchronization.
- To introduce the critical-section problem, whose solutions can be used to ensure the consistency of shared data
- To present both software and hardware solutions of the critical-section problem
- To examine several classical process-synchronization problems
- To explore several tools that are used to solve process synchronization problems






Background

- Processes can execute concurrently
 - May be interrupted at any time, partially completing execution
- Concurrent access to shared data may result in data inconsistency
- Maintaining data consistency requires mechanisms to ensure the orderly execution of cooperating processes
- Illustration of the problem:

Suppose that we wanted to provide a solution to the consumer-producer problem that fills **all** the buffers. We can do so by having an integer **counter** that keeps track of the number of full buffers. Initially, **counter** is set to 0. It is incremented by the producer after it produces a new item to the buffer and is decremented by the consumer after it consumes an item from the buffer.





Producer

```
while (true) {  
    /* produce an item in next  
    produced */  
  
    while (counter == BUFFER_SIZE)  
    ;  
  
    /* do nothing */  
    buffer[in] = next_produced;  
    in = (in + 1) % BUFFER_SIZE;  
    counter++;  
}
```





Consumer

```
while (true) {  
    while (counter == 0)  
        ; /* do nothing */  
    next_consumed = buffer[out];  
    out = (out + 1) % BUFFER_SIZE;  
  
    counter--;  
  
    /* consume the item in next  
consumed */  
}
```

*counter keeps track of how many items are there
in the buffer*





Race Condition

- when 2/more process/thread update the same shared variable at the same time without proper synchronisation, so the final result depends on order of execution.

- `counter++` could be implemented as

```
register1 = counter
register1 = register1 + 1
counter = register1
```

- `counter--` could be implemented as

```
register2 = counter
register2 = register2 - 1
counter = register2
```

- Consider this execution interleaving with “count = 5” initially:

S0: producer execute	<code>register1 = counter</code>	{register1 = 5}
S1: producer execute	<code>register1 = register1 + 1</code>	{register1 = 6}
S2: consumer execute	<code>register2 = counter</code>	{register2 = 5}
S3: consumer execute	<code>register2 = register2 - 1</code>	{register2 = 4}
S4: producer execute	<code>counter = register1</code>	{counter = 6}
S5: consumer execute	<code>counter = register2</code>	{counter = 4}





Critical Section Problem

- Consider system of n processes $\{p_0, p_1, \dots, p_{n-1}\}$
- Each process has **critical section** segment of code
 - Process may be changing common variables, updating table, writing file, etc
 - When one process in critical section, no other may be in its critical section
- **Critical section problem** is to design protocol to solve this
- Each process must ask permission to enter critical section in **entry section**, may follow critical section with **exit section**, then **remainder section**
do non shared stuff

Cool





Critical Section

- General structure of process P_i

do {

entry section

critical section

exit section

remainder section

} while (true);





Solution to Critical-Section Problem

1. **Mutual Exclusion** - If process P_i is executing in its critical section, then no other processes can be executing in their critical sections
2. **Progress** - If no process is executing in its critical section and there exist some processes that wish to enter their critical section, then the selection of the processes that will enter the critical section next cannot be postponed indefinitely
3. **Bounded Waiting** - A bound must exist on the number of times that other processes are allowed to enter their critical sections after a process has made a request to enter its critical section and before that request is granted
 - Assume that each process executes at a nonzero speed
 - No assumption concerning **relative speed** of the n processes





Critical-Section Handling in OS

preemption = taking CPU away from the process

Two approaches depending on if kernel is preemptive or non- preemptive

- **Preemptive** – allows preemption of process when running in kernel mode
- **Non-preemptive** – runs until exits kernel mode, blocks, or voluntarily yields CPU
 - ▶ Essentially free of race conditions in kernel mode





Peterson's Solution

- Good algorithmic description of solving the problem
- Two process solution
- Assume that the **load** and **store** machine-language instructions are atomic; that is, cannot be interrupted
- The two processes share two variables:
 - **int turn;**
 - **Boolean flag[2]**
- The variable **turn** indicates whose turn it is to enter the critical section
- The **flag** array is used to indicate if a process is ready to enter the critical section. **flag[i] = true** implies that process P_i is ready!





Algorithm for Process P_i

Two process - P_i & P_j

do {

flag[i] = true;

turn = j;

while (flag[j] && turn == j);

critical section

flag[i] = false;

remainder section

} while (true);

*I tell the system I want to enter
I tell P_j to go first if they want to enter
If P_j is not interested or it's my turn, I go in
Once I'm done, I say I'm no longer interested.
Then I do my own stuff and repeat.*





Peterson's Solution (Cont.)

- Provable that the three CS requirements are met:

1. Mutual exclusion is preserved

P_i enters CS only if:

either `flag[j] = false` or `turn = i`

2. Progress requirement is satisfied *→ P_i does not wait unnecessarily*
3. Bounded-waiting requirement is met

*↓
no process waits forever*





Synchronization Hardware

- Many systems provide hardware support for implementing the critical section code.
- All solutions below are based on idea of **locking**
 - Protecting critical regions via locks
- Uniprocessors – could disable interrupts
 - Currently running code would execute without preemption
 - Generally too inefficient on multiprocessor systems
 - ▶ Operating systems using this not broadly scalable
- Modern machines provide special atomic hardware instructions
 - ▶ **Atomic** = non-interruptible
 - test memory word and set value
 - swap contents of two memory words





Solution to Critical-section Problem Using Locks

```
do {  
    acquire lock  
    critical section  
    release lock  
    remainder section  
} while (TRUE);
```





test_and_set Instruction



hardware supported atomic instruction used to implement locks for critical sections

Definition:

```
boolean test_and_set (boolean *target)
{
    boolean rv = *target;
    *target = TRUE;
    return rv;
}
```

1. Executed atomically
2. Returns the original value of passed parameter
3. Set the new value of passed parameter to "TRUE".

FALSE = lock is open
TRUE = lock is closed





Solution using test_and_set()

- Shared Boolean variable lock, initialized to FALSE
- Solution:

```
do {  
    while (test_and_set(&lock))  
        ; /* do nothing */  
        /* critical section */  
    lock = false;  
        /* remainder section */  
} while (true);
```

for P_i
↳ test_and_set(&lock) is called
↳ if lock == FALSE (free) → P_i sets it to true and enters critical section
↳ P_i sets lock to false
↳ P_i goes to remainder section





compare_and_swap Instruction

↳ atomic instruction used to create locks in multiprocessor systems

Definition:

```
int compare_and_swap(int *value, int expected, int
new_value) {
    int temp = *value;

    if (*value == expected)
        *value = new_value;
    return temp;
}
```

1. Executed atomically
2. Returns the original value of passed parameter “value”
3. Set the variable “value” the value of the passed parameter “new_value” but only if “value” == “expected”. That is, the swap takes place only under this condition.





Solution using compare_and_swap

- Shared integer “lock” initialized to 0;
- Solution:

```
do {  
while (compare_and_swap(&lock, 0, 1) != 0)  
    ; /* do nothing */  
    /* critical section */  
lock = 0; // open the lock  
    /* remainder section */  
} while (true);  
if lock == 0 (free), it becomes 1 and Pi enters critical section  
lock == 1 Pi waits
```





Bounded-waiting Mutual Exclusion with test_and_set

```
do {
    waiting[i] = true;
    key = true;
    while (waiting[i] && key)
        key = test_and_set(&lock);
    waiting[i] = false;
    /* critical section */
    j = (i + 1) % n;
    while ((j != i) && !waiting[j])
        j = (j + 1) % n;
    if (j == i)
        lock = false;
    else
        waiting[j] = false;
    /* remainder section */
} while (true);
```





Mutex Locks

↳ mutual exclusion

- Previous solutions are complicated and generally inaccessible to application programmers
- OS designers build software tools to solve critical section problem
- Simplest is mutex lock
- Protect a critical section by first **acquire()** a lock then **release()** the lock
 - Boolean variable indicating if lock is available or not
- Calls to **acquire()** and **release()** must be atomic
 - Usually implemented via hardware atomic instructions
- But this solution requires **busy waiting**
 - This lock therefore called a **spinlock**





acquire() and release()

*available = 0 → lock is taken
= 1 → lock is free*

- ```
acquire() {
 while (!available)
 ; /* busy wait */
 available = false;
}
```
- ```
release() {  
    available = true;  
}
```
- ```
do {
 acquire lock
 critical section
 release lock
 remainder section
} while (true);
```

*} keeps spinning until lock becomes available  
→ take the lock*





# Semaphore

- Synchronization tool that provides more sophisticated ways (than Mutex locks) for process to synchronize their activities.
- Semaphore **S** – integer variable
- Can only be accessed via two indivisible (atomic) operations
  - **wait()** and **signal()**
    - ▶ Originally called **P()** and **V()**
- Definition of the **wait()** operation

```
wait(S) {
 while (S <= 0)
 ; // busy wait
 S--;
}
```

- Definition of the **signal()** operation

```
signal(S) {
 S++;
}
```







# Semaphore Usage

- Counting semaphore – integer value can range over an unrestricted domain
- Binary semaphore – integer value can range only between 0 and 1

- Same as a mutex lock

- Can solve various synchronization problems

- Consider  $P_1$  and  $P_2$  that require  $S_1$  to happen before  $S_2$

*P<sub>1</sub> must finish task S<sub>1</sub> before P<sub>2</sub> can start task S<sub>2</sub>*

Create a semaphore “synch” initialized to 0

P1:

$S_1$ ;

signal(synch); *→ make synch = 1*

P2:

wait(synch); *→ wait until synch ≤ 0, then decrements*

$S_2$ ;

- Can implement a counting semaphore  $S$  as a binary semaphore





# Semaphore Implementation

- Must guarantee that no two processes can execute the `wait()` and `signal()` on the same semaphore at the same time
- Thus, the implementation becomes the critical section problem where the `wait` and `signal` code are placed in the critical section
  - Could now have **busy waiting** in critical section implementation
    - ▶ But implementation code is short
    - ▶ Little busy waiting if critical section rarely occupied
- Note that applications may spend lots of time in critical sections and therefore this is not a good solution





# Semaphore Implementation with no Busy waiting

- With each semaphore there is an associated waiting queue
- Each entry in a waiting queue has two data items:
  - value (of type integer)
  - pointer to next record in the list
- Two operations:
  - **block** – place the process invoking the operation on the appropriate waiting queue
  - **wakeup** – remove one of processes in the waiting queue and place it in the ready queue
- ```
typedef struct{  
    int value;  
    struct process *list;  
} semaphore;
```

when process calls wait but value ≤ 0 , it cannot proceed so instead of busy waiting





Implementation with no Busy waiting (Cont.)

```
wait(semaphore *S) {  
    S->value--;  
    if (S->value < 0) {  
        add this process to S->list;  
        block();  
    }  
}
```

*no resources are available
so add it to waiting list and block (put it to sleep)*

```
signal(semaphore *S) {  
    S->value++;  
    if (S->value <= 0) {  
        remove a process P from S->list;  
        wakeup(P);  
    }  
}
```





Deadlock and Starvation

- **Deadlock** – two or more processes are waiting indefinitely for an event that can be caused by only one of the waiting processes
- Let S and Q be two semaphores initialized to 1

P_0
`wait(S) ;`
`wait(Q) ;`
`...`
`signal(S) ;`
`signal(Q) ;`

P_1
`wait(Q) ;`
`wait(S) ;`
`...`
`signal(Q) ;`
`signal(S) ;`

- **Starvation** – **indefinite blocking**
 - A process may never be removed from the semaphore queue in which it is suspended
- **Priority Inversion** – Scheduling problem when lower-priority process holds a lock needed by higher-priority process
 - Solved via **priority-inheritance protocol**





Classical Problems of Synchronization

- Classical problems used to test newly-proposed synchronization schemes
 - Bounded-Buffer Problem
 - Readers and Writers Problem
 - Dining-Philosophers Problem





Bounded-Buffer Problem

- n buffers, each can hold one item
- Semaphore **mutex** initialized to the value 1
- Semaphore **full** initialized to the value 0
- Semaphore **empty** initialized to the value n





Bounded Buffer Problem (Cont.)

- The structure of the producer process

```
do {  
    ...  
    /* produce an item in next_produced */  
    ...  
    wait(empty);  
    wait(mutex);  
    ...  
    /* add next produced to the buffer */  
    ...  
    signal(mutex);  
    signal(full);  
} while (true);
```





Bounded Buffer Problem (Cont.)

- The structure of the consumer process

```
Do {  
    wait(full);  
    wait(mutex);  
    ...  
    /* remove an item from buffer to next_consumed */  
    ...  
    signal(mutex);  
    signal(empty);  
    ...  
    /* consume the item in next consumed */  
    ...  
} while (true);
```





Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - Readers – only read the data set; they do **not** perform any updates
 - Writers – can both read and write
- Problem – allow multiple readers to read at the same time
 - Only one single writer can access the shared data at the same time, *not any reader/writer can access at that time*
- Several variations of how readers and writers are considered – all involve some form of priorities
- Shared Data
 - Data set
 - Semaphore **rw_mutex** initialized to 1
 - Semaphore **mutex** initialized to 1
 - Integer **read_count** initialized to 0





Readers-Writers Problem (Cont.)

- The structure of a writer process

```
do {  
    wait(rw_mutex) ;  
    ...  
    /* writing is performed */  
    ...  
    signal(rw_mutex) ;  
} while (true) ;
```





Readers-Writers Problem (Cont.)

- The structure of a reader process

```
do {
```

```
    wait(mutex); → mutex is for managing read-count variable
```

```
    read_count++;
```

```
    if (read_count == 1)
```

```
        wait(rw_mutex); → now writer can't enter
```

```
    signal(mutex);
```

```
    ...
```

```
    /* reading is performed */
```

```
    ...
```

```
    wait(mutex); → mutex for read-count variable
```

```
    read_count--;
```

```
    if (read_count == 0) { if no readers, writer can enter
```

```
        signal(rw_mutex);
```


```
    signal(mutex);
```

```
} while (true);
```





Dining-Philosophers Problem



- Philosophers spend their lives alternating thinking and eating
- Don't interact with their neighbors, occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - Need both to eat, then release both when done
- In the case of 5 philosophers
 - Shared data
 - ▶ Bowl of rice (data set)
 - ▶ Semaphore **chopstick** [5] initialized to 1





Dining-Philosophers Problem Algorithm

- The structure of Philosopher i :

```
do {  
    wait (chopstick[i] );  
    wait (chopStick[ (i + 1) % 5] );  
  
    // eat  
  
    signal (chopstick[i] );  
    signal (chopstick[ (i + 1) % 5] );  
  
    // think  
  
} while (TRUE);
```

- What is the problem with this algorithm?





Dining-Philosophers Problem Algorithm (Cont.)

■ Deadlock handling

- Allow at most 4 philosophers to be sitting simultaneously at the table.
- Allow a philosopher to pick up the forks only if both are available (picking must be done in a critical section).
- Use an asymmetric solution -- an odd-numbered philosopher picks up first the left chopstick and then the right chopstick. Even-numbered philosopher picks up first the right chopstick and then the left chopstick.





Problems with Semaphores

- Incorrect use of semaphore operations:
 - signal (mutex) wait (mutex) – violates ME
 - wait (mutex) ... wait (mutex) – results in deadlock
 - Omitting of wait (mutex) or signal (mutex) (or both) – both ME & deadlock violation



End of Chapter 6

