



Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages
Pointers
volatile

inline functions

Macros
inline

Summary

Module 06: Programming in Modern C++

Constants and Inline Functions

Instructors: Abir Das and Sourangshu Bhattacharya

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

{ abir, sourangshu }@cse.iitkgp.ac.in

Slides taken from NPTEL course on Programming in C++

by **Prof. Partha Pratim Das**



Module Objectives

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives & Outline

`const-ness &
cv-qualifier`

`const-ness`
`Advantages`
`Pointers`
`volatile`

`inline functions`

`Macros`
`inline`

`Summary`

- Understand `const` in C++ and contrast with *Manifest Constants*
- Understand `inline` in C++ and contrast with *Macros*



Module Outline

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives & Outline

const-ness &
cv-qualifier

const-ness

Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

- const-ness and cv-qualifier
 - Notion of const
 - Advantages of const
 - ▷ Natural Constants – π , e
 - ▷ Program Constants – array size
 - ▷ Prefer const to #define
 - const and pointer
 - ▷ const-ness of pointer / pointee. How to decide?
 - Notion of volatile
- inline functions
 - Macros with params
 - ▷ Advantages
 - ▷ Disadvantages
 - Notion of inline functions
 - ▷ Advantages



Program 06.01: Manifest constants in C

- Manifest constants are defined by `#define`
- Manifest constants are replaced by CPP (C Pre-Processor)

Source Program	Program after CPP
<pre>#include <iostream> #include <cmath> using namespace std; #define TWO 2 // Manifest const #define PI 4.0*atan(1.0) // Const expr. int main() { int r = 10; double peri = TWO * PI * r; cout << "Perimeter = " << peri << endl; }</pre>	<pre>// Contents of <iostream> header replaced by CPP // Contents of <cmath> header replaced by CPP using namespace std; // #define of TWO consumed by CPP // #define of PI consumed by CPP int main() { int r = 10; double peri = 2 * 4.0*atan(1.0) * r; // By CPP cout << "Perimeter = " << peri << endl; }</pre>
Perimeter = 62.8319	Perimeter = 62.8319
<ul style="list-style-type: none"> • <code>TWO</code> is a manifest constant • <code>PI</code> is a manifest constant as macro • <code>TWO</code> & <code>PI</code> look like variables 	<ul style="list-style-type: none"> • CPP replaces the token <code>TWO</code> by <code>2</code> • CPP replaces the token <code>PI</code> by <code>4.0*atan(1.0)</code> and evaluates • Compiler sees them as constants • <code>TWO * PI = 6.28319</code> by constant folding of compiler



Notion of const-ness

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

- The value of a `const` variable *cannot be changed after definition*

```
const int n = 10; // n is an int type variable with value 10. n is a constant
```

```
...
```

```
n = 5; // Is a compilation error as n cannot be changed
```

```
...
```

```
int m;
```

```
int *p = 0;
```

```
p = &m; // Hold m by pointer p
```

```
*p = 7; // Change m by p; m is now 7
```

```
...
```

```
p = &n; // Is a compilation error as n may be changed by *p = 5;
```

- Naturally, a `const` variable *must be initialized when defined*

```
const int n; // Is a compilation error as n must be initialized
```

- A variable of *any data type* can be declared as `const`

```
typedef struct _Complex {
```

```
    double re;
```

```
    double im;
```

```
} Complex;
```

```
const Complex c = {2.3, 7.5}; // c is a Complex type variable
```

```
// It is initialized with c.re = 2.3 and c.im = 7.5. c is a constant
```

```
...
```

```
c.re = 3.5; // Is a compilation error as no part of c can be changed
```



Program 06.02: Compare #define and const

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness

Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

Using #define

```
#include <iostream>
#include <cmath>
using namespace std;

#define TWO 2
#define PI 4.0*atan(1.0)

int main() { int r = 10;
    // Replace by CPP
    double peri = 2 * 4.0*atan(1.0) * r;
    cout << "Perimeter = " << peri << endl;
}
```

Perimeter = 62.8319

- TWO is a manifest constant
- PI is a manifest constant
- TWO & PI *look like variables*
- Types of TWO & PI may be indeterminate
- TWO * PI = 6.28319 by constant folding of compiler

Using const

```
#include <iostream>
#include <cmath>
using namespace std;

const int TWO = 2;
const double PI = 4.0*atan(1.0);

int main() { int r = 10;
    // No replacement by CPP
    double peri = TWO * PI * r;
    cout << "Perimeter = " << peri << endl;
}
```

Perimeter = 62.8319

- TWO is a const variable initialized to 2
- PI is a const variable initialized to 4.0*atan(1.0)
- TWO & PI *are variables*
- Type of TWO is const int
- Type of PI is const double



Advantages of const

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness

Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

- Natural Constants like π , e , Φ (*Golden Ratio*) etc. can be compactly defined and used

```
const double pi = 4.0*atan(1.0);           // pi = 3.14159
const double e = exp(1.0);                 // e = 2.71828
const double phi = (sqrt(5.0) + 1) / 2.0;   // phi = 1.61803
```

```
const int TRUE = 1;                        // Truth values
const int FALSE = 0;
```

```
const int null = 0;                        // null value
```

Note: `NULL` is a manifest constant in C/C++ set to `0`

- Program Constants like number of elements, array size etc. can be defined at one place (at times in a header) and used all over the program

```
const int nArraySize = 100;
const int nElements = 10;

int main() {
    int A[nArraySize];           // Array size
    for (int i = 0; i < nElements; ++i) // Number of elements
        A[i] = i * i;
}
```



Advantages of const

- Prefer `const` over `#define`

Using #define

Manifest Constant

- Is `not` type safe
- Replaced `textually` by CPP
- Cannot be *watched* in debugger
- Evaluated as *many times as replaced*

Using const

Constant Variable

- Has its `type`
- `Visible` to the compiler
- Can be *watched* in debugger
- Evaluated *only on initialization*



const and Pointers

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

- **const**-ness can be used with Pointers in one of the two ways:
 - **Pointer to Constant data** where the *pointee* (pointed data) cannot be changed
 - **Constant Pointer** where the *pointer* (address) cannot be changed
- Consider usual **pointer-pointee** computation (without **const**):

```
int m = 4;
int n = 5;
int * p = &n; // p points to n. *p is 5
...
n = 6;        // n and *p are 6 now
*p = 7;       // n and *p are 7 now. POINTEE changes
...
p = &m;        // p points to m. *p is 4. POINTER changes
*p = 8;       // m and *p are 8 now. n is 7. POINTEE changes
```



const and Pointers: *Pointer to Constant data*

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

Consider pointed data

```
int m = 4;
const int n = 5;
const int * p = &n;
...
n = 6; // Error: n is constant and cannot be changed
*p = 7; // Error: p points to a constant data (n) that cannot be changed
p = &m; // Okay
*p = 8; // Error: p points to a constant data. Its pointee cannot be changed
```

Interestingly,

```
int n = 5;
const int * p = &n;
...
n = 6; // Okay
*p = 6; // Error: p points to a constant data (n) that cannot be changed
```

Finally,

```
const int n = 5;
int *p = &n; // Error: If this were allowed, we would be able to change constant n
...
n = 6; // Error: n is constant and cannot be changed
*p = 6; // Would have been okay, if declaration of p were valid
```



const and Pointers: Example

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros

inline

Summary

What will be the output of the following program:

```
#include <iostream>
using namespace std;

int main() {
    const int a = 5;
    int *b;
    b = (int *) &a;
    *b = 10;
    cout << a << " " <<b<<" "<< &a <<" "<< *b <<"\n";
}
```



const and Pointers: Example

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros

inline

Summary

What will be the output of the following program:

```
#include <iostream>
using namespace std;

int main() {
    const int a = 5;
    int *b;
    b = (int *) &a;
    *b = 10;
    cout << a << " " <<b<<" "<< &a <<" "<< *b <<"\n";
}
```

Standard g++ compiler prints: 5 0x16b58f4ec 0x16b58f4ec 10

b actually points to a

But when accessed through a the compiler substitutes the constant expression Technically the behavior is **undefined**



const and Pointers: *Constant Pointer*

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

Consider pointer

```

int m = 4, n = 5;
int * const p = &n;
...
n = 6; // Okay
*p = 7; // Okay. Both n and *p are 7 now
...
p = &m; // Error: p is a constant pointer and cannot be changed

```

By extension, both can be **const**

```

const int m = 4;
const int n = 5;
const int * const p = &n;
...
n = 6; // Error: n is constant and cannot be changed
*p = 7; // Error: p points to a constant data (n) that cannot be changed
...
p = &m; // Error: p is a constant pointer and cannot be changed

```

Finally, to decide on **const**-ness, draw a mental line through *

```

int n = 5;
int * p = &n;           // non-const-Pointer to non-const-Pointee
const int * p = &n;      // non-const-Pointer to const-Pointee
int * const p = &n;      // const-Pointer to non-const-Pointee
const int * const p = &n; // const-Pointer to const-Pointee

```



const and Pointers: The case of C-string

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

Consider the example:

```
char * str = strdup("IIT, Kharagpur");  
str[0] = 'N'; // Edit the name  
cout << str << endl;  
str = strdup("JIT, Kharagpur"); // Change the name  
cout << str << endl;
```

Output is:

NIT, Kharagpur

JIT, Kharagpur

To stop editing the name:

```
const char * str = strdup("IIT, Kharagpur");  
str[0] = 'N'; // Error: Cannot Edit the name  
str = strdup("JIT, Kharagpur"); // Change the name
```

To stop changing the name:

```
char * const str = strdup("IIT, Kharagpur");  
str[0] = 'N'; // Edit the name  
str = strdup("JIT, Kharagpur"); // Error: Cannot Change the name
```

To stop both:

```
const char * const str = strdup("IIT, Kharagpur");  
str[0] = 'N'; // Error: Cannot Edit the name  
str = strdup("JIT, Kharagpur"); // Error: Cannot Change the name
```



Notion of volatile

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

- Variable Read-Write
 - The value of a variable can be *read and / or assigned* at any point of time
 - The value assigned to a variable does not change till a next assignment is made
- **const**
 - A **const** variable's value is set *only at initialization* – *can't be changed* afterwards
- **volatile**
 - In contrast, the value of a **volatile** variable can be modified by actions other than those in the user application.
 - Therefore, the volatile keyword is useful for declaring variables in **shared memory** that can be accessed by multiple processes for communication with interrupt service routines. It can be *changed by hardware, the kernel, another thread* etc.
 - When a name is declared as volatile, the compiler **reloads the value from memory each time** it is accessed by the program. This dramatically reduces the possible optimizations.
- **cv-qualifier**: A declaration may be prefixed with a qualifier – **const** or **volatile**



Using volatile

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

Consider:

```
static int i;  
void fun(void) {  
    i = 0;  
    while (i != 100);  
}
```

This is an *infinite loop*! Hence the compiler should optimize as:

```
static int i;  
void fun(void) {  
    i = 0;  
    while (1);          // Compiler optimizes  
}
```

Now qualify `i` as `volatile`:

```
static volatile int i;  
void fun(void) {  
    i = 0;  
    while (i != 100);  // Compiler does not optimize  
}
```

Being `volatile`, `i` can be changed by hardware anytime. *It waits till the value becomes 100* (possibly some hardware writes to a port).



Program 06.03: Macros with Parameters

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

- Macros with Parameters are defined by **#define**
- Macros with Parameters are replaced by CPP

Source Program	Program after CPP
<pre>#include <iostream> using namespace std; #define SQUARE(x) x * x int main() { int a = 3, b; b = SQUARE(a); cout << "Square = " << b << endl; }</pre>	<pre>#include <iostream> // Header replaced by CPP using namespace std; // #define of SQUARE(x) consumed by CPP int main() { int a = 3, b; b = a * a; // Replaced by CPP cout << "Square = " << b << endl; }</pre>
<p>Square = 9</p>	<p>Square = 9</p>
<ul style="list-style-type: none"> • SQUARE(x) is a macro with one param • SQUARE(x) looks like a function 	<ul style="list-style-type: none"> • CPP replaces the SQUARE(x) substituting x with a • Compiler does not see it as function



Pitfalls of macros

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness

Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

Consider the example:

```
#include <iostream>
using namespace std;

#define SQUARE(x) x * x

int main() {
    int a = 3, b;

    b = SQUARE(a + 1); // Error: Wrong macro expansion

    cout << "Square = " << b << endl;
}
```

Output is 7 in stead of 16 as expected. On the expansion line it gets:

```
b = a + 1 * a + 1;
```

To fix:

```
#define SQUARE(x) (x) * (x)
```

Now:

```
b = (a + 1) * (a + 1);
```



Pitfalls of macros

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros
inline

Summary

Continuing ...

```
#include <iostream>
using namespace std;
```

```
#define SQUARE(x) (x) * (x)
```

```
int main() {
    int a = 3, b;

    b = SQUARE(++a);

    cout << "Square = " << b << endl;
}
```

Output is 25 in stead of 16 as expected. On the expansion line it gets:

```
b = (++a) * (++a);
```

and *a* is *incremented twice* before being used! There is no easy fix.



inline Function

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness

Advantages

Pointers

volatile

inline functions

Macros

inline

Summary

- An **inline** function is just a function like any other
- The function prototype is preceded by the keyword **inline**
- An **inline** function is *expanded* (*inlined*) at the site of its call and the overhead of passing parameters between caller and callee (or called) functions is avoided



Program 06.04: Macros as inline Functions

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros

inline

Summary

- Define the function
- Prefix function header with **inline**
- *Compile function body and function call together*

Using macro	Using inline
<pre>#include <iostream> using namespace std; #define SQUARE(x) x * x int main() { int a = 3, b; b = SQUARE(a); cout << "Square = " << b << endl; }</pre>	<pre>#include <iostream> using namespace std; inline int SQUARE(int x) { return x * x; } int main() { int a = 3, b; b = SQUARE(a); cout << "Square = " << b << endl; }</pre>
Square = 9	Square = 9
<ul style="list-style-type: none"> • SQUARE(x) is a macro with one param • Macro SQUARE(x) is efficient • SQUARE(a + 1) fails • SQUARE(++a) fails • SQUARE(++a) does not check type 	<ul style="list-style-type: none"> • SQUARE(x) is a function with one param • inline SQUARE(x) is equally efficient • SQUARE(a + 1) works • SQUARE(++a) works • SQUARE(++a) checks type



Macros & inline Functions: Compare and Contrast

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros

inline

Summary

Macros

- Expanded at the place of calls
- Efficient in execution
- Code bloats
- Has *syntactic and semantic pitfalls*
- *Type checking* for parameters is *not done*
- *Errors* are *not checked during compilation*
- *Not available* to *debugger*

inline Functions

- Expanded at the place of calls
- Efficient in execution
- Code bloats
- *No pitfall*
- *Type checking* for parameters is *robust*
- *Errors* are *checked during compilation*
- *Available* to *debugger* in *DEBUG* build



Limitations of Function inlineing

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

const-ness &
cv-qualifier

const-ness
Advantages

Pointers
volatile

inline functions

Macros

inline

Summary

- **inline**ing is a *directive* – compiler may not inline functions with large body
- **inline** functions may not be *recursive*
- Function body is needed for **inline**ing at the time of function call. Hence, implementation hiding is not possible. *Implement inline functions in header files*
- **inline** functions *must not have two different definitions*



Module Summary

Module 06

Instructors: Abir
Das and
Sourangshu
Bhattacharya

Objectives &
Outline

`const-ness &
cv-qualifier`

`const-ness`

Advantages

Pointers

`volatile`

`inline functions`

Macros

`inline`

Summary

- Revisit manifest constants from C
- Understand `const-ness`, its use and advantages over manifest constants
- Understand the interplay of `const` and pointer
- Understand the notion and use of `volatile` data
- Revisit macros with parameters from C
- Understand `inline` functions and their advantages over macros
- Limitations of `inlineing`