PRACTICE LAB 6

Sarthak Sethi 2410110472

```
mysql> Create table employee( emp_id INT AUTO_INCREMENT PRIMARY KEY, emp_name VARCHAR(50) NOT NULL, performance_score REAL, salary DECIMAL(10,2), department VARCHAR(50), designation VARCHAR(30))AUTO_INCREMENT=101;
ERROR 1050 (42S01): Table 'employee' already exists
mysql> Alter table employee AUTO_INCREMENT=101;
Query OK, 0 rows affected (0.020 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> describe employee;
+--------------------+----------------+------+-----+----------+----------------+
| Field              | Type           | Null | Key | Default  | Extra          |
+--------------------+----------------+------+-----+----------+----------------+
| emp_id             | int            | NO   | PRI | NULL     | auto_increment |
| emp_name           | varchar(50)    | NO   |     | NULL     |                |
| performance_score  | double         | YES  |     | NULL     |                |
| salary             | decimal(10,2)  | YES  |     | NULL     |                |
| department         | varchar(50)    | YES  |     | NULL     |                |
| designation        | varchar(30)    | YES  |     | NULL     |                |
+--------------------+----------------+------+-----+----------+----------------+
6 rows in set (0.020 sec)
```

```
mysql> INSERT INTO Employee (emp_name, performance_score, salary, department, designation)
    -> VALUES
    -> ('Akshit Mahajan', 4.2, 25000.00, 'HR', 'Low Performer'),
    -> ('Sara Zafar', 6.5, 32000.00, 'Finance', 'Average Performer'),
    -> ('Meera Mittal', 8.7, 45000.75, 'Marketing', 'High Performer'),
    -> ('Utkarsh Sharma', 7.8, 38000.00, 'HR', 'Average Performer'),
    -> ('Rohan Das', 3.9, 30000.00, 'IT', 'Low Performer'),
    -> ('Neha Gupta', 2.8, 50000.00, 'Sales', 'Low Performer');
Query OK, 6 rows affected (0.006 sec)
Records: 6  Duplicates: 0  Warnings: 0

mysql> select * from employee;
+--------+---------------+------------------+----------+------------+------------------+
| emp_id | emp_name      | performance_score | salary   | department | designation      |
+--------+---------------+------------------+----------+------------+------------------+
|    107 | Akshit Mahajan |              4.2 | 25000.00 | HR         | Low Performer    |
|    108 | Sara Zafar     |              6.5 | 32000.00 | Finance    | Average Performer |
|    109 | Meera Mittal   |              8.7 | 45000.75 | Marketing  | High Performer   |
|    110 | Utkarsh Sharma |              7.8 | 38000.00 | HR         | Average Performer |
|    111 | Rohan Das      |              3.9 | 30000.00 | IT         | Low Performer    |
|    112 | Neha Gupta     |              2.8 | 50000.00 | Sales      | Low Performer    |
+--------+---------------+------------------+----------+------------+------------------+
6 rows in set (0.001 sec)
```

```
mysql> Create table emp_txn ( emp_id INT,
    -> emp_name VARCHAR(50),
    -> txn_amount DECIMAL(10,2),
    -> txn_datetime DATETIME NOT NULL);
Query OK, 0 rows affected (0.018 sec)

mysql> describe emp_txn;
+--------------+----------------+------+-----+----------+-------+
| Field        | Type           | Null | Key | Default  | Extra |
+--------------+----------------+------+-----+----------+-------+
| emp_id       | int            | YES  |     | NULL     |       |
| emp_name     | varchar(50)    | YES  |     | NULL     |       |
| txn_amount   | decimal(10,2)  | YES  |     | NULL     |       |
| txn_datetime | datetime       | NO   |     | NULL     |       |
+--------------+----------------+------+-----+----------+-------+
4 rows in set (0.005 sec)
```

PRACTICE LAB 6

Sarthak Sethi 2410110472

```
Query OK, 0 rows affected (0.011 sec)

mysql> DELIMITER $$
mysql>
mysql> CREATE TRIGGER Validate_Employee
    -> BEFORE INSERT ON employee
    -> FOR EACH ROW
    -> BEGIN
    ->     IF NEW.performance_score < 0 OR NEW.performance_score > 10 THEN
    ->         SIGNAL SQLSTATE '45000'
    ->         SET MESSAGE_TEXT = 'Performance score must be between 0 and 10';
    ->     END IF;
    ->
    ->     IF NEW.salary < 20000 THEN
    ->         SIGNAL SQLSTATE '45000'
    ->         SET MESSAGE_TEXT = 'Minimum Salary must be 20000';
    ->     END IF;
    -> END $$
Query OK, 0 rows affected (0.005 sec)

mysql>
mysql> DELIMITER ;
mysql> INSERT INTO Employee (emp_name, performance_score, salary, department, designation) VALUES ('Rahul',11,30000.0,'IT','Manager');
ERROR 1644 (45000): Performance score must be between 0 and 10
mysql> INSERT INTO Employee (emp_name, performance_score, salary, department, designation) VALUES ('Simaran',7,15000.0,'HR','Executive');
ERROR 1644 (45000): Minimum Salary must be 20000
```

```
mysql> UPDATE Employee SET salary = salary + 1000 WHERE emp_id = 109;
Query OK, 1 row affected (0.007 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> select * from emp_txn;
+---------+--------------+------------+---------------------+
| emp_id | emp_name     | txn_amount | txn_datetime        |
+---------+--------------+------------+---------------------+
|    109 | Meera Mittal |   46000.75 | 2026-03-30 16:20:11 |
+---------+--------------+------------+---------------------+
1 row in set (0.001 sec)
```

```
mysql> DELIMITER $$
mysql>
mysql> CREATE TRIGGER Salary_Update_Log
    -> AFTER UPDATE ON Employee
    -> FOR EACH ROW
    -> BEGIN
    ->     IF OLD.salary != NEW.salary THEN
    ->         INSERT INTO Emp_txn(emp_id, emp_name, txn_amount, txn_datetime)
    ->         VALUES (NEW.emp_id, NEW.emp_name, NEW.salary, NOW());
    ->     END IF;
    -> END$$
Query OK, 0 rows affected (0.010 sec)
```

```
mysql> DELIMITER $$
mysql>
mysql> CREATE TRIGGER Salary_Update_Log
    -> AFTER UPDATE ON Employee
    -> FOR EACH ROW
    -> BEGIN
    ->     IF OLD.salary <> NEW.salary THEN
    ->         INSERT INTO emp_txn(emp_id, emp_name, txn_amount, txn_datetime)
    ->         VALUES (NEW.emp_id, NEW.emp_name, NEW.salary, NOW());
    ->     END IF;
    -> END$$
Query OK, 0 rows affected (0.009 sec)
```