

MAD and PWA Lab

Name: Sarvadnya Awaghad

Class: D15A

Roll no:04

Experiment - 8

Aim: To code and register a service worker, and complete the install and activation process for a new service worker for the E-commerce PWA.

Theory:

Service Worker

Service Worker is a script that works on browser background without user interaction independently. Also, It resembles a proxy that works on the user side. With this script, you can track network traffic of the page, manage push notifications and develop “offline first” web applications with Cache API.

Things to note about Service Worker:

A service worker is a programmable network proxy that lets you control how network requests from your page are handled.

Service workers only run over HTTPS. Because service workers can intercept network requests and modify responses, "man-in-the-middle" attacks could be very bad.

The service worker becomes idle when not in use and restarts when it's next needed. You cannot rely on a global state persisting between events. If there is information that you need to persist and reuse across restarts, you can use IndexedDB databases.

What can we do with Service Workers?

You can dominate Network Traffic

You can manage all network traffic of the page and do any manipulations. For example, when the page requests a CSS file, you can send plain text as a response or when the page requests an HTML file, you can send a png file as a response. You can also send a true response too.

You can Cache

You can cache any request/response pair with Service Worker and Cache API and you can

access these offline content anytime.

You can manage Push Notifications

You can manage push notifications with Service Worker and show any information message to the user. You can Continue Although Internet connection is broken, you can start any process with Background Sync of Service Worker.

What can't we do with Service Workers?

You can't access the Window

You can't access the window, therefore, You can't manipulate DOM elements. But, you can communicate to the window through post Message and manage processes that you want.

You can't work it on 80 Port

Service Worker just can work on HTTPS protocol. But you can work on localhost during development.

Registration

To install a service worker, you need to register it in your main JavaScript code. Registration tells the browser where your service worker is located, and to start installing it in the background. Let's look at an example:

```
if ('serviceWorker' in navigator) { navigator.serviceWorker.register('/service-worker.js')
.then(function(registration) {
console.log('Registration successful, scope is:', registration.scope);
})
.catch(function(error) {
console.log('Service worker registration failed, error:', error);
});
}
```

This code starts by checking for browser support by examining navigator.serviceWorker. The service worker is then registered with navigator.serviceWorker.register, which returns a promise that resolves when the service worker has been successfully registered. The scope of the service worker is then logged with registration.scope. If the service worker is already

installed, `navigator.serviceWorker.register` returns the registration object of the currently active service worker.

The scope of the service worker determines which files the service worker controls, in other words, from which path the service worker will intercept requests. The default scope is the location of the service worker file, and extends to all directories below. So if `service-worker.js` is located in the root directory, the service worker will control requests from all files at this domain.

You can also set an arbitrary scope by passing in an additional parameter when registering. For example:

`main.js`

```
navigator.serviceWorker.register('/service-worker.js', { scope: '/app/'
});
```

In this case we are setting the scope of the service worker to `/app/`, which means the service worker will control requests from pages like `/app/`, `/app/lower/` and `/app/lower/lower`, but not from pages like `/app` or `/`, which are higher.

If you want the service worker to control higher pages e.g. `/app` (without the trailing slash) you can indeed change the scope option, but you'll also need to set the `Service-Worker-Allowed` HTTP Header in your server config for the request serving the service worker script.

`main.js`

```
navigator.serviceWorker.register('/app/service-worker.js', { scope: '/app'
});
```

Installation

Once the browser registers a service worker, installation can be attempted. This occurs if the service worker is considered to be new by the browser, either because the site currently doesn't have a registered service worker, or because there is a byte difference between the new service worker and the previously installed one.

A service worker installation triggers an `install` event in the installing service worker. We can

include an install event listener in the service worker to perform some task when the service worker installs. For instance, during the install, service workers can precache parts of a web app so that it loads instantly the next time a user opens it (see caching the application shell). So, after that first load, you're going to benefit from instant repeat loads and your time to interactivity is going to be even better in those cases. An example of an installation event listener looks like this:

service-worker.js

```
// Listen for install event, set callback
self.addEventListener('install', function(event) {
// Perform some task
});
```

Activation

Once a service worker has successfully installed, it transitions into the activation stage. If there are any open pages controlled by the previous service worker, the new service worker enters a waiting state. The new service worker only activates when there are no longer any pages loaded that are still using the old service worker. This ensures that only one version of the service worker is running at any given time.

When the new service worker activates, an activate event is triggered in the activating service worker. This event listener is a good place to clean up outdated caches (see the Offline Cookbook for an example).

Code:

index.html

```
<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Amazon.com: Online Shopping for Electronics, Apparel, Computers, Books, DVDs &
more</title>

  <link href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/4.7.0/css/font-awesome.min.css"
rel="stylesheet">
  <link rel="stylesheet"
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstrap.min.css"
integrity="sha384-BVYiISIFeK1dGmJRAkycuHAHRg32OmUcww7on3RYdg4Va+PmSTsz/K68vbdEjh4u"
```

```
crossorigin="anonymous">
  <link rel="stylesheet" href="css/style.css"/>
</head>

<body>
  <a id="banner" href="#"></a>
  <!-- Main body -->

  <header>
    <a id="nav-top"></a>
    <nav id="nav-main">
      <div class="nav-left">
        <div class="nav-shop">
          <a class="nav-a" href="#">
            Departments
            <i class="fa fa-caret-down" aria-hidden="true"></i>
          </a>
        </div>
      </div>
      <div class="nav-right">
        <a class="nav-a" href="#">
          <span>EN</span>
          <i class="fa fa-globe" aria-hidden="true"></i>
          <i class="fa fa-caret-down" aria-hidden="true"></i>
        </a>

        <a class="nav-a" href="#">
          <span>Hello. Sign in</span>
          Accounts & Lists
          <i class="fa fa-caret-down" aria-hidden="true"></i>
        </a>

        <a class="nav-a" href="#">
          Orders
        </a>

        <a class="nav-a" href="#">
          Try Prime
          <i class="fa fa-caret-down" aria-hidden="true"></i>
        </a>

        <a class="nav-a cart" href="#">
          <span>0</span>
          Cart
        </a>
      </div>
      <div class="nav-fill">
        <ul>
          <li><a href="#">Your Amazon.com</a></li>
          <li><a href="#">Today's Deals</a></li>
          <li><a href="#">Gift Cards & Registry</a></li>
          <li><a href="#">Sell</a></li>
          <li><a href="#">Help</a></li>
        </ul>
      </div>
    </nav>
  </header>
</body>
</html>
```

```

    </ul>
  </div>
</nav>
</header>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.2.1/jquery.min.js"></script>
<script src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstrap.min.js"
integrity="sha384-Tc5IQib027qvyjSMfHjOMaLkfuWVxZxUPnCJA7l2mCWNIpG9mGCD8wGNlIcPD7Txa
" crossorigin="anonymous"></script>
<script src="js/app.js"></script>
</body>
</html>

```

main.css

```

html, body {
  margin: 0;
  font-family: arial,sans-serif;
  min-width: 900px;
  line-height: 14px;
  font-size: 14px;
}

* {
  box-sizing: border-box;
}

a {
  color: #0066c0;
}

a:hover {
  color: #c45500;
}

#banner {
  background: #F6F6F6 url('../img/banner.jpg') no-repeat top left;
  height: 55px;
  background-size: 1920px;
  min-width: 1000px;
  display: block;
}

header {
  background-color: #232f3e;
  height: 99px;
}

```

app.js

```

if ('serviceWorker' in navigator) {
  window.addEventListener('load', () => {
    navigator.serviceWorker.register('/service-worker.js')
      .then(registration => {
        console.log('Service Worker registered with scope:', registration.scope);
      })
      .catch(error => {

```

```

        console.error('Service Worker registration failed:', error);
    });
});
}

```

service-worker.js

```

const cacheName = 'ecommerce-pwa-v1';
const assetsToCache = [
    '/',
    '/index.html',
    '/main.css',
    '/app.js'
]

self.addEventListener('install', event => {
    event.waitUntil(
        caches.open(cacheName)
            .then(cache => {
                return cache.addAll(assetsToCache);
            })
    );
});

self.addEventListener('activate', event => {
    event.waitUntil(
        caches.keys().then(cacheNames => {
            return Promise.all(
                cacheNames.filter(name => {
                    return name !== cacheName;
                }).map(name => {
                    return caches.delete(name);
                })
            );
        })
    );
});

```

Steps for Execution

Create a folder and put all 4 files main.css , service-worker.js, app.js, index.html
open visual studio
install extension Live server
open folder in visual studio open index.html
on bottom right corner click go Live
it will open html page in browser
go to developer tools


Output:

Dimensions: Responsive 719 x 669 96% No throttling

Departments

EN Hello. Sign in Accounts & Lists Orders Try Prime 0 Cart

- Your Amazon.com
- Today's Deals
- Gift Cards & Registry
- Sell
- Help



amazon echo
\$179.99 \$139.99


Welcome

Sign in for the best experience

Sign in securely

New to Amazon? [Start here](#)

Explore AmazonBasics



Application

- Manifest
- Service workers
- Storage

Storage

- Local storage
- Session storage
- IndexedDB
- Web SQL
- Cookies
- Private state tokens
- Interest groups
- Shared storage
- Cache storage

Background services

- Back/forward cache
- Background fetch
- Background sync
- Bounce tracking mitigations
- Notifications
- Payment handler
- Periodic background sync
- Speculative loads
- Push messaging
- Reporting API

Frames

- top

Service workers

Offline Update Bypass for network

http://127.0.0.1:5500/ [Network requests](#) [Update](#) [Unregister](#)

Source [service-worker.js](#)

Received 3/19/2024, 10:02:51 AM

Status ● #898 activated and is stopped [start](#)

Push [Push](#)

Sync [Sync](#)

Periodic Sync [Periodic Sync](#)

Update Cycle

Version	Update Activity	Timeline
#898	Install	
#898	Wait	
#898	Activate	

Service workers from other origins


[See all registrations](#)

Dimensions: Responsive 719 x 669 96% No throttling

Departments

EN Hello. Sign in Accounts & Lists Orders Try Prime 0 Cart

- Your Amazon.com
- Today's Deals
- Gift Cards & Registry
- Sell
- Help



Amazon Fashion
Father's Day Gift Ideas
What dads really want


Welcome

Sign in for the best experience

Sign in securely

New to Amazon? [Start here](#)

Explore AmazonBasics



Application

- Manifest
- Service workers
- Storage

Storage

- Local storage
- Session storage
- IndexedDB
- Web SQL
- Cookies
- Private state tokens
- Interest groups
- Shared storage
- Cache storage

Background services

- Back/forward cache
- Background fetch
- Background sync
- Bounce tracking mitigations
- Notifications
- Payment handler
- Periodic background sync
- Speculative loads
- Push messaging
- Reporting API

Frames

- top

Filter by Path

http://127.0.0.1:5500

Origin http://127.0.0.1:5500

Bucket name default

Is persistent No

Durability relaxed

Quota 0 B

Expiration None

#	Name	Respon...	Conten...	Content...	Time C...	Vary He...
0	/	basic	text/html	1,878	3/19/20...	Origin
1	/app.js	basic	applicat...	428	3/19/20...	Origin
2	/index.html	basic	text/html	1,878	3/19/20...	Origin
3	/main.css	basic	text/css	79	3/19/20...	Origin

Select a cache entry above to preview

Conclusion:

In this experiment, we have registered a service worker, and completed the install and activation process for a new service worker for the E-commerce PWA.