

Your API base URL will be:

```
http://127.0.0.1:8000/api
```

1. Public Endpoints

Health Check

```
GET http://127.0.0.1:8000/api/health
```

No authentication required.

Login

```
POST http://127.0.0.1:8000/api/login
```

Body (JSON)

```
{
  "email": "admin@transitops.com",
  "password": "password",
  "device_name": "Postman"
}
```

Expected response

```
{
  "success": true,
  "message": "Login successful.",
  "data": {
    "token": "1|xxxxxxxxxxxxxxxxxx",
    "user": {
      ...
    }
  }
}
```

Copy the token.

2. Authorization

For every endpoint below add Header

```
Authorization  
Bearer YOUR_TOKEN
```

Also add

```
Accept  
application/json
```

3. Authentication

Current User

```
GET http://127.0.0.1:8000/api/me
```

Logout

```
POST http://127.0.0.1:8000/api/logout
```

4. Dashboard

```
GET http://127.0.0.1:8000/api/dashboard
```

Permission:

```
view dashboard
```

5. Reports

Vehicle Report

```
GET http://127.0.0.1:8000/api/reports/vehicles
```

Optional query

```
?status=available
```

Driver Report

```
GET http://127.0.0.1:8000/api/reports/drivers
```

Trip Report

```
GET http://127.0.0.1:8000/api/reports/trips
```

Optional

```
?status=completed
```

Fuel Report

```
GET http://127.0.0.1:8000/api/reports/fuel
```

Expense Report

```
GET http://127.0.0.1:8000/api/reports/expenses
```

Maintenance Report

```
GET http://127.0.0.1:8000/api/reports/maintenance
```

Financial Report

```
GET http://127.0.0.1:8000/api/reports/financial
```

Performance Report

```
GET http://127.0.0.1:8000/api/reports/performance
```

6. Vehicles

List

```
GET /api/vehicles
```

Show

```
GET /api/vehicles/{id}
```

Example

```
GET /api/vehicles/1
```

Create

POST /api/vehicles

Example

```
{
  "registration_number": "MH12AB1234",
  "name": "Tata Truck",
  "type": "Truck",
  "max_load_capacity": 12000,
  "odometer": 50000,
  "acquisition_cost": 2500000,
  "status": "available"
}
```

Update

PUT /api/vehicles/{id}

Delete

DELETE /api/vehicles/{id}

Retire

POST /api/vehicles/{id}/retire

7. Drivers

List

GET /api/drivers

Show

GET /api/drivers/{id}

Create

POST /api/drivers

Example

```
{
  "name": "John Doe",
  "license_number": "DL12345678",
  "license_category": "Heavy",
  "license_expiry": "2030-12-31",
  "contact_number": "9876543210",
  "email": "john@example.com",
  "address": "Mumbai",
  "date_of_birth": "1990-01-01",
  "joining_date": "2025-01-01",
  "safety_score": 95,
  "status": "available"
}
```

Update

PUT /api/drivers/{id}

Delete

DELETE /api/drivers/{id}

Suspend

Suspend

```
POST /api/drivers/{id}/suspend
```

Activate

```
POST /api/drivers/{id}/activate
```

8. Trips

List

```
GET /api/trips
```

Show

```
GET /api/trips/{id}
```

Create

```
POST /api/trips
```

Example

```
{
  "vehicle_id": 1,
  "driver_id": 1,
  "source": "Mumbai",
  "destination": "Pune",
  "cargo_weight": 5000,
  "planned_distance": 160,
  "starting_odometer": 50000,
  "remarks": "Morning Delivery"
```

```
}
```

Update

```
PUT /api/trips/{id}
```

Delete

```
DELETE /api/trips/{id}
```

Dispatch

```
POST /api/trips/{id}/dispatch
```

Complete

```
POST /api/trips/{id}/complete
```

Example

```
{
  "actual_distance": 162,
  "fuel_consumed": 22,
  "ending_odometer": 50162,
  "remarks": "Completed Successfully"
}
```

Cancel

```
POST /api/trips/{id}/cancel
```

Maintenance

List

GET /api/maintenance

Show

GET /api/maintenance/{id}

Create

POST /api/maintenance

```
{
  "vehicle_id": 1,
  "maintenance_type": "preventive",
  "title": "Oil Change",
  "description": "Routine service",
  "cost": 5000,
  "start_date": "2026-07-12",
  "status": "scheduled",
  "remarks": "Routine"
}
```

Update

PUT /api/maintenance/{id}

Delete

DELETE /api/maintenance/{id}

Start

POST /api/maintenance/{id}/start

Complete

POST /api/maintenance/{id}/complete

Cancel

POST /api/maintenance/{id}/cancel

Fuel Logs

List

GET /api/fuel-logs

Show

GET /api/fuel-logs/{id}

Create

POST /api/fuel-logs

```
{
  "vehicle_id": 1,
  "trip_id": 1,
  "quantity": 45,
  "price_per_liter": 95,
  "odometer_reading": 50100,
  "fuel_date": "2026-07-12 10:00:00",
  "remarks": "IOC Pump"
}
```

Update

```
PUT /api/fuel-logs/{id}
```

Delete

```
DELETE /api/fuel-logs/{id}
```

11. Expenses

List

```
GET /api/expenses
```

Show

```
GET /api/expenses/{id}
```

Create

POST /api/expenses

```
{
  "vehicle_id": 1,
  "trip_id": 1,
  "expense_type": "toll",
  "title": "Expressway Toll",
  "amount": 450,
  "expense_date": "2026-07-12",
  "paid_by": "Driver",
  "payment_method": "cash",
  "receipt_number": "TOLL123",
  "remarks": "Mumbai Pune"
}
```

Update

PUT /api/expenses/{id}

Delete

DELETE /api/expenses/{id}

Recommended Postman Workflow

1. GET /health
2. POST /login (copy the Bearer token)
3. GET /me
4. GET /dashboard
5. Create Vehicle
6. Create Driver
7. Create Trip
8. Dispatch Trip
9. Create Fuel Log
10. Create Expense
11. Create Trip

- 11. **Complete Trip**
- 12. **Create Maintenance**
- 13. **Start Maintenance**
- 14. ****Complete Maintenance`**
- 15. **Test Reports**

This sequence follows your business rules and avoids validation errors caused by missing related records or invalid state transitions.