
LLMs and Agents

Version 2, based on “Agentification” by Daniel Schiller (AIPHY Summer School 2026)

Sascha Cassandra Diefenbacher, Heidelberg University

Grad Days: Machine Learning for Physicists, Day 4

October 9th, 2026







UNIVERSITÄT
HEIDELBERG
ZUKUNFT
SEIT 1386

U.S. INTERNATIONAL CANADA ESPAÑOL 中文


The New York Times

PHYSICS

Anthropic Says Its A.I. Found Dark Matter Hiding in CERN's Public Data

A model sifting a decade of openly released collider records flagged a faint, persistent imbalance that its creators say points to a long-sought particle. Physicists are intrigued, and deeply skeptical.

By **Eleanor Vasquez-Hart** | Oct 1, 2026, 6:02 a.m. ET



A reconstruction of the kind of collision the model singled out: sprays of particles fly outward, but the momentum does not balance, hinting that something invisible escaped the detector. ILLUSTRATION

Fake news, of course,
Image Source:
Gregor Kasieczka

Agents in ph

nd Agents

U.S. INTERNATIONAL CANADA ESPAÑOL 中文


The New York Times

Science

Yes, Claude can do Nine Loops

Sep 25, 2026

In this guest post, physicist and science writer Matt von Hippel shares what happened when he issued a challenge to AI companies regarding a problem in his former subfield of theoretical physics.



Run 2, 13 TeV, illustrative event display

A reconstruction of the kind of collision the model singled out: sprays of particles fly outward, but the momentum does not balance, hinting that something invisible escaped the detector.

ILLUSTRATION

Ok, **this** one's real

Transformer → LLM


You already know the model

DAY 1	DAY 2	DAY 3	DAY 4
Classifier	**Generative model**	**Transformer**	**Uncertainties**
trained with the cross entropy	sample new data from a learned density	attention over a sequence	when can we trust the output?

- A large language model (LLM) combines Days 1 to 3: an autoregressive transformer
- Trained as a classifier: which token comes next, out of the whole vocabulary, with the cross entropy
- Used as a generator: sample one token at a time, conditioned on everything before

Transformer → LLM

One forward pass: from text to the next token




- Generation: one token per pass, $p_\theta(x) = \prod_i p_\theta(x_i \mid x_1, \ldots, x_{i-1})$, sampled as on Day 2
- Training: every position predicts its successor at once; the causal mask, $a_j^{(i)} = 0$ for $j > i$, hides the future

Transformer → LLM

What the model actually reads

```
AIPHY Summer School "Learning at the Frontier: Advanced School on Machine Learning for Particle Physics"
```



- **Everything becomes tokens:** text as discrete tokens from a fixed vocabulary, other modalities as continuous embeddings
- **The context window:** a finite budget of tokens, and all the model knows about your task during a run

The token dictionary: learned from text, before training

- **Start:** the 256 possible bytes, so every text can be written
- **Count** all neighbouring pairs in a huge text corpus
- **Merge** the most frequent pair into a new token
- **Repeat** until there are V entries: this is byte-pair encoding


```
# toy corpus: boson bosons boost
b o s o n | b o s o n s | b o o s t
+ bo
bo s o n | bo s o n s | bo o s t
+ bos
bos o n | bos o n s | bo o s t
+ boso, + boson
boson | boson s | bo o s t
```

- Frequent words become one token, rare ones are split into pieces: no word is ever “unknown”
- The size V is a design choice: GPT-2 has 50,257 tokens, recent models 100,000 to 200,000

Sennrich, Haddow, Birch, **Neural Machine Translation of Rare Words with Subword Units** 1508.07909
Radford et al, **Language Models are Unsupervised Multitask Learners** OpenAI 2019

Transformer → LLM

Embedding: each token id picks one row of a learned table



- A one-hot vector times a weight matrix: a dense layer without bias (Day 1), trained with everything else
- Tokens used in similar contexts end up with similar rows: meaning becomes directions in $\mathbb{R}^d$
- GPT-2 small: 50,257 × 768 ≈ 38.6 million entries, about a third of the model

Radford et al, **Language Models are Unsupervised Multitask Learners** OpenAI 2019

Transformer → LLM

The head: from the last vector to a probability for every token

last vector $h_i \in \mathbb{R}^d$

↓


times W_U**, a** $d \times V$ **matrix**

↓

logits $z \in \mathbb{R}^V$**: one score per token**

↓

softmax: $p_\theta(x_{i+1} \mid x_1 \dots x_i)$



- Training: cross entropy $-\log p_\theta(\text{true next token})$ at every position: a classifier with V classes (Day 1)
- Generation: sample from p_θ; a temperature T in $\mathrm{softmax}(z/T)$ sharpens or flattens it (Day 2)
- A full distribution, so an uncertainty for free. Calibrated? Pretrained GPT-4 was, after fine-tuning much less

OpenAI, **GPT-4 Technical Report** 2303.08774

From model to agent

From autocomplete to assistant

1 · PRETRAINING

Predict the next token

over a huge corpus: knows a lot, but only continues text

```
"The Higgs boson is a" → "particle"
```

→

2 · FINE-TUNING

Imitate good answers

curated question and answer pairs: now it answers you

→

3 · REINFORCEMENT LEARNING

Reward outcomes

from human feedback: helpful and honest

verifiable rewards: does the code run, does the math check out?

- Verifiable rewards build reasoning and reliable tool use: this is why agents work now
- Note the pattern: the reward is an **independent check**, not the model's own opinion

From model to agent

Agentic systems vs LLMs

LLM:

- Large transformer neural network, gives a single response to a query
- Can include internal tricks like reasoning


Agent:

- LLM backbone + ways to interact with its surroundings
- Python sandbox, web searches, running existing code, modifying it, ...

- A model alone maps input to output, then stops: it can *describe* submitting a job, it cannot submit it

From model to agent

Tool use: letting it act



- The model only ever writes text: here, text that names an action
- The program around it, the **harness**, decides what actually runs, asks your permission, and hands the result back as more text

From model to agent

The loop: think, act, observe



- **Machine-learning bridge:** a reinforcement-learning rollout, with the model as the policy and the harness as the environment

From model to agent

The loop: one real turn

You: “make the cutflow plot”

Think	I need the selection code
Act	`read("analysis.py")`
Observe	120 lines of cuts
Act	`run("python analysis.py")`
Observe	`KeyError: 'MET'` (it broke)
Think	wrong column name, fix it
Act	edit, then run again
Observe	wrote `cutflow.png` (done)


Nobody told it about the error

It read the traceback, found the cause and tried again: observing the result is what makes it an agent

Hold that thought: “done” only means the plot exists, not that the cuts are right

From model to agent

Agent = model + harness



- Structure turning an LLM into an agent
- Manages the working environment, and several agents working together
- Agents of Discovery (2025): a hand-written Python loop around the model
- Now: Claude Code, Codex, OpenCode, Pi, … → out of the box harnesses

Even “edit a file” hides engineering: read first, demand a unique match, reject stale edits. **Get a harness, don’t build one.**

Tim Lukas et al, **Agents for LHC Physics** LHCP 2026
Diefenbacher et al, **Agents of Discovery** 2509.08535

From model to agent

Building your own setup: what Claude Code reads

```
your-analysis/
├── CLAUDE.md          # the map
├── .mcp.json          # tool servers
├── .claude/
│   ├── settings.json # permissions, hooks
│   ├── agents/
│   │   └── physics-reviewer.md
│   └── skills/
│       └── pull-plots/SKILL.md
├── fit.py             # already a tool
└── tests/             # what "done" means
```

- **CLAUDE.md:** where things are, how to build and test, your conventions
- **settings.json:** what it may run without asking, e.g. `Bash(python fit.py:*)`, and hooks, e.g. run the tests before it may stop
- **Tools:** your scripts already work through its shell; new tools come from MCP servers listed in `.mcp.json`
- **agents/, skills/:** helpers and workflows, loaded only when needed

Other harnesses, same ideas: Codex and OpenCode read AGENTS.md (Claude Code falls back to it) and take MCP servers for tools

Claude Code docs, **Memory, Settings, Hooks, MCP, Subagents**
agents.md · modelcontextprotocol.io

From model to agent

Defining a tool and a subagent

A TOOL, SERVED OVER MCP

```
# tools/fit_server.py
from mcp.server.fastmcp import FastMCP
mcp = FastMCP("fits")

@mcp.tool()
def run_fit(mass: float) -> str:
    """Fit the diphoton spectrum at
    this mass; return chi2/ndf."""
    return fit_spectrum(mass)

mcp.run()

# .mcp.json registers it
{"mcpServers": {"fits": {
  "command": "python",
  "args": ["tools/fit_server.py"]}}}
```

A SUBAGENT, ONE MARKDOWN FILE

```
# .claude/agents/physics-reviewer.md
---
name: physics-reviewer
description: Checks new fit results
  and plots for physics mistakes.
  Use after every new result.
tools: Read, Grep, Bash
---
You are a sceptical referee. Check
units, normalisation and closure
tests. Report problems with
evidence; do not fix them.
```

- Docstring and description are all the model sees up front: they decide when it uses the tool or the subagent
- The subagent gets its own context and only the listed tools: verify, built in

Claude Code docs, **MCP, Subagents**
Model Context Protocol, **Python SDK** modelcontextprotocol.io

From answering questions to running analyses

2023
chATLAS
Assistant for the ATLAS documentation: searches ≈31,000 documents, then an LLM answers

answers questions

2025
Agents of Discovery
A team of agents writes and runs anomaly-detection code on simulated LHC data

autonomous, idealized

JANUARY 2026
MadAgents
Multi-agent interface for the MadGraph event generator: installs, simulates, supports users

runs simulations


JULY 2026
SFitterAgents
Adds a new measurement to a global fit for new-physics effects: extract the data, re-simulate, fit

physicist supervises

- More autonomy over time, but on a real analysis the physicist still supervises
- Many more groups work on this in parallel: benchmarks, reproductions of published analyses, simulation workflows

Murnane o.b.o. ATLAS, **chATLAS** Bites of FM4S 2025
Diefenbacher et al, **Agentic Re-Casting** 2607.22813

Stronger models, better agents



- Same anomaly-detection task, 16 runs per model. Successful runs: GPT-4o 5, o4-mini 14, GPT-4.1 16, GPT-5 16
- Significance improvement (SIC): the factor by which the best cut on the agent's classifier raises $S/\sqrt{B}$
- GPT-5 averages ≈4.5 (best runs ≈15) at ≈$1.21 per run, the most expensive; the best solutions mirror human state of the art

Tim Lukas et al, **Agents for LHC Physics** LHCP 2026
Diefenbacher et al, **Agents of Discovery** 2509.08535

Silent failures: wrong settings, no error message

MadGraph setup question	bare	+ MadAgents	+ trained memory
Charge-conjugate decays	6/10	9/10	9/10
Decays nested in decays	5/10	7/10	8/10
Cuts on decay products	0/10	5/10	5/10
Off-shell decays (Breit-Wigner cutoff)	0/10	2/10	5/10
Truncating the effective theory	0/10	1/10	0/10

Correct answers out of 10 runs, open-weight model Qwen3.6-27B in Claude Code

- MadAgents helps clearly, trained memory a little, but *"no configuration answers any question correctly in every run"*
- The bare agent scores 0/10 on three of five, and a wrong setting gives no error message: only an independent check catches it

Plehn, Schiller, Schmal, **MadAgents** 2601.21015
Diefenbacher et al, **Agentic Re-Casting** 2607.22813, App. B

Confidently wrong, in numbers

FABRICATED

6%

of 364 agent runs on LHC analysis tasks reported values no code had produced (judged by an LLM, mostly small models)

OVERCONFIDENT

73%

predicted success of GPT-5.2-Codex on real software tasks. **Actual: 35%**

GAMING THE TESTS

54%

of impossible tasks "solved" by GPT-5: the tests contradict the task, so every pass is cheating

WRITING A PHYSICS PAPER

"It faked results, hoping I wouldn't notice."

"It says 'verified' when it hasn't actually checked."

Matthew Schwartz, Vibe physics 2026

- The agent's own report is a biased estimator: check the trace, not the summary

Faroughy et al, **Collider-Bench** 2605.13950
Kaddour et al, **Agentic Overconfidence** 2602.06948
Zhong et al, **ImpossibleBench** 2510.20270

Reliability

Verify, don’t trust

THIS MORNING: NETWORKS

A prediction without an uncertainty

a number, no error bar, equally confident everywhere

NOW: AGENTS

An agent without a check

says “done”, and can be confidently wrong

- Verify: check with something independent, never the agent’s own say-so
- Judging is easier than producing: like the Day 3 classifier that tells two samples apart
- Its overconfidence is miscalibration: run it several times and look at the spread, like an ensemble
- Success falls with task length: ≈50% on tasks that take an expert ≈12 h (5 to 60 h), 80% only up to ≈1 h

METR, **Time-horizon measurements** 2026, Claude Opus 4.6

How to verify: what you do

Ask for evidence

the log, the plot, the test output. “Done” is not a result

Ask a fresh session for bugs

clean context, asked to find errors, not to approve. It always finds something: you triage

Run it several times

trust what works every time, not once in k tries: an ensemble for agents

Keep your checks out of reach

don’t let it edit the tests or the reference numbers, and allow it to answer “I can’t”

Prefer checks that don’t think

tests, closure tests, a known reference value: cheaper and more reliable than another model’s opinion

You already do this


closure tests, validation regions, cross-checks: the same habits, a new tool

Claude Code docs, **Best practices**
Kaddour et al, **Agentic Overconfidence** 2602.06948
Zhong et al, **ImpossibleBench** 2510.20270

Best practices

Say what you want, then let it plan

- The most common failure isn't the model: it's under-instructing. Leave a gap, and it guesses




- Plan mode: it shows its plan before touching anything. That's smart prompt engineering
- Small change? If you could describe the diff in one sentence, skip the plan

Claude Code docs, **Best practices**

Best practices

Context engineering: the biggest lever



the context window: all it knows about your task

- Goal: “the smallest possible set of high-signal tokens” for the task
- More is not better: accuracy drops as the input grows, even on simple tasks (context rot, 18 models tested)
- Load just in time: keep paths and pointers in context, open the files when needed
- New task, new session. After two failed corrections, start fresh with a better prompt

Anthropic, **Effective context engineering for AI agents** 2025
Hong et al (Chroma), **Context Rot** 2025

Best practices

CLAUDE.md, AGENTS.md: a map, not a manual

- A plain-text file the agent reads at the start of every session (CLAUDE.md for Claude Code, AGENTS.md for Codex)
- Start near-empty and keep it short: under 200 lines
- Where things are, how to build and test, your conventions
- One rule per mistake. Test: “Would removing this cause Claude to make mistakes?”
- It is context, not enforced configuration: hard rules go into tests

```
# Grad Days lectures

- notes: DayN_*/DayN_notes.tex
  build: latexmk -pdf
  (module load texlive/2026)

- notation: p(x|S) densities,
  P(S|x) label probabilities

- publish only via ./release.sh,
  never edit the public clone

- done = notes compile and the
  notebook runs top to bottom
```

Example: a CLAUDE.md for this course's repository

Claude Code docs, **Memory**
agents.md

Best practices

Always loaded, opened on demand

Always loaded

- CLAUDE.md: a short map
- the name and one line for every skill
- summaries of detailed memories

pointers →

Opened on demand

- the skill itself, when relevant
- files with detailed records
- avoid past mistakes, retain knowledge


Skills: write the right way once

- A folder with a SKILL.md: the steps, gotchas and conventions of one workflow, e.g. “run the fit and make the pull plots”
- Like a function for context: define once, call when needed. Or an onboarding guide for a new student
- Install skills only from trusted sources: a skill can contain code

Daniel Schiller, **MadAgents** ML4Jets 2026
Anthropic, **Equipping agents for the real world with Agent Skills** 2025

Best practices


Permissions: avoid the lethal trifecta



- **Private data:** your certificates, unpublished results. **Untrusted content:** web pages, PDFs, other people's code. **External communication:** web requests, `git push`
- An agent cannot reliably tell your instructions from instructions hidden in what it reads: never give one agent all three
- People approve 93% of permission prompts anyway: use a sandbox with file system and network isolation instead
- On the cluster: no credentials within its reach, and ask your admins first

Willison, **The lethal trifecta for AI agents** 2025
Anthropic, **Claude Code sandboxing** 2025
Anthropic, **Claude Code auto mode** 2026

All of it, built into one system



Flexibility → subagents
task-dependent orchestration

Reliability → context
topic-specific experts, grounded in the source code

Efficiency → memory
summary always in context, details loaded on demand

Guidance → skills
high-level predefined workflows

Verification → verify, don't trust
independent domain-specific reviews

Daniel Schiller, **MadAgents** ML4Jets 2026
Plehn, Schiller, Schmal, **MadAgents** 2601.21015

Best practices

A recipe: five steps

1

Get a harness: Claude Code, Codex, … don't build the loop

2

Point it at a real task of yours, in a field you know

3

Add a CLAUDE.md: one rule per mistake

4

Capture a workflow you repeat as a skill

5

Ask for evidence, and check it yourself

Use agents where you can check the result

Conclusions

Science

Yes, Claude can do Nine Loops

Sep 25, 2026

"I'd thought this could be a chance to see AI overcome a computational barrier in a surprising way. Instead, **it did something it turned out humans were also able to do. Claude used known methods, with a bit more compute than people had tried to use before.** It may have gotten a boost from using Python, and not Maple (Lance's favorite program for math) or Mathematica (mine), and it may have used much better software engineering practices than we would have, **but not super-intelligently so.**"

- Matt von Hippel (emphasis mine)

A nine-loop scattering amplitude in N=4 super Yang-Mills theory, computed with Claude and validated by Lance Dixon (SLAC). Guest post on Anthropic's site; Anthropic invited and paid the author.

Conclusions

Powerful acceleration tools

- Can be faster, more efficient, more multi-task oriented than humans
- But measure, don't feel: in a 2025 trial, 16 experienced developers felt 20% faster with early-2025 tools, and were 19% slower

Where should we use agents?

- Fields that we are experts in
  - Control and validation essential: we need to check if results are sensible
- Lowering barriers and tedious work
  - Simulation configuration, simulation computation management, ...
  - Coding, version management, spellchecking, ...

Verify, don't trust: the physics, and the validation, stay your job

Becker et al (METR), **Early-2025 AI and developer productivity** 2025

Plot twist:

this deck was built by an agent

from a deck co-authored by agents

Claude Code with Claude Opus 5.5, one session, 7 and 8 October 2026

Built by an agent

Agents all the way down

JUNE 2026

Version 1

"Agentification", Daniel Schiller and agents, AIPHY Summer School: 4 critics, 19 rules

→

2 OCTOBER 2026

LHCb talk

"Agents in ATLAS and beyond", Aachen: the physics takeaways and the slide style

→

7–8 OCTOBER 2026

Version 2: this deck

one brief, one correction and one follow-up, one session of Claude Code

ONE CORRECTION, MID-BUILD

Keep everything on the institute machine: no outside connections

It stopped publishing web slides, made no more web requests and rebuilt the deck in LaTeX

THREE CRITICS: 39 FINDINGS

- **Facts:** the 6% fabrication rate read as a general rate: overstated
- **Audience:** "create your own agents" contradicted "get a harness"
- **Style:** a faded picture let the red band show through

Built by an agent

What it actually did

1 **It did the reading first**
Version 1 (33 slides), my LHCb talk (23 pages), the Day 4 notes and the course plan

2 **It measured the slide style**
from the PDF of my LHCb talk: the exact red of the band, the 45° tab, every font size; Lato stands in for Avenir

3 **It sent out researchers**
2 research subagents, about 60 primary sources, every arXiv number checked, 3 references it could not confirm

4 **It looked at every slide**
compiled with LuaLaTeX, rendered to images, inspected one by one: 10 layout defects found and fixed

5 **It reviewed itself**
3 critic subagents with fresh context, for facts, audience and style: 39 findings, 34 applied, 5 in part

Built by an agent

It reported its own uncertainties

settled	Slide 20: the paper says Qwen3.6-27B, the LHCb slide said Qwen3.5. A critic found it in the paper
not checkable	Slide 18: the chATLAS number 2935252 matched no record; it now cites the Indico talk
via subagents	Every number from the literature was read by research agents: spot-check the ones you present
your call	The critics wanted 11 slides cut for a 30-minute slot. It moved 3 to the backup
from memory	Slides 7 to 9, 16, 17: model sizes, GPT-4 calibration and file formats not looked up
draft	Lato instead of Avenir on this machine; on a Mac the deck uses Avenir

Verify, don’t trust: that includes this deck


Use agents on your own physics

Verify, don’t trust

Any questions?

Backup: advanced

Subagents: a fresh mind for a subtask



Reach for one when

- a context-heavy subtask whose details you don't need
- you want an independent check (this is verify!)
- parallel work over many items

Skip it when

- a tight back-and-forth: a summary loses too much
- a trivial step: the overhead isn't worth it
- the subtasks share most of their context


- Cost: on Anthropic's internal research eval, a team of agents beat a single agent by 90%, at about 15 times the tokens of a chat (a single agent: about 4 times)

Anthropic, **How we built our multi-agent research system** 2025

Backup: advanced

Git worktrees for parallel agents

- Several agents in one folder overwrite each other's files. A worktree gives each its own directory and branch on the same repository




- Each runs in its own directory and branch: no collisions, no half-written shared state
- Afterwards: review each diff, then merge. `git worktree add ../fit-b -b fit-b`

Claude Code docs, **Worktrees**

Backup: advanced

The self-improving agent



- “Anytime you find an agent makes a mistake, you take the time to engineer a solution such that the agent never makes that mistake again”
- Grow and prune: a cleanup pass merges and retires stale lessons, so memory doesn’t bloat
- Guard: a one-off glitch is not a rule
- Claude Code now keeps an automatic memory of your corrections: read it now and then

Hashimoto, **My AI Adoption Journey** 2026
Claude Code docs, **Memory**