



03 — Component & Page Inventory

every reusable component and every routed page that exists today in the NexFlow web app (``artifacts/nexflow/src/``) and the mobile app (``artifacts/mobile/``). The doc is split into two parts:





Contents

03 — Component & Page Inventory

Part A — Component inventory

A.1 Web — bespoke components

src/components/layout/TopBar.tsx (384 lines)

src/components/layout/Sidebar.tsx

src/components/layout/LivingMesh.tsx

src/components/layout/NexFlowLogo.tsx

src/components/VoiceCallModal.tsx (544 lines)

src/components/ui/*.tsx

A.2 Web — hooks

A.3 Mobile — artifacts/mobile/components/

A.4 Other artifacts (sandbox / video)

Part B — Pages by TopBar section

B.1 Home

B.2 Sales

B.3 Call Center

B.4 Marketing

B.5 Automation

B.6 AI Hub

B.7 Insights

B.8 Data

B.9 Account Settings hub

B.10 Mobile pages (expo-router)

App / routing (Expo Router)

B.11 Cross-section: AI surfaces



Document scope: every reusable component and every routed page that exists today in the NexFlow web app (`artifacts/nexflow/src/`) and the mobile app (`artifacts/mobile/`). The doc is split into two parts:

- **Part A — Component inventory.** Every file under `artifacts/nexflow/src/components/` and `artifacts/mobile/components/` , with key props, behavior, and primary callers. This is the canonical "component tree" view.
- **Part B — Pages by TopBar section.** Every routed page in `artifacts/nexflow/src/pages/` , grouped by the eight TopBar mega-dropdown sections (matching the actual `NAV_GROUPS` array in `src/components/layout/TopBar.tsx`). Pages are listed here because each page is itself a top-level component, but the bespoke building blocks they use are catalogued in Part A.

The web app uses `shadcn/ui` (Radix primitives + Tailwind) plus a small set of bespoke layout / brand components. The mobile app uses Expo + React Native with hand-rolled UI primitives (no shadcn there). Pages are routed via `wouter` on web and `expo-router` on mobile.

Part A — Component inventory

■ A.1 Web — bespoke components

`src/components/layout/TopBar.tsx` (384 lines)

Sticky glassmorphism header. The single source of truth for navigation: the `NAV_GROUPS` array at the top of the file declares the eight mega-dropdowns (`home` , `sales` , `call-center` , `marketing` , `automation` , `ai-hub` , `insights` , `data`) and every link inside each. Each group renders as a click-triggered overlay with one tile per route; tiles include an icon (lucide-react), a label, and a one-line `desc` .

- **Props:** `{ dark: boolean; onDark: (v: boolean) => void }` — receives the light/dark mode flag from `App.tsx` and the toggle handler.
- **A11y:** every trigger button has `aria-haspopup="true"` , `aria-expanded` , `aria-controls={panelId}` ; every panel has `role="menu"` and labelled tile buttons.
- **Dismissal:** outside click (mousedown listener), route change (`useLocation` from `wouter`), Escape key, and clicking a tile.



- **Right-hand affordances:** global search input slot, notifications bell driven by `useNotifications()` from `src/hooks/useApi.ts` (badge with unread count), dark-mode toggle, avatar dropdown linking to `/account-settings` and a sign-out item.
- **Mobile:** below `lg` breakpoint the header collapses to a burger that opens a full-screen overlay listing every group + every link.
- **Imported by:** `src/App.tsx` (always, above the routed page).

`src/components/layout/Sidebar.tsx`

Legacy left-rail nav, kept in the repo as a fallback for narrow drawer scenarios but **not mounted anywhere in the current `App.tsx`**. Safe to delete once the responsive design has been signed off; left in for now to preserve the option of a side-drawer mode.

`src/components/layout/LivingMesh.tsx`

The brand background. 10 absolute-positioned blurred radial gradient nodes in the chameleon palette (Lavender, Rose-Mauve, Seafoam, Sand, Mist, Olive). Each node has its own animation duration in the 22–34 second range, deliberately coprime so the composition never visually loops within a single user session. Mounted once at app root with `z-[-1]` so all UI floats above it.

- **Props:** none.
- **Imported by:** `src/App.tsx`.

`src/components/layout/NexFlowLogo.tsx`

Two named exports:

- `NexFlowLogo({ size?: number })` — the diamond mark only. Default size `36`. Renders inline SVG with the chameleon stroke gradient.
- `NexFlowWordmark({ className?: string })` — the full lockup (mark + "NexFlow" wordmark + tagline `ORCHESTRATING SUPREME MARKET CLARITY`). Fixed wordmark width of 160 px in the SVG.

Imported by: `TopBar`, the auth shell, error boundary, and any "branded" page header. The mobile app uses its own hand-rolled equivalent in `artifacts/mobile/app/_layout.tsx`.

`src/components/VoiceCallModal.tsx` (544 lines)

Full-screen "live call" overlay. Used from the call center, contact profile, and power-dialer flows.

- **Props:**
`{ contact: { id, first_name?, last_name?, title?, company_name? }, onClose: () => void, onCallSaved?: (callId: string) => void }`.



- **Speech pipeline (browser-side):** `window.SpeechRecognition` || `window.webkitSpeechRecognition` captures each user utterance; `window.speechSynthesis.speak(new SpeechSynthesisUtterance(text))` speaks the AI reply. There is no PSTN, no Twilio, and no server-side Whisper involved — see `docs/02-tech-stack.md` §7 for the full clarification.
- **AI round-trip:** every captured utterance is appended to a local `messages: Message[]` array and POSTed to `POST /api/calls/voice-response`, which returns `{ reply: string }`. The system prompt branches on `language === "ar"` to produce a Gulf-Arabic reply when the contact is Arabic-language.
- **Persistence:** the full transcript is saved to the `calls` table on hangup via `apiFetch("/api/calls/log")`.
- **UI:** mic on/off, end-call, live transcript pane, AI assistant suggestion column, post-call scorecard (calls `POST /api/calls/scorecard`).

`src/components/ui/*.tsx`

A complete shadcn/ui install of Radix-based primitives. Each file is a thin wrapper that adds Tailwind classes and the chameleon design tokens.

Files present (54 total):

`accordion.tsx`, `alert-dialog.tsx`, `alert.tsx`, `aspect-ratio.tsx`, `avatar.tsx`, `badge.tsx`, `breadcrumb.tsx`, `button-group.tsx`, `button.tsx`, `calendar.tsx`, `card.tsx`, `carousel.tsx`, `chart.tsx`, `checkbox.tsx`, `collapsible.tsx`, `command.tsx`, `context-menu.tsx`, `dialog.tsx`, `drawer.tsx`, `dropdown-menu.tsx`, `empty.tsx`, `field.tsx`, `form.tsx`, `hover-card.tsx`, `input-group.tsx`, `input-otp.tsx`, `input.tsx`, `item.tsx`, `kbd.tsx`, `label.tsx`, `menubar.tsx`, `navigation-menu.tsx`, `pagination.tsx`, `popover.tsx`, `progress.tsx`, `radio-group.tsx`, `resizable.tsx`, `scroll-area.tsx`, `select.tsx`, `separator.tsx`, `sheet.tsx`, `sidebar.tsx`, `skeleton.tsx`, `slider.tsx`, `sonner.tsx`, `spinner.tsx`, `switch.tsx`, `table.tsx`, `tabs.tsx`, `textarea.tsx`, `toast.tsx`, `toaster.tsx`, `toggle-group.tsx`, `toggle.tsx`, `tooltip.tsx`.

Most-used in the codebase: `Card` / `CardHeader` / `CardContent`, `Button`, `Input`, `Select`, `Tabs`, `Dialog`, `DropdownMenu`, `Badge`, `Tooltip`. Variants are wired via `class-variance-authority` and the chameleon CSS variables (`--nf-primary`, `--nf-secondary`, etc. — see `docs/01-brand-palette-motion.md` §2).

■ A.2 Web — hooks

`src/hooks/`:

- `useApi.ts` — wraps the generated hooks from `@workspace/api-client-react` (e.g. `useNotifications`, `useContacts`, `useDeals`, `useCompanies`, `useDealsForUser`). Adds the in-app conventions: toast-on-error, query invalidation on mutations, and the `apiFetch(path, init)` escape hatch for calls that aren't yet in the OpenAPI spec.



■ A.3 Mobile — `artifacts/mobile/components/`

The mobile app (Expo SDK 54, React Native, expo-router) has its own minimal component set — no shadcn, no Radix.



FILE	LINES	PURPOSE	NOTABLE PROPS
<code>ErrorBoundary.tsx</code>	54	Top-level React error boundary that swaps the tree for <code>ErrorFallback</code> on crash. Reports the error via <code>console.error</code> (mobile is allowed <code>console.*</code> ; the server is not).	<code>{ children: ReactNode }</code>
<code>ErrorFallback.tsx</code>	278	The user-visible crash screen. Branded with the chameleon gradient, includes a "Try again" CTA (<code>onReset</code>), a copy-to-clipboard "Copy diagnostic" button, and a NexFlow lockup.	<code>{ error: Error; resetError: () => void }</code>
<code>KeyboardAwareScrollViewCompat.tsx</code>	29	Cross-platform compatibility shim around <code>react-native-keyboard-aware-scroll-view</code> . Avoids iOS-vs-Android keyboard avoidance regressions on form-heavy screens like the call-log composer.	accepts standard <code>ScrollView</code> props
<code>ui/Card.tsx</code>	34	Base card surface with the chameleon glass background and rounded corners. Used as the wrapper for every list item, every detail header.	<code>{ children, style? }</code>
<code>ui/Avatar.tsx</code>	21	Round avatar with initials fallback.	<code>{ name?: string; uri?: string; size?: number }</code>
<code>ui/Badge.tsx</code>	28	Pill-shaped status indicator with palette variants (<code>primary</code> , <code>secondary</code> , <code>seafoam</code> , <code>sand</code> , <code>mist</code> , <code>olive</code>).	<code>{ variant?, children }</code>
<code>ui/StatTile.tsx</code>	35	KPI tile with a label, a large value, and a delta chip. Used on the mobile dashboard / briefing screen.	<code>{ label, value, delta?, variant? }</code>



■ A.4 Other artifacts (sandbox / video)

For completeness — not used by the production CRM:

- `artifacts/mockup-sandbox/src/components/ui/*` — a separate, smaller shadow copy used by the design canvas. Independent of the nexflow web app.
 - `artifacts/marketing-demo-video/src/components/video/` — `VideoTemplate.tsx`, `VideoWithControls.tsx`, `ReplitLoadingScene.tsx`, `ScreenshotFrame.tsx` — components specific to the 90-second marketing demo video artifact. Not reusable inside the CRM.
-



Part B — Pages by TopBar section

The eight section headings below correspond exactly to the eight entries in the `NAV_GROUPS` array at the top of `artifacts/nexflow/src/components/layout/TopBar.tsx`. Each row is a routed page (a top-level component that lives in `src/pages/`).

B.1 Home

Landing & always-on AI surfaces. TopBar paths: `/`, `/insights`, `/assistant`.

PAGE / COMPONENT	PATH	WHAT IT DOES
Command Center (<code>/</code>)	<code>src/pages/briefing.tsx</code>	Daily briefing: morning agenda, top deals to push today, AI-flagged risks, weather-style summary of the pipeline. Hero card uses the chameleon gradient.
Daily Insights (<code>/insights</code>)	<code>src/pages/insights.tsx</code>	Stream of AI-generated insight cards (<code>opportunity</code> , <code>warning</code> , <code>critical</code> per the <code>insightSeverityEnum</code>). Each card has accept / dismiss / "do it for me" actions.
AI Assistant (<code>/assistant</code>)	<code>src/pages/assistant.tsx</code>	Conversational chat. Suggestion chips for "Brief me", "Draft follow-ups", "Find at-risk deals". Bilingual (English / Arabic).
Dashboard (<code>/dashboard</code>)	<code>src/pages/dashboard.tsx</code>	The default dashboard payload from <code>/api/dashboard</code> . Tile widgets for pipeline value, this-week activities, top reps.

B.2 Sales

Pipeline + accounts. TopBar paths: `/funnel`, `/contacts`, `/companies`, `/accounts`, `/quotes`, `/forecasting`, `/business-cards`, `/health-scores`.



PAGE / COMPONENT	PATH	WHAT IT DOES
Pipeline & Deals (/funnel)	src/pages/funnel.tsx , supporting src/pages/ deals.tsx	Drag-and-drop kanban over dealStageEnum . Each card shows owner avatar, value, probability, days-in-stage. Spring-snappy reorders.
Contacts (/ contacts)	src/pages/ contacts.tsx	Virtualized table view with saved-view tabs, filter chips, bulk actions, "AI enrich" button.
Contact Profile (/contacts/:id)	src/pages/contact- profile.tsx	Header (avatar, lead score, status), 4 tabs (Overview, Activities, Deals, Notes), and the new PROPERTIES card (owner, lead stage, score, company link, title, tags, last engaged, created/updated).
Companies (/ companies)	src/pages/ companies.tsx + company-detail.tsx	Account-level table + drill-in. Pulls cached intelligence JSONB from the company row.
Account Hub (ABM) (/ accounts)	src/pages/ accounts.tsx	Account-based selling view — a target list with multi-stakeholder cards per account.
Quotes & CPQ (/quotes)	src/pages/quotes.tsx	Quote list, line-item editor, send-via-email action.
Quote-to-Cash (/quote-to- cash)	src/pages/quote-to- cash.tsx	The Marketing dropdown also exposes this; it bridges accepted quotes → invoice → payment provider stub (Mada / Tap / HyperPay / PayTabs).
Forecasting (/ forecasting)	src/pages/ forecasting.tsx	Pipeline + commit + best-case rollup with confidence chips.
Card Scanner (/ business-cards)	src/pages/business- cards.tsx	Camera / upload → OCR (server in routes/ business-cards.ts) → auto-create contact.
Health Scores (/health- scores)	src/pages/health- scores.tsx	Per-account health score with contributing signals. Reads from /api/health-scores .

■ B.3 Call Center

Voice + messaging hub. TopBar paths: /call-list , /calls , /power-dialer , /
conversation-intelligence , /voice-agents , /scripts , /email , /messages , /whatsapp .



PAGE / COMPONENT	PATH	WHAT IT DOES
Call Dashboard (/call-list)	src/pages/call-list.tsx	Live call activity, predictive conversion metrics, connection rates, AI post-call orchestrator toggles.
Calls & Transcripts (/calls)	src/pages/calls.tsx	Full call history; click-through reveals transcript, sentiment, AI insights, coaching notes.
Power Dialer (/power-dialer)	src/pages/power-dialer.tsx	AI-prioritized outbound queue. Auto-skips no-answers, surfaces best call time per contact.
Conversation Intelligence (/conversation-intelligence)	src/pages/conversation-intelligence.tsx	Coaching: keywords, talk-listen ratio, objection handling, AI-suggested follow-ups.
AI Voice Agent (/voice-agents)	src/pages/voice-agents.tsx	Configures AI agents that dial autonomously. Bilingual (English / Arabic).
Knowledge Base / Scripts (/scripts)	src/pages/scripts.tsx	Script library across scriptTypeEnum (cold_call, follow_up, demo, objection_handling, closing) and language (en/ar/both).
Email (/email)	src/pages/email.tsx	1-to-1 email composer hooked to Resend.
Messages (/messages)	src/pages/messages.tsx	Unified inbox across email / WhatsApp / SMS.
WhatsApp (/whatsapp)	src/pages/whatsapp.tsx	WhatsApp Business UI. Conversation thread + template picker.
VoiceCallModal	src/components/VoiceCallModal.tsx	Shared modal opened from any of the above.

B.4 Marketing

Campaigns + content + GCC localization. TopBar paths: /campaigns , /sequences , /marketing-assistant , /meetings , /templates , /audiences , /web-forms , /document-tracking , /quote-to-cash , /cultural-intelligence .



PAGE / COMPONENT	PATH	WHAT IT DOES
Campaigns (/ campaigns)	src/pages/campaigns.tsx	Campaign list across the campaignChannelEnum (email, whatsapp, sms, linkedin, voice).
Sequences (/ sequences)	src/pages/sequences.tsx	Multi-step automated cadences.
Marketing AI (/ marketing-assistant)	src/pages/marketing-assistant.tsx	Conversational assistant for campaigns. Generates copy, hero images, subject lines, GCC-localized variants.
Meetings (/meetings)	src/pages/meetings.tsx	Booked-meeting list.
Templates (/ templates)	src/pages/templates.tsx	Reusable email / message templates.
Audiences (/ audiences)	src/pages/audiences.tsx	Built segments for outreach.
Web Forms (/web-forms)	src/pages/web-forms.tsx	Lead-capture form builder + embed snippet.
Document Tracking (/document-tracking)	src/pages/document-tracking.tsx	Per-document open / scroll / forward analytics.
Cultural Intelligence (/cultural-intelligence)	src/pages/cultural-intelligence.tsx	GCC-specific cultural calendar, naming, dialect, payment-method, and Hijri-aware send-time guidance.

■ B.5 Automation

Build flows + auto-routing. TopBar paths: /workflows , /automation , /agents , /lead-routing , /activity-capture .



PAGE / COMPONENT	PATH	WHAT IT DOES
Workflow Builder (/ workflows)	src/pages/workflows.tsx	Visual node-and-edge builder. Trigger nodes from automationTriggerEnum (stage_change, activity_completed, signal_received, no_answer, form_submitted, score_threshold, schedule, campaign_open).
Automation Rules (/ automation)	src/pages/automation.tsx	If-this-then-that list view of the same triggers, simpler to author.
Agent Builder (/agents)	src/pages/agent-builder.tsx	Custom AI agent author — system prompt + variables + templates (Quote Wizard, Discovery Coach). "Improve with AI" rewrites the prompt. Each agent persists to ai_agents ; runs persist to ai_agent_runs .
Lead Routing (/lead-routing)	src/pages/lead-routing.tsx	Round-robin / weighted / territory-based assignment to reps.
Activity Capture (/ activity-capture)	src/pages/activity-capture.tsx	Auto-log emails & calls; toggles for which channels are captured.

B.6 AI Hub

AI-first surfaces beyond the always-on assistant. TopBar paths: /intelligence , /ai , /predictive , /sourcing , /lead-enrich , /signals , /playbooks .



PAGE / COMPONENT	PATH	WHAT IT DOES
Lead Intelligence (/ intelligence)	src/pages/intelligence.tsx	Cross-signal scoring + prioritization queue.
AI Workforce (/ai)	src/pages/ai.tsx	Catalog of pre-built AI workers (SDR, researcher, coach, redactor).
Predictive (/ predictive)	src/pages/predictive.tsx	Forecasts, churn risk, deal slip probability.
Enrichment (/ sourcing)	src/pages/sourcing.tsx	Bulk lead-source AI flow.
Quick Enrich Lead (/ lead-enrich)	src/pages/lead-enrich.tsx	Single-shot AI enrichment for one contact.
Signals (/signals)	src/pages/signals.tsx	Buying-intent feed. Reads <code>signals</code> table, color-coded by <code>signalTypeEnum</code> .
Sales Playbooks (/ playbooks)	src/pages/playbooks.tsx	Battle-tested plays per industry / vertical.
VoiceAgents (cross-listed)	src/pages/voice-agents.tsx	Also reachable from Call Center; the AI Hub view focuses on agent-team management.

B.7 Insights

Dashboards + reports. TopBar paths: `/dashboards`, `/reports`, `/analytics`, `/team`, `/attribution`, `/report-builder`.



PAGE / COMPONENT	PATH	WHAT IT DOES
Dashboards (/ dashboards)	src/pages/ dashboards.tsx + dashboard-detail.tsx	List + drill-in. Widgets are persisted to dashboard_widgets . AI Dashboard Generator from a natural-language prompt.
Reports (/reports)	src/pages/reports.tsx	Saved reports.
Analytics (/ analytics)	src/pages/analytics.tsx	Funnel + KPI deep-dive with time-series charts (Recharts).
Team Performance (/ team)	src/pages/team.tsx	Rep leaderboards. Activity volume + conversion + sentiment.
Attribution (/ attribution)	src/pages/ attribution.tsx	Multi-touch revenue attribution (first-touch, last-touch, U-shape, W-shape, custom).
Report Builder (/ report-builder)	src/pages/report-builder.tsx	Drag-and-drop report author.

B.8 Data

Records, segments, custom fields, migration. TopBar paths: /lists , /segments , /dedup , /migration , /account-settings/properties .

PAGE / COMPONENT	PATH	WHAT IT DOES
Lists (/lists)	src/pages/lists.tsx + list-detail.tsx	Static + dynamic lists. Static lists persist to static_lists + static_list_members .
Segments (/segments)	src/pages/ segments.tsx	Smart segments backed by saved filter queries.
Deduplication (/ dedup)	src/pages/dedup.tsx	Scanner + merge UI. Server in routes/ dedup.ts .
Migration (/ migration)	src/pages/ migration.tsx	CSV import / export wizard.
Properties (/account-settings/properties)	src/pages/ properties.tsx	Custom property registry across propertyObjectEnum and propertyTypeEnum .



■ B.9 Account Settings hub

Routes: `/account-settings` and `/account-settings/:section`. Single tabbed page (`src/pages/account-settings.tsx`) consolidating:

SECTION	PAGE MODULE
Settings	<code>settings.tsx</code>
Permissions	<code>permissions.tsx</code> (field-level matrix + approval rules)
Properties	<code>properties.tsx</code>
Trust Center	<code>trust-center.tsx</code>
Public Trust	<code>public-trust.tsx</code> (linked, not embedded)
Capabilities	<code>capabilities.tsx</code>
Migration	<code>migration.tsx</code>

Side-nav groups: ACCOUNT / DATA & FIELDS / SECURITY & TRUST / PLATFORM. Lazy-loaded. Invalid section keys redirect to `/account-settings/settings`.

■ B.10 Mobile pages (expo-router)

Source: `artifacts/mobile/`.



App / routing (Expo Router)

FILE	ROUTE	PURPOSE
<code>app/_layout.tsx</code>	root	Theme + providers (<code>@tanstack/react-query</code> , fonts).
<code>app/(tabs)/_layout.tsx</code>	tabs container	Bottom tab bar.
<code>app/(tabs)/index.tsx</code>	<code>/</code>	Dashboard tile feed.
<code>app/(tabs)/contacts.tsx</code>	<code>/contacts</code>	Contact list.
<code>app/(tabs)/calls.tsx</code>	<code>/calls</code>	Call history + log-call action.
<code>app/(tabs)/pipeline.tsx</code>	<code>/pipeline</code>	Mobile-friendly pipeline kanban.
<code>app/(tabs)/agents.tsx</code>	<code>/agents</code>	Manage AI agents on the go.
<code>app/contact/[id].tsx</code>	<code>/contact/:id</code>	Contact detail.
<code>app/sourcing.tsx</code>	<code>/sourcing</code>	Quick-enrich flow.
<code>app/notifications.tsx</code>	<code>/notifications</code>	Notification feed.
<code>app/+not-found.tsx</code>	404	Fallback.

The mobile app reuses the typed API client from `@workspace/api-client-react` so there's no duplicate request layer. For the per-file mobile component reference, see Part A.3 above.

■ B.11 Cross-section: AI surfaces

Components that render AI behavior live across the dropdowns; for clarity:

- **Always-on:** `assistant.tsx` (conversational), `briefing.tsx` (daily morning brief).
- **Author:** `agent-builder.tsx` (define agents), `marketing-assistant.tsx` (campaign copy + assets), `report-builder.tsx` (NL → report), AI Dashboard Generator inside `dashboards.tsx`.
- **Apply:** `intelligence.tsx`, `predictive.tsx`, `signals.tsx`, `lead-enrich.tsx`, `sourcing.tsx`, `playbooks.tsx`, `conversation-intelligence.tsx`, `voice-agents.tsx`.
- **Govern:** `redaction` (PII out of recordings; server in `routes/redaction.ts`), `permissions.tsx` (who sees AI-derived fields), `trust-center.tsx`.

All AI surfaces ultimately call `aiChat` / `aiJson` in `artifacts/api-server/src/lib/ai.ts`. See `docs/02-tech-stack.md` §7.