

```
import pkg from 'pg';
const { Pool } = pkg;
```

```
const pool = new Pool({
  user: 'postgres',
  host: 'localhost',
  database: 'testdb',
  password: '123',
  port: 5432
});
```

```
export default pool;
```

```
import pool from "./db.js";
```

```
const createUser = async(name, email)=>{
  const result = await pool.query(
    "INSERT INTO users (name, email) VALUES ($1, $2) RETURNING *",
    [name, email]
  );
  console.log("Created:", result.rows[0]);
}
```

```
const getUsers = async()=>{
  const result = await pool.query("SELECT * FROM users");
  console.log("All Users:", result.rows);
}
```

```
const updateUser = async(id, name)=>{
  const result = await pool.query(
    "UPDATE users SET name = $1 WHERE id = $2 RETURNING *",
    [name, id]
  );
  console.log("Updated:", result.rows[0]);
}
```

```
const deleteUser = async(id)=>{
  const result = await pool.query(
    "DELETE FROM users WHERE id = $1 RETURNING *",
    [id]
  );
  console.log("Deleted:", result.rows[0]);
}
```

```
// Call functions in an async wrapper one by one
```

```
async function main() {  
  await createUser("Navneet", "navneet@example.com");  
  // await getUsers();  
  // await updateUser(16, "Dr. Navneet Kaur");  
  // await deleteUser(16);  
  
  pool.end();  
}  
  
main();
```