

Company Name	Aker Solutions	Project Title	
Group/Team Name		Subtitle	
Designer	Mangesh More	Job Number	
Date	04 /06 /2016	Method	Limit State Design (No Earthquake Load)


Design Conclusion	
Finplate	Pass
Finplate	
Connection Properties	
Connection	
Connection Title	Single Finplate
Connection Type	Shear Connection
Connection Category	
Connectivity	Column flange-Beam web
Beam Connection	Bolted
Column Connection	Welded
Loading (Factored Load)	
Shear Force (kN)	160
Components	
Column Section	
Material	Fe 410
Beam Section	
Material	Fe 410
Hole	STD
Plate Section	
Thickness (mm)	10
Width (mm)	100
Depth (mm)	320
Hole	STD
Weld	
Type	Double Fillet
Size (mm)	8
Bolts	
Type	HSFG
Grade	8.8
Diameter (mm)	20
Bolt Numbers	3
Columns (Vertical Lines)	1
Bolts Per Column	3
Gauge (mm)	0
Pitch (mm)	120
End Distance (mm)	40


Edge Distance (mm)	40
Assembly	
Column-Beam Clearance (mm)	20


Company Name	Aker Solutions	Project Title	
Group/Team Name		Subtitle	
Designer	Mangesh More	Job Number	
Date	04 /06 /2016	Method	Limit State Design (No Earthquake Load)

Design Check			
Check	Required	Provided	Remark
Bolt shear capacity (kN)		$V_{dsb} = (800 \times 0.6126 \times 20 \times 20) / (\sqrt{3} \times 1.25 \times 1000)$ $= 90.529$ [cl. 10.3.3]	
Bolt bearing capacity (kN)		$V_{dpb} = (2.5 \times 0.508 \times 20 \times 8.9 \times 410) / (1.25 \times 1000)$ $= 74.148$ [cl. 10.3.4]	
Bolt capacity (kN)		Min (90.529, 74.148) = 74.148	
No. of bolts	160/74.148 = 2.2	3	Pass
No. of column(s)	≤ 2	1	
No. of bolts per column		3	
Bolt pitch (mm)	$\geq 2.5 \times 20 = 50, \leq \text{Min}(32 \times 8.9, 300) = 285$ [cl. 10.2.2]	120	Pass
Bolt gauge (mm)	$\geq 2.5 \times 20 = 50, \leq \text{Min}(32 \times 8.9, 300) = 285$ [cl. 10.2.2]	0	
End distance (mm)	$\geq 1.7 \times 22 = 37.4, \leq 12 \times 8.9 = 106.8$ [cl. 10.2.4]	40	Pass
Edge distance (mm)	$\geq 1.7 \times 22 = 37.4, \leq 12 \times 8.9 = 106.8$ [cl. 10.2.4]	40	Pass
Block shear capacity (kN)	≥ 160	$V_{db} = 453$	Pass
Plate thickness (mm)	$(5 \times 160 \times 1000) / (320 \times 250) = 10.0$ [Owens and Cheal, 1989]	10	Pass
Plate height (mm)	$\geq 0.6 \times 400 = 240.0, \leq 400 - 16 - 14 - 10 = 330.0$ [cl. 10.2.4, Insdag Detailing Manual, 2002]	320	Pass
Plate width (mm)		100	
Plate moment capacity (kNm)	$(2 \times 90.529 \times 120^2) / (120 \times 1000) = 14.485$	$M_d = (1.2 \times 250 \times Z) / (1000 \times 1.1) = 46.55$ [cl. 8.2.1.2]	Pass
Effective weld length (mm)		320 - 2 × 8 = 304	
Weld strength (kN/mm)	$\sqrt{[(14485 \times 6) / (2 \times 304^2)]^2 + [160 / (2 \times 304)]^2}$ $= 0.539$	$f_v = (0.7 \times 8 \times 410) / (\sqrt{3} \times 1.25)$ $= 1.06$ [cl. 10.5.7]	Pass

Weld thickness (mm)	$\text{Max}((0.539 \cdot 1000 \cdot \sqrt{3} \cdot 1.25) / (0.7 \cdot 410), 10 \cdot 0.8) = 8.0$ [cl. 10.5.7, Insdag Detailing Manual, 2002]	8	Pass
--------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------	---	-------------

		<div> <div>Created with</div> <div>  Osdag </div> </div>	
Company Name	Aker Solutions	Project Title	
Group/Team Name		Subtitle	
Designer	Mangesh More	Job Number	
Date	04 /06 /2016	Method	Limit State Design (No Earthquake Load)

Views	
	

		Created with  Osdag	
Company Name	Aker Solutions	Project Title	
Group/Team Name		Subtitle	
Designer	Mangesh More	Job Number	
Date	04 /06 /2016	Method	Limit State Design (No Earthquake Load)
Additional Comments			