Company Name		**Project Title**	
Group/Team Name		**Subtitle**	
Designer		**Job Number**	
Date	**03 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Conclusion	
Finplate	**Pass**
Finplate	
Connection Properties	
Connection	
Connection Title	Single Finplate
Connection Type	Shear Connection
Connection Category	
Connectivity	Column web-Beam web
Beam Connection	Bolted
Column Connection	Welded
Loading (Factored Load)	
Shear Force (kN)	100
Components	
Column Section	ISSC 200
Material	Fe 410
Beam Section	ISMB 400
Material	Fe 410
Hole	STD
Plate Section	240X100X10
Thickness (mm)	10
Width (mm)	100
Depth (mm)	240
Hole	STD
Weld	
Type	Double Fillet
Size (mm)	8
Bolts	
Type	Black Bolt
Grade	3.6
Diameter (mm)	20
Bolt Numbers	3
Columns (Vertical Lines)	1
Bolts Per Column	3
Gauge (mm)	0
Pitch (mm)	80
End Distance (mm)	40

Edge Distance (mm)	40
Assembly	
Column-Beam Clearance (mm)	20

Company Name		Project Title	
Group/Team Name		Subtitle	
Designer		Job Number	
Date	03 /06 /2016	Method	Limit State Design (No Earthquake Load)

Design Check			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = (300*0.6126*20*20)/(√3*1.25*1000) = 33.948 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.508*20*8.9*410)/(1.25*1000) = 74.148 [cl. 10.3.4]	
Bolt capacity (kN)		Min (33.948, 74.148) = 33.948	
No. of bolts	100/33.948 = 2.9	3	**Pass**
No.of column(s)	≤ 2	1	
No. of bolts per column		3	
Bolt pitch (mm)	≥ 2.5* 20 = 50, ≤ Min(32*8.9, 300) = 285 [cl. 10.2.2]	80	**Pass**
Bolt gauge (mm)	≥ 2.5*20 = 50, ≤ Min(32*8.9, 300) = 285 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*22 = 37.4, ≤ 12*8.9 = 106.8 [cl. 10.2.4]	40	**Pass**
Edge distance (mm)	≥ 1.7*22 = 37.4, ≤ 12*8.9 = 106.8 [cl. 10.2.4]	40	**Pass**
Block shear capacity (kN)	≥ 100	V_{db} = 338	**Pass**
Plate thickness (mm)	(5*100*1000)/(240*250) = 8.33 [Owens and Cheal, 1989]	10	**Pass**
Plate height (mm)	≥ 0.6*400=240.0, ≤ 400-16-14-10=330.0 [cl. 10.2.4, Insdag Detailing Manual, 2002]	240	**Pass**
Plate width (mm)		100	
Plate moment capacity (kNm)	(2*33.948*80^2)/(80*1000) = 6.0	M_d = (1.2*250*Z)/(1000*1.1) = 26.18 [cl. 8.2.1.2]	**Pass**
Effective weld length (mm)		240-2*8 = 224	
Weld strength (kN/mm)	√[(6000*6)/(2*224^2)]^2 + [100/(2*224)]^2 = 0.423	f_v= (0.7*8*410)/(√3*1.25) = 1.06 [cl. 10.5.7]	**Pass**

Weld thickness (mm)	Max((0.423*1000*√3* 1.25)/(0.7 * 410),10* 0.8) = 8.0 [cl. 10.5.7, Insdag Detailing Manual, 2002]	8	**Pass**

Company Name		Project Title	
Group/Team Name		Subtitle	
Designer		Job Number	
Date	03 /06 /2016	Method	Limit State Design (No Earthquake Load)

Views



Company Name		Project Title	
Group/Team Name		Subtitle	
Designer		Job Number	
Date	03 /06 /2016	Method	Limit State Design (No Earthquake Load)

Additional Comments	