Company Name	**LERA**	**Project Title**	**Renaissance**
Group/Team Name	**Superkings**	**Subtitle**	
Designer	**Charan**	**Job Number**	
Date	**06 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Conclusion	
Cleat Angle	**Pass**
Cleat Angle	
Connection Properties	
Connection	
Connection Title	Double Angle Web Cleat
Connection Type	Shear Connection
Connection Category	
Connectivity	Beam-Beam
Beam Connection	Bolted
Column Connection	Bolted
Loading (Factored Load)	
Shear Force (kN)	100.0
Components	
Column Section	ISMB 450
Material	Fe 410
Beam Section	ISMB 300
Material	Fe 410
Hole	STD
Cleat Section	ISA 80X80X8
Thickness (mm)	8
Cleat Leg Size B (mm)	80
Cleat Leg Size A (mm)	80
Hole	STD
Bolts on Beam	
Type	Black Bolt
Grade	4.8
Diameter (mm)	16
Bolt Numbers	4
Columns (Vertical Lines)	1
Bolts Per Column	4
Gauge (mm)	0
Pitch (mm)	40
End Distance (mm)	30

Edge Distance (mm)	30
Bolts on Column	
Type	Black Bolt
Grade	4.8
Diameter (mm)	16
Bolt Numbers	8
Columns (Vertical Lines)	1
Bolts Per Column	4
Gauge (mm)	0
Pitch (mm)	40
End Distance (mm)	30
Edge Distance (mm)	30
Assembly	
Column-Beam Clearance (mm)	20

Company Name	LERA	Project Title	Renaissance
Group/Team Name	Superkings	Subtitle	
Designer	Charan	Job Number	
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Design Check: Secondary Beam Connectivity			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = ((2*400*0.6126*16*16)/(√3*1.25*1000) = 58.012 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.491*16*7.7*400)/(1.25*1000) = 48.393 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V_{dpb} = (2.5*0.491*16*7.7*410)/(1.25*1000) = 49.603 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.491*16*8*410)/(1.25*1000) = 51.535 [cl. 10.3.4]	
Bearing capacity (kN)		Min (48.393, 49.603, 51.535) = 48.393	
Bolt capacity (kN)		Min (58.012, 48.393) = 48.393	
Critical bolt shear (kN)	≤ 48.393	22.535	**Pass**
No. of bolts		4	
No.of column(s)	≤ 2	1	
No. of bolts per column		4	
Bolt pitch (mm)	≥ 2.5* 16 = 40, ≤ Min(32*7.7, 300) = 247 [cl. 10.2.2]	40	**Pass**
Bolt gauge (mm)	≥ ;2.5*16 = 40, ≤ Min(32*7.7, 300) = 247 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*18.0 = 30.6, ≤ 12*7.7 = 92.4 [cl. 10.2.4]	30	**Pass**
Edge distance	≥ 1.7*18.0 = 30.6, ≤ 12*7.7 = 92.4	30	**Pass**

(mm)	[cl. 10.2.4]		
Block shear capacity (kN)	≥ 100.0	V_{db} = 173.167 [cl. 6.4.1]	**Pass**
Cleat height (mm)	≥ 0.6*300.0=180.0, ≤ 300.0-13.1-14.0-17.4-15.0- 5=235.5 [cl. 10.2.4, Insdag Detailing Manual, 2002]	180	**Pass**
Cleat moment capacity (kNm)	(2*58.012*40^2)/(40*1000) = 2.5	M_d = (1.2*250*Z)/(1000*1.1) = 77.76 [cl. 8.2.1.2]	**Pass**

Company Name	LERA	Project Title	Renaissance
Group/Team Name	Superkings	Subtitle	
Designer	Charan	Job Number	
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Design Check: Primary Beam Connectivity			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = ((400*0.6126*16*16)/(√3*1.25*1000) = 29.006 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.491*16*8.0*400)/(1.25*1000) = 50.278 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V_{dpb} = (2.5*0.491*16*9.4*410)/(1.25*1000) = 60.554 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.491*16*8*410)/(1.25*1000) = 51.535 [cl. 10.3.4]	
Bearing capacity (kN)		Min (50.278, 60.554, 51.535) = 51.535	
Bolt capacity (kN)		Min (29.006, 51.535) = 29.006	
Critical bolt shear (kN)	≤ 29.006	23.749	**Pass**
No. of bolts		8	
No.of column(s) per angle	≤ 2	1	
No. of bolts per column per angle		4	
Bolt pitch (mm)	≥ 2.5* 16 = 40, ≤ Min(32*8.0, 300) = 256 [cl. 10.2.2]	40	**Pass**
Bolt gauge (mm)	≥ 2.5*16 = 40, ≤ Min(32*8.0, 300) = 256 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*18.0 = 30.6, ≤ 12*8.0 = 96.0 [cl. 10.2.4]	30	**Pass**
	≥1.7*18.0 = 30.6, ≤12*8.0 =		

Edge distance (mm)	96.0 [cl. 10.2.4]	30	**Pass**
Block shear capacity (kN)	≥100.0	V_{db} = 173.167 [cl. 6.4.1]	**Pass**
Cleat height (mm)	≥ 0.6*300.0=180.0, ≤ 300.0-13.1-14.0-17.4-15.0- 5=235.5 [cl. 10.2.4, Insdag Detailing Manual, 2002]	180	**Pass**
Cleat moment capacity (kNm)	$(2*29.006*40^2)/(40*1000)$ = 2.692	M_d = $(1.2*250*Z)/(1000*1.1)$ = 77.76 [cl. 8.2.1.2]	**Pass**

		Created with Osdag	
Company Name	**LERA**	**Project Title**	**Renaissance**
Group/Team Name	**Superkings**	**Subtitle**	
Designer	**Charan**	**Job Number**	
Date	**06 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Views	
	

Company Name	LERA	Project Title	Renaissance
Group/Team Name	Superkings	Subtitle	
Designer	Charan	Job Number	
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Additional Comments	