


		Created with 	
Company Name	Aker Solutions	Project Title	Set 2.1
Group/Team Name	Aker Solutions	Subtitle	
Designer	Vishal Nalwar	Job Number	Set 2.1
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Design Conclusion	
Cleat Angle	Pass
Cleat Angle	
Connection Properties	
Connection	
Connection Title	Double Angle Web Cleat
Connection Type	Shear Connection
Connection Category	
Connectivity	Beam-Beam
Beam Connection	Bolted
Column Connection	Bolted
Loading (Factored Load)	
Shear Force (kN)	100.0
Components	
Column Section	ISMB 450
Material	Fe 410
Beam Section	ISMB 300
Material	Fe 410
Hole	STD
Cleat Section	ISA 100X100X8
Thickness (mm)	8
Cleat Leg Size B (mm)	100
Cleat Leg Size A (mm)	100
Hole	STD
Bolts on Beam	
Type	Black Bolt
Grade	4.8
Diameter (mm)	20
Bolt Numbers	4
Columns (Vertical Lines)	1
Bolts Per Column	4
Gauge (mm)	0
Pitch (mm)	50
End Distance (mm)	37
Edge Distance (mm)	37
Bolts on Column	
Type	Black Bolt
Grade	4.8
Diameter (mm)	20
Bolt Numbers	6

Columns (Vertical Lines)	1
Bolts Per Column	3
Gauge (mm)	0
Pitch (mm)	50
End Distance (mm)	62
Edge Distance (mm)	37
Assembly	
Column-Beam Clearance (mm)	20

Company Name	Aker Solutions	Project Title	Set 2.1
Group/Team Name	Aker Solutions	Subtitle	
Designer	Vishal Nalwar	Job Number	Set 2.1
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)


Design Check: Secondary Beam Connectivity			
Check	Required	Provided	Remark
Bolt shear capacity (kN)		$V_{dsb} = ((2*400*0.6126*20*20)/(\sqrt{3}*1.25*1000)) = 90.529$ [cl. 10.3.3]	
Bolt bearing capacity (kN)		$V_{dpb} = (2.5*0.508*20*7.7*400)/(1.25*1000) = 62.586$ [cl. 10.3.4]	
Bearing capacity of beam web (kN)		$V_{dpb} = (2.5*0.508*20*7.7*410)/(1.25*1000) = 64.15$ [cl. 10.3.4]	
Bearing capacity of cleat (kN)		$V_{dpb} = (2.5*0.508*20*8*410)/(1.25*1000) = 66.65$ [cl. 10.3.4]	
Bearing capacity (kN)		Min (62.586, 64.15, 66.65) = 62.586	
Bolt capacity (kN)		Min (90.529, 62.586) = 62.586	
Critical bolt shear (kN)	≤ 62.586	22.66	Pass
No. of bolts		4	
No.of column(s)	≤ 2	1	
No. of bolts per column		4	
Bolt pitch (mm)	$\geq 2.5*20 = 50, \leq \text{Min}(32*7.7, 300) = 247$ [cl. 10.2.2]	50	Pass
Bolt gauge (mm)	$\geq ;2.5*20 = 50, \leq \text{Min}(32*7.7, 300) = 247$ [cl. 10.2.2]	0	
End distance (mm)	$\geq 1.7*22.0 = 37.4, \leq 12*7.7 = 92.4$ [cl. 10.2.4]	37	Pass
Edge distance (mm)	$\geq 1.7*22.0 = 37.4, \leq 12*7.7 = 92.4$ [cl. 10.2.4]	37	Pass
Block shear capacity (kN)	≥ 100.0	$V_{db} = 217.254$ [cl. 6.4.1]	Pass
Cleat height (mm)	$\geq 0.6*300.0=180.0, \leq 300.0-13.1-14.0-17.4-15.0-5=235.5$ [cl. 10.2.4, Insdag Detailing Manual, 2002]	224	Pass
Cleat moment	$(2*90.529*50^2)/(50*1000) = 3.15$	$M_d = (1.2*250*Z)/(1000*1.1) = 120.422$	Pass

capacity (kNm)		[cl. 8.2.1.2]	
----------------	--	---------------	--


Company Name	Aker Solutions	Project Title	Set 2.1
Group/Team Name	Aker Solutions	Subtitle	
Designer	Vishal Nalwar	Job Number	Set 2.1
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)


Design Check: Primary Beam Connectivity			
Check	Required	Provided	Remark
Bolt shear capacity (kN)		$V_{dsb} = ((400 \times 0.6126 \times 20 \times 20) / (\sqrt{3} \times 1.25 \times 1000)) = 45.264$ [cl. 10.3.3]	
Bolt bearing capacity (kN)		$V_{dpb} = (2.5 \times 0.508 \times 20 \times 8.0 \times 400) / (1.25 \times 1000) = 65.024$ [cl. 10.3.4]	
Bearing capacity of beam web (kN)		$V_{dpb} = (2.5 \times 0.508 \times 20 \times 9.4 \times 410) / (1.25 \times 1000) = 78.313$ [cl. 10.3.4]	
Bearing capacity of cleat (kN)		$V_{dpb} = (2.5 \times 0.508 \times 20 \times 8 \times 410) / (1.25 \times 1000) = 66.65$ [cl. 10.3.4]	
Bearing capacity (kN)		Min (65.024, 78.313, 66.65) = 66.65	
Bolt capacity (kN)		Min (45.264, 66.65) = 45.264	
Critical bolt shear (kN)	≤ 45.264	37.35	Pass
No. of bolts		6	
No.of column(s) per angle	≤ 2	1	
No. of bolts per column per angle		3	
Bolt pitch (mm)	$\geq 2.5 \times 20 = 50, \leq \text{Min}(32 \times 8.0, 300) = 256$ [cl. 10.2.2]	50	Pass
Bolt gauge (mm)	$\geq 2.5 \times 20 = 50, \leq \text{Min}(32 \times 8.0, 300) = 256$ [cl. 10.2.2]	0	
End distance (mm)	$\geq 1.7 \times 22.0 = 37.4, \leq 12 \times 8.0 = 96.0$ [cl. 10.2.4]	62	Pass
Edge distance (mm)	$\geq 1.7 \times 22.0 = 37.4, \leq 12 \times 8.0 = 96.0$ [cl. 10.2.4]	37	Pass
Block shear capacity (kN)	≥ 100.0	$V_{db} = 213.164$ [cl. 6.4.1]	Pass
Cleat height (mm)	$\geq 0.6 \times 300.0 = 180.0, \leq 300.0 - 13.1 - 14.0 - 17.4 - 15.0 - 5 = 235.5$ [cl. 10.2.4, Insdag Detailing Manual, 2002]	224	Pass
Cleat moment		$M_d = (1.2 \times 250 \times Z) / (1000 \times 1.1) =$	Pass

capacity (kNm)	$(2 \cdot 45.264 \cdot 50^2) / (50 \cdot 1000) = 3.342$	120.422 [cl. 8.2.1.2]	
----------------	---	--------------------------	--


		<div> <div>  <div> <div>Osdag</div> <div>Created with</div> </div> </div> </div>	
Company Name	Aker Solutions	Project Title	Set 2.1
Group/Team Name	Aker Solutions	Subtitle	
Designer	Vishal Nalwar	Job Number	Set 2.1
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Views







Top view (Sec A-A) (All distances are in "mm")



Side View (Sec B-B) (All distances are in "mm")



Front view (Sec C-C) (All distances are in "mm")

		Created with 	
Company Name	Aker Solutions	Project Title	Set 2.1
Group/Team Name	Aker Solutions	Subtitle	
Designer	Vishal Nalwar	Job Number	Set 2.1
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)
Additional Comments		Beam to beam cleat angle shear connection	