Company Name	**LERA**	**Project Title**	**Design prob 4**
Group/Team Name	**Individual**	**Subtitle**	
Designer	**Karthik Bandi**	**Job Number**	**P786**
Date	**06 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Conclusion	
Finplate	**Pass**
Finplate	
Connection Properties	
Connection	
Connection Title	Single Finplate
Connection Type	Shear Connection
Connection Category	
Connectivity	Column flange-Beam web
Beam Connection	Bolted
Column Connection	Welded
Loading (Factored Load)	
Shear Force (kN)	200
Components	
Column Section	ISSC 200
Material	Fe 410
Beam Section	ISMB 400
Material	Fe 410
Hole	STD
Plate Section	250X100X16
Thickness (mm)	16
Width (mm)	100
Depth (mm)	250
Hole	STD
Weld	
Type	Double Fillet
Size (mm)	13
Bolts	
Type	HSFG
Grade	8.8
Diameter (mm)	12
Bolt Numbers	7
Columns (Vertical Lines)	1
Bolts Per Column	7
Gauge (mm)	0
Pitch (mm)	31
End Distance (mm)	30
Edge Distance (mm)	30
Assembly	

Column-Beam Clearance (mm)	20

Company Name	**LERA**	**Project Title**	**Design prob 4**
Group/Team Name	**Individual**	**Subtitle**	
Designer	**Karthik Bandi**	**Job Number**	**P786**
Date	**06 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Check			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = (800*0.6126*12*12)/(√3*1.25*1000) = 31.223 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.519*12*8.9*410)/(1.25*1000) = 45.452 [cl. 10.3.4]	
Bolt capacity (kN)		Min (31.223, 45.452) = 31.223	
No. of bolts	200/31.223 = 6.4	7	**Pass**
No.of column(s)	≤ 2	1	
No. of bolts per column		7	
Bolt pitch (mm)	≥ 2.5* 12 = 30, ≤ Min(32*8.9, 300) = 285 [cl. 10.2.2]	31	**Pass**
Bolt gauge (mm)	≥ 2.5*12 = 30, ≤ Min(32*8.9, 300) = 285 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*13 = 22.1, ≤ 12*8.9 = 106.8 [cl. 10.2.4]	30	**Pass**
Edge distance (mm)	≥ 1.7*13 = 22.1, ≤ 12*8.9 = 106.8 [cl. 10.2.4]	30	**Pass**
Block shear capacity (kN)	≥ 200	V_{db} = 467	**Pass**
Plate thickness (mm)	(5*200*1000)/(250*250) = 16.0 [Owens and Cheal, 1989]	16	**Pass**
Plate height (mm)	≥ 0.6*400=240.0, ≤ 400-16-14-10=330.0 [cl. 10.2.4, Insdag Detailing Manual, 2002]	250	**Pass**
Plate width (mm)		100	
Plate moment capacity (kNm)	(2*31.223*31^2)/(31*1000) = 14.0	M_d = (1.2*250*Z)/(1000*1.1) = 45.45 [cl. 8.2.1.2]	**Pass**
Effective weld length (mm)		250-2*16 = 218	
Weld strength (kN/mm)	√[(14000*6)/(2*218^2)]^2 + [200/(2*218)]^2 = 0.996	f_v= (0.7*13*410)/(√3*1.25) = 2.121 [cl. 10.5.7]	**Pass**
	Max((0.996*1000*√3* 1.25)/(0.7 *		**Pass**

Weld thickness (mm)	410),16* 0.8) = 12.8 [cl. 10.5.7, Insdag Detailing Manual, 2002]	13	Pass

Company Name	**LERA**	**Project Title**	**Design prob 4**
Group/Team Name	**Individual**	**Subtitle**	
Designer	**Karthik Bandi**	**Job Number**	**P786**
Date	**06 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Views





Top view (Sec A-A)



Side view (Sec B-B)



Front view (Sec C-C)

Company Name	LERA	Project Title	Design prob 4
Group/Team Name	Individual	Subtitle	
Designer	Karthik Bandi	Job Number	P786
Date	06 /06 /2016	Method	Limit State Design (No Earthquake Load)

Additional Comments	