IIT Bombay		Created with Osdag	
Company Name	**PVPIT**	**Project Title**	**Project 03**
Group/Team Name	**OSDAG**	**Subtitle**	
Designer	**USER 03**	**Job Number**	**123**
Date	**05 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Conclusion	
Cleat Angle	**Pass**
Cleat Angle	
Connection Properties	
Connection	
Connection Title	Double Angle Web Cleat
Connection Type	Shear Connection
Connection Category	
Connectivity	Beam-Beam
Beam Connection	Bolted
Column Connection	Bolted
Loading (Factored Load)	
Shear Force (kN)	100.0
Components	
Column Section	ISMB 450
Material	Fe 410
Beam Section	ISMB 300
Material	Fe 410
Hole	STD
Cleat Section	ISA 70X70X8
Thickness (mm)	8
Cleat Leg Size B (mm)	70
Cleat Leg Size A (mm)	70
Hole	STD
Bolts on Beam	
Type	Black Bolt

Grade	4.8
Diameter (mm)	12
Bolt Numbers	6
Columns (Vertical Lines)	1
Bolts Per Column	6
Gauge (mm)	0
Pitch (mm)	30
End Distance (mm)	22
Edge Distance (mm)	22
Bolts on Column	
Type	Black Bolt
Grade	4.8
Diameter (mm)	12
Bolt Numbers	12
Columns (Vertical Lines)	1
Bolts Per Column	6
Gauge (mm)	0
Pitch (mm)	30
End Distance (mm)	22
Edge Distance (mm)	22
Assembly	
Column-Beam Clearance (mm)	20

IIT Bombay		Created with Osdag	
Company Name	**PVPIT**	**Project Title**	**Project 03**
Group/Team Name	**OSDAG**	**Subtitle**	
Designer	**USER 03**	**Job Number**	**123**
Date	**05 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Check: Secondary Beam Connectivity			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = ((2*400*0.6126*12*12)/(√3*1.25*1000) = 31.223 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.519*12*7.7*400)/(1.25*1000) = 38.364 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V_{dpb} = (2.5*0.519*12*7.7*410)/(1.25*1000) = 39.324 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.519*12*8*410)/(1.25*1000) = 40.856 [cl. 10.3.4]	
Bearing capacity (kN)		Min (38.364, 39.324, 40.856) = 38.364	
Bolt capacity (kN)		Min (31.223, 38.364) = 31.223	
Critical bolt shear (kN)	≤ 31.223	14.144	**Pass**
No. of bolts		6	
No.of column(s)	≤ 2	1	

No. of bolts per column		6	
Bolt pitch (mm)	≥ 2.5* 12 = 30, ≤ Min(32*7.7, 300) = 247 [cl. 10.2.2]	30	**Pass**
Bolt gauge (mm)	≥ ;2.5*12 = 30, ≤ Min(32*7.7, 300) = 247 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*13.0 = 22.1, ≤ 12*7.7 = 92.4 [cl. 10.2.4]	22	**Pass**
Edge distance (mm)	≥ 1.7*13.0 = 22.1, ≤ 12*7.7 = 92.4 [cl. 10.2.4]	22	**Pass**
Block shear capacity (kN)	≥ 100.0	V_{db} = 177.029 [cl. 6.4.1]	**Pass**
Cleat height (mm)	≥ 0.6*300.0=180.0, ≤ 300.0-13.1-14.0-17.4-15.0-5=235.5 [cl. 10.2.4, Insdag Detailing Manual, 2002]	194	**Pass**
Cleat moment capacity (kNm)	$(2*31.223*30^2)/(30*1000)$ = 2.4	M_d = (1.2*250*Z)/(1000*1.1) = 90.326 [cl. 8.2.1.2]	**Pass**

IIT Bombay		Created with Osdag	
Company Name	**PVPIT**	**Project Title**	**Project 03**
Group/Team Name	**OSDAG**	**Subtitle**	
Designer	**USER 03**	**Job Number**	**123**
Date	**05 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Design Check: Primary Beam Connectivity			
Check	**Required**	**Provided**	**Remark**
Bolt shear capacity (kN)		V_{dsb} = ((400*0.6126*12*12)/(√3*1.25*1000) = 15.611 [cl. 10.3.3]	
Bolt bearing capacity (kN)		V_{dpb} = (2.5*0.519*12*8.0*400)/(1.25*1000) = 39.859 [cl. 10.3.4]	
Bearing capacity of beam web (kN)		V_{dpb} = (2.5*0.519*12*9.4*410)/(1.25*1000) = 48.005 [cl. 10.3.4]	
Bearing capacity of cleat (kN)		V_{dpb} = (2.5*0.519*12*8*410)/(1.25*1000) = 40.856 [cl. 10.3.4]	
Bearing capacity (kN)		Min (39.859, 48.005, 40.856) = 40.856	
Bolt capacity (kN)		Min (15.611, 40.856) = 15.611	
Critical bolt shear (kN)	≤ 15.611	14.895	**Pass**
No. of bolts		12	
No.of column(s) per angle	≤ 2	1	
No. of bolts			

per column per angle		6	
Bolt pitch (mm)	≥ 2.5* 12 = 30, ≤ Min(32*8.0, 300) = 256 [cl. 10.2.2]	30	**Pass**
Bolt gauge (mm)	≥ 2.5*12 = 30, ≤ Min(32*8.0, 300) = 256 [cl. 10.2.2]	0	
End distance (mm)	≥ 1.7*13.0 = 22.1, ≤ 12*8.0 = 96.0 [cl. 10.2.4]	22	**Pass**
Edge distance (mm)	≥1.7*13.0 = 22.1, ≤12*8.0 = 96.0 [cl. 10.2.4]	22	**Pass**
Block shear capacity (kN)	≥100.0	V_{db} = 177.029 [cl. 6.4.1]	**Pass**
Cleat height (mm)	≥ 0.6*300.0=180.0, ≤ 300.0-13.1-14.0-17.4-15.0-5=235.5 [cl. 10.2.4, Insdag Detailing Manual, 2002]	194	**Pass**
Cleat moment capacity (kNm)	$(2*15.611*30^2)/(30*1000)$ = 2.592	M_d = (1.2*250*Z)/(1000*1.1) = 90.326 [cl. 8.2.1.2]	**Pass**

IIT Bombay		Created with Osdag	
Company Name	**PVPIT**	**Project Title**	**Project 03**
Group/Team Name	**OSDAG**	**Subtitle**	
Designer	**USER 03**	**Job Number**	**123**
Date	**05 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Views





Top view (Sec A-A) (All distances are in "mm")



Side View (Sec B-B) (All distances are in "mm")



Front view (Sec C-C) (All distances are in "mm")

IIT Bombay		Created with Osdag	
Company Name	**PVPIT**	**Project Title**	**Project 03**
Group/Team Name	**OSDAG**	**Subtitle**	
Designer	**USER 03**	**Job Number**	**123**
Date	**05 /06 /2016**	**Method**	**Limit State Design (No Earthquake Load)**

Additional Comments	