

# Rajalakshmi Engineering College

Name: SASHTIGAN M

Email: 241501190@rajalakshmi.edu.in

Roll no: 241501190

Phone: 6381207853

Branch: REC

Department: I AIML AD

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 4

Attempt : 2

Total Mark : 10

Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Kavya, a software developer, is analyzing data trends. She has a list of integers and wants to identify the  $n$ th largest number in the list after sorting the array using QuickSort.

To optimize performance, Kavya is required to use QuickSort to sort the list before finding the  $n$ th largest number.

##### ***Input Format***

The first line of input consists of an integer  $n$ , representing the size of the array.

The second line consists of  $n$  space-separated integers, representing the elements of the array `nums`.

The third line consists of an integer  $k$ , representing the position of the largest

number you need to print after sorting the array.

### **Output Format**

The output prints the k-th largest number in the sorted array (sorted in ascending order).

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 6  
-1 0 1 2 -1 -4  
3

Output: 0

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>

#include <stdio.h>
```

```
void swap(int* a, int* b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}
```

```
int partition(int arr[], int low, int high) {
    int pivot = arr[high];
    int i = low - 1;
    for (int j = low; j < high; j++) {
        if (arr[j] <= pivot) {
            i++;
            swap(&arr[i], &arr[j]);
        }
    }
    swap(&arr[i + 1], &arr[high]);
    return i + 1;
}
```

```
void quickSort(int arr[], int low, int high) {
    if (low < high) {
        int pi = partition(arr, low, high);
        quickSort(arr, low, pi - 1);
        quickSort(arr, pi + 1, high);
    }
}

void findNthLargest(int* nums, int n, int k) {
    quickSort(nums, 0, n - 1);
    // Since array is sorted ascending, kth largest is at index n-k
    printf("%d", nums[n - k]);
}

int main() {
    int n, k;
    scanf("%d", &n);
    int* nums = (int*)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }
    scanf("%d", &k);
    findNthLargest(nums, n, k);
    free(nums);
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10