Crowd Shield: measuring crowd danger with ordinary cameras, tested on Indian crowds

Khushi · Technical report, October 2026 · Code, data and models: github.com/khushi-git-7/Crowd_shield · huggingface.co/Khushi-7/crowd-shield-counting · live demo: crowd-shield-india.streamlit.app

Abstract

Crowd crushes happen when too many people stand in too little space and the crowd starts to push. In most recent Indian disasters, at the Hathras satsang (2024), New Delhi railway station (2025) and the Maha Kumbh (2025), those warning signs were visible minutes earlier. Crowd Shield is an open-source tool that measures them from ordinary photos and video:

- people per square metre in each zone
- how fast and how chaotically the crowd moves
- how long a zone has until it becomes dangerous
- where to move people so that no zone is overfilled

Counting uses a point model (PET) fine-tuned with a strictly held-out protocol. On the ShanghaiTech test sets it reaches **86.5%** accuracy on packed crowds and **92.7%** on street scenes, against **7%** and **42%** for the detector the project started with. A movement alarm catches **11 of 11** escape events in the UMN videos with no false alarms. A new test set of freely licensed Indian crowd photos shows the counter at about **90%** on 9 of 10 hand-checked photos, with one systematic failure: railway ballast seen from above is read as heads. Fine-tuning on empty-track photos fixed that failure but cost accuracy elsewhere, so it was not shipped. A field test on handheld Indian festival video showed that motion readings need a fixed camera, which led to an automatic moving-camera check. This report gives every number with the data and code behind it.

1. Why measure density

Crowd-safety research gives physical thresholds:

Density	What happens
About 2.2 people/m²	Normal walking breaks down (Fruin)
Above 5 people/m²	A serious risk (Still)
Around 7 people/m²	The crowd moves "almost as a fluid mass"

Helbing, Johansson and Al-Abideen (2007) showed in video of the 2006 Hajj disaster that *crowd pressure* (density × the local variance of velocity) rose above about 0.02 per s² before turbulent pushing began, and the crush came at its peak. A headcount alone is therefore not enough: the quantities that matter are people per square metre and how the crowd moves.

2. System

Crowd Shield is a Python package (crowdshield/) and a Streamlit app. The package has no UI code and is covered by tests.

1. **Count.** A point model puts one point on each head (§3). A density-map model and YOLO are fallbacks.
2. **Ground area.** For a fixed camera, four clicks on a floor rectangle of known size give a homography (direct linear transform with Hartley normalisation). The local area of each pixel is $|\det H| / w^3$, so counts become people/m². On the site map, each zone is a polygon on satellite imagery, and its area comes from the spherical-excess formula (Chamberlain & Duquette, 2007), the same formula Leaflet and Turf use.
3. **Movement.** Dense optical flow (Farnebäck) gives speed, the moving share of the view and turbulence. Crowd pressure uses the variance of velocity within 1 m cells.
4. **Early warning.** A Theil-Sen trend over the last minute of density estimates when a zone reaches 5 people/m². Theil-Sen is used because one bad count cannot swing it.
5. **Response.** Zones that touch (or lie within a set distance) form a walking graph. Each High Risk or Critical zone is paired with the nearest reachable Safe zone that has room, counting people already sent

there so no zone is overfilled. The route is drawn on the map, and each zone's contact gets an email.

3. Counting people

Data. ShanghaiTech Part A has 482 photos of packed crowds and Part B has 716 street photos, with every head marked by hand. The test sets (182 photos averaging 433 people, and 316 photos averaging 124) were used once, at the end.

Protocol.


- 10% of the *training* photos (70) were held out. They pick the best training round and fit the count correction.
- The published DM-Count and PET training scripts pick the best round by looking at the test set; we did not.

Models.

- **DM-Count** was trained from scratch on A+B, with the best round (130) picked on the held-out photos.
- **PET** (Liu et al., ICCV 2023) started from its authors' JHU-Crowd++ model and was fine-tuned for 9.5 h on a free Kaggle T4, with the best round (240) picked on the held-out photos.
- **One count correction,** true ≈ 1.375 × raw^0.942, was fitted on the same 70 photos. It trims PET's overcounting in packed crowds and its undercounting on streets.

Results (accuracy = 1 − Σ|error| ÷ Σ true count):

Counter	A: accuracy	A: off by per photo	B: accuracy	B: off by per photo
Original app (YOLO + Haar faces)	7%	403	42%	72
DM-Count (this project)	84%	70.1	86%	16.9
PET + correction (the app's counter)	86.5%	58.5	92.7%	9.0



On Part A, PET's error is a little lower than the DM-Count paper's (59.7) and higher than PET's own paper (49.1), which selected its model on the test set and trained one model per part. On the very largest crowds (1,000+ people), DM-Count is slightly more accurate (85% against 83%).

Why the original detector failed. YOLOv8 trained on COCO counted 13–21 people in most photos, whether a photo held 9 people or 539. COCO marks a tight group as a single "crowd" region, which is left out of YOLO's training labels, so the detector learns to treat crowds as background. A suspected bug, the

300-box cap, changed only 1 of 498 test photos.

4. Indian crowds

Test set. 105 freely licensed Wikimedia Commons photos:

- melas and pilgrimages (Kumbh, Gangasagar)
- festivals (Ganesh, Durga Puja, Chhath, Holi, Onam, Attukal Pongala, Bonalu, Madurai's Chithirai festival)
- temples and processions, stations, markets, stadiums and ghats

Each photo is credited and tagged with a scene. They are used only for testing.

Labelling protocol. The model's points are loaded as suggestions into a browser tool. A person adds every missed head, removes wrong points, marks covered heads (sarees, dupattas, turbans) and draws *ignore zones* over people too small or blurry to mark. Both truth and model are counted outside the ignore zones. A second reviewer audits each photo with zoomed crops. So far, 10 photos (3,507 heads) are complete.

Pilot results.

- The counter is within about 10% on 9 of the 10 photos: 94, 89, 96, 81, 100, 90, 84, 92 and 93%.
- Overall accuracy is 66.7% (mean error 116.9), because of one systematic failure. On a top-down Mumbai railway photo it counted 1,267 heads against 415: the gravel between the tracks looks like a dense crowd.

A negative result. We tried to fix the railway failure by fine-tuning PET on ShanghaiTech, the labelled Indian photos (oversampled) and 23 photos of empty Indian tracks with a true count of zero.

- **Protocol:** 5-fold cross-validation over the Indian photos, so every photo was scored by a model that never saw it, with a fixed number of training rounds and no checkpoint picking.
- **The railway photo was fixed:** 379 against 415, and overall India accuracy rose from 66.7% to 87.3%.
- **The other 9 photos got worse:** 89.5% → 86.8%. The model became cautious and undercounted small crowds; one photo fell from 90% to 68%.
- **ShanghaiTech also slipped slightly:** A 86.6% → 86.3%, B 92.6% → 92.6%.

Under the project's rule (ship a new model only if it is at least as good on ShanghaiTech and better on held-out Indian photos), the fine-tuned model was not shipped. The failure stays documented in the app.

5. Movement

Panic alarm.

- **Test data:** the UMN crowd-escape videos, 11 clips in 3 scenes, each ending with everyone running away.
- **The alarm:** it fires when the crowd moves at least 2× its own normal speed, or when movement energy (speed × moving share) reaches 8× normal, for half a second.
- **Result:** it caught all 11 escapes with no false alarms, a median 0.7 s before the dataset's "abnormal" label, which runs about a second late by inspection.
- **Speed alone missed three indoor escapes,** where running people look only 1.4–2× faster from a distant camera.
- **The 8× level wasn't just tuned to these clips:** with each scene held out in turn, the other two scenes chose the same 8× level every time, and every held-out escape was caught with no false alarm.
- **Caveat:** 3 scenes is a small test, and in one clip the score briefly touches the line.

Indian field test. The video monitor ran on 15 Commons clips of Indian crowds: Holi in Howrah (2026), the Bhagoriya fair, Gangasagar pilgrims, an eclipse crowd and a railway platform.

- There are no hand counts, so this checks behaviour, not accuracy.
- Head points held up in packed, partly covered crowds, from 10 to 330 people per frame.
- Analysis took about 1.4 s of T4 time per second of video.
- Every clip was handheld. That makes speed, pressure and the alarm measure the camera, not the crowd.

Holi, Howrah (2026)



Bhagoriya fair, Ranapur (2026)



Gangasagar pilgrims, Kolkata (2013)



We added a camera-motion check: phase correlation between frames gives how far the whole picture shifts.

- The fixed UMN camera stays at or under 1.4% of the frame width per second, even while people run.
- The handheld clips score 8–36%.
- Above 5%, the app warns and switches motion readings off, while still counting people.

6. Privacy and ethics

- **No identity.** The counter outputs anonymous head points. There is no face recognition and no tracking of individuals; video measures movement per zone.
- **No storage.** Photos stay in the browser session, and video is written to a temporary file only while it's decoded.
- **What leaves the app.** Only optional email alerts, which include the busiest photo.
- **GDPR.** Keeping only aggregate counts follows data minimisation (GDPR Art. 5(1)(c)). A real deployment would still need a data protection impact assessment (Art. 35), signage, retention rules and a trained operator.
- **A prompt, not a decision.** Counts can be wrong, as §4 shows, so an alert is a prompt for a person to look, not an automatic decision.

7. Limitations

- The India test is a pilot: 10 of 105 photos are labelled.
- Density and pressure need a calibrated, fixed camera.
- The early warning extends a straight-line trend.
- The movement alarm was validated on 3 scenes.
- Map zones in the demos are illustrative, not official plans.
- The counter fails on top-down views of railway ballast.

8. Reproducibility

- Every number above comes from scripts in eval/ and per-photo or per-clip results in results/.
- Trained weights are GitHub releases (pet-shab-v1, dmcount-shab-v1), checked by SHA-256 when downloaded, and mirrored on Hugging Face.
- Heavy runs used free Kaggle GPUs. Their scripts are in the repository.
- Tests run in GitHub Actions on every change.

Credits

Crowd Shield began as a two-person final-year project by Khushi and Sasmita (@SasmitaRK), who built the original Streamlit app. This report covers the v2 rebuild.

References

- Chamberlain, R. G., & Duquette, W. H. (2007). *Some algorithms for polygons on a sphere.* JPL Publication 07-03.
- Fruin, J. J. (1971). *Pedestrian Planning and Design.*
- Helbing, D., Johansson, A., & Al-Abideen, H. Z. (2007). Dynamics of crowd disasters: An empirical study. *Physical Review E*, 75, 046109.
- Liu, C., Lu, H., Cao, Z., & Liu, T. (2023). Point-Query Quadtree for Crowd Counting, Localization, and More (PET). *ICCV*.
- Mehran, R., Oyama, A., & Shah, M. (2009). Abnormal crowd behavior detection using social force model

(UMN dataset). *CVPR*.
- Still, G. K. (2014). *Introduction to Crowd Science*. CRC Press.
- Wang, B., Liu, H., Samaras, D., & Hoai, M. (2020). Distribution Matching for Crowd Counting (DM-Count). *NeurIPS*.
- Zhang, Y., Zhou, D., Chen, S., Gao, S., & Ma, Y. (2016). Single-image crowd counting via multi-column CNN (ShanghaiTech). *CVPR*.