Task 1: Guided Activity, User profile with missing data

```swift
struct Address {
    var city: String?
}
struct User {
    var name: String
    var age: Int?
    var address: Address?
}
func describe(_ user: User) -> String {
    guard let age = user.age else {
        return "\(user.name): Age unknown"
    }
    let city = user.address?.city ?? "unknown city"
    return "\(user.name), Age: \(age), City: \(city)"
}

let user1 = User(
    name: "Asha",
    age: 21,
    address: Address(city: "Chennai")
)
let user2 = User(
    name: "Ravi",
    age: nil,
    address: Address(city: "Coimbatore")
)

let user3 = User(
    name: "Kiran",
    age: 22,
    address: Address(city: nil)
)

print(describe(user1))
print(describe(user2))
print(describe(user3))

print(Int("42") as Any)
print(Int("abc") as Any)
```

Output:

```
Asha, Age: 21, City: Chennai
Ravi: Age unknown
Kiran, Age: 22, City: unknown city
Optional(42)
nil
```

Task 2: Practice Task, Safe number parsing

```swift
let inputs = ["10", "x", "25", "", "7.5", "40"]

let validNumbers = inputs.compactMap { Int($0) }
let sum = validNumbers.reduce(0, +)
let invalidCount = inputs.count - validNumbers.count
let firstDoubled = validNumbers.first.map { $0 * 2 }

print("Valid integers:", validNumbers)
print("Sum:", sum)
print("Invalid entries:", invalidCount)
print("First valid number doubled:", firstDoubled as Any)
```

Output:

```
Valid integers: [10, 25, 40]
Sum: 75
Invalid entries: 3
First valid number doubled: Optional(20)
```

Task 3: Debug Task, Remove the crashes

```swift
let scores = ["Asha": 90, "Ravi": 72]

if let kiran = scores["Kiran"] {
    if let number = Int("12a") {
        print(kiran + number)
    } else {
        print("Invalid number")
    }
} else {
    print("Kiran's score not found")
}
```

Output:

```
Kiran's score not found
```