SAFETY DATA SHEET

Spotcheck SKL-WP2 Aerosol

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name:	Spotcheck SKL-WP2 Aerosol
Unique formula identifier (UFI):	9SWV-R01N-5005-87A8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:	Non-destructive testing Restricted to professional users.
Uses advised against :	This product is not recommended for any use other than the identified uses above.

1.3. Details of the supplier of the safety data sheet

Company and address:	**Magnaflux® (A Division of ITW Ltd)** Faraday Road, South Dorcan Industrial Estate SN3 5HE Swindon, Wiltshire United Kingdom T +44 (0)1793 524566 https://magnaflux.eu/en
E-mail:	support.eu@magnaflux.com
Revision:	10/04/2025
SDS Version:	8.0
Date of previous version:	03/04/2025 (7.0)

1.4. Emergency telephone number

Emergency phone number: +44(0)203 394 9866
Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 112 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Skin Irrit. 2; H315, Causes skin irritation.
Eye Dam. 1; H318, Causes serious eye damage.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s):
Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
Causes serious eye damage. (H318)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

General: -

Prevention:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Wash hands and exposed skin thoroughly after handling. (P264)
Wear eye protection/protective gloves/protective clothing. (P280)

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Immediately call a POISON CENTER/doctor. (P310)

Storage:
Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal:
Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances:
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Alcohols, C12-15-branched and linear, ethoxylated propoxylated
Alcohols, C12-14-secondary, ethoxylated
Hydrocarbons, C10-C13, aromatics, < 1% naphthalene

▼*Additional labelling:*
1.84 % of the mixture consists of ingredients of unknown toxicity.

UFI: 9SWV-R01N-5005-87A8

2.3. Other hazards

Additional warnings:
In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No.: EC No.: 920-107-4 UK-REACH: Index No.:	25-40%	EUH066 Asp. Tox. 1, H304	[3]
butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-004-00-0	15-25%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	[3]
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-003-00-5	10-15%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
Alcohols, C12-15-branched and linear, ethoxylated propoxylated	CAS No.: 120313-48-6 EC No.: UK-REACH: Index No.:	10-15%	Acute Tox. 4, H302 Eye Dam. 1, H318	[19]
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
Alcohols, C12-14-secondary, ethoxylated	CAS No.: 84133-50-6 EC No.: 617-534-0 UK-REACH: Index No.:	5-10%	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412	[19]
N-(2-hydroxypropyl)oleamide	CAS No.: 111-05-7 EC No.: 203-828-2 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)	CAS No.: EC No.: 701-188-3 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Hydrocarbons, C10-C13, aromatics, < 1% naphthalene	CAS No.: EC No.: 922-153-0 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 UK-REACH: Index No.: 601-052-00-2	<0.01%	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼Other information

[1] European occupational exposure limit.
[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.
[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:	In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
Inhalation:	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
Skin contact:	Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
Eye contact:	If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.
Burns:	Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. ▼Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)
This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.
The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media
Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture
Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Nitrogen oxides (NO_x)
Carbon oxides (CO / CO2)

5.3. Advice for firefighters
Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: None

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures
Accidental releases always pose a serious risk of fire or explosion.
Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.

6.2. Environmental precautions
Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections
See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material:	Keep only in original packaging.
Storage conditions:	10 - 30°C
Incompatible materials:	Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. ▼Control parameters

butane
Long term exposure limit (8 hours) (ppm): 600
Long term exposure limit (8 hours) (mg/m³): 1450
Short term exposure limit (15 minutes) (ppm): 750
Short term exposure limit (15 minutes) (mg/m³): 1810
Annotations:
Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Short term exposure limit (15 minutes) (mg/m³): 10

naphthalene
Long term exposure limit (8 hours) (ppm): 10
Long term exposure limit (8 hours) (mg/m³): 53
Short term exposure limit (15 minutes) (ppm): 15
Short term exposure limit (15 minutes) (mg/m³): 80

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼DNEL

2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	2.29 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	6.35 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	7.96 mg/m³
Long term – Systemic effects - Workers	Inhalation	44.8 mg/m³
Long term – Systemic effects - General population	Oral	0.42 mg/kg bw/day

Hydrocarbons, C10-C13, aromatics, < 1% naphthalene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	7.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	12.5 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	32 mg/m³
Long term – Systemic effects - Workers	Inhalation	151 mg/m³
Long term – Systemic effects - General population	Oral	7.5 mg/kg bw/day

PNEC

2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		12 µg/L
Freshwater sediment		0.263 mg/kg dw
Marine water		1.2 µg/L
Marine water sediment		0.0263 mg/kg dw
Predators		16.6 mg/kg
Sewage treatment plant		2.57 mg/L
Soil		0.046 mg/kg dw

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this product.

Exposure limits: Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures: Ensure that eyewash stations and safety showers are located within easy reach.


Hygiene measures: Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure: Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	AX		Brown	EN14387	

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,38	> 480	EN374-2, EN16523-1, EN388	

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Aerosol

Colour: Red

Odour / Odour threshold: Mild pine

pH: Not applicable

Density (g/cm^3): 0.88 (20 °C)

Kinematic viscosity: 8 mm^2/s (38 °C)

Particle characteristics: Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C): No data available

Softening point/range (°C): Does not apply to aerosols.

Boiling point (°C): >230

Vapour pressure: <0.5 mmHg (20 °C)

Relative vapour density: >1

Decomposition temperature (°C): No data available

Data on fire and explosion hazards

Flash point (°C): >93

Flammability (°C): The material is ignitable.

Auto-ignition temperature (°C): >200

Lower and upper explosion limit (% v/v): No data available

Solubility

Solubility in water: Emulsifies

n-octanol/water coefficient (LogKow): No data available

Solubility in fat (g/L): No data available

9.2. Other information

Note: The above properties are for the bulk product and not the aerosol.
Flash point of the aerosol propellent: -40 °C

Evaporation rate (n-butylacetate = 100):	<0.1
Oxidizing properties:	No data available
Other physical and chemical parameters:	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼Acute toxicity

Based on available data, the classification criteria are not met.

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>5000 mg/kg

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)

Result:	>5000 mg/m³

Product/substance	Alcohols, C12-15-branched and linear, ethoxylated propoxylated
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	300-2000 mg/kg

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	8270 mg/kg

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 2000 mg/kg

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	4.76 mg/L

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 402
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg bw

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>6318 mg/kg bw

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>4778 mg/L

Product/substance	naphthalene
Test method:	OECD 401
Species:	Rat

Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg bw

Product/substance	naphthalene
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	0.4 mg/L

Skin corrosion/irritation

Product/substance Alcohols, C12-14-secondary, ethoxylated

Causes skin irritation.

Serious eye damage/irritation

Product/substance Alcohols, C12-14-secondary, ethoxylated

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

▼Reproductive toxicity

Product/substance	naphthalene
Test method:	OECD 414
Species:	Rat, female
Test:	LOAEL
Result:	50 mg/kg bw

Product/substance	naphthalene
Test method:	OECD 414
Species:	Rat, female
Test:	LOAEL
Result:	450 mg/kg bw

Product/substance	naphthalene
Test method:	OECD 414
Species:	Rabbit, female
Test:	NOAEL
Result:	120 mg/kg bw

▼STOT-single exposure

Based on available data, the classification criteria are not met.

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 413
Species:	Rat
Route of exposure:	Inhalation
Test:	NOAEC
Result:	2230 mg/m^3

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Species:	Rat, male
Route of exposure:	Oral

Test:	NOAEL
Result:	250 mg/kg bw/day

Product/substance	naphthalene
Test method:	OECD 408
Species:	Rat
Route of exposure:	Oral
Duration:	90 days
Test:	LOAEL
Result:	400 mg/kg bw

Product/substance	naphthalene
Test method:	OECD 413
Species:	Rat
Route of exposure:	Inhalation
Duration:	90 days
Test:	LOAEC
Result:	0.011 mg/L

Product/substance	naphthalene
Test method:	OECD 411
Species:	Rabbit
Route of exposure:	Dermal
Duration:	90 days
Test:	NOAEL
Result:	1000 mg/kg bw

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Product/substance	butane
Species:	Rat, male/female
Route of exposure:	Inhalation
Duration:	42 days
Test:	NOAEL
Result:	16000 ppm

Product/substance	isobutane
Species:	Rat, male/female
Route of exposure:	Inhalation
Duration:	42 days
Test:	NOAEL
Result:	16000 ppm

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

▼Other information

naphthalene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼Toxicity

Based on available data, the classification criteria are not met.

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LCLo
Result:	>1000 mg/L

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Test method:	OECD 202
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	>1000 mg/L

Product/substance	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	NOEC
Result:	>1000 mg/L

Product/substance	butane
Test method:	QSAR
Species:	Fish
Test:	LC50
Result:	147.54 mg/L

Product/substance	propane
Test method:	QSAR
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	147.54 mg/L

Product/substance	propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	49.9 mg/L

Product/substance	propane
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	27.1 mg/L

Product/substance	propane
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	11.9 mg/L

Product/substance	Alcohols, C12-15-branched and linear, ethoxylated propoxylated
Species:	Fish, Leuciscus idus

Duration:	96 hours
Test:	LC50
Result:	1-10 mg/L
Other information:	Analogous: Assessment derived from products with similar chemical character

Product/substance	Alcohols, C12-15-branched and linear, ethoxylated propoxylated
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	1-10 mg/L
Other information:	Analogous: Assessment derived from products with similar chemical character

Product/substance	isobutane
Test method:	QSAR
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	147.54 mg/L

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Pimephales promelas
Duration:	96 hours
Test:	LC50
Result:	1 - < 10 mg/L

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Test method:	OECD 202
Species:	Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	1 - < 10 mg/L

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Algae
Test:	ErC50
Result:	2.01 mg/L

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Fish
Test:	NOEC
Result:	0.87 mg/L

Product/substance	Alcohols, C12-14-secondary, ethoxylated
Species:	Daphnia magna
Test:	NOEC
Result:	0.2 mg/L

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 203
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	12 mg/L

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 202
Species:	Daphnia
Duration:	48 hours

Test:	EC50
Result:	12 mg/L

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 201
Species:	Algae
Duration:	72 hours
Test:	ErC50
Result:	68 mg/L

Product/substance	2-(4-methylcyclohex-3-en-1-yl)propan-2-ol (multi-constituent)
Test method:	OECD 201
Species:	Algae
Test:	NOEC
Result:	3.9 mg/L

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	ErC50
Result:	3.8 mg/L

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	QSAR
Species:	Fish
Duration:	28 days
Test:	NOEC
Result:	0.103 mg/L

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 211
Species:	Crustacean
Duration:	21 days
Test:	NOEC
Result:	0.179 mg/L

Product/substance	Hydrocarbons, C10-C13, aromatics, < 1% naphthalene
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	NOEC
Result:	0.179 mg/L

Product/substance	naphthalene
Species:	Crustacean
Test:	EC50
Result:	2.16 mg/L

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. ▼Mobility in soil

naphthalene
LogKoc = 2.6, Moderate mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1	-	No	Limited quantitie

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
			Classification code: 5F 			s: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: None

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: Restricted to professional users.
People under the age of 18 shall not be exposed to this product.

Demands for specific education: No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances: P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

UK-REACH, Annex XVII:	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics is subject to restrictions, UK-REACH annex XVII (entry 3). butane is subject to UK-REACH restrictions (entry 40). propane is subject to UK-REACH restrictions (entry 40). isobutane is subject to UK-REACH restrictions (entry 40).
Additional information:	Not applicable.
Sources:	The Management of Health and Safety at Work Regulations 1999. The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29). Control of Major Accident Hazards (COMAH) Regulations 2015. Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law. Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

▼Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H220, Extremely flammable gas.
H280, Contains gas under pressure; may explode if heated.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H351, Suspected of causing cancer.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.
H411, Toxic to aquatic life with long lasting effects.
H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Magnaflux

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product.
Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en