MAINTENANCE CHEMICALS

RUST REMOVER & CLEANER

DESCRIPTION:

A concentrated acid based liquid which can be used neat or diluted, depending on the degree of build-up. Cleans oil and dirt, then chemically reacts with and removes all traces of rust from iron and steel. Will remove the heaviest deposits completely, eliminating hazardous, costly and ineffective sand-blasting, grinding, chipping and wire brushing.

After cleaning, RUST REMOVER leaves a protective film on the surface to provide temporary protection against corrosion and an etched surface for excellent primer and paint adhesion.

Also used effectively to clean and brighten aluminium, brass, copper and other metals.

WHERE TO USE:

- Maintenance paint shops
- Production steel shops
- Reclaiming scrap metal
- Refinishing tools, jigs, fixtures
- Storage tanks
- Truck and auto body repair
- Parts and component salvaging
- Architectural trim
- Metal fabrication
- Metal filter cleaning
- Oven cleaning
- Pre-painting surface preparation
- Disassembly of machinery, bolts, nuts, fasteners

ADVANTAGES:

- Safer to use than sandblasting, grinding
- Cleans effectively
- Removes rust
- Provides anti-corrosion protection against flash rusting
- Provides etched surface for primer and paint adhesion
- Completely removes rust unlike chipping or wire brushing
- Saves man-hours as it works automatically in dip operation
- Economical, can be diluted with water for any thickness of rust
- Quickly removes oxide films from non-ferrous metals to clean and brighten without scrubbing

PACKAGING:

5 ltr pails
20 ltr pails
30 ltr pails
210 ltr drum

SAFETY ENGINEERING GUIDE:

CORROSIVE
HARMFUL
NON-FLAMMABLE
ACID BASED PRODUCT - TAKE CARE WHEN USING

SEE REVERSE SIDE FOR USAGE, SAFETY & HANDLING INFORMATION

WARRANTY: Unispec Chemicals Limited sister company of Chela Ltd. We guarantee our products to be free of defects and bad workmanship and we will replace goods proven not to so conform. As the Company has no control over the applications or end-uses of its products the Company excludes all other warranties, express or implied, by statute or otherwise, as to the products' fitness for any particular purpose. The Company's liability shall not, under any circumstances, exceed that of the replacement of the defective product and no claims for consequential damages shall be accepted. Purchase of our products by end-users or distributors assumes awareness of our warranty as shown above.

Unispec Chemicals Limited
68 Bilton Way, Enfield, EN2 0ER
T: 020 8805 2150 | E: sales@unispec-chemicals.co.uk

UNISPEC GROUP

USAGE, SAFETY & HANDLING INFORMATION

RUST REMOVER & CLEANER

DIRECTIONS:

Clean surface of any loose rust, scale, dirt, grease or oil before applying RUST REMOVER.

Apply undiluted by brush or dip and allow 10-15 minutes for penetration.

Rinse well with fresh water and allow surface to dry completely before painting.

Paint surface within a maximum of 48 hours after rust removal treatment.

RUST STAIN REMOVAL

Remove loose dirt from surface.

Prepare solution of 1 part RUST REMOVER to 3 parts fresh water.

Apply solution by brush or dip and allow 10-15 minutes for penetration.

Rinse surface thoroughly with fresh water and allow to dry.

NOTE:

If RUST REMOVER is used on aluminium surfaces, rinse thoroughly within 5 minutes of application.

DO NOT USE on tin, zinc or galvanized surfaces.

SAFETY MEASURES:

HAZARDS

CAUTION: Causes severe burns (contains phosphoric acid). Harmful if inhaled or ingested.

PROTECTIVE MEASURES: Wear appropriate acid-resistant protective clothing, gloves, and eye/face protection during use. Use in well ventilated areas. Avoid inhalation and contact with eyes, skin.

SPILLAGE: Personnel should wear protective, acid-resistant clothing. Confine spills and ventilate the area. Collect with absorbent agent and dispose of in authorized areas. Do not dispose of in sewage systems.

FIRE: Non-flammable product. In case of fire, use foam, CO_2, sand. **DO NOT USE WATER.** Always wear respiratory protection as toxic fumes may be released in fire.

FIRST AID

EYES: DO NOT DELAY. Wash eyes immediately with flowing water for at least 15 minutes and seek IMMEDIATE medical attention.

SKIN: DO NOT DELAY. Remove contaminated clothing and wash affected area with soap and water. Continue to rinse for at least 15 mins. Seek medical attention.

INHALATION: DO NOT DELAY. In case of prolonged inhalation or severe chest pain, remove affected person to fresh air and seek medical attention.

INGESTION: DO NOT DELAY. DO NOT INDUCE VOMITING. Obtain **IMMEDIATE** medical attention. Give large amount of water.

HANDLING

STORAGE: Store away from alkalis, other chemicals and foodstuffs in a cool, dry, ventilated storage area. Avoid storing at temperatures above 50°C, near flames or incandescent material.

KEEP AWAY FROM CHILDREN

PROPERTIES

COMPATIBILITY:
METALS: Prolonged contact may corrode common steel, cast-iron, aluminium and its alloys, zinc and galvanized material.
RUBBER: No known reaction. Test sample area before use.

EMERGENCY MEDICAL CONSULTATION CENTRE (GREECE) Tel. (01) 779-3777

WARRANTY:

We guarantee our products to be free of defects and bad workmanship and we will replace goods proven not to so conform. As the Company has no control over the applications or end-uses of its products the Company excludes all other warranties, express or implied, by statute or otherwise, as to theproducts' fitness for any particular purpose.The Company's liability shall not, under any circumstances, exceed that of the shall be accepted. Purchase of our products by end-users or distributors assumes awareness of our warranty as shown above.

Registered Office 42 Ermou Str.,Glyfada 166 74 GREECE Tel. 301-898-1798,898-2197, Fax.: 968-1405
Unispec Corp. Hellas Ltd 32, Papastratou Str,Pireaus 185 45 GREECE. Tel.:301-413-2859, Marine Division Fax.: 413-2938
Unispec Corp.UK Ltd.Liverpool, UK Tel.: 44-951-7223061 Fax.: 722-9645 Unispec/SSK Enterprises J.V. Dubai UAE
Tel.: 971-4-3472255 Fax.: 3472055, http/www.unispec.gr secondary e-mail: unispec@ath.forthnet.gr