NATIONAL PAINTS

THINNERS

MATERIAL SAFETY DATA SHEET

1. PRODUCT : **NATIONAL LACQUER THINNER**

Intended use: Cleaning and paint thinning compound.

Manufacturer: **National Paints Factories Co. Ltd. Sharjah, U.A.E.**

2. COMPOSITION/INFORMATION OF INGREDIENTS

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Names / CAS-No.	Conc.range	Symbol	R-phrases(*)
Aromatic Hydrocarbon			
1330-20-7	15.00 - 20.00%	Xn	20
108-88-3	35.00 - 45.00%	Xn	20

3. HAZARDS IDENTIFICATION OF THE PREPARATION

Highly inflammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.

4. FIRST AID MEASURES

General:
In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation :
Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

Eye contact:
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact :
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do ***NOT*** use solvents or thinners.

Ingestion:
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do ***NOT*** induce vomiting.

CamScanner

NATIONAL PAINTS

5. FIRE-FIGHTING MEASURES

Extinguishing media :
Recommended: alcohol resistant foam, CO2, powders, waterspray.
Not to be used: waterjet.
Recommendations:
Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate Breathing Apparatus may be required.
Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 7 and 8. Contain and collect spillage with non-combustible adsorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or water-courses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Handling:
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electrostatically : always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and floors should be of the conducting type.

Keep container tightly closed. Isolate from sources of heat , sparks and open flame. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Smoking, eating and drinking should be prohibited in application area.

For personnel protection see Section 8.

Never use pressure to empty : container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Storage:
Store in accordance with local rules and legislation.
Observe label precautions.
Store between 5 and 30°C in a dry, well ventilated place away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers, which are opened must be carefully resealed and kept upright to prevent leakage.

NATIONAL PAINTS

8. EXPOSURE CONTROLS/PERSONNEL PROTECTION

Engineering Measures:
Provide adequate ventilation. Where reasonably practicable this should be achieved by use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personnel Protection.

Respiratory protection:
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection:
For prolonged or repeated contact, wear suitable gloves. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection:
Use safety eyewear designed to protect against splash of liquids.

Skin protection:
Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state :	Liquid
Viscosity at 20° C :	14 sec. by Fordcup B4
Specific Gravity at 20° C:	0.85 ± 0.01
Vapour density :	heavier than air
Lower explosion limit:	1.00 Vol. %
Solubility in water :	not miscible with water

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions. (See section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.
Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself.

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. ECOLOGICAL INFORMATION

There are no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses.
Waste and emptied containers should be disposed of according to the local rules and legislation.

CamScanner

NATIONAL PAINTS

14. TRANSPORT INFORMATION

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

ADR/RID :
Class : 3 item : 3b Label : 3
IMDG :
Class : 3.2 UN-No: 1993 Label : Fla.L
Proper shipping name :
FLAMMABLE LIQUID, N.O.S.
Marine pollutant : No
EmS : 3-07 MFAG : 300
ICAO/IATA
Class : 3 UN-Nr: 1993 Label : Fla.L
Proper shipping name :
FLAMMABLE LIQUID, N.O.S.
Packing group : II

15. REGULATORY INFORMATION

In accordance with the Dangerous Preparations Directive 88/379/EEC the product is labeled as follows :
Danger Classification :
F Highly flammable
Xn Harmful

Contains :
Aromatic Hydrocarbons, Alcohols, Ketones.

R phrases :
Highly inflammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.

S phrases :
Wear suitable protective clothing and gloves.
Use only in well ventilated areas.
Keep away of sources of ignition - No smoking.
Take precautionary measures against static discharges.

16. OTHER INFORMATION

Full text of R phrases with no. appearing in section 2.
20 Harmful by inhalation
21 Harmful in contact with skin.

The information of this MSDS is based on the present state of our knowledge and on current EEC and national laws. As the users' working conditions are beyond our knowledge and control, the product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product; it is not to be considered as a guarantee of the products' properties.

Note: This information is given to the best of our knowledge and experience, and supersedes previously issued data sheet.

National Paints Factories Co. Ltd.
Tel: +971 6 5130000, Fax: +971 6 5340222
P.O. Box: 5822, Shariah - U.A.E.
www.national-paints.com
ISO 9001 & 14001
OHSAS 18001
CERTIFIED FACTORY
شركة مصانع الأصباغ الوطنية المحدودة
هاتف: ٥١٣٠٠٠٠ ٦ ٩٧١+، فاكس: ٥٣٤٠٢٢٢ ٦ ٩٧١+
ص.ب: ٥٨٢٢، الشارقة - ا.ع.م

CamScanner